

Product Catalog Measuring instruments and sensors





Please refer to our Internet site www.ahlborn.com

The quick and easy way to access even more information:

- News
- Trade fairs
- Online services
- Downloads
- Applications
- FAQ

and much more besides

How do you want to measure?









Universal instruments

Refenence instruments

Contents

The ALMEMO [®] system	01.02
ALMEMO [®] measuring instruments, overview	01.04
Input connectors	01.05
General technical specifications	01.06
Measuring ranges	01.08
Measuring ranges, ALMEMO [®] 2450, 2490, 2470, 2590	01.10
Compact ALMEMO [®] measuring instrument ALMEMO [®] 2450	01.12
Basic measuring instrument ALMEMO [®] 2490-1L	01.13
Basic measuring instrument ALMEMO [®] 2490	01.14
Professional measuring instrument ALMEMO® 2470	01.16
Professional measuring instrument ALMEMO [®] 2590	01.19
Precision measuring instrument ALMEMO [®] 2690-8A	01.22
Precision measuring instrument ALMEMO [®] 2890-9	01.24
Professional measuring instrument ALMEMO [®] 202 V7	01.26
Professional measuring instrument ALMEMO [®] 202 V7	01.28
Precision measuring instrument ALMEMO [®] 710 V7	01.31
Wireless measuring instrument ALMEMO [®] 470	01.34
Precision measuring instrument ALMEMO [®] 500 V7	01.40
Precision measuring instrument ALMEMO [®] 809 V7	01.44
Precision measuring instrument for measured data acquisition ALMEMO [®] 5690	01.46
Precision measuring instrument for measured data acquisition ALMEMO [®] 8590/8690	01.60
Universal ALMEMO [®] transmitter 2450 / 2490	01.62
Precision measuring instrument ALMEMO® 4390 in fitted panel design	01.64
Reference measuring instrument ALMEMO® 1020-2 X6	01.66
Reference measuring instrument ALMEMO® 1030-2 X6	01.68
Reference measuring instrument ALMEMO® 1033-2 X6	01.70
Reference measuring instrument ALMEMO® 1036-2 X6	01.72
Reference measuring instrument ALMEMO® 8036-9 X6	01.74



The ALMEMO[®] system

The ALMEMO® system comprises an ALMEMO® measuring instrument and intelligent ALMEMO® connectors for the relevant sensor equipment.

An extensive range of measuring instrument variants is thus available from the single-channel transmitter right through to data acquisition systems with over 1000 measuring points.

The only differences between most of the measuring instruments in the ALMEMO®

instruments, desktop instruments, 19inch systems, fitted panel instruments, transmitters, etc.), the number of measuring inputs (1 to 250), the display, output, and operating controls, and their respective power supplies.

As soon as a sensor or interface cable is connected, the ALMEMO® measuring instrument will, thanks to the intelligent **ALMEMO[®]** connector system, be

series concern their housing (i.e. handheld completely programmed right through to process scheduling.

> These measuring instruments provide a uniform range of functions with many configurable options. All parameters can be accessed via the interface and can, since the media in the connectors are always overwritten, be freely modified as and whenever necessary.

The ALMEMO® principle: Only one measuring instrument for all sensors

sensors, and signals can be connected to any measuring input on virtually any ALMEMO[®] measuring instrument - all via the ALMEMO[®] plug system Since all the sensor data is saved in the connector, no extra programming is required; as soon

An extensive range of transducers, instrument is configured automatically. The sensor data memory (EEPROM) ensures that each sensor can be identified, scaled, and calibrated - all on the basis of its own unique designation. This system of individual sensor designations avoids confusion and makes the measuring setup as a sensor is connected, the measuring clear and logical. Sensor errors can be by a graduated locking function.

corrected within the plug, turning simple sensors into precision transducers.

Standard signals can be displayed in their original dimensions. For multi-purpose sensors (e.g. temperature and humidity) only one shared plug will usually be required. Programming can be protected

With ALMEMO[®] measuring instruments you will not need new sensors

For your existing sensors we will provide You can also program ALMEMO® plugs the plug can be overwritten as and whenefit quickly and easily.

you with a matching adapter that you can yourself quickly and easily via keypad, ver necessary. terminal, or software. The data medium in

ALMEMO[®] measuring instruments are ideal for all sorts of application

circuitry. For applications that are not sector-specific there are more than 60 standard measuring ranges available, e.g. for measuring :

Temperature, humidity, flow velocity, flow rate, heat flow, pressure, rotational speed,

force, strain factor, displacement, pH value, redox potential, conductivity, O₂, CO₂, CO, of programmable maximum / minimum O3, etc. Maximum and minimum values values. Measured values can be corrected are saved automatically. Measured values with regard to zero point and gain and can can be averaged over a series of individual be scaled by factor, base value, exponent, measurements, over the output cycle, and units.

All incorporate the same measuring input frequency, resistance, current, voltage, or over the actual measuring duration; limit values can be monitored in terms

ALMEMO[®] measuring instruments are real individuals

cognize the specifications of a sensor as it is connected. Specific functions will only be activated as and when the appropriate connector, interface cable, or module the prevailing atmospheric pressure can be is detected. With humidity sensors the dew point, mixture ratio, vapor pressure, and enthalpy will be calculated automa-

ALMEMO® instruments automatically re- tically. Measuring operations involving psychrometers, dynamic pressure probes, or probes for solute oxygen may require pressure compensation; for this purpose entered manually or calculated automatically by an integrated pressure transducer. When measuring dynamic pressure, pH

value, atmospheric humidity, solute oxygen, or conductivity it is possible similarly to perform temperature compensation. When using flow sensors to measure volume flow the appropriate cross-section can be entered. For certain special sensors there are connectors available incorporating an integrated adapter circuitry.

ALMEMO[®] measuring instruments meet even the most stringent requirements

ALMEMO® devices incorporate a high- calibration. Optimal cold junction com- and interfaces are all electrically isolated

resolution 16-bit A/D converter, digital pensation is ensured by means of precislinearization (for Pt100 sensors with the ion thermistors incorporated in the socket new ITS 90 temperature scale), and digital spring. Measuring inputs, power supply,

from each other.

The ALMEMO[®] data acquisition system adapts to your requirements

The internal measured data memory incorporated in ALMEMO[®] data loggers can be expanded by adding external capacity and can be configured either as linear or ring memory.

This memory can be read out selectively according to time or number. The switchover between measuring points is electrically isolated using semiconductor relays that are totally wear-resistant. Continuous measuring point scanning at 10 or 50 measuring operations per

second can thus be performed troublefree. Measuring point scans can be individually programmed. Measuring cycles and output cycles can be selected independently; measured values, average values, and maximum / minimum values can be selectively output and / or saved to memory. The start / stop of each measuring point scan can be variably controlled (by keypad or interface, by date and time-of-day, by limit values, or by an external signal). All measuring

instruments can be addressed via interface and are thus fully network-capable. Up to 100 devices can be networked either via cable or over a wireless link. The output of measured values from all devices in the whole network can be initiated from any one such device. For covering longer distances RS422 drivers and distributors are available. This system minimizes hardware requirements, cabling costs, and possible EMC problems, and can be expanded as and when required.

ALMEMO[®] measuring instruments accept virtually any peripheral equipment while maintaining optimal data transmission

themselves but in the connectors and various connecting cables.

integrated in the measuring instruments can be connected, e.g. analog outputs, trigger inputs. interfaces (RS232, Depending on optic fiber, current loop, Ethernet, phone network.

Analog or digital interfaces are not requirements a wide variety of adapters Bluetooth), alarm signaling devices, or The data can also be RS422, transmitted via Internet or via mobile

ALMEMO® measuring instruments provide evaluation of measured data easily and conveniently

Suitable output formats are provided for presentation and the evaluation of mea- ckages available. spreadsheet software. For the graphical sured data there are various software pa-

ALMEMO[®] instruments can be programmed quickly and easily

The software protocol and the commands parameters and to scan the measured data. available for this purpose. list are identical for all devices. Only There is a free configuration software, one terminal is enough to program all ALMEMO® Control, with terminal,

ALMEMO[®] measuring instruments, overview

	Measurie	Expansions	Display	Graphics dia .	Data Inc.	Integrated	Interface / mit	Precision .	Measuring	Measure (mops) max	Multi-point	Portahu	Deslat	Fitted device	Catalog page
Compact measuring instrument ALMEMO [®] 2450-1L	1		~					С	2.5	35		~			01.16
Basic measuring instrument ALMEMO® 2490-1A ALMEMO® 2490-2A	1 2		ン ン				v v	B B	10 10	65 65		ン ン			01.18 01.18
Professional measuring instrume ALMEMO [®] 470 V7 wireless	ent	10		~	~	~	~						~		01.12
ALMEMO® 202 V7 ALMEMO® 204 V7	2 4			v v	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	~	~ ~		1000 1000		opt. opt.	ン ン			01.20 01.xx
ALMEMO [®] 2470-1S/-SCRH ALMEMO [®] 2470-2S ALMEMO [®] 2470-2	1 2 2	~	v v	~	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	~~	A 1	10 A A	65 10 10	65 65	~	~ ~		01.22	01.22 01.22
ALMEMO® 2590-2A ALMEMO® 2590-4AS	2 4			v v	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	~	v v	A A	10 10	65 65		ン ン			01.25 01.25
Precision measuring instrument ALMEMO [®] 2690-8A	5			~	~	~	~	AA	100	66	opt.	~			01.28
ALMEMO® 2890-9	9			V	V	~	~	AA	100	66	opt.	~			01.30
ALMEMO® 710 V7	10			~	V	•	~	AA	2000	66	opt.	~			01.32
ALMEMO® 8590-9 ALMEMO® 8690-9A ALMEMO® 809 V7	9 9 9				ンンン	opt. opt.	ンンン	AA AA AA	100 100 2000	66 66 66	opt. opt. opt.		ンンン		01.36 01.36 01.38
ALMEMO [®] 5690-1M09 ALMEMO [®] 5690-2M09	9 9	opt. opt.		~	ン ン	opt.	~ ~	AA AA	100 100	66 66	opt. opt.		ン ン		01.40 01.40
ALMEMO [®] 5690-1CPU ALMEMO [®] 5690-2CPU		opt. opt.		~	v v	v v	> >	AA AA	100 100	66 66	opt. opt.		v v		01.48 01.48
ALMEMO® 500 CPU V7	20	opt.		~	~	~	~	AA	4000	66	opt.		~	~	01.54
ALMEMO® 4390-2	1		~		V	~	~	AA	100	66				~	01.60
Basic device (transmitter) ALMEMO [®] 2490-1R02U ALMEMO [®] 2490-2R02U	1 2		<i>v v</i>				~ ~	B B	10 10	65 65				~ ~	01.58 01.58
Reference measuring instrument ALMEMO® 1020-2 X6 ALMEMO® 1030-2 X6 ALMEMO® 1033-2 X6	2 2 2			~ ~ ~ ~	~ ~ ~ ~		~ ~ ~	AS AS AS	1.25 1.25 2.5	4 1 2	~ ~ ~	~~~			01.62 01.65 01.xx
ALMEMO [®] 1036-2 X6 ALMEMO [®] 8036 X6	2 9			~	~		~	AS AS	1.25 1.25	7	~	V	~		01.67 01.69

Input connector

ALMEMO® input connector, also for existing sensors, see chapter ALMEMO® input connectors

ALMEMO[®] standard plug

- The ALMEMO[®] measuring system makes it possible to process four channels per measuring input depending on the sensor and the measuring instrument.
- The ALMEMO® plug incorporates 6 screw terminals 2 for the sensor's power supply and 4 for its measuring signal.
- With Pt100 sensors using 4-conductor circuitry all 4 free connections will be required for the measuring signal. Only one sensor of this type can be connected therefore per measuring input.
- Electrical signals only require 2 connections for the measuring signal. One plug can thus acquire two different measuring signals over just one measuring channel.
- An atmospheric humidity sensor can example usually be combined with a temperature sensor. The associated operands (e.g. dew point, mixture ratio, partial vapor pressure, enthalpy) are programmed in the plug as additional measuring channels.

ALMEMO® D6 plugs for digital sensors

- The digital ALMEMO[®] D6 sensor can be connected to any ALMEMO[®] measuring instrument without in any way affecting its measuring accuracy. The A/D converter incorporated in the ALMEMO[®] D6 sensor is exclusively responsible for the measuring accuracy of the whole system.
- The digital ALMEMO[®] D6 sensor is calibrated without involving the ALMEMO[®] measuring instrument (DAkkS / factory) and can be replaced or exchanged as and whenever necessary.
- The connecting cable for the digital ALMEMO[®] D6 sensor can be extended using pluggable extension cables quickly and easily and without any line losses. (see chapter "General accessories") These digital extension cables provide high transmission reliability; they have no effect on measuring accuracy.
- The configuration of the digital ALMEMO[®] D6 sensors (i.a. the selection of the measuring ranges) is effected by an ALMEMO[®] V7 measuring instrument, e.g. ALMEMO[®] 710 or ALMEMO[®] 202 (refer to chapter ALMEMO[®] Universal Measuring Instruments), or directly on the PC by using the USB adapter cable ZA1919AKUV (refer to chapter Network technology).

New generation: ALMEMO[®] V7 ALMEMO[®] D7

ALMEMO® V7 measuring instrument and ALMEMO® D7 plug for digital sensors

- With the ALMEMO[®] D7 plug technology, the measurement ranges of the sensors are completely independent of the measuring instrument. Each ALMEMO[®] D7 measurement plug features up to 10 display and function channels.
- The new ALMEMO[®] D7 measurement plug enables high measuring speeds or high measuring accuracy applicable for a vast variety of measuring tasks.
- The ALMEMO[®] D7 plug measures dynamic processes using the setting High Speed Measuring Operations at high sampling rate. The ALMEMO[®] V7 measuring instrument saves the measured values, and the WinControl measuring software displays them in graphical form. In case high resolution and stable values are needed (e.g. for accuracy transducers), the ALMEMO[®] D7 measurement plug measures with reduced sampling rate, if the setting High Resolution is selected.
- The digital ALMEMO[®] D7 measurement plug comes with an integrated A/D converter. The measuring rate is solely determined by the A/D converter. All D7 measurement plugs run in parallel on the ALMEMO[®] V7 measuring instrument with their own measuring rate. The minimal scanning cycle of the measuring instrument is determined by the measuring rates of the D7 measurement plugs and is virtually independent from the number of plugs.
- The overall accuracy of the measurement is independent from the ALMEMO[®] V7 display device / data logger and form the extension cable used. The complete measuring chain, consisting of sensor and connected ALMEMO[®] D7 measurement plug, is calibrated.
- The measured values can be complemented with a unit featuring up to 6 characters. To designate a sensor it is possible to program comments with up to 20 characters. The user can easily perform the configuration via the ALMEMO[®] V7 measuring instrument.

Important! ALMEMO[®] D7 measurement plugs can only be connected to ALMEMO[®] measuring instruments of the V7 generation, i.a. ALMEMO[®] 500, ALMEMO[®] 710, ALMEMO[®] 809, ALMEMO[®] 202.







General technical specifications

Inputs

inputs		
Channel switching		
between input sockets		
for analog sensors	4-contact with photo-MOS relays	
-	Potential separation maximum 50 V	
	Measuring modules with higher potential separation	(see chapter "Input modules")
	Offset voltage $<5 \mu\text{V}$	
Cold junction compensation (CJC)	effective in range -30 to +100 °C, Accuracy ± 0.2 K (± 0.2 K)	0.01 K / °C)
Nominal temperature	22 °C ±2 K	,
Sensor power supply	6 to 12 V depending on power supply	
Self-calibration	Automatic zero-point correction, measuring current cal	ibration
Monitoring functions	Automatic sensor recognition and sensor breakage dete	ection

		Basic measuring instruments	Professional measu- ring instruments	Precision measuring instruments	
Precision class	С	В	Α	A	Α
ALMEMO [®] series	2450, 2420	24900	2470, 2790 2590A	4390	500, 710, 809, 2690A, 2890, 5690 8590, 8690
Measuring rates Measuring operations per second (mops)	2.5 mops	2.5 / 10mops	2.5 / 10mops	2.5 / 10 / 50 / 100mops Option 400mops* Option 500mops *	
Input range	0.26 to +2.6 V	-2 to +5 V	-1.9 to +2.9 V	meas. range 2.6 V: -3 to +3 V in all other meas. ranges -2.3 to +1.3 V	-1.9 to +2.9 V
Overload	-4 to +5 V	-2 to +5 V	-2 to +5 V	± 12V	$\pm 12V$
Input current	< 2nA	< 10nA	100pA	Meas. range 2.6 V: 500 nA in all other meas. ranges 500 pA	100pA
Measuring current		Pt100/1000: 0.3mA	Pt100: 1mA, Pt1000: 0.1mA	Pt100: 1mA, Pt1000: 0.1mA	
System accuracy at 2.5 mops	0.1% of measured value ±4 digits	0.03% of mea- sured value ±4 digits	0.03% of measured value ±3 digits	0.02% of measured value ± 2 digits	
Temperature drift	0.01% / K (100 ppm)	0.005% / K (50 ppm)	0.003% / K (30 ppm)	0.003% / k	K (30 ppm)

*Measuring rate 400 mops (Option SA0000Q4)

*Measuring rate 500 mops (Option SA0000Q5):

It is also possible, in addition to the standard conversion rates, to set 400 or 500 mops (measuring operations per second). At the rate of 400 or 500 mops just one selected measuring channel can be saved. This can only be used with sensors with voltage or current ranges or with NTC sensors. Nor is it possible to change channels in the course of a measuring operation.

The resolution, accuracy, and sensitivity to disturbance caused by mains hum or electromagnetic interference are comparable with measuring operations performed at a rate of 50 mops. Care must be taken to ensure that the environment is free from interference and that the sensor lines are kept short. Data can only be output to a micro SD card. Accessories ZA1904SD Memory connector with micro SD Data is saved in table format (separated by semi-colons) and with a time-stamp resolution of 0.0001 seconds. This format can be processed using the WinControl software (as of version 6.1.1.6).

Environmental conditions for ALMEMO® devices and ALMEMO® connectors

Humidity range: 10 to 90% (non-condensing)

Temperature range:

for ALMEMO devices without battery

Operating temperature: -10 to +50 °C Storage temperature: -20 to +60 °C

for ALMEMO devices with rechargeable NiMH battery

Operating temperature: -5 to +50 °C Storage temperature: -20 to +60 °C

for ALMEMO devices with rechargeable battery Li-Ion

Operating temperature: 0 to +45 °C Storage temperature: -20 to +60 °C

for ALMEMO connectors

Operating temperature: -10 to +50 °C Storage temperature: -20 to +60 °C

for power supply NA11/NA12

Operating temperature: NA11: 0 to +45 °C NA12: 0 to +50 °C Storage temperature: -40 to +70 °C

Outputs

ALMEMO [®] socket A1	Digital interface	Baud rates up to 115.2 kilobaud
		Data : 8 bit serial, 1 start bit, 1 stop bit, no parity
		ALMEMO® data link via USB, RS232, Ethernet
		wireless link via Bluetooth, WLAN, mobile, cloud,
		(see chapter "Networking")
	Analog output	ALMEMO [®] analog cable and analog interface
	U 1	(see chapter "Output modules")
ALMEMO [®] socket A2	Networking A1/A2	ALMEMO [®] network cable
-	0	(see chapter "Networking")
		× 1 " U /
	Saving data	ALMEMO [®] memory connector with memory card
		(see chapter "General accessories")
	Analog output	ALMEMO [®] analog cable and analog interface
	-	(see chapter "Output modules")
	Trigger input	ALMEMO [®] trigger cable and trigger interface
		(see chapter "Output modules")
	Relay output	ALMEMO [®] relay cable and relay interface
	-	(see chapter "Output modules")
	Relay output	ALMEMO [®] relay cable and relay interface
		(see chapter "Output modules"
		Software for display and evaluation of measured values,
		software for ALMEMO [®] configuration,
		(see chapter "Software")
	inControl	
100		
20		
	7	
frank schm	nidt & dirk sloboda	
copyright @		

Mains adapter and DC supply cable

see chapter "General accessories"

Measuring ranges

Sensor type	Туре	Meas	suring nge	Units	Resolutior	n Linearization accuracy	Connector programming
Resistance temperature det	ectors:						
Pt100 / Pt1000 -1 4-wire	FP Axxx	-200.0 to	+850.0	°C	0.1 K	± 0.05 K ± 0.05 % of measured value	e ZA 9030 FS1/4
Pt100 / Pt1000 -2 4-wire	FP Axxx	-200.00 to	+400.00	°C	0.01 K	±0.05 K	ZA 9030 FS2 / 5
Pt100 -3 4-wire	FP Axxx	-8.000 to +	65.000	°C	0.001 K	±0.002 K	ZA 9030 FS7
Ni100/1000 4-wire		-60.00 to +	240.00	°C	0.1 K	±0.05 K	ZA 9030 FS3 / 6
NTC type N	FN Axxx	-50.00 to	+125.00	°C	0.01 K	±0.05 K	ZA 9040 FS
Thermocouples							
NiCr-Ni (K)	FT Axxx	-200.0 to	+1370.0	°C	0.1 K	$\pm 0.05~K \pm 0.05$ % of measured value	e ZA 9020 FS
NiCroSil-NiSil (N)		-200.0 to	+1300.0	°C	0.1 K	± 0.05 K ± 0.05 % of measured value	e ZA 9021 FSN
Fe-CuNi (L)		-200.0 to	+900.0	°C	0.1 K	$\pm 0.05~K \pm 0.05$ % of measured value	e ZA 9021 FSL
Fe-CuNi (J)		-200.0 to	+1000.0	°C	0.1 K	$\pm 0.05~K \pm 0.05$ % of measured value	e ZA 9021 FSJ
Cu-CuNi (U)		-200.0 to	+600.0	°C	0.1 K	$\pm 0.05~K \pm 0.05$ % of measured value	2A 9000 FSU
Cu-CuNi (T)		-200.0 to	+400.0	°C	0.1 K	$\pm 0.05~K \pm 0.05$ % of measured value	e ZA 9021 FST
PtRh10-Pt (S)		0.0 to	+1760.0	°C	0.1 K	±0.3 K	ZA 9000 FSS
PtRh13-Pt (R)		0.0 to	+1760.0	°C	0.1 K	±0.3 K	ZA 9000 FSR
PtRh30-PtRh6 (B)		+400.0 to	+1800.0	°C	0.1 K	±0.3 K	ZA 9000 FSB
AuFe-Cr		-270.0 to	+60.0	°C	0.1 K	±0.1 K	ZA 9000 FSA
Electrical and digital signal	ls:						
Millivolts DC		-10.0 to	+55.0	mV	1 μV	-	ZA 9000 FS0
Millivolts 1 DC		-26.0 to	+26.0	mV	1 μV	-	ZA 9000 FS1
Millivolts 2 DC		-260.0 to	+260.0	mV	0.01 mV	-	ZA 9000 FS2
Volts DC		-2.6 to	+2.6	*	V	0.1 mV	– ZA 9000 FS3
Volts DC		-26 to	+26	V	1 mV	-	ZA 9602 FS
For measuring bridges Sur	oply 5 V (Exampl	e) -26.0 to	+26.0	mV	1 μV	-	ZA9650 FS1V
For potentiometers Supply	2.5 V	-2.6 to	+2.6	*	V	0.1 mV	- ZA9025 FS3
Volt AC (50 Hz to 2 kHz) (Example)	0 to	+26	V	0.1 V	_	ZA 9603 AK3
Volt AC (11 Hz to 250 Hz)	(Example)	0 to	+400	V	1 V	_	ZA 9903 AB5
Ampere AC (11 Hz to 250	Hz) (Example)	0 to	+10.00	А	0.01 A	_	ZA 9904 AB2
Volts DC (sampling rate 1 l	kHz) (Example)	0 to	+400	V	1 V	-	ZA 9900 AB5
Ampere DC (sampling rate	1 kHz) (Example	e) 0 to	+10.00	А	0.01 A	_	ZA 9901 AB4
Milliamperes DC	, , , ,	-32.0 to	+32.0	*	mA	1 µA	- ZA 9601 FS1
Percent (4 / 20mA DC)		0.0 to	100.0	%	0,01 %		ZA 9601 FS2
Ohms		0.00 to	500.00	*	Ω	0.01 Ω	– ZA 9003 FS
Ohms		0.0 to	5000.0	*	Ω	0.1 Ω	- ZA 9003 FS2
Frequency		0 to	15000	Hz	1 Hz	_	ZA 9909 AK1U
Pulses / measuring cycle		0 to	65000			_	ZA 9909 AK2U
Digital interface		0 to	65000			_	ZA 9919 AKxx
Digital input		0.00 to	100.00	%		-	ZA 9000 ES2
Capacitive humidity sensor	'S:						
Rel: humidity	FH A646	5.0 to	98.0	%Н	0,1 %	-	
Rel: humidity with TC	FH A646-R	5.0 to	98.0	%Н	0,1 %	±0,5 %	
Dew-point temperature		-25.0 to	+100.0	°C	0.1 K	±0.2 K	
Mixture ratio		0.0 to	500.0	g/kg	0.1 g/kg	± 0.5 % of measured value	
Partial vapor pressure		0.0 to	1013.2	mbar	0.1 mbar	± 0.1 mbar ± 0.1 % of measured value	e
Enthalpy		0.0 to	400.0	kJ/kg	0.1 kJ/kg	± 0.5 % of measured value	
Psychrometer	FN A846					ZA 9846 AK	
Wet temperature		0.00 to	+100.00	°C	0.01 K	±0.05 K	
Relative humidity		0.0 to	+100.0	%Н	0.1 %	±1,0 %H	
Dew-point temperature		-25.0 to	+100.0	°C	0.1 K	±0.2 K	
Mixture ratio		0.0 to	500.0	g/kg	0.1 g/kg	$\pm 0.5\%$ of measured value	
Partial vapor pressure		0.0 to	1013.2	mbar	0.1 mbar	± 0.1 mbar $\pm 0.1\%$ of measured value	2
Enthalpy		0.0 to	400.0	kJ/kg	0.1 kJ/kg	$\pm 0.5\%$ of measured value.	

* Data may vary depending on device. (see relevant device data sheet)

Sensor type	Туре	Measuran	uring Ige	Units	Resolution	Linearization accuracy	Connector programming
Flow sensors							
Rot. vane, snap-on head	FV AD15-Sx (e.g.	.) 0.50 to	40,00	m/s	0.01 m/s	-	
Rotating vane Macro	FV AD15-MA1	0.10 to	20.00	m/s	0.01 m/s		
Water turbine	FV AD15-WM1	0.00 to	5.00	m/s	0.01 m/s		
Dynamic pressure sensor	FD A602-S1K	0.5 to	40.0	m/s	0.1 m/s	$\pm 0.1 \text{ m/s}$	
Dynamic pressure sensor	FD A602-S6	1.8 to	90.0	m/s	0.1 m/s	$\pm 0.1 \text{ m/s}$	
Hot-wire anemometer	FV A935-TH4	0 to	2.000	m/s	0.001 m/s	-	
Hot-wire anemometer	FV A935-TH5	0 to	20.00	m/s	0.01 m/s	—	
Hot-wire anemometer	FV A605-TA1	0.01 to	1.000	m/s	0.001 m/s	-	
Hot-wire anemometer	FV A605-TA5	0.15 to	5.00	m/s	0.01 m/s	-	
Chemical probes							
Conductivity	FY A641-LF (e.g.) 0 to	20.000	mS	0.001 mS	$\pm 0.2\%$ of measured value	
O ₂ dissolved saturation	FY A640-O2	0 to	260	%	1%	_	
O ₂ dissolved, concentr:	FY A640-O2	0.0 to	40.0	mg/l	0.1 mg/l	±0.2 mg/l	
O ₂ in gases	FY 9600-O2	1 to	100	%	1%	-	
O, in gases	FY 9600-O3	0 to	300	ppb	20 ppb	-	
CO probe	FY A600-CO (e.g	.) 0 to	300	ppm	1 ppm	_	
CO, in gases	FY A600-CO2 (e.	g.) 0.000 to	2.500	%	0.01%	$\pm 0.2\%$ of measured value	
pH probe	FY96PH-Ex	0.0 to	14.00	рH	0.01 pH	_	ZA 9610 AKY4W
Redox probe	FY96RX-Ex	0.0 to	2600.0	mV	0.1 mV	_	ZA 9610 AKY5W
Optical radiation (Examp	les)						
Lux measuring probe	FLA613-VL	0 to	260000	lux	1 hux	_	
Lux measuring probe	FL A603-VL2	0.05 to	12500	lux	0.01 lux	_	
Lux measuring probe	FL A603-VL2	0.05 to	250000	lux	1 lux	_	
LW measuring probe	FL A613 UV	1 to	230000	W/m^2	$0.01 W/m^2$	_	
UVA measuring probe	FL A603 UV24	0.0004 to	100	mW/cm^2	0.01 W/m^2	_	
D vA measuring probe	FL A603-0 V24	0.0004 to	100	mW/cm^2	$0.1 \mu \text{W/cm}^2$		
Photosynthesis probe	FL A603 PS5	0.00004 to	100	$mmo1/m^2s$	$0.01 \mu \text{W/cm}$	_	
i notosyntnesis probe	FL A003-1 55	0.0002 10	100	1111101/111 5	0.1µm01/m s	_	
Other connectable sensors	s / transducers (Exa	mples)					
Heat flow plates	FQ Axxx	-260.0 to	+260.0	mV	0.01 mV	—	ZA 9007 FS
Moisture content probe	FH A696-MF	0 to	50.0	%	0,1%	_	
Differential pressure	FD A612-SR	0 to	1000	mbar	0.1 mbar	—	
Barometer	FD A612-SA	0.0 to	1050 mł	bar	0.1 mbar	-	
Pressure transducer FDA	FD A602-xx (e.g.)) 0.00 to	10.00	bar	0.01 bar	-	
Force transducer	FK Axxx (e.g.)	0.0 to	50.00	kN	0.01 kN		
Displacement transducer	FW Axxx(e.g.)	0.0 to	150.00	mm	0.01 mm	-	
Tachometer	FU A919-2	8 to	30000	rpm	1 rpm		ZA 9909 AK4U
Function values							
Differential						—	
Maximum value						_	
Minimum value						-	
Average value over time						-	
Average value over measu	iring point					—	
Summation over measurin	ng points	0 to	65000			_	
Total number of pulses	ZA 9909-AK2U	0 to	65000			-	
Pulses / print cycle	ZA 9909-AK2U	0 to	65000			_	
Alarm value		0.0 to	100.00	%		_	
Thermal coefficient	M (q) / M (ΔT)						
Wet-bulb globe temperatu	re (WBGT)(0.1 TD	0 + 0.7 TW -	+0.2 TG)		-	
Measured value							
Cold junction temperat	ure				°C		
Number of averaged va	lues						
Volume flow		0 to	65000	m³/h	1 m ³ /h		

Measuring ranges, ALMEMO[®] 2450, 2490, 2470, 2590A series

	ALMEMO [®] series Precision class	2450 C	2490 B	2470 A	2590A A
Sensor type / Measuring range	Туре				
Temperature					
Thermocouple sensor					
NiCr-Ni Typ K (NiCr)	FTA xxx	X	X	X	X
NiCroSil-NiSil Typ N (NiSi)		×	×	×	X
Fe-CuNi Typ L/J (FeCo/IrCo)		×	X	X	×
Cu-CuNi Typ U/T (CuCo/CoCo)		×	×	X	X
PtRh10-Pt Typ S (Pt10)		×	X	X	×
PtRh13-Pt Typ R (Pt13)		Range	X	X	×
PtRh30-PtRh6 Typ B (EL18)		Range	X	X	X
AuFe-Cr (AuFe)		Range	X	X	×
Resistance temperature detectors					
Pt100/1000 (P104, P204)	FPA xxx	Range	X	X	X
Ni100/1000 (N104)		Range	X	X	X
NTC Typ N (NTC)	FNA xxx	X	X	X	X
Heat flow	FQA xxx, FQADxx	X	X	X	×
Atmospheric numidity					
Capacitive with NTC	FHA 646 xxx	×	X	X	X
Digital temperature / humidity sensor	FHAD 46x	×	X	X	×
Digital temperature / humidity sensor	FHAD 36 Rx	×	X	X	X
Psychrometric with NTC	FNA 846	Range	Function	Function	X
Psychrometric with Pt100 (2 plugs)	FPA 8363	Range	Function	Function	X
Digital psychrometer Dew point	FNAD46, FNAD463	X	X	X	X
Digital dewpoint sensor	FH A646 DTC1	X	X	X	×
Dew detector	FHA 9461	X	X	X	X
Moisture in materials		-	-	-	
Water detection probe	FHA 936 WD	X	X	X	X
Sensor for measuring moisture in materials	FHA 696 MF	Function	Function	X	X
Moisture probe for wood	FHA 636 MFx, FHA 696 MFS1	X	X	X	X
Material moisture sensor for granulates	FHA 696 GF1	X	X	X	×
Moisture in the soil	FDA 602 TM	×	X	X	×
Rotating vanes for air	FVAD 15 Sxxx, FVAD 15 MA1	X *	X *	X **	X
Differential pressure for Pitot tube	FDA 602 S1K. FDA 602 S6K	Range	X*	X**	X
Thermo-anemometer probe	FVAD 35 THxx	X*	X*	X**	x
Thermo-electric flow sensor	FVA 605 TAxx	X*	X*	X**	X
* An average value channel is not possible with	h flow measurement; (no start of contin	nuous or cyclic	measuring)		
** Smoothing is possible for 1 measuring channels	lel	-			
Dressure transducer for liquid					
Pressure transducer for liquid	ED 4 602 L ***	v	v	v	Y
The second means the second se	FDA 002 LXX ED 9214	~	Ň	[×]	[×]
Differential transmitter	FD 6214	~	Ň	[×]	[×]
Differential transmitter	FDA 002 D EDAD 22 EDAD 25M	~	Ň	[×]	[×]
Digital pressure sensor	FDAD 33, $FDAD 33WIED 9612 DDS / ADS / DDT$	~	Ň	[×]	[×]
Pressure transducer, for wall mounting	FD 8012 DPS / APS / DP1	A	×	×	×
Barometric pressure	FDA 012 SA	Kange	×	×	×
Barometric pressure, digital	FDAD I2 SA EDA(12 SP, EDA(02 SrrV)	A	×	×	×
Force	FDA6 12 SK, FDA 602 SXK	Kange	×	X	×
Push / pull force	FKA xxx	X *	X *	X *	X
* Only temporary zero-setting is possible; (no fi Tachometer	nal value adjustment)	•	•		•
Tachometer	FI14 9192	¥	¥	Y	¥
	1 0/11 / 1 / 2	~	r r	r	r

Measuring ranges, ALMEMO[®] 2450, 2490, 2470, 2590A series

	ALMEMO [®] series	2450 C	2490 B	2470	2590A
Sensor type / Measuring range	Type	C	D	A	A
Displacement					
Displacement transducer, potentiometric	FWA xxx T	X *	Χ*	Χ*	×
Displacement gauge, potentiometric	FWA xxx TR	X*	X*	X*	X
* Only temporary zero-setting is possible; (no f	inal value adjustment)				
Axial turbine flowmeter for liquids	FVA 915 VTHxxx	×	X	X	X
Flow sensor with temperature Electrical variables	FVA 645 GVx	X	×	X	×
Split-core-type transformer for AC current	FEA 6042, FEA 604 MN, FEA 6044 N	X X	X X	X X	X X
ALMEMO [®] measuring modules for		~	~	~	~
DC voltage, DC	ZA 9900 ABx, ZA 9901 ABx,	X	X	X	X
AC voltage, AC Meteorology	ZA 9903 ABx, ZA 9904 ABx	×	×	×	×
Meteo Multi (2 plugs)	FMA 510, FMA 510H	Function	X	X	X
Wind velocity sensor	FVA 615-2	X	X	X	X
Wind direction sensor	FVA 614	X	X	X	X
Rainfall and precipitation sensor	FRA 916, FRA 916 H	Function	Function	Χ*	X
Rainfall detector	FRA 616 D	X	X	X	X
Radiation probe head	FLA 613 x	X	X	X	X
Star pyranometer	FLA 628 S	×	×	X	×
* for ALMEMO® 2470-2 - function missing					
Indoor climate and air conditioning					
Globe thermometer Optical radiation	FPA 805 GTS	Range	×	×	×
Radiation sensor	FLA 603 x	X	X	X	X
Radiation sensor	FLA 613 x	X	X	X	X
Radiation sensor	FLA 623 x	X	X	X	X
Digital color temperature sensor	FLAD 23 CCTx	X	X	X	X
Water analysis		•	•	•	•
pH One-Bar Measuring Chain	FY 96 PH x	Adjustment	X	X	X
Redox-One-Bar Measuring Chain	FY 96 RXEK	Adjustment	×	X	×
Conductivity probe	FYA 641 LF xxx	Range	×	X	×
Oxygen sensor Gas concentrations in air	FYA 640 O2	Adjustment	×	×	X
Digital carbon dioxide sensor, hand-held	FYAD 00 CO2	X	X	X	X
Carbon dioxide probe	FYA 600 CO2	Range	X	X	X
Carbon monoxide probe	FYA 600 CO	X	×	X	X
Oxygen probe	FYA 600 O2	Adjustment	×	X	X
Ozone measuring transducer	FYA 600 O3	X	×	X	X
Gas probes	FYA 600 Ax	X	X	X	X
Infra-red temperature measurement					
ALMEMO [®] infra-red probe head	FIA 844	×	×	X	X
Infra-red probe	MR 7838, MR 7842	X	X	X	X
Hand-held IR device	MR 781420 SB	X	X	X	X
Digital IR sensor	FIAD 43	X *	X *	X *	X
* Emissivity cannot be modified					

Prerequisites missing for perfect functioning

- Range:	Measuring range missing or restricted -> Measured value cannot be shown.
- Function:	Function missing for showing sensor-specific measured data (e.g. average value / cycle)
	or for necessary programming
- Adiustment:	Measured value adjustment of this sensor is not possible (pressure, force, displacement, O2, pH, conductivity)

ALMEMO® 2450-1L



Compact ALMEMO[®] measuring instrument 1 measuring input, over 35 measuring ranges. Runs in battery mode

Technical data and functions

- Generously dimensioned 2-row segment display including units
- Easy and convenient to operate by means of 7 keys.
- Over 35 measuring ranges for
- Thermocouple and NTC sensors For the customer's own sensors ready-to-use ALMEMO[®] connectors are available. (see chapter 07)
- Atmospheric humidity sensor, capacitive, dewpoint sensor, water detection probe, moisture in wood FHA636MF (see chapter 08)
- Pressure transducer FDA602L/D, FD8214, FD8612, Tachometer, turbine flowmeter (see chapter 10) Current clamps FEA604, Voltage / current measuring modules ZA990xAB (see chapter 11)

- Meteorological radiation probe heads FLA613 (see chapter 12)
- Carbon dioxide sensor FYAD00CO2, Carbon monoxide probe and ozone probe (see chapter 15),
- ALMEMO[®] plugs with multi-point adjustment are supported.
 Measuring functions
- Measured value, zero-setting, saving of maximum / minimum values, hold function
- Test functions
- Segment monitoring, range monitoring, sensor breakage indication, battery voltage check and display.

Technical data

Measuring input	1 ALMEMO [®] socket	Resolution	(see page 01.08 / 01.09)	
Precision class	C (see page 01.06)	Linearization accuracy	(see page 01.08 / 01.09)	
Measuring rate	2.5 mops	Sensor power supply	9 V, maximum 0.5 A	
Measuring ranges (see 01 Fe-CuNi(J).	.05 / 01.06) NiCr-Ni(K), NiCroSil-NiSil(N),Fe-CuNi(L), Cu-CuNi(U), Cu-CuNi(T), PtRh10-Pt(S), -200 to +950 °C	Standard equipment LCD 7 segments	Measured value 5 characters, 15 mm Function 4 ¹ / ₂ characters, 9 mm Units 2 characters, 9 mm	
NTC Voltage	-20 to +100 °C -26 to +26 mV, -260 to +260mV, 0 to 2.6V	Keypad	9 symbols 7 silicone keys	
Current	0 to 26 mA, 4 to 20 mA Double connectors with 2 x differenti al voltage / differential current (input D - B) are not possible.	Power supply Battery set Current consumption Housing ABS (max 70 °C	3 AA alkaline batteries approx. 10 mA without input modules	
Humidity, capacitive 0 to 100 % RH, (% RH, HcRH, HRH) Dew point, mixture ratio, partial vapor pressure, enthalpy, rotating vanes, digital process (0 / 100 %), frequency, pulse, rotational speed, digital		Environmental conditions and general technical data see page 01.04 onwards		

Accessories	Order no
	Order no.
Rubberized impact protection, gray	ZB2490GS2
DIN rail mounting	ZB2490HS
Magnetic fastening	ZB2490MH
Instrument case	ZB2490TK2
Standard delivery	Order no.
Batteries, operating instructions, manufacturer's test certificate	
Compact measuring instrument ALMEMO [®] 2450-1L	MA24501L

DAkkS or works calibration KE90xx, electrical, for measuring instrument (see chapter "Calibration certificates"). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

ALMEMO® 2490-1L



ALMEMO[®] basic measuring instrument Ideal for all sorts of application, quick and easy to operate 1 measuring input, over 65 measuring ranges Runs in battery mode

Technical data and functions ALMEMO® 2490-1L

- Generously dimensioned 2-row static 7 / 16 segment display including units
- Easy and convenient to operate by means of 7 keys
- Over 65 standard measuring ranges

Measuring ranges as on page 01.08 - but

Measuring inputs

Precision class

Measuring rate

Battery set

Milliamperes DC

Sensor power supply

Current consumption

- Memory sufficient for 100 measured values, can be called up and viewed in the display
- Good measuring accuracy, measuring rate up to 2.5 measuring operations per second (mops)

1 ALMEMO® input socket

2.5 measuring operations per second

approx. 20 mA without input modules

B (see page 01.06)

3 AA alkaline batteries

9 V, maximum 0.5 A

-26 to +26 mA

Technical data ALMEMO[®] 2490-1L

- Support for ALMEMO[®] plugs with multi-point adjustment, special linearization, and special measuring ranges
- Measuring functions Measured value, zero-setting, sensor adjustment, saving of maximum / minimum values, memory for 100 values, cold junction compensation, and temperature compensation
- Test functions Segment monitoring, range monitoring, sensor breakage indication, battery voltage check and display

Standa	rd equipment		
LCD 7 segments		Measured value 5 characters, 15 mm	
		Function 4 ¹ / ₂ characters, 9 mm	
	16 segments	Units 2 characters, 9 mm	
		9 symbols	
Keypad		7 silicone keys	
Housin	g	ABS (maximum 70 °C)	
		127 x 83 x 42 mm (LxWxH)	
Environmental conditions and general technical data			

Environmental conditions and general technical data see page 01.04 onwards

Accessories ALMEMO [®] 2490-1L			Order n
DIN rail mounting Rubberized impact protection, green	ZB2490HS ZB2490GS1	Magnetic fastening Instrument case	ZB2490M ZB2490TK
DIN rail mounting		Rubberized protection	Magnetic fastening



ALMEMO® 2490-1L

Standard delivery

Order no.

Batteries, operating instructions, manufacturer's test certificate, Basic measuring instrument ALMEMO[®] 2490-1L MA24901L

DAkkS or works calibration KE90xx, electrical, for measuring instrument (see chapter "Calibration certificates"). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

ALMEMO[®] 2490A



ALMEMO[®] basic measuring instrument Ideal for all sorts of application, quick and easy to operate 1 or 2 measuring inputs, over 65 measuring ranges

Technical data and functions ALMEMO[®] 2490 series

- Generously dimensioned 2-row static 7 / 16 segment display including units
- Easy and convenient to operate by means of 7 keys
- Over 65 standard measuring ranges
- Memory sufficient for 100 measured values, can be called up and viewed in the display
- Good measuring accuracy, measuring rate up to 10 measuring operations per second (mops)
- Support for ALMEMO[®] plugs with multi-point adjustment, special linearization, and special measuring ranges
- Measuring functions : Measured value, zero-setting, sensor adjustment, saving of maximum / minimum values, memory for 100 values, cold junction compensation, and temperature compensation
- Test functions : Segment monitoring, range monitoring, sensor breakage indication, battery voltage check and display
- 2 ALMEMO[®] output sockets, suitable for all interface cables, network cables, trigger / relay cables *new*: Ethernet data cable ZA1945-DK
- Complete sensor and device programming via interface
- ALMEMO[®] DC socket for mains adapter.

Technical data ALMEMO® 2490 series

Precision class	B (see page 01.06)	Standard equipment	
Measuring rate	2.5 / 10 measuring operations per second	LCD 7 segments	Measured value 5 characters, 15 mm
Measuring ranges as on Milliamperes DC	page 01.08 / 01.09 - but -26 to +26 mA	16 segments	Function 4½ characters, 9 mm Units 2 characters, 9 mm 9 symbols
Measuring input		Keypad	7 silicone keys
2490-1A 2490-2A	1 ALMEMO [®] input socket 2 ALMEMO [®] input sockets, el. isol., with semicond. relays (50V)	Power supply: Battery set	3 AA alkaline batteries <i>new:</i> 12 VDC not electr. isolated ZA1312NA12
Additional channels	4 function channels, device-internal	Mains adapter	
Sensor power supply <i>new:</i> 9 V, maximum 0.4 A in battery mode new: 12 V maximum 0.4 A via mains unit		Current consumption	100 to 240 VAC to 12 VDC, 1.5 A approx. 20 mA without input modules
Outputs 2 ALMEMO® sockets, suitable for all interface cables		Environmental conditions see page 01.04 onwards	and general technical data





Basic measuring instrument, 2 measuring inputs with interface Runs in battery mode or via mains unit

Accessories			Order no.
DIN rail mounting Rubberized impact protection, green Magnetic fastening Instrument case Mains adapter 12 V, 1.5 A, with ALMEMO [®] plug DC adapter cable 10 to 30 VDC, 12 V / 0.25 A, e	g electrically isolated		ZB2490HS ZB2490GS1 ZB2490MH ZB2490TK2 ZA1312NA12 ZA2690UK
DIN rail mounting	Rubberized protection	Magnetic fastening	

Connecting cables

USB data cable, electrically isolated Ethernet data cable electrically isolated Analog output cable, -1.25 to +2.0 V, 0.1 mV / digit V24 data cable, electrically isolated Network technology, Bluetooth modules (see chapter "Networking")

Standard delivery	Order no.
Batteries, operating instructions, manufacturer's test certificate	
Basic measuring instrument ALMEMO [®] 2490-1A	MA24901A
Basic measuring instrument ALMEMO [®] 2490-2A	MA24902A

DAkkS or works calibration KE90xx, electrical, for measuring instrument (see chapter "Calibration certificates"). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Order no.

ZA1919DKU

ZA1945DK

ZA1601RK

ZA1909DK5

ALMEMO[®] 2470



ALMEMO[®] professional measuring instrument with data logger function

Functions for all application areas, 1 or 2 measuring inputs Also with integrated sensor for temperature, atmospheric humidity, atmospheric pressure

Technical data and functions, ALMEMO® 2470 series

- Segmented color display with bright, white illumination Clear and easy-to-understand display of programming and measured values in 5 different colors and alarm display on a red background
- In the event of a limit value being overshot / undershot various freely configurable alarm messages are available, namely acoustic signal, visual LED signal, alarm display on a red background.
- With the 2470-1S /-2S these alarm messages are also configurable for long-term recording; in sleep mode the messages remain active and the most recent measured value is displayed continuously.
- Good measuring accuracy, measuring rate up to 10 measuring operations per second (mops)

Technical data. ALMEMO[®] 2470 series

- More than 65 standard measuring ranges
- Support for ALMEMO[®] plugs with multi-point adjustment, special linearization, and special measuring ranges
- Easy and convenient to operate by means of 7 keys, with configurable locking for keys and functions
- Measuring functions : Maximum and minimum values, measured value smoothing, zero-setting, sensor adjustment
- Programming functions : Limit values, sensor correction with base value and factor
- All ALMEMO® functions programmable via interface
- Modern, compact housing

Precision class Measuring rate	A (see page 01.04) 2.5 / 10 measuring operations per second	Power supply Mains adapter	1 ALMEMO [®] DC socket ZA1312NA12 100 to 230 VAC
Sensor power supply Battery mode Sensor voltage 6 V, 400 mA 9 V, 300 mA and 12 V, 200 mA With mains adapter 12 V, 400 mA		DC adapter cable, el. isol. Current consumption (with Active without illuminati	ZA2690UK 10 to 30 V, 0.25 A out input and output modules) on approx. 12 mA
Standard equipment		Sleep mode	approx. 50 mA approx. 60 μA
Display 16 segments	Measured value 5 characters, 15 mm Units 2 characters, 9 mm Europian 416 characters, 9 mm	Housing	127 x 83 x 42 mm (LxWxH) ABS, 290g
/ segmentsFunction4½ characters, 9 mm21 symbols, Illumination2 RGB LEDsKeypad7 silicone keys		Environmental condition see page 01.04 onwards	as and general technical data

ALMEMO[®] 2470 series, accessories

Rubberized impact protection, gray Instrument case Mains adapter 12 V / 1.5 A



Automatic alarm (red background). Display shows incorrect measured value



ZB2490GS2

ZB2490TK2

ZA1312NA12

Dual display 1. Humidity Measured value overshoots limit value (red).

2. Temperature

DC cable 10 to 30 V, 12 V / 0.25 A, electr. isol. DIN rail mounting Magnetic fastening Order no. ZA2690UK ZB2490HS ZB2490MH



- 1. Measured value is inside limit values (green).
- 2. Peak value MAX overshoots limit value (red)

Programming of 1. Save-to-memory cycle

2. Sleep mode

∠. Sieep mode

ALMEMO[®] 2470-1S



Professional measuring instrument, 1 measuring input Data logger with integrated memory

Technical data and functions

- Technical data and functions as for ALMEMO® 2470 series
- Data logger functions: Internal EEPROM, memory cycle, realtime clock
- Long-term recording in sleep mode with AA batteries
- Operating time up to 1.5 years with memory cycle of 15 minutes and temperature / humidity sensor.

Technical data

Measuring inputs	1 ALMEMO [®] input socket
Outputs	ALMEMO [®] DC socket for mains adapter or USB cable with supply ZA 1919 DKU5
Memory, internal	EEPROM sufficient for 100,000 measured values
Date and time-of-day	Real-time clock, buffered by device battery
Power supply	3 AA batteries

ALMEMO® 2470-1SCRH



Professional measuring instrument, 1 measuring input, Data logger with integrated memory, Integrated sensor for temperature, atmospheric humidity, atmospheric pressure

Technical data and functions

- Technical data and functions, as for ALMEMO[®] 2470 series
- Data logger functions
- Internal EEPROM, memory cycle, real-time clock
- Long-term recording in sleep mode with AA batteries
- Operating time up to 1.5 years with memory cycle of 15 minutes and temperature / humidity sensor.

Technical data

Measuring inputs	1 ALMEMO [®] input socket	
Outputs	ALMEMO [®] DC socket for mains adapter or USB cable with supply ZA 1919 DKU5	
Memory, internal	EEPROM sufficient for 100,000 measured values	
Date and time-of-day Real-time clock, buffered by device battery		
Power supply 3 AA batteries		
Digital sensor for humidit	y / temperature / air pressure FH0D 46-C2, d in on the measuring instrument.	

General description and technical data (see chapter "Atmospheric humidity").

Connecting cable

USB data cable with 5-V power supply

Order no. ZA1919DKU5

Connecting cable

USB data cable with 5-V power supply

Order no.

ZA1919DKU5

Standard delivery

Order no.

Batteries, operating instructions, manufacturer's test certificate Professional measuring instrument ALMEMO® 2470-1S MA24701S

Standard delivery

Order no.

Batteries, digital plug-in sensor for temperature, atmospheric humidity and air pressure, operating instructions, manufacturer's test certificate. Professional meas. instrument ALMEMO® 2470-1SCRH **MA24701SCRH**

DAkkS or works calibration KE90xx, electrical, for measuring instrument (see chapter "Calibration certificates"). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.



Technical data and functions

Technical data Measuring inputs

Additional channels

Individual value memory

Outputs

Power supply

- Technical data and functions, as for ALMEMO® 2470 series
- Power supply, 3 AA rechargeable NiMH batteries, with charging via the device itself.

2 ALMEMO® input sockets

4 channels, device-internal

ALMEMO® sockets A1 and A2,

suitable for all output modules (analog, data, trigger, relay cables, etc.)

99 individual measured values3 AA rechargeable NiMH batteries

(see chapter "Networking")

Integrated charge circuitry

(e.g. difference)

el. isol., with semicond. relays (50 V)

Technical data and functions

- Technical data and functions, as for ALMEMO[®] 2470 series
- Power supply, 3 AA rechargeable NiMH batteries, with charging via the device itself
- Data logger functions: Internal EEPROM or external memory connector (accessory), memory cycle, real-time clock
- Long-term recording in sleep mode, internal memory, AA rechargeable NiMH batteries. Operating time up to 1 year with memory cycle of 15 minutes and temperature / humidity sensor.

Technical data

Measuring inputs	2 ALMEMO [®] input sockets el. isol., with semicond. relays (50 V)
Additional channels	4 channels, device-internal (e.g. difference)
Outputs	ALMEMO [®] sockets A1 and A2, suitable for all output modules (analog, data, trigger, relay cables, etc.) (see chapter "Networking")
Memory, internal EEPROM	sufficient for 100,000 measured values
Date and time-of-day	Real-time clock, buffered by device battery
Power supply	3 AA rechargeable NiMH batteries Integrated charge circuitry

Accessories	Order no.
Memory connector with micro SD card	ZA1904SD

Connecting cables	Order no.
USB data cable, electrically isolated	ZA1919DKU
USB data cable with 5-V power supply	ZA1919DKU5
V24 data cable, electrically isolated	ZA1909DK5
Ethernet data cable, electrically isolated	ZA1945DK
Analog output cable, -1.25 to +2.0 V, 0.1 mV / digit	ZA1601RK
Trigger and relay cable (2 relays, 500 mA, 50 V)	ZA1006EKG
Network technology, Bluetooth modules (see chapte	r "Networking")

Standard delivery

Connecting cables

USB data cable, electrically isolated

V24 data cable, electrically isolated Ethernet data cable, electrically isolated

USB data cable with 5-V power supply

Analog output cable, -1.25 to +2.0 V, 0.1 mV / digit

Trigger and relay cable (2 relays, 500 mA, 50 V)

Order no.

Order no.

ZA1919DKU

ZA1945DK

ZA1601RK ZA1006EKG

ZA1919DKU5 ZA1909DK5

Rechargeable batteries, operating instructions, manufacturer's test certificate, carry case, mains unit

Network technology, Bluetooth modules (see chapter "Networking")

Professional measuring instrument ALMEMO[®] 2470-2 MA24702KN

Standard delivery

Order no.

Rechargeable batteries, operating instructions, manufacturer's test certificate, carry case, mains unit

Professional measuring instrument ALMEMO® 2470-28 MA24702SKN

DAkkS or works calibration KE90xx, electrical, for measuring instrument (see chapter "Calibration certificates"). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

01.18

ALMEMO® 2590A



ALMEMO[®] professional measuring instrument with data logger function,

Comprehensive range of functions for all application areas, Graphics display for showing measured values and programming,

2 or 4 measuring inputs

Technical data and functions, ALMEMO[®] 2590A series

- Good measuring accuracy, measuring rate up to 10 measuring Function operations per second (mops) Maximum
- Over 65 standard measuring ranges
- Support for ALMEMO[®] plugs with multi-point adjustment, special linearization, and special measuring ranges
- Graphics display with white illumination, easy and convenient operation by means of 4 soft-keys and cursor block
- Clear and easy-to-understand menu system 3 measuring menus (1 menu can be freely configured by user from a range of 50 functions), measured values displayed numerically, 1 to 12 measured values can be displayed in two sizes or graphically in bar chart form.
- Intelligent sensor readings with sensor-specific functions old junction compensation, temperature compensation, and atmospheric pressure compensation
- Measuring functions Measured value, zero-setting, setpoint adjustment

Function menus Maximum value, minimum value, memory sufficient for 99 measured values, average value over time / individual values / measuring points, smoothing, volume flow with center point measuring, two-point adjustment, scaling, data logger with configuration menus

- Option VN Volume flow determined from matrix measuring as per DIN EN 12599
- Programming menus for clear and easy-to-understand sensor programming, range, units, designation, right through to special functions, configuration of device parameters and of output modules
- Choice of languages : German, English, French
- 2 ALMEMO[®] output sockets, suitable for digital interfaces, analog output, trigger input, alarm contacts, memory card
- External memory connector with micro SD can simply be plugged in.
- Sleep mode for long-term recording

Technical data ALMEMO® 2590A series

Precision class	A (see page 01.04)	Date and time-of-day	Real-time clock, buffered by battery
Measuring rate	2.5 / 10 measuring operations per second	Power supply	
Additional channels	4 function channels, device-internal	Battery set	3 AA alkaline batteries
Sensor power supply	6 / 9 / 12 V, maximum 0.5 A	Mains adapter	ZA1312NA12 100 to 240 VAC to 12 VDC 1.5 A
Outputs	2 ALMEMO [®] sockets, suitable for all output modules (analog / data / trigger / relay cables, memory, etc.)	DC adapter cable, electrically isolated ZA2690-UK 10 to 30 V	
Standard equipment Display	Graphics display, 128 x 64 pixels, 8 rows Illumination 2 white LEDs	Active mode With illumination Sleep mode	approx. 12mA approx. 32 mA approx. 0.05 mA
Keypad	7 silicone keys (of which 4 soft-keys)	Housing	127 x 83 x 42 mm (LxWxH) ABS, 290 g

Environmental conditions and general technical data see page 01.04 onwards

Serie ALMEMO® 2590A

Accessories	Order no.
Memory connector with micro SD (see page 06.02)	ZA1904SD
Mains adapter 12 V / 1.5 A	ZA1312NA12
DC adapter cable, 10 to 30 VDC, 12 V / 0.25 A, electrically isolated	ZA2690UK
Rubberized impact protection, green	ZB2490GS1
Magnetic fastening	ZB2490MH
DIN rail mounting	ZB2490H8
Instrument case	ZB2490TK2
Network technology, Bluetooth modules (see chapter "Networking")	
Connecting cables	Order no.
USB data cable, electrically isolated	ZA1919DKU
Ethernet data cable, electrically isolated	ZA1945DK
Analog output cable, electrically isolated, 1 x 20mA	ZA1601RI
Analog output cable, electrically isolated, 2 x 10V	ZA1602RU

Analog output cable, electrically isolated , 2 x 10V

V24 data cable, electrically isolated. Network technology, Bluetooth modules (see chapter "Networking")



ZA1909DK5

ALMEMO® 2590-2A



Professional measuring instrument, 2 measuring inputs, Data logger with external memory connector (accessory)

Technical data and functions

 Technical data and functions as for ALMEMO[®] 2590A series

Technical data

Technical data as for ALMEMO [®] 2590A series		
Measuring inputs 2 ALMEMO [®] input sockets,		
	el. isol., with semicond. relays (50V)	

Option	Order no.
Volume flow determined from matrix measuring as per DIN EN 12599 Temperature ranges for 8 refrigerants	OA2590VN SB0000R2
Standard delivery	Order no.

Measuring instrument, batteries, operating instructions, manufacturer's test certificate Professional measuring instrument ALMEMO[®] 2590-2A MA25902A

ALMEMO® 2590-4AS



Professional measuring instrument, 4 measuring inputs, Data logger with internal memory or external memory connector

Technical data and functions

- Technical data and functions, as for ALMEMO[®] 2590A series
- Internal EEPROM sufficient for 100 000 measured values, configurable as linear or ring memory

Technical data

Technical data as for Se	erie ALMEMO [®] 2590A series
Measuring inputs	4 ALMEMO [®] input sockets, el. isol., with semicond. relays (50V)
Memory, internal EEPI	ROM sufficient for 100,000 measured values

Option	Order no.
Volume flow determined from matrix measuring	
as per DIN EN 12599	OA2590VN
Temperature ranges for 8 refrigerants	SB0000R2

Standard deliveryOrder no.Measuring instrument, batteries, operating instructions,
manufacturer's test certificate.Professional measuring instrument
ALMEMO® 2590-4ASMA25904AS

Measuring instrument, batteries, rubberized impact protection ZB2490GS1, Mains unit ZA1312NA12, USB data cable ZA1919DKU, Case ZB2490TK2, Operating instructions, manufacturer's test certificate

Professional measuring instrument ALMEMO® 2590-4AS Case set MA25904ASKSU

DAkkS or works calibration KE90xx, electrical, for measuring instrument (see chapter "Calibration certificates"). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.



Humidity reading with further humidity variables, e.g. temperature, dew point, mixture ratio



Overview of all sensors connected



Temperature / humidity display in bar chart form



pH reading, measured value with automatic temperature compensation



Flow reading, measured value with automatic temperature compensation and atmospheric pressure compensation



Function menus

ALMEMO[®] 2690-8A



ALMEMO[®] precision measuring instrument with data logger function. Comprehensive range of functions for all application areas. Increased measuring accuracy, fast measuring rate. Generously dimensioned graphics display, bright illumination, 5 measuring inputs. Runs on rechargeable batteries, charging via the device itself

Technical data and functions ALMEMO[®] 2690-8A

- · Increased measuring accuracy and stability
- Fast measuring rate, up to 50 measuring operations per second With SD memory card, up to 100 mops, optional for 1 channel up to 500 mops
- 5 measuring inputs, electrically isolated
- Integrated atmospheric pressure sensor, for automatic pressure humidity variables
- Over 65 standard measuring ranges
- Support for ALMEMO[®] plugs with multi-point adjustment, special linearization, and special measuring ranges
- Option KL for independent multi-point adjustment or special linearization programmable in 30 points and management of calibration data saved in the sensor connector and the measuring instrument
- Option GT for higher measuring quality thanks to electrical isolation between measuring inputs and device power supply (device ground)
- Improved cold junction compensation with 2 sensors

- Data logger with internal EEPROM, sufficient for 200,000 measured values, configurable as linear or ring memory
- Memory connector with micro SD (accessory)
- · Sleep mode for long-term recording
- Generously dimensioned graphics display, bright illumination, large display of measured values
- compensation, inter alia for Pitot tube flow measurement and Measured values can be displayed graphically in line chart or bar chart form or numerically in various sizes.
 - 3 user-defined menus can be freely configured from a range of 50 functions.
 - Easy to operate by means of 4 soft-keys and cursor block, menu-guided with wizards and context-sensitive help windows
 - Choice of languages : German, English, French
 - 2 ALMEMO® output sockets, suitable for digital interfaces, analog output, trigger input, alarm contacts, memory card
 - Runs on rechargeable batteries (standard), high-speed charging in the device itself using the mains unit, included in delivery
 - · Modern housing with rubberized impact protection and folding stand.

Technical data

Precision class	AA (see page 01.04)	Keypad	9 tactile silicone keys (4 soft-keys)	
Measuring rate	(100), 50, 10 and 2.5 mops	Memory	EEPROM	
Measuring inputs	5 ALMEMO [®] input sockets		sufficient for 200,000 measured values	
Electrical isolation	with semiconductor relays (50 V)	Date and time-of-day	Real-time clock, buffered with battery	
Option GT	for analog sensors Additional electrical isolation between measuring inputs and power supply (device ground)	Power supply Rechargeable battery/ies Mains adapter	3 AA batteries NiMH or alkaline integrated, high-speed charging (2.5 hours) ZA1312NA12 100 to 240 VAC	
Additional channels	4 function channels, device-internal	1	to 12 VDC, 1.5 A electrically isolated	
Sensor power supply Rechargeable battery/ies	6 / 9 / 12 V, maximum 0.5 A	DC adapter cable	electrically isolated ZA2690-UK2 10 to 30 V, 1 A	
Mains adapter	12 V, maximum 0.5 A	Current consumption (with	out input and output modules)	
Atmospheric pressure sense Measuring range Accuracy	or Integrated 700 to 1100 mbar ±2.5 mbar (at 23 °C ±5 K)	Active mode With illumination Sleep mode	approx. 17 mA approx. 25 to 140 mA approx. 0.05 mA	
Outputs	2 ALMEMO [®] sockets, suitable for all output modules (analog / data / trigger /	Housing	209 x 107 x 54 mm (LxWxH) ABS, 570 g	
	relay cables, memory, etc.)	Environmental conditions and general technical data see page 01.04 onwards		
Graphics display Illumination	128 x 128 pixels, 16 rows 5 white LEDs, 3 brightness levels			

ALMEMO[®] 2690-8A



Precision measuring instrument, 5 measuring inputs Data logger with internal memory or external memory connector (accessory)

Accessories			Order no.
Memory connector with micro SD, including USB car DC adapter cable, 10 to 30 VDC, 12 V / 1 A, electrica Generously dimensioned carry case, aluminum profile	rd reader (see cl lly isolated frame / ABS	napter "General accessories")	ZA1904SD ZA2690UK2 ZB2590TK2
Connecting cables			Order no.
Ethernet data cable, electrically isolated Analog output cable, electrically isolated , 1 x 20mA Analog output cable, electrically isolated , 2 x 10V	ZA1945DK ZA1601RI ZA1602RU	Trigger and alarm cable (2 relays, 0.5 A, 50 V) Network technology, Bluetooth modules (see cha	ZA1006EKG pter "Networking")
Options			Order no.
Measuring module electrically isolated Multi-point adjustment, special linearization, managen Temperature ranges for 8 refrigerants Measuring rate 500 mops (SD card required) DIN rail mounting	nent of calibrati	on data	OA2690GT OA2690KL SB0000R2 SA0000Q5 OA2290HS
Standard delivery			Order no.
3 rechargeable NiMH batteries, rubberized protect Case ZB2490TK2, Operating instructions, manual Precision measuring instrument ALMEMO® 2	ction, mains un facturer's test o 2 690-8A in cas	nit ZA1312NA12, USB data cable ZA1919DK certificate e set	U, MA26908AKSU
as above but with RS232 data cable ZA1909DK5 Precision measuring instrument ALMEMO [®] 2	5 690-8A in cas	e set	MA26908AKS
DAkkS or works calibration KE90xx, e DAkkS calibration meets all the requ	lectrical, for me irements regard	asuring instrument (see chapter "Calibration certific ing test resources laid down in DIN EN ISO/IEC 17	cates"). 025.
Operating concept as for precision m	easuring i	nstruments ALMEMO® 2690, 2890 u	nd 5690 / 5790
* ALMEMO 2690-8 *	N R01 * 💶		0M * 🗪

* ALMEMO 2630-8 * MEASURING-Menus: Standard display UI Meas. Ualue correction U2 Averaging U3 Uolume flow Data logger Multi channel display *List of measuring Points Bar charts Line diagram Menul PROGRAMMING-Menus Menu2 ASSISTENT-Menus POFF #ON FMENUL MENU2	С Р REC COM IP PRO1 * 01: Velocity m/s 28.67 Мах Value: 31.34 mis Cycle-timer: 00:02:30 Un Memory free: 512.0 kB STOP MINU M PRINT ESG	C • REC COM INNI ROI * Time: 12:34:56 Date: 01.01.04 O1: 25.45 °C Nto: TemPeratur 11: 54.5 %H HorH r. Humidity 21: -12.5 °C H DT Dew Point STRET MENU M PRINT ESC C	C ► REC COM * ■ Meas.value list: Comment Time: 12:34:56 Date: 01.01.04 CVcle-Timer: 00:00:30 Sn 00: 23.12 °C TemPeratur 01: 11.37 mls Uelocitu 02: 12:34 ml U2.4 10: 536 SAH r.Humidity 20: 15.2 °C Dew Point 30: 11.2 glk a.Humidity STOP MANU F PRINT ESC
Menu selection	Standard display	Multi-channel display	Measuring points list
C ▶ REC COM I▶ R01 * ■ Time: 12:34:56 Date: 01.01.04 01: 21:87 °C TemPeratur 10:00 Nte °C 30.0 11: 78 ×H Rhumidty 0.0 × rH ×H 20.0 21: -14:2 °C Dew Point -20.0 H DT °C 0.0 31: 1.2 sik R.Humidty	C ► REC COM * ■ 40.0°C NICr 16:33	* ALMEMO 2690-8 * PROGRAMMING-Menus: Times, cucles Reporting to memory Output from memory Sensor programming Special functions Device conflauration Output modules Power supply	ALMEMO 2690-8 ASSISTENT-Menus: Start-Stop Roverasing Volume flow Scaling Sensor adjustment Limits. Alarm Analog outPut Thermal coefficient Wet-Bulb-Globe-TemPeratur
0.0 H ÁH GIK 10.0 START MANU M PRINT ESC	20.0°C M00 00:02 STOP M ESC	Menu1 ASSISTENT-Menus Menu2 MEASURING-Menus POFF *ON F MENU1 MENU2	Menu1 MEASURING-Menus Menu2 PROGRAMMIER-Menus POFF **ON F MENU1 MENU2

Programming rmenu

Bar chart

Line diagram

Assistent menu

ALMEMO® 2890-9



ALMEMO[®] precision measuring instrument with data logger function. Comprehensive range of functions for all application areas. Increased measuring accuracy, fast measuring rate. Generously dimensioned graphics display, bright illumination. 9 measuring inputs Runs on rechargeable batteries, charging via the device itself

Technical data and functions

- · Increased measuring accuracy and stability
- Fast measuring rate, up to 50 measuring operations per second With SD memory card, up to 100 mops, optional for 1 channel up to 500 mops
- 9 measuring inputs, electrically isolated
- Over 65 standard measuring ranges
- Support for ALMEMO[®] plugs with multi-point adjustment, special linearization, and special measuring ranges
- Option KL for independent multi-point adjustment or special linearization programmable in 30 points and management of calibration data saved in the sensor connector and the measuring instrument
- Higher measuring quality thanks to electrical isolation between Runs on rechargeable batteries (as standard), high-speed measuring inputs and device power supply (device ground)
- Improved cold junction compensation with 2 sensors
- Data logger with internal EEPROM, sufficient for 100,000 measured values, configurable as linear or ring memory
- Memory connector with micro SD (accessory)

- Sleep mode for long-term recording
- Generously dimensioned graphics display, bright illumination, large display of measured values
- · Measured values can be displayed graphically in line chart or bar chart form or numerically in various sizes.
- 3 user-defined menus can be freely configured from a range of 50 functions.
- Easy to operate by means of 4 soft-keys and cursor block, menu-guided with wizards and context-sensitive help windows
- Choice of languages : German, English, French
- 2 ALMEMO[®] output sockets, suitable for digital interfaces, analog output, trigger input, alarm contacts, memory card
- charging in the device itself using mains unit, included in delivery

Technical data

Precision class	AA (see page 01.04)	Keypad	9 membrane keys (4 soft-keys),
Measuring rate	(100), 50, 10 and 2.5 mops		thumb-wheel
	(measuring operations per second)	Memory, EEPROM	sufficient for 100,000 measured values
Measuring inputs	9 ALMEMO [®] input sockets	Date and time-of-day	Real-time clock, buffered with battery
Electrical isolation for analog sensors	with semiconductor relays (50 V) Additional electrical isolation between measuring inputs and power supply (device ground)	Power supply Rechargeable battery pack Mains adapter	6 rechargeable NiMH batteries, 1600 mA Integrated high-speed charging (2.5 h) ZB1112NA10 100 to 230 VAC
Additional channels	4 function channels, device-internal		to 12 VDC, 2 A electrically isolated
Sensor power supply Rechargeable battery/ies	9 or 12 V, maximum 0.5 A	DC adapter cable	electrically isolated ZB2590-UK 10 to 30 V, 1 A ut input and output modules)
Mains adapter Outputs	12 V, maximum 0.3 A 2 ALMEMO [®] sockets, suitable for all output modules (analog / data / trigger /	Active mode With illumination Sleep mode	approx. 37 mA approx. 45 to 100 mA approx. 0.05 mA
Standard equipment	relay cables, memory, etc.)	Housing	204 x 109 x 44 mm (LxWxH) ABS, 550g
Graphics display Illumination	128 x 128 pixels, 16 rows 5 white LEDs, 3 brightness levels	Environmental conditions and general technical data see page 01.04 onwards	

ALMEMO[®] 2890-9



Precision measuring instrument, 9 measuring inputs Data logger with internal memory or external memory connector (accessory)

Accessories	Order no.
Memory connector with micro SD, including USB card reader (see chapter "General accessories") DC adapter cable, 10 to 30 VDC, 12 V / 1 A, electrically isolated Generously dimensioned carry case, aluminum profile frame / ABS	ZA1904SD ZB2590UK ZB2590TK2
Connecting cables	Order no.
V24 data cable, electrically isolated Ethernet data cable, electrically isolated Analog output cable, electrically isolated , 1 x 20mA Analog output cable, electrically isolated , 2 x 10V Trigger and alarm cable (2 relays, 0.5 A, 50 V) Network technology, Bluetooth modules (see chapter ,,Networking")	ZA1909DK5 ZA1945DK ZA1601RI ZA1602RU ZA1006EKG
Options	Order no.
Multi-point adjustment, special linearization, management of calibration data Temperature ranges for 8 refrigerants Measuring rate 500 mops (SD card required)	OA2890KL SB0000R2 SA0000Q5
Standard delivery	Order no.
Rechargeable battery pack, mains unit ZB1112NA12, USB data cable ZA1919DKU, case ZB2490TK2,	

Precision measuring instrument ALMEMO[®] 2890-9

DAkkS or works calibration KE90xx, electrical, for measuring instrument (see chapter "Calibration certificates"). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.



MA28909

ALMEMO[®] 202



ALMEMO[®] professional measuring instrument, latest V7 generation with data logger function Two measuring inputs for all digital ALMEMO[®] D6 and D7 sensors, for ALMEMO[®] standard sensors with the DIGI measuring range. Special functions for applications using ALMEMO[®] D7 sensors

Technical data and functions

Professional measuring instrument from our latest V7 generation

Professional measuring instrument ALMEMO[®] 202 provides numerous outstanding functions for special applications using digital ALMEMO[®] D6 sensors and the latest ALMEMO[®] D7 sensors.

Brightly lit graphics display, easy and convenient operation by means of soft-keys

The white, illuminated graphics display ensures that functions and measured values can be viewed in the clearest way possible. The device is easy and convenient to operate by means of 4 soft-keys and a cursor block. The menu guidance is clearly structured and easy-to-understand.

The sensor display shows the measured values together with all relevant sensor-specific functions, e.g. temperature compensation, atmospheric pressure compensation. Measured values, peak values, average values, and limit values can all be displayed in an easy-to-understand way in various forms, namely lists or bar charts.

Users can even configure their own customized user menus from a range of 50 different parameters to display exactly those parameters required by a particular application. Choice of languages : German, English, French

End-to-end programming of all parameters for ALMEMO[®] D6 and D7 sensors

The ALMEMO[®] 202 professional measuring instrument provides a programming menu for the end-to-end programming of all the parameters needed for digital ALMEMO[®] D6 and D7 sensors. The required measuring ranges are selected (with ALMEMO[®] D7 sensors up to 10 measuring channels) and other relevant sensor parameters are configured, e.g. moving average, atmospheric pressure compensation, temperature compensation.

One measuring instrument for every need

This compact, handy device can, as an option, be fitted with rubberized impact protection for mobile use. The latest energysaving technology ensures long operating times. For stationary applications a DIN rail mounting is available.

Data logger for all storage applications

To save measured values an external memory is available in the form of a plug-in SD card.

For autonomous long-term monitoring the data logger can also be run in energy-saving sleep mode.

Two measuring inputs for all digital ALMEMO[®] D6 and D7 sensors

All new digital ALMEMO[®] D6 and D7 sensors for a wide variety of measurable variables can be connected and evaluated. ALMEMO[®] standard sensors with the DIGI measuring range can also be used, e.g. for crossflow turbines and high-voltage modules for thermocouples and DC and AC voltages.

The ALMEMO® 202 supports all ALMEMO® functions.

New digital ALMEMO® D7 sensors

With these digital ALMEMO[®] D7 sensors the ALMEMO[®] system is enhanced by many new functions and applications.

ALMEMO[®] D7 sensors operate via an all-digital interface to the ALMEMO[®] 202 professional measuring instrument ensuring high-speed serial transmission of all measured values.

The measuring ranges of ALMEMO[®] D7 plugs are independent of the ALMEMO[®] measuring instrument being used and can be expanded as and when required for new applications.

Measured values can be displayed with up to 8 digits (depending on range) and the units with up to 6 characters. Sensor designation and information can be up to 20 characters.

Each connected D7 sensor has its own processor. They all work in parallel at their own sensor-specific sampling rate. D7 sensors thus attain very high measuring speeds in dynamic measuring operations. Scanning times on the ALMEMO[®] 202 professional measuring instrument can be set individually for quick-acting and slow-acting sensors.

The ALMEMO[®] D7 plug can process up to 10 channels for measured values and function values. This includes new applications, especially for multi-purpose sensors (e.g. Meteo sensors) and for linking up to complex third-party devices (e.g. chemical analysers, power analysers).

Other equipment

The two ALMEMO[®] output sockets can be used to connect a PC / network and an ALMEMO[®] output interface with relays and analog output at the same time.

With option KL it is possible - for a digital ALMEMO[®] sensor (e.g. ALMEMO[®] D6 / D7 temperature or pressure sensors) - to program multi-point adjustment or linearization in the ALMEMO[®] plug itself. This option is possible with all digital ALMEMO[®] plug versions. Standard connector (DIGI), ALMEMO[®] D6 and D7 plugs.



ALMEMO[®] 202



Professional measuring instrument, latest V7 generation Two measuring inputs for all digital ALMEMO® D6 and D7 sensors for ALMEMO® standard sensors with the DIGI measuring range Data logger with external memory connector (accessory)

Technical data

Technical data		Keypad	7 silicone keys (of which 4 soft-keys)
Measuring inputs	2 ALMEMO [®] input sockets for all digital	Date and time-of-day	Real-time clock, buffered by device battery
	ALMEMO [®] D6 and D7 sensors and for ALMEMO [®] standard sensors	Memory, internal	99 measured values, can be called onto display
with the DIGI measuring range Precision class depends on the digital ALMEMO [®] sensor being used		External mem. (accessory)	ALMEMO [®] plug-in memory with micro SD card, 512 MB (sufficient for up to 30 million measured values)
Measuring rate	total sampling rate up to 1000 mops	Power supply	
for ALMEMO® D6 se	ensors and ALMEMO [®] standard sensor (DIGI):	Battery set	3 AA alkaline batteries
10 and 2.5 mops, for ALMEMO [®] D7 sensors: up to 1000 mops (depending on sensor)		Mains adapter	ZA1312NA12 100 to 240 VAC to 12 VDC, 1.5 A electrically isolated
Channels	Up to 20 measuring channels with ALMEMO [®] D7 sensors	DC adapter cable	ZA2690-UK 10 to 30 V, 0.25 A electrically isolated
Sensor power supply	6 / 9 / 12 V, maximum 0.4 A	Current consumption (with	nout input and output modules)
Outputs	2 ALMEMO [®] sockets, suitable for all output modules (analog / data / trigger /	 Active mode approx. 35 mA With display illumination approx. 70 mA Sleepmode approx. 0.05 mA 	
Standard equipment	relay cables, etc.)	Housing	127 x 83 x 42 mm (LxWxH) ABS Weight 290 g
Display	Graphics display, 128 x 64 pixels, 8 rows Illumination 2 white LEDs	Environmental conditions and general technical data see page 01.04 onwards	

Accessories

Mains adapter 12 V / 1.5 A DC adapter cable, 10 to 30 VDC, 12 V / 0.25A, electrically isolated Rubberized impact protection, gray Magnetic fastening DIN rail mounting Instrument case Network technology, Bluetooth modules (see chapter "Networking")

Connecting cables

USB data cable, electrically isolated Ethernet data cable, electrically isolated Analog output cable, electrically isolated, 1 x 20mA Analog output cable, electrically isolated, 2 x 10V V24 data cable, electrically isolated Network technology, Bluetooth modules (see chapter "Networking")

Option	Order no.
Multi-point adjustment and / or linearization can - with all digital ALMEMO® plug versions - be programmed by users themselves	OA202KL
Standard delivery	Order no.
Measuring instrument, batteries, operating instructions, ALMEMO [®] 202 professional measuring instrument	MA202

MA202

Order no. ZA1312NA12

ZA2690UK ZB2490GS2

ZB2490MH

ZB2490HS ZB2490TK2

Order no.

ZA1919DKU ZA1945DK

ZA1601RI

ZA1602RU

ZA1909DK5



ALMEMO[®] 204



ALMEMO[®] data logger, professional measuring instrument of the latest V7 generation.

Four measuring inputs for all digital ALMEMO[®] D6 and D7 sensors, for ALMEMO[®] standard sensors with the DIGI measuring range.

Applications

ALMEMO® devices can be used for a variety of applications, examples::

Monitoring the indoor climate conditions: temperature, air humidity, CO₂ level, air flow.

Measuring the illumination and the UV exposure at the workplace: illuminance in lux, UV index.

Mobile measurements in ventilation systems: air velocity, temperature, air humidity.

Meteorological station with meteo multi sensor and radiation sensors: air velocity, wind direction, temperature, air humidity, atmospheric pressure, global radiation, UV radiation, UV index.

Monitoring temperatures in test stands and in industrial processes: temperature, non-contact measurement (infrared sensor).

Mobile test measurement in heating furnaces and climatic chambers: temperature, air humidity, dew point, absolute humidity.

Measuring the quality of deionized process water (ultrapure water): electrical conductivity in the lower range of few µS/cm.

Test measurement of process water and waste water in industry (i.a. chemistry, pharmacy, paper, food): pH value, redox value, electrical conductivity, temperature. Test measurements in compressed air systems: fast pressure measurement (up to 500 mops), dew point measurement (residual moisture).

Measuring AC and DC voltage signals with high galvanic isolation: voltage/power/output DC (up to 1000 mops), true RMS value AC.

Technical data and functions

Data logger of the latest V7 generation

The professional measuring instrument ALMEMO[®] 204 provides numerous outstanding functions for special applications using digital ALMEMO[®] D6 sensors and the latest ALMEMO[®] D7 sensors.

Four measuring inputs for all digital ALMEMO[®] D6 and D7 sensors

All new digital ALMEMO[®] D6 and D7 sensors for a wide variety of measurable variables can be connected and evaluated. ALMEMO[®] standard sensors with the DIGI measuring range can also be used, e.g. for crossflow turbines and high-voltage modules for thermocouples, and DC and AC voltages. The ALMEMO[®] 204 supports all ALMEMO[®] functions.

New digital ALMEMO® D7 sensors

With these digital ALMEMO[®] D7 sensors the ALMEMO[®] system is enhanced by many new functions and applications. ALMEMO[®] D7 sensors operate via an all-digital interface to the ALMEMO[®] 204 data logger ensuring high-speed serial transmission of all measured values. Each ALMEMO[®] D7 sensor has its own processor. They all work in parallel at their own sensor-specific sampling rate. D7 sensors thus attain very high measuring speeds in dynamic measuring operations.

Digitize and calibrate the existing sensor technology

Using the ALMEMO[®] V7 input plugs the existing sensor technology can easily be digitized. For digital sensors the overall accuracy of the measurement is independent from the ALMEMO[®] V7 display device / data logger. The complete measuring chain, consisting of sensor and connected ALMEMO[®] D7 measurement plug, can be calibrated. The accuracy during the calibration process can be increased by using multi-point adjustment.

Data logger for all storage applications

To save measured values a large flash memory is integrated. For monitoring tasks it can also be configured as a ring memory.

For larger amounts of data, an external memory is available featuring a plug-in SD card.

For autonomous long-term monitoring the data logger can also be run in energy-saving sleep mode.

One measuring instrument for every need

This compact, handy device can, as an option, be fitted with rubberized impact protection for mobile use. The latest energy saving technology ensures long operating times. For stationary applications a H-rail mounting is available.



Bright graphics display, easy and convenient operation by End-to-end programming of all parameters for ALMEMO® means of soft-keys

The white, illuminated graphics display ensures that functions and measured values can be viewed in the clearest way possible. The device is easy and convenient to operate by means of 4 softkeys and a cursor block. The menu guidance is clearly structured and easy to understand.

Users can even configure their own customized user menus from a range of 50 different parameters to display exactly those parameters required by a particular application. Choice of languages: German, English, French.

D6 and D7 sensors

The ALMEMO® 204 professional measuring instrument provides a programming menu for the end-to-end programming of all the parameters needed for digital ALMEMO® D6 and D7 sensors.

Other equipment

The two ALMEMO® output sockets can be used to connect a PC / network and an ALMEMO[®] output interface with relays and analog output at the same time. With option KL it is possible - for a digital ALMEMO[®] sensor (i.a. ALMEMO[®] D6 / D7 temperature or pressure sensors) to program multi-point adjustment or linearization in the ALMEMO® plug itself.

Accessories	Order no.
Memory plug with Micro-SD incl. USB card reader (see chapter General Accessories)	ZA1904SD
Mains adapter 12 V / 1.5 A	ZA1312NA12
DC adapter cable, 10 to 30 VDC, $12 V / 0.25A$, electrically isolated	ZA2690UK
Rubberized impact protection, gray	ZB2490GS2
Magnetic fastening	ZB2490MH
DIN rail mounting	ZB2490HS
Instrument case	ZB2490TK2

Order no.
ZA1919DKU
ZA1945DK
ZA1601RI
ZA1602RU
ZA1909DK5

ALMEMO® 204



Data logger, professional measuring instrument, latest V7 generation Four measuring inputs for all digital ALMEMO[®] D6 and D7 sensors, for ALMEMO[®] standard sensors with the DIGI measuring range Data logger with internal memory or with external memory connector (accessory)

Technical data

Measuring inputs:	4 ALMEMO [®] -input sockets for all digital ALMEMO D6 and D7 sensors and for ALMEMO [®] standard sensors with the DIGI measuring range	Standard equipment:		
		Display:	Graphics display, 128 x 64 pixels, 8 rows Illumination: 2 white LEDs	
		Keypad:	7 silicone keys (of which 4 soft-keys)	
Precision class:	depends on the digital ALMEMO [®] sensor used	Date and time-of-day:	Real-time clock, buffered by device battery	
Measuring rate: for ALMEMO [®] D6 sen	total sampling rate up to 1000 mops sors and ALMEMO [®] standard sensor (DIGI):	Single value memory, internal: 10 measured values, can be called onto display		
for ALMEMO [®] D7 sen	10 and 2.5 mops, sors: up to 1000 mops (depending on sensor).	Memory:	8 MB internal, approx. 400 000 measured values	
Channels:	up to 40 measuring channels (depending on sensor)		(depending on number of channels)	
		Power supply:		
Sensor power supply:	6 / 9 / 12 V, maximum 0.4 A	Battery set:	3 AA alkaline batteries	
Outputs:	2 ALMEMO® sockets suitable for all output modules (analog / data / trigger / relay cables, etc.)	Mains adapter:	ZA1312NA12 100 to 240 VAC to 12 VDC, 1.5 A galvanically isolated	
		DC-adapter cable galvanical	ly isolated: ZA2690-UK, 10 to 30V, 0.25A	
		Current consumption (witho Active mode: with display illumination: Sleep mode:	ut input and output modules): approx 35mA approx. 70mA approx. 0.05 mA	
		Housing:	127 x 83 x 42 mm (LxWxH), ABS Weight 290g	
		Environmental conditions ar see page 01.04 onwards	nd general technical data	

Option	Order no.
Multi-point adjustment and / or linearization can - with all digital ALMEMO® plug versions - be programmed by users themselves	OA204KL
Standard delivery	Order no.
Measuring instrument, batteries, instruction manual, data logger,	
ALMEMO® 204 professional measuring instrument	MA204
Measuring instrument, batteries, rubberized impact protection ZB2490GS1,	
mains adapter ZA1312NA12, USB data cable ZA1919DKU, device case ZB2490TK2,	
instruction manual, data logger,	
ALMEMO [®] 204 professional measuring instrument in a carrying case kit	MA204KSU
mains adapter ZA1312NA12, USB data cable ZA1919DKU, device case ZB24901K2, instruction manual, data logger, ALMEMO [®] 204 professional measuring instrument in a carrying case kit	MA204KSU
ALMEMO[®] 710



Data logger from our latest V7 generation

Data logger ALMEMO $^{\ensuremath{\circledast}}$ 710 offers outstanding functions - thanks to our latest D7 sensors.

High-quality display - easy and convenient touchscreen operation

The brightly illuminated, generously dimensioned 5.7-inch color graphics display shows all measured values and functions clearly and precisely. The device is operated easily and conveniently via touchscreen. The menu guidance system, incorporating wizards and help windows, has a clear, straightforward structure.

Measured values, peak values, average values, and limit values can all be displayed in an easy-to-understand way in various forms, namely list, bar chart, or line graph (up to 5 lines).

Users can even configure their own customized user menus to display those parameters required by a particular application. Choice of languages : German, English, French, Czech

One measuring instrument for every use

The measuring instrument is enclosed in a handy, compact housing with rubberized impact protection. This device can be used in a wide variety of ways, in mobile applications or as a desktop unit, on a folding stand or as a stationary unit in a wallmounted housing.

It incorporates a powerful rechargeable lithium battery to ensure a long operating time.

Data logger for all storage applications

For the purpose of saving measured values the device incorporates an 8-MB flash memory. This can also be configured as a ring memory for monitoring tasks.

To save larger data quantities an external memory is available in the form of a plug-in SD card.

For autonomous long-term monitoring the data logger can also be run in energy-saving sleep mode.

Measuring inputs for 10 ALMEMO® sensors, all generations Data logger ALMEMO® 710 incorporates 10 measuring inputs. All new and already existing sensors designed for any measurable variable can be connected and evaluated.

Sensors using analog signals pass via the integrated high-speed, high-resolution A/D converter. Additional electrical isolation between measuring inputs and power supply (device ground) increases measuring quality.

Digital D6 and the latest digital D7 sensors transfer measured values to the measuring instrument directly in digital form.

The measuring instrument supports all ALMEMO^{\otimes} plug connectors and sensor functions. Digital D6 / D7 sensors can be configured directly via the touchscreen.

ALMEMO[®] precision measuring instrument, latest V7 generation With data logger function and touchscreen. Comprehensive range of functions for all application areas. Increased measuring accuracy, fast measuring rate. 10 measuring inputs

New digital ALMEMO® D7 sensors

With these digital ALMEMO[®] D7 sensors the ALMEMO[®] system is enhanced by many new functions.

They operate via an all-digital interface to the ALMEMO[®] 710 measuring instrument ensuring high-speed serial transmission of all measured values.

The measuring ranges of ALMEMO[®] D7 plugs are independent of the measuring instrument and can be expanded as and when required for new applications.

Measured values can be displayed with up to 8 digits (depending on range) and the units with up to 6 characters. Sensor designation and information can be up to 20 characters.

The ALMEMO[®] D7 sensor has its own processor. These all work in parallel at their sensor-specific sampling rate. D7 sensors thus attain very high measuring speeds in dynamic measuring operations. Scanning times on the ALMEMO[®] 710 can be set individually for quick-acting and slow-acting sensors.

The ALMEMO[®] D7 plug can process up to 10 channels for measured values and function values. This includes new applications, especially for multi-purpose sensors (e.g. Meteo sensors) and for linking up to complex third-party devices (e.g. chemical analysers, power analysers).

Other equipment

With 3 ALMEMO[®] output sockets it is possible to connect simultaneously a PC / network, an ALMEMO[®] output interface with relays and analog output, and an SD memory card.

The ALMEMO[®] 710 incorporates an atmospheric pressure sensor to ensure automatic pressure compensation for measuring operations involving inter alia air flow or humidity variables.

With option KL it is possible - for an ALMEMO[®] sensor (e.g. temperature or pressure sensors) - to program multi-point adjustment or linearization in the ALMEMO[®] plug itself.

This option is possible with all ALMEMO[®] plug versions.

Standard connector (analog or DIGI), ALMEMO[®] D6 and D7 plugs..



ALMEMO® 710



Precision measuring instrument, latest V7 generation, 10 measuring inputs Data logger with internal memory or external memory connector (accessory)

Technical data

Measuring inputs	10 ALMEMO [®] input sockets for ALMEMO [®] sensors, all generations analog sensors, D6 and D7 sensors	Illumination Keypad	white LED, dimmable Capacitive touchscreen and 3 additional touch keys
Precision class	AA (see page 01.04)	Memory	8-MB flash memory
Total sampling rate:	up to 2000 measurements/s		(400,000 up to 1.5 million meas. values)
Measuring rate for analog	sensors, D6 sensors 2.5 / 10 / 50 / 100 mops	Date and time-of-day	Real-time clock (4.7 ppm) buffered with lithium battery
	(measuring operations per second)	Power supply	
Electrical isolation	with semiconductor relays (50 V)	Rechargeable battery/ies	2 rechargeable lith. batteries, total 15.6 Ah Integrated, high-speed charging (3 hours)
for analog sensors	measuring inputs and power supply (device ground)	Mains adapter	ZA1312NA11 100 to 240 VAC to 12 VDC, 2.5 A, electr. isol.
Channels	nnels Up to 100 measuring channels per device		out input and output modules)
Sensor power supply	6/9/12 V, maximum 2 x 400 mA	Active mode Sleep mode	approx. 300 to 500 mA approx. 0.05 mA
	12 V, maximum 2 x 400 mA	Housing	222 x 169 x 61 mm (WxDxH) 1200 g
Atmospheric pressure sens	sor Integrated, meas. range 700 to 1100 mbar ± 2.5 mbar (at 23 °C ± 5 K)		with rubberized impact protection
Outputs	3 ALMEMO® sockets, suitable for all output modules (data / analog / trigger /	ALMEMO [®] 710 ALMEMO [®] 710 WG	with folding stand with DIN rail fixture for wall-mounting, connections facing downwards
Standard equipment Display	relay cables, memory connector, etc.)	Environmental condition see page 01.04 onwards	s and general technical data
Graphics display	5.7-inch TFT LCD VGA, 640 x 480 pixels		

Accessories	Order no.
Memory connector with micro SD, including USB card reader (see chapter "General accessories")	ZA1904SD
Large carry case, aluminum profile frame / ABS, inside dimensions 48 x 35 x 6+6 cm (WxDxH)	ZB2590TK2

Connecting cables	Order no.
Ethernet data cable, electrically isolated	ZA1945DK
Analog output cable, electrically isolated, 1 x 20mA	ZA1601RI
Analog output cable, electrically isolated, 2 x 10V	ZA1602RU
Trigger and alarm cable (2 relays, 0.5 A, 50 VDC)	ZA1006EKG
Note on WinControl measuring software	

As measuring software WinControl is suitable for current version 7 and above. Variants and description (see chapter "Software").

Option	Order no.
Multi-point adjustment and / or linearization can - with all ALMEMO [®] plug versions - be programmed by users themselves Temperature ranges for 8 refrigerants	OA710KL SB0000R2
Standard delivery	Order no.
USP data apple 7A 1010 DKU Maing unit 7A 1212 NA 11 Manufacturar's test continents	

USB data cable ZA1919DKU, Mains unit ZA1312NA11, Manufacturer's test certificateMA710Mobile device with folding stand, in case ZB9710TK Precision measuring instrument ALMEMO® 710MA710Stationary device with wall-mounting, Precision measuring instrument ALMEMO® 710WGMA710WG

DAkkS or works calibration KE90xx, electrical, for measuring instrument (see chapter "Calibration certificates"). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

ALMEMO[®] 710 Clear, precise display - easy and convenient touchscreen operation

< Bac	k sensor channels	🔧 🗠	4 🕕 🌶	21.01.12 13:34	
мо	FHA746-2	value	max	min	
0.0	T, t	123.4 °C	234.6	79.4	>
0.1	RH, Uw	56.8 %rH	67.3	48.9	>
0.2	DT, td	15.2 °C	23.5	11.7	>
0.3	MH, r	11.2 g/kg	14.4	9.3	>
0.4	VP, e	8.8 mbar	9.4	4.6	>
0.5	AH, dv	8.2 g/m3	8.4	6.3	>
0.6	AP, p	998.8 mbar	999.8	834.9	>
<	•				
Stop	Manuell		×	adjustme	nts



List of active measuring channels

Display of measured values as a bar chart



< Back	chann	el indi	cation		X.	<u>~</u> (21.01.12 D 13:34 O
Channel	3.0 tem	peratu	re			chann	el select	•
channel i	ndication					*J CJ-t	emperat	ture
use ter	np. sens	or as e	xternal o	old ju	nction (*J)		
use ter	np. sens	orofc	onnecto	r as co	old junc	tion (#J)		
conver	flow par	amete	rs to sta	ndard	(#N)			
q v	v e		r t		z	u	i	о р
а	S	d	f	g	h	j	k	1
<u>↑</u>	у	х	с	۷	b	n	m	OK
~	123/;					Clr	÷	UK

Display of measured values as a line graph

Keypad for programming

< Back measuring channel $\sqrt{21.01.12}$ \sim 13.34	< Back adjustments	21.01.12 D 13:34 O
	Sensor adjustments	>
M0 0.1 mixture ratio	channel functions	>
	display adjustments	>
$\gamma \gamma \Delta^{-1}$	(B) data logger	>
	BBB output modules	>
H AH Max 45.4 Min 9.4	device adjustments	>
atmospheric pressure compensation 943.5 mbar	Locking mode	>
	power supply	>
	memory	>
Start Manuell X adjustments	(i) info	>

Generously dimensioned display of measured values

Settings for all sensor and device parameters



ALMEMO[®] 470-1



Wireless data logger ALMEMO[®] 470-1.

Wireless ALMEMO[®] sensor for temperature, atmospheric humidity, atmospheric pressure. For monitoring the room air condition or with extended operating temperature range from -40 to +85 °C.

Wireless ALMEMO[®] interface for ALMEMO[®] D7 sensor. For various measurable variables.

Wireless ALMEMO[®] sensor for carbon dioxide, air temperature, air pressure.

Wireless data logger, Wireless ALMEMO® sensor and wireless ALMEMO® interface

ALMEMO[®] 470-1 wireless data logger

The professional measuring instrument ALMEMO[®] 470-1 is a professional wireless data logger, which receives the measured values with timestamp from wireless sensors that are positioned remotely, saves the measured values and shows them on graphical display. The acquisition of the measured values occurs in a cycle that can be individually adjusted to each wireless sensor: for measurements, i.a. in climate chambers, for long term measurements with wireless sensors in sleep mode, i.a for monitoring the room air condition or environmental measurements. The data logger ALMEMO[®] 470-1 is intended to be mounted on a wall. The power is supplied via an external mains unit. An additional rechargeable battery in the device serves as a temporary buffer in case of power failure or during a brief mobile usage.

Reliable radio transmission build upon a star-shaped and meshed net structure

To provide wireless communication, the data logger ALMEMO[®] 470-1 operates in the 2.4 GHz frequency band. To increase the wireless range and the transmission reliability, the wireless sensors automatically configure themselves as a star-shaped and meshed net structure. Repeater functionality is integrated in each wireless sensor by default, so the sensor can forward data from adjacent wireless sensors to the data logger. This means that more distant sensors, which do not have a wireless connection to the data logger, can still be integrated into the wireless net. The transmission power of the network is configurable in the data logger to 1, 10, or 100mW such that local networks in the immediate neighborhood as well as long distance networks are possible.

Wireless ALMEMO[®] sensor for temperature, atmospheric humidity, and atmospheric pressure.

The wireless sensors operate with a plugged-on digital multisensor module for temperature, atmospheric humidity, and atmospheric pressure. The sensor module has a data medium on which all sensor specific data, such as serial number, adjustment data, and calibration data, is saved. The sensor module can therefore be replaced any time.

For monitoring the room air condition or with extended operating temperature range from -40 to +85 °C.

The standard version of the wireless sensor is used for monitoring the room air condition. The version with an extended operating temperature range from -40 to +85 °C and splashwater protection is used i.a. for measurements in conditioning and climate chambers or for outdoor tasks in the environmental measurement technology.

Wireless ALMEMO[®] Sensor for indoor air quality: carbon dioxide, air temperature, air pressure.

The wireless sensors operate with a built-in sensor module for carbon dioxide, air temperature and air pressure. This allows simultaneous assessment of air quality by measuring CO_2 concentration and occupancy quality (comfort) by measuring air temperature. If several wireless sensors are distributed in the room, a meaningful room profile can be created via the time-synchronous measurement; There is no need for complex wiring!

Wireless ALMEMO[®] interface for ALMEMO[®] D6 and D7 sensors. For a vast variety of measurable variables.

The digital wireless interface broadens the range of applications considerably. Almost all ALMEMO[®] D6 and D7 sensors for various measurable variables can be connected via the integrated ALMEMO[®] input socket to the wireless interface and their measured values can be transferred over the air to the wireless data logger. This way the amount of CO₂ in the atmosphere, surface temperatures on objects, or the illuminance at measuring locations can be recorded.

Power supply of the wireless sensors and the wireless interfaces

The wireless sensors and the interfaces are supplied by an integrated rechargeable battery. The rechargeable battery can be charged via the integrated micro USB port. A continuous power supply via mains unit is possible as well.

Long runtimes in battery mode with activated sleep mode For long-term applications, the measured values are recorded in the wireless sensor or wireless interface with a large measuring cycle and transmitted to the data logger. For battery operation, significantly extended runtimes are achieved by using the sleep

ALMEMO[®] V7

ALMEMO® Measuring Instruments

mode. In this energy saving mode, the power supply and the plug/sensor supply are switched automatically. In sleep mode, the wireless sensor cannot operate as a repeater (only possible in continuous operation).

Visualize measuring data on the data logger

To visualize measuring data, the display of the data logger features a list of the measuring channels as well as a single measurement value display. In addition, the user can configure his own individual display as a customer specific user menu on the data logger by only adding his own selection of measuring channels.

Evaluation and storage of the measured data.

Via an external PC measured data is recorded and visualized by the WinControl software. The data logger ALMEMO® 470-1 and the PC are either connected via USB interface or via Ethernet interface. An industrial SD card integrated in the data logger ensures a safe storage of the measured data. Additionally, the actual measured data is cached in every wireless sensor to make sure that the complete measured data is available also in case of a short-time failure of either the wireless connection or the data logger.

Configuration of the wireless system

The sensors in the wireless network are configured and managed on the data logger ALMEMO[®] 470-1 via the clear touch display. Various functions are available, i.a. to couple and de-couple the wireless sensors with the data logger or to configure the cycles and limit values of the wireless sensors. In addition, it is possible to add a comment to every wireless sensor to be able



ALMEMO® 470 Mesh-Viewer

to assign a particular measurement point to the sensors. The program ALMEMO[®] 470 Mesh-Viewer makes it possible to display the signal strength of every single sensor node / wireless sensor as well as the entire network topology on the PC. This, in combination with the configurable signal strength in the data logger, enables a fast and optimal installation of the wireless network.

Accessories for installing the components for different applications

Thanks to an integrated holder, the data logger ALMEMO[®] 470-1 can be mounted to the wall. Regarding the wireless sensors, different accessories for mounting the sensors are available: wall mount, suction cup fastening, magnetic mount, or rope to hang the sensors.



ALMEMO[®] V7



Wireless data logger for 10 wireless sensors. Interface to the PC for WinControl software for measured data scanning and measured value processing.

Technical data

Measuring inputs:	10 wireless sensors of type - wireless ALMEMO® sensor	Memory:	up to 2 million measured values, industrial flash memory as micro SD card.
	for atmospheric humidity, temperature and atmospheric pressure FH 1746-1Cx	Date and time-of-day:	Real-time clock (4.7 ppm) buffered with lithium battery
	- wireless ALMEMO [®] interface for ALMEMO [®] D6 and D7sensor ZA 1770-1IF	Power supply: Rechargeable battery:	5 rechargeable NiMH batteries AA (1900 mAh),
Channels:	up to 40 measuring channels	_	Failure buffer for up to 6 hours
Interfaces:	USB, Ethernet for connection to the PC and measured value scanning via WinControl	mains adapter:	in power saving mode ZB 1112-NA12 100 to 240 VAC to 12 VDC, 1.5 A, galvanically isolated,
Standard equipment:			
Display:	graphics display 5,7", TFT-LCD VGA 640x480, illumination while LED, dimmable	Protection class: Dimensions:	IP50 190 x 135 x 40 mm (WxHxD)
Keypad:	capacitive touch screen and 2 additional keys on front foil	Weight:	(without wall mount) ca. 0.8 kg (including rechargeable batteries)
		Ambient conditions see from page 01.04	

Accessories Order no. Base (snap-on) for ALMEMO* 470, desk form, for wall mounting or as table desk. ZB9470S Image: Control software for measured value scanning with protocol and functionality for ALMEMO 470 from program version Standard WC2 (or higher WC3/WC4) SW5600WC2 For further explanations and descriptions, see chapter Software SW5600WC2

Standard delivery

Order no.

MA4701

Wireless data logger ALMEMO[®] 470-1 with Ethernet interface and USB interface, SD memory, rechargeable battery. Including mains unit ZB1112NA12 and wall mount, incl. ALMEMO[®] 470 Mesh-Viewer

Wireless ALMEMO[®] sensor for atmospheric humidity, temperature, atmospheric pressure



Replacement multi-sensor module FH0D 46-C

Replacement sensor module FH0D 46-C2

- For room climate monitoring in production and storage.
- For measurements in climatic and conditioning chambers.
- For environmental measurements.
- Version with extended temperature range
- and splash water protection
- Sleep mode for long operating time with rechargeable battery

Technical data

Measuring input:	for 1 multi-sensor element for humidity, temperature and atmospheric pressure FH0D 46-Cx	mains adapter:	ZB 1505-NA1 100 to 240 VAC to 5 VDC, 2 A, galvanically isolated, via micro USB	
Channels:	4 measuring channels	Operating temperature:	-5 to +50 °C (standard version)	
Measuring ranges:	Temperature: see operating temperature Humidity: 5 98 % r.H.		-40 to +85 °C (version with extended temperature range)	
	Air pressure: 700 1100 mbar	Storage temperature:	-20 to +60 °C (standard version).	
Accuracy:	see sensor specification FH0D 46-Cx		-40 to $+85$ °C (version with	
Galvanic Isolation:	yes (wireless)		extended temperature range)	
Measuring cycle *:	10 s to 24 h	Housing: Protection class:	(with sensor)	
Output cycle*:	10 s to 24 h	FH 1746-1C4	IP54	
Interfaces:	Radio, repeater function integrated** USB for supply and update	FH 1746-1C2VR1 Dimensions:	IP20 (without mount)	
Standard equipment:		FH 1746-1C4	43 x 135+30* x 21 mm (WxHxD).	
Display: Keypad:	3 LEDs foil keypad	FH 1746-1C2VR1	(*filter cap) 43 x 135+50* x 21+50* mm (WxHxD). (*sensor tube)	
Memory:	ring memory for 128 measured values	FH 1746-1C2VR2	$43 \times 135+40^{\circ} \times 21+100^{\circ} \text{ mm} (WxHxD).$	
Date and time-of-day:	clock synchronization via data logger ALMEMO [®] 470-1	Weight:	(*sensor tube) approx. 0.1 kg	
Power supply:			(including rechargeable batteries)	
Rechargeable battery: 2 rechargeable NiMH batteries AA (1900 mAh)		* depending on the number of	f data logged with the data logger	
Operating time with rechargeable battery: depending on		ALMEMO [®] 470-1 connected wireless sensors		

measuring cycle, output cycle, sleep mode ** Repeater operation not in sleep mode

Standard delivery (Power supply unit see under accessories) Wireless ALMEMO [®] sensor (radio, repeater function integrated) with multi-sensor module for humidity, temperature and atmospheric pressure. Ring memory, integrated rechargeable battery.	Order no.
Straight sensor version, with protective cap PTFE. Standard version. Straight sensor version, with extended operating temperature range. Digital replacement multi-sensor module for humidity, temperature and atmospheric pressure (adjusted pluggable) for FH 1746-164	FH17461C4 FH17461C4HT FH0D46C
Angled sensor version, with short angled sensor tube, slotted sensor cover. Angled sensor version, with long angled sensor tube, slotted sensor cover. Digital replacement multi-sensor module for humidity, temperature and atmospheric pressure	FH17461C2VR1 FH17461C2VR2
(adjusted, pluggable) enclosed in slotted sensor cover for FH 1746-1C2x	FH0D46C2

DAkkS or works calibration KH9xxx, humidity, temperature and KD92xx, atmospheric pressure, for digital sensors (see chapter "Calibration certificates"). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025





• For ALMEMO® D6 and D7 sensors incl. sensor supply.

• Sleep mode for long operating time with rechargeable battery.

Measuring input:	1 ALMEMO® socket for ALMEMO® D6 or D7 sensors	Power supply: Rechargeable battery:	2 rechargeable NiMH batteries AA
Channels:	up to 10 measuring channels	-	(1900 mAh)
Accuracy:	see specifications of the ALMEMO [®] D7 sensor	 Operating time with rech 	argeable battery: depends on current consumption of the AI MEMO [®] D7 sensor
Galvanic isolation:	yes (wireless)	_	and the measuring cycle, output cycle,
Sensor supply:	6 V, 30 mA (operated with rechargeable battery or with mains adapter)	Mains adapter:	sleep mode ZB 1505-NA1 100 to 240 VAC to 5 VDC, 2 A, galvanically isolated,
Measuring cycle*:	10 s to 24 h		via micro USB
Output cvcle*:	10 s to 24 h	Operating temperature:	-5 to +50 °C
Interfaces:	Radio repeater function integrated**	Storage temperature:	-20 to +60 °C
	USB for supply and update	Housing:	
Standard equipment: Display: Keypad: Memory: Date and time-of-day:	3 LEDs foil keypad ring memory for 128 measured values clock synchronization via data longer ALMEMO® 470-1	 Protection class: Dimension: Weight: 	IP50 43 x 135 x 21 mm (WxHxD) (without mount) ca. 0.1 kg (including rechargeable batteries)
		* depending on the number	of data logged with the data logger

Technical data

ALMEMO® 470-1 connected wireless sensors ** Repeater operation not in sleep mode

Standard delivery (Power supply unit see under accessories)	Order no.
Wireless ALMEMO [®] Interface (radio, repeater function integrated) with 1 ALMEMO [®] input socket for 1 ALMEMO [®] D6 or D7 sensor. Ring memory, integrated rechargeable battery.	ZA177011F

Accessories for wireless ALM	MEMO [®] sensor	and wireless ALMEMO [®] interface	Order no.
For battery charge respectively permanent sup Switch-mode power supply / connector version	pply: pn, 100 to 240 V AC / 5	V DC including cable with micro USB plug	ZB1505NA1
Wall mount: mounting plate (including magnet). Dimension: 35 x 50 mm (WxH). Suction cup fastening: 2 suction cups with mount (including magnet). Dimension: approx. 50 x 110 mm (WxH). Magnet mount: round magnet (including fastening screw). Dimension: Ø 31 mm.			ZB9700WH ZB9700SH ZB9700MH
Magnet mount	Mounting plate	Suction cup fastening	

ALMEMO[®] V7



Wireless ALMEMO[®] Sensor for Carbon Dioxide, Temperature and Air Pressure FY 1700-1CO2M0B05



- To assess the air quality via the measurement of the CO_2 concentration.
- At the same time to assess the quality of stay (comfort) via the measurement of air temperature.
- Sleep mode for long operating time with rechargeable battery.

Technical data

Measuring input:	built-in multi-sensor element for carbon dioxide, temperature and air pressure
Galvanic Isolation:	yes (wireless)
Channels:	up to 4 measuring channels
measuring ranges:	CO ₂ : up to 5000 ppm temperature: -5 to +50 °C Air pressure: 700 to 1100 mbar
Accuracy:	CO_2 : $\pm(50 \text{ ppm} + 3 \% \text{ of mesured value})$ temperature: typical $\pm 0.5 \text{ °C}$ (at 25 °C) air pressure: typical $\pm 2 \text{ mbar}$
Nominal conditions:	25 °C , 1013 mbar
Ansprechzeit t63:	140 s
Response time t63:	140 s
Switch-on time:	15 s
Refresh rate:	15 s for all 3 channels
Measuring cycle*:	10 s to 24 h
Output cycle*:	10 s to 24 h
Interfaces:	Radio, repeater function integrated** USB for supply and update
Standard equipment:	
Display:	3 LEDs
Keypad:	foil keypad
Memory:	ring memory for 128 measured values

Date and time-of-day:	clock synchronization
Dute and time of aug.	via data logger ALMEMO [®] 470-1
Power supply:	
Rechargeable battery:	2 rechargeable NiMH batteries AA (1900 mAh)
Operating time with recha	rgeable battery: depending on
mains adapter:	measuring cycle, output cycle, sleep mode ZB 1505-NA1 100 to 240 VAC to 5 VDC, 2 A, galvanically isolated, via micro USB
Operating temperature:	-5 to +50 °C 0 to 95 % r.H. (non condensing) 700 to 1100 mbar
Storage temperature:	-20 to +60 °C
Housing:	
Protection class: Dimensions:	IP20 43 x 186* x 22 mm (WxHxD) (without mount) (*incl. protective cap)
Weight:	approx. 0.1 kg (including rechargeable batteries)

* depending on the number of data logged with the data logger ALMEMO[®] 470-1 connected wireless sensors

** Repeater operation not in sleep mode

Order no.

Wireless ALMEMO[®] sensor (repeater function integrated) with built-in multi-sensor element for carbon dioxide, temperature and air pressure, ring memory, built-in rechargeable battery

Standard delivery (Power supply unit see under accessories)

FY17001CO2M0B05

10/2021 • We reserve the right to make technical changes

ALMEMO[®] 500



ALMEMO[®] precision measuring instrument and data logger, up to 90 measuring inputs. Comprehensive functions covering all application areas. Tablet control via app.



Solving complex measuring tasks using the ALMEMO® 500

The increasing digitalization and networking changes the entire chain of production. This also applies to measuring instruments that must be able to integrate themselves into existing networks – Keyword Industry 4.0. Our new web-based technology positions us future-proof for the era of increasing networking.

Our customer receives a scalable system for recording numerous measuring points with maximum precision. The device can be controlled via tablet and state-of-the-art interfaces such as USB. A web service makes the measurement data accessible anywhere and anytime.

The new networking features are perfect for e.g. monitoring climate or production processes.

It is possible to access all networking features and measured value enquiries via tablet app or - as usual with Ahlborn devices - via PC using the WinControl software.

Modern control via app and web service

The user operates the ALMEMO[®] 500 via an included 8-inch tablet and a preinstalled app. An integrated web service enables access to the data logger.

However, the app not only visualizes the measurement data. The software also allows the user to configure the entire data logger as well as all attached sensors conveniently on the tablet. It is possible to export data to Excel as well. This is useful in case the measurement data shall be further processed in Excel or other programs.

Thanks to the web service it is possible for several users to simultaneously log into the device e.g. from different locations in case of decentralized measured value monitoring. An intelligent permission management ensures that measurements are not accidentally changed.

A Wi-Fi hotspot integrated in the data logger is responsible for the connection between the tablet and the data logger. In the standard configuration this is set up as an access point, which provides the user with a secure Wi-Fi network.

Alternatively, the data logger can also connect to an existing network as client. This is enabled by a special client mode in the measuring instrument that allows the user to access the data logger via a company network or an external VPN connection.

A configuration website integrated in the data logger allows the user to configure the Wi-Fi hotspot, e.g network settings or encryption, in just a few steps. This works similar to the configuration of a router.

The ALMEMO[®] 500 enables the user to view historical measurement sequences saved on the measurement data storage using the app. The measurement sequences can be loaded offline as well as during measurement operations.

Monitor up to 90 measuring inputs in fail-safe operation

Ahlborn features the ALMEMO[®] 500 standard version with 20 galvanically isolated measuring input sockets. Depending on the housing width, the device can be augmented to up to 90 measuring input sockets by inserting further plug-in cards.

For thermocouple measurements, the data logger features internal cold junction compensation.

Optionally available battery compartments enable fail-safe longterm measurements. Operated with batteries, the ALMEMO[®] 500 can be used as a mobile device as well.

Store 600 million measured values internally

A 4GB SD memory card is integrated in the data memory of the ALMEMO[®] 500. Depending on the measurement resolution, this card is sufficient for up to 600 million measured values. For long-term measurements, it is possible to configure the data memory as a ring memory. In case the memory is not sufficient, the user can plug in additional memory in form of an USB flash drive or an USB hard disk via the USB port. The ALMEMO[®] 500 will then save all measurement data to the external medium.

Networking thanks to state-of-the-art interfaces

It is possible to link several ALMEMO[®] 500 devices via the USB interfaces or via the integrated access point, using either Wi-Fi or LAN network. The user operates all devices via the ALMEMO[®] 500 app. Additionally, the measured values can also be queried and displayed using the measured value acquisition software WinControl.

Depending on the use case: desktop housing or rack housing Ahlborn features the ALMEMO[®] 500 with a desktop housing of type TG6 and TG8. The side frames are manufactured using two-component injection molding (2-shot-molding). The device can be carried on stable aluminum handles. Rubberized components prevent the ALMEMO[®] 500 from slipping. Thanks to the particular form of the side frames, the housings are stackable.

Apart from the desktop housing, Ahlborn features an additional device version in the classic 19-inch rack housing suitable for cabinet solutions..

ALMEMO[®] 500



Ports for ALMEMO[®] sensors and for networking (OLED status display)



Easy programming and visualization of measurement data via tablet

Technical data and functions ALMEMO® 500

- ALMEMO[®] data logger from the latest V7 generation
- · Access via integrated web service and access point, two Wi-Fi access modes: access point or client (for integration in an existing network)
- The device is easy and intuitive to use thanks to an 8-inch tablet with a preinstalled app (included in delivery)
- · Visualizing measured values and configuring the data logger via the preinstalled app, simultaneous login of several users possible, integrated user and permission management
- Connecting the new ALMEMO[®] D7 sensor generation: Measuring rate up to 1000 mops, simultaneous operation of high speed and low speed sensors, display of measured values up to 8 digits, up to 10 channels per sensor, comments up to 20 characters, dimensions up to 6 characters, measured value damping for up to 4 channels per sensor
- Display of measured values as numerical single measurement Choice of languages: German, English (other options available values, value lists or freely configurable displays
- Graphic display of measured values as line graph for depicting up to 20 measurement sequences, integrated sidebar for switching quickly between three display modes
- Measurement function: measured value, minimum value, maximum value, zeroing, target value comparison, damping, average value over a period of time or over several measurement points, limit value monitoring, cold junction compensation and temperature compensation
- Stored measurement sequences can be displayed offline well as during ongoing measurement operation as

- Modern desktop housing in two variants: TG6 and TG8, side frames manufactured by the use of 2-shot-molding, stackable or available in 19-inch rack housing
- 20 ALMEMO[®] input sockets (galvanically isolated) for connecting up to 20 ALMEMO[®] sensors of all generations (standard), up to 200 sensor channels, can be upgraded to up to 90 ALMEMO[®] input sockets, up to 900 sensor channels
- 2 USB ports for connecting external memory and PC, Ethernet and Wi-Fi for accessing the web service via app
- Networking via integrated access point, using LAN or Wi-Fi network, or via USB using WinControl
- High speed and high resolution A/D Converter (ADC)
- Integrated 4GB SD card, sufficient storage for up to 600 million measured values, configurable as linear or ring memory, memory expansion possible via USB port
- on request)
- Programming menu for concise parametrization of e.g. cycles, times, memory and power supply
- OLED display (0.82 inch) and LED displays for visualization of network parameters and system messages directly on the device
- Option KL: multi-point adjustment, customer specific linearization
- Battery compartments (accessory) for fail-safe long-term measurements or for mobile device usage
- new: Relay/trigger/analog interface RTA6 as plug-in card (as accessory) for output of alarm and control signals.

Technical data

Measuring inputs: Standard configuration:	20 ALMEMO [®] -input sockets for all	Standard equipment: Control unit	industrial tablet (Samsung SM T365)	
	ALMEMO [®] sensors (standard, DIGI, D6, D7)	Memory:	500 MB SD card (built-in)	
Channels (standard):	up to 200 measurement channels		(for up to 75 million measured values)	
Expansion: device housing)	up to 90 input sockets (depending on the	Date and time-of-day:	buffered with lithium battery	
Precision class:	AA (see Catalog, p.01.04)	Power supply: Mains adapter	7B1212NA11_100 to 240VAC	
Total sampling rate	CPU up to 4000 mops, per input board up to 2000 mops	Recharg. battery (accessory)	12VDC, 2.5A galvanically isolated : 2 lithium-batteries, total of 13.8 Ah,	
Measuring rate for analog sensors, DIGI and D6 sensors:			integrated high-speed charging (3h)	
Galvanic Isolation for analog sensors	100 / 50 / 10 / 2.5 mops using semiconductor relays (50V) additional galvanic isolation between	Power consumption (without	at input and output modules) approx. 300 mA without sensors (default configuration)	
0	measuring input and power supply (device ground)	Housing Desktop housing TG6 390 x	x 160 x 260 mm (W x H x D), appr. 4 kg	
Sensor power supply:	6 / 9 / 12V, per board max. 400mA, each data logger max. 1.2 A	Desktop housing TG8 497 x Rack housing BT8 483 x 13	x 160 x 260 mm (W x H x D), appr. 4.5 kg 2 x 273 mm (W x H x D), appr. 4.5 kg	
Interfaces:	2 USB ports for additional memory and networking, Ethernet, Wi-Fi for accessing	Environmental conditions and general technical data see page 01.04 onwards		
	the web service and networking			

ALMEMO® 500

Numerous measured value displays

The ALMEMO[®] 500 app offers different measured value displays.

- Measured values can be displayed as numerical single measurement values, value lists or freely configurable measurement value displays.
- The measurement functions include inter alia measured value, minimum value, maximum value and average value.
- To graphically display the measured values, the line graph is able to show 20 measurement sequences.
- An integrated sidebar enables the user to quickly switch between three different display modes: automatic, manual and entire measurement.

-• B		11 î	.11 60%	10:57 💼
< Back	Line chart V	2	×	16.02.16 10:57
36	and you wanter			36
24	1		+	27
· 18	A maint			22,5 റ്
12				18
6				13,5
0	10:18:20 10:20:00 10:21:40 10:23:20 10:25:00 10:26:40 10:28:20 10:30:00 10:	31:40	10:33:20	_]"
Ston			¥ a	ettinos

Line graphs for monitoring measurement sequences for a set period of time

Back Me	easuered value displa	ау				\mathcal{S}		8 . (1)	∦ 78% ★	15.
=	× 1									
_										
	M000_1	humidity 01								
			20	2			_			
			28	.3		%⊦				
	Range	DIGI	Maximum value	33.3	Minimum value	20.7	2			

Single measurement value displays for monitoring single measured values

Back Channel list			V 🔤 🐵 🗙 15.02.16
Measuring channel	Measured value	Maximum value	Minimum value
W000_0 temperature 01	23.1 °C	25.3 °C	20.7 *0
M000_1 humidity 01	28.3 %H	33.3 %H	20.7 %
M000_2 dew point 01	5.1 °C	5.3 °C	4.7 *0
W000_3 atm. pressure	938.1 mb	939.3 mb	937.8 mb
M001_0 temperature 02	22.7 °C	24.3 °C	18.7 °C
M001_1 temperature 03	18.2 °C	19.7 °C	18 °C
M001_2 temperature 04	18.1 °C	19.3 °C	18 °C
M001_3 temperature 05	17.9 °C	19.3 °C	17.8 °C

Value lists for displaying several measurement values and function values simultaneously

Accessories	Order no.
Active measuring circuit card MA10 and MMU (expansion). 10 see next page <i>new:</i> Relay/trigger/analog card, 2 slots. Up to 4 cards are supported per system, see chap. output modules Li-Ion battery pack, 13.8 Ah. Required space: 2 slots Carrying case, aluminum profile frame, suitable for ALMEMO [®] 500 in desktop housing TG6 Rack case with handle, suitable for ALMEMO [®] 500 in rack case BT8	ES500RTA6 ES500AP ZB500TK1 ZB5090RC

Option	Order no.
Multi-point adjustment or linearization can be programmed by the customer with any ALMEMO® plug version	OA500KL

Standard delivery

Data logger ALMEMO[®] 500

CPU card including interfaces and web service. 4GB SD memory card. 2 active measuring circuit cards MA10 featuring 20 input sockets for all ALMEMO[®] sensors (standard, DIGI, D6, D7). Manufacturer's test certificate. Mains adapter ZB 1212 NA11 PC connecting cable (USB, Ethernet). Control unit (Tablet Samsung SM T365) with preinstalled app, mount for control unit. In desktop housing TG6, 9 free slots MA500CPUA20TG6B In desktop housing TG8, 15 free slots MA500CPUA20TG8B

In 19-inch rack housing, 15 free slots

DAkkS / DKD or factory calibration KE90xx, electrical, for measuring instruments, see chapter Calibration certificates. The DAkkS calibration meets the requirements of DIN EN ISO/IEC 17025 for test equipment.

Order no.

MA500CPUA20BT8B

CPU board, active measuring circuit boards and expansions for datalogger ALMEMO[®] 500



Input boards for ALMEMO[®] 500

Technical data and functions

- Active measuring circuit boards with own A/D converter
- There are several design variants for different installations / input plugs.

101	. X	
41	(X))	
12	.xc;	0N
43	200.	
14	(XC)	ALARM
M5	.xc;	
16	(XC)	
47	(x::)	
48 N		
19	Exc.	

Input board M-A10

10 inputs for all ALMEMO[®] sensors. (default, digit, D6, D7) For flexible applications with individual sensors and measuring signals.

Technical data

Measuring inputs	10 ALMEMO [®] input sockets, electr. isolated for all ALMEMO [®] connectors (default, digit, D6, D7).
Measuring ranges	All ranges (see page 01.05)
Sensor supply	6, 9 or 12 V, max. 400mA (per datalogger max. 1.2 A)
Footprint	2 slots

Standard delivery

Active	measuring	circuit	board	MA10
ACTIVE	measuring	circuit	UUalu	IVIA I U

Order no.	
ES500MA10	

Input board MMU

10 inputs for ALMEMO[®] 10 MU connectors. For permanently installing groups of 10, especially temperature sensors.

Technical data

Measuring inputs	10 inputs, electrically isolated, socket strip for ALMEMO [®] 10-way MU connector
Measuring ranges	all thermocouples, Pt100, Ni100, NTC ohms, 2.6 V, 260 mV, 55 mV, 26 mV
Sensor supply	None
Footprint	1 slot

Standard delivery

Active measuring circuit board MMU ALMEMO[®] 10-way MU connector

Order no. ES500MMU ZA5690MU

10/2021 • We reserve the right to make technical changes

ALMEMO® 809



ALMEMO[®] precision measuring instrument, latest V7 generation Nine measuring inputs for all sensors Operates as data logger or PC interface Increased measuring accuracy, fast sampling rate, with ALMEMO[®] D7 sensors up to 1000 measuring operations per second

Data logger from our latest V7 generation.

Data logger ALMEMO[®] 809 offers outstanding functions and applications using our latest D7 sensors. This measuring instrument operates either as data logger or as PC interface using the WinControl measuring software (an accessory). The device parameters can be fully configured by means of the ALMEMO[®] Control software (included in delivery).

New digital ALMEMO® D7 sensors

With these digital ALMEMO[®] D7 sensors the existing ALMEMO[®] system is enhanced by many new functions. These operate via an all-digital interface to the ALMEMO[®] 809 measuring instrument ensuring high-speed serial transmission of all measured values. The measuring ranges of ALMEMO[®] D7 plugs are independent of the measuring instrument and can be expanded as and when required for new applications.

Measured values can be displayed with up to 8 digits (depending on quantity and range) and the units with up to 6 characters. Sensor designation and information can be up to 20 characters. Each ALMEMO[®] D7 sensor has its own processor. They all work in parallel at their own sensor-specific sampling rate. D7 sensors thus attain very high measuring speeds in dynamic measuring operations. Scanning times on the ALMEMO[®] 809 can be set individually for quick-acting and slow-acting sensors. The ALMEMO[®] D7 plug can process up to 10 channels for measured values and function values. This includes new applications, especially for multi-purpose sensors (e.g. Meteo sensors) and for linking up to complex third-party devices (e.g. chemical analysers, power analysers).

Measuring inputs for nine ALMEMO® sensors, all generations

Data logger ALMEMO[®] 809 incorporates nine measuring inputs. The measuring instrument can process up to 90 measuring channels - depending on the sensors connected. All new and already existing sensors designed for any measurable variable can be connected and evaluated. Sensors using analog signals pass via the integrated high-speed, high-resolution A/D converter. Additional electrical isolation between measuring inputs and power supply (device ground) increases measuring quality. Digital D6 and the latest digital D7 sensors transfer measured values to the measuring instrument directly in digital form.

The measuring instrument supports all ALMEMO® plug connectors and sensor functions. All sensor parameters for

ALMEMO[®] standard / D6 / D7 sensors can be fully configured by means of the ALMEMO[®] Control software (included in delivery).

Data logger for all storage applications

For the purpose of saving measured values the device incorporates an 8-MB flash memory. This can also be configured as a ring memory for monitoring tasks.

To save larger data quantities an external memory is available in the form of a plug-in SD card.

For autonomous long-term monitoring the data logger can also be run in energy-saving sleep mode.

Other equipment

With two ALMEMO[®] output sockets it is possible to connect simultaneously a PC / network, an ALMEMO[®] output interface with relays and analog output, or an ALMEMO[®] memory connector with an SD card.

There are five LEDs for indicating various operating states. The operating key is used to switch on the device and to start / stop a measuring operation.

With option KL it is possible - for an ALMEMO[®] sensor (e.g. temperature or pressure sensors) - to program multi-point adjustment or linearization in the ALMEMO[®] plug itself. This option is possible with all ALMEMO[®] plug versions, standard connectors (analog or DIGI), ALMEMO[®] D6 and D7 plugs.



ALMEMO® Measuring Instruments

ALMEMO® 809



Precision measuring instrument, latest V7 generation, nine measuring inputs Data logger with internal memory or external memory connector (accessory)

Technical data

Measuring inputs	Nine ALMEMO [®] input sockets suitable for all generations of ALMEMO [®] sensors,	Standard equipment Operation	1 key, 5 LEDs, 2 coding switches
	analog sensors, D6 and D7 sensors	Memory	8-MB flash memory
Precision class	AA see page 01.04		(400,000 up to 1.5 million meas. values)
Total sampling rate:	up to 2000 measurements/s	Date and time-of-day	Real-time clock (4.7 ppm)
Sampling rate for analog	sensors, D6 sensors		with lithium buffer battery
1 0 0	2.5 / 10 / 50 / 100 mops	Power supply	
Electrical isolation for analog sensors	with semiconductor relays (50 V) Additional electrical isolation between measuring inputs and power supply	Mains adapter	ZB1212NA12 100 to 240 VAC to 12 VDC, 1.5 A, electrically isolated
0		Current consumption without Input and output modules	
(device ground)		active mode	approx. 50 mA
Channels	Up to 90 measuring channels per device	Sleep mode	approx. 0.05 mA
Sensor power supply	12 V, maximum 400 mA	Housing	180 x 049 x 137 mm (LxWxH)
Outputs	Two ALMEMO [®] sockets, suitable for all		Polystyrene (PS) Weight approx. 490 g
	output modules (data / analog / trigger / relay cables, memory connector, etc.)	Environmental conditions and general technical data see page 01.04 onwards	

Accessories

Accessories	Order no.
Plug-in memory with micro SD card, including USB card reader (see chapter ,General accessories') DC adapter cable, 10 to 30 VDC, 12 V / 1 A, electrically isolated	ZA1904SD ZB3090UK2
WinControl software for measured data acquisition per device up to 20 channels for any number of devices and channels	SW5600WC1 SW5600WC2
Note on WinControl measuring software WinControl measuring software is suitable for version 7 and above. For versions and description see Chapter Software.	

Connecting cables

Connecting cables	Order no.
USB data cable, electrically isolated Ethernet data cable, electrically isolated Analog output cable, electrically isolated , 1 x 20mA	ZA1919DKU ZA1945DK ZA1601RI ZA1601RI
Trigger and alarm cable (2 relays, 0.5 A, 50 VDC)	ZA1602RU ZA1006EKG

Option	Order no.
Multi-point adjustment and / or linearization can - with all ALMEMO [®] plug versions - be programmed by users themselves Temperature ranges for 8 refrigerants	OA809KL SB0000R2
Standard delivery	Order no.

Measuring instrument, Mains unit ZB1212NA12, Manufacturer's test certificate Precision measuring instrument ALMEMO 809

MA809

ALMEMO® Measuring Instruments

ALMEMO[®] 5690 data acquisition system



ALMEMO[®] precision measuring instrument for measured data acquisition, with data logger function. **Comprehensive range of functions** for all application areas. Increased measuring accuracy, fast measuring rate. Up to 99 / 190 measuring inputs Operates as data logger or PC interface, also with generously dimensioned graphics display.

Technical data and functions, ALMEMO[®] 5690

- Multi-functional data acquisition systems with up to 99 or 190 measuring inputs (applies to ALMEMO® 5690-xCPU with option XU or XM)
- · Increased measuring accuracy and stability
- Fast measuring rate, up to 50 measuring operations per second With SD memory card, up to 100 mops, optional for 1 channel up to 500 mops (does not apply to ALMEMO® 5690-xCPU with option XM)
- Measuring rate increased to over 100 channels / second with several measuring circuit boards (applies **ALMEMO®** 5690-xCPU with option XM) to The measuring circuit boards operate in parallel, thus ensuring • 8 rechargeable NiMH batteries with high-speed battery short scanning times for a large number of channels.
- Over 65 standard measuring ranges

Technical data, ALMEMO[®] 5690

· Option KL for independent multi-point adjustment or special linearization programmable in 30 points and management of calibration data saved in the sensor connector and the measuring instrument

- · Higher measuring quality thanks to electrical isolation between measuring inputs and device power supply (device ground)
- Improved cold junction compensation with 2 sensors per input card
- Operates as data logger (internal EEPROM / RAM or SD memory card, sleep mode for long-term recording) or as interface for PC online operation
- ALMEMO[®] 5690-1 (variant without display), ALMEMO[®] 5690-2 (variant with display and operating controls)
- 5 LEDs for displaying the operating status of the measuring circuit and the CPU
- charging (accessory)
- Relay / trigger / analog interface as plug-in board (accessory) for output of alarm and control signals
- ALMEMO® output sockets, suitable for digital interfaces, analog output, trigger input, alarm contacts, memory card
- Housing in several variants: Desktop housing TG1, TG3, TG8 Wall-mounted housing WG3, Rack housing BT8.

Order no.

Order no.

	•		
Precision class Measuring rate	AA (see page 01.04) (100), 50, 10 and 2.5 mops	Power supply Mains adapter ZB1212NA11 100 to 240 VA to 12 VDC, 2.5 A DC adapter cable electrically isolated ZB3090-UK2 10 to 30 VDC, Rechargeable battery pack 8 rechargeable NiMH ba	ZB1212NA11 100 to 240 VAC
Electrical isolation for analog sensors	with semiconductor relays (50 V) Additional electrical isolation between measuring inputs and power supply (device ground)		to 12 VDC, 2.5 A electrically isolated ZB3090-UK2 10 to 30 VDC, 12 VDC, 1 A ry pack 8 rechargeable NiMH batteries, 9 to 11 V 1600 mAb. With intelligent
Date and time-of-day	Real-time clock, buffered with lithium battery		high-speed charging (3.5 hours)
Supply current	For system boards and sensor supply		Supply current Entire system maximum 1.5 A
	Entire system, max. 2.5 A, per board max. 0.5 A	Environmental condit see page 01.04 onwar	ions and general technical data ds

Accessories ALMEMO[®] 5690

Rechargeable batteries, 1600 mAh, 1 slot	ES5690AP
DC cable, 10 to 30 VDC, 12 VDC, 1.25 A	ZB3090UK2
Relay / trigger / analog board (see chapter "Output modules") 2 slots	ES5690RTA5
Carry case, aluminum profile frame / ABS, suitable for ALMEMO® 5690 in desktop housing TGx	ZB5600TK3
Rack case with handle, suitable for ALMEMO [®] 5690 in rack housing BT8	ZB5090RC

Connecting cables ALMEMO[®] 5690

USB data cable, electrically isolated **ZA1919DKU** Ethernet data cable, electrically isolated **ZA1945DK** ZA1006EKG Trigger and relay cable (2 relays, 0.5 A, 50 V) Analog output cable, -1.25 to +2.0 V, 0.1 mV / digit **ZA1601RK** V24 data cable, electrically isolated ZA1909DK5 Network technology, Bluetooth modules (see chapter "Networking") Relay trigger analog adapter (see chapter "Output modules")

ALMEMO[®] data acquisition systems - a comparison

Function

System type	5690-xM09	5690-xCPU	5690-xCPU with option XU	5690-xCPU with option XM
Measuring circuit	Master measuring circuit board with 9 measuring inputs	CPU	Measuring circuit J board (without measuring ir	nputs)
Measuring inputs	up to 99 inputs	up to 100 inputs	up to 190 inputs	up to 190 inputs
Number of channels	up to 99 channels	up to 100 channels	up to 250 channels	up to 250 channels
Expansions Selector switch boards	up to 9	up to 10	up to 19	None
Expansions Active measuring circuit boards	None	None	None	up to 19
Scanning time (approx.) At conversion rate 10 Hz At conversion rate 50Hz	For 1 to 99 channels in total 0.1 to 10 seconds 0.02 to 2 seconds	For 1 to 100 channels in total 0.1 to 10 seconds 0.02 to 2 seconds	For 1 to 190 channels in total 0.1 to 19 seconds 0.02 to 4 seconds	For 100 / 190 channels in total = 10/19 measuring circuit boards with 10 channels each 1.1 / 1.1 seconds* 0.3 / 0.5 seconds* *for systems without display
ALMEMO [®] plug with special measuring range / multi-point calibration, linearization	Up to 9 ALMEMO® plugs (master measuring circuit)	Up to 100 ALMEMO® plugs	Up to 190 ALMEMO® plugs	Up to 190 ALMEMO® plugs
ALMEMO [®] outputs	Sockets A1 and A2	Sockets A1 to A5	for expanding the periphery, relay / trigger / analog output	optional socket P0 s)

Operating modes

System type	5690-1M09	5690-2M09	5690-1CPU	5690-2CPU
Online operation via PC	yes		yes	
Display and operating controls	no	yes	no	yes
Data logger	Accessory ZA1904SD Memory connector inclu- ding micro SD	Micro SD drive, integra- ted, including micro SD (as standard)	Accessory ZA1904SD Memory connector inclu- ding micro SD	Micro SD drive, integra- ted, including micro SD (as standard)
Internal memory	100 000 values E	EPROM (option)	400 000 values RAM, battery-buffered (standard) or 400 000 values FeRAM, non-volatile (option)	

ALMEMO[®] 5690-1M09

Technical data and functions

- Technical data and functions, as for ALMEMO[®] 5690 series
- Master measuring circuit, 9 ALMEMO[®] input sockets, electrically isolated, suitable for 9 ALMEMO[®] sensors
- Up to 9 ALMEMO[®] connectors; special ranges / multi-point calibration / linearization possible (only on master measuring circuit)
- Expansion up to 99 inputs by means of various selector switch boards, maximum 99 measuring channels
- Data logger option : with internal EEPROM or external AL-MEMO[®] memory connector with micro SD card

Technical data

Technical data, as for ALMEMO [®] 5690 series		as linear or ring memory		
9 ALMEMO [®] input sockets Expansion up to 99 inputs by means of	External memory (accessory)	ALMEMO [®] memory connector with micro SD card		
selector switch boards	Outputs	2 ALMEMO [®] sockets, suitable for all		
Measuring channels Expansion up to maximum 99 measuring channels		output modules (analog / data / trigger / relay cables, etc.)		
Internal EEPROM sufficient for 100,000 measured values, configurable		Alarm signal transmitter, internal		
	Operation	1 key, 5 LEDs, 2 coding switches		
	MO® 5690 series 9 ALMEMO® input sockets Expansion up to 99 inputs by means of selector switch boards Expansion up to maximum 99 measuring channels Internal EEPROM sufficient for 100,000 measured values, configurable	MO* 5690 series as linear or ring memory 9 ALMEMO* input sockets External memory (accessory) Expansion up to 99 inputs by means of selector switch boards Outputs Expansion up to maximum 99 measuring channels Outputs Internal EEPROM sufficient for 100,000 measured values, configurable Operation		

Accessories

Memory connector with micro SD, including USB card reader (see chapter "General accessorie	s") ZA1904SD
--	--------------

Expansions	Order no.
Selector switch boards U-A10, U-MU, U-TH2	(see page 01.46)
Relay / trigger / analog board, 2 slots Per system up to 7 boards are supported. (see chapter "Output modules")	ES5690RTA5

Optionen	Order no.
Internal data memory sufficient for 100,000 values	OA5690S
Multi-point adjustment, special linearization, management of calibration data	OA5690KL
Temperature ranges for 8 refrigerants (see 10.08)	SB0000R2
Measuring rate for 1 measuring channel, 500 mops (SD card required)	SA0000Q5

Standard delivery

Precision measuring instrument, data acquisition system with master measuring circuit board MM-A9, mains plug assembly ZB1212NA11, Operating instructions, manufacturer's test certificate

DAkkS or works calibration KE90xx, electrical, for measuring instrument (see chapter "Calibration certificates"). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

ALMEMO[®] 5690-1M09TG1



Dimensions: 77 x 145 x 218 mm (WxHxD)

Data acquisition system in desktop housing TG1, 9 inputs, 1 free slot MA56901M09TG1 Expansion with 1 U-MU board (10 inputs)

ALMEMO[®] 5690-1M09TG8



Dimensions: 444 x 158 x 232 mm (WxHxD)

Data acquisition system in desktop housing TG8, 9 inputs, 19 free slots MA56901M09TG8 Expansion with 9 U-A10 boards or U-TH2 or U-MU (90 inputs) or 7 RTA5 boards

ALMEMO[®] 5690-1M09TG3



Dimensions: 179 x 158 x 232 mm (WxHxD)

Data acquisition system in desktop housing TG3, 9 inputs, 6 free slots MA56901M09TG3 Expansion with 3 U-A10 boards or U-TH2 (30 inputs) or 6 U-MU boards (60 inputs) or 3 RTA5 boards

ALMEMO[®] 5690-1M09BT8



Dimensions: 483 x 132 x 273 mm (WxHxD)

Data acquisition system in 19-inch rack housing, 9 inputs, 19 free slots MA56901M09BT8 Expansion with 9 U-A10 boards or U-TH2 or U-MU (90 inputs) or 7 RTA5 boards

or / RTAS boards



Carry case, aluminum profile frame ZB5600TK3 for ALMEMO[®] 5690-1/ -2



Rack case with handle ZB5090RC for ALMEMO[®] 5690-xxBT8 in 19-inch rack housing

ALMEMO[®] 5690-2M09

Technical data and functions

- Technical data and functions, as for ALMEMO® 5690 series
- Master measuring circuit, 9 ALMEMO[®] input sockets, electrically isolated, suitable for 9 ALMEMO[®] sensors
- Up to 9 ALMEMO[®] connectors; special ranges / multi-point calibration / linearization possible (only on master measuring circuit)
- Expansion up to 99 inputs by means of various selector switch boards, maximum 99 measuring channels
- Generously dimensioned graphics display, bright illumination, large display of measured values
- Measured values can be displayed graphically in line chart or bar chart form or numerically in various sizes.

- 3 user-defined menus can be freely configured from a range of 50 functions.
- Easy to operate by means of 4 soft-keys and cursor block, menu-guided with wizards and context-sensitive help windows
- Choice of languages : German, English, French
- Data logger with micro SD (standard)
- Option, internal EEPROM.

Technical data

Technical data, as for ALMEMO® 5690 series		Outputs	2 ALMEMO [®] sockets, suitable for all
Measuring inputs	9 ALMEMO [®] input sockets Expansion up to 99 inputs by means of selector switch boards		output modules (analog / data / trigger / relay cables, etc.) Alarm signal transmitter, internal
Measuring channels	Expansion up to maximum 99 measuring channels	Display Graphics display	128 x 128 pixels, 16 rows
Memory	Micro SD card, integrated drive	Illumination	5 white LEDs, 3 brightness levels
Internal memory (option S)	Internal EEPROM sufficient for 100,000 measured values, configurable as linear or ring memory	Operation	9 keys (4 soft-keys and cursor block) 9 status LEDs on front panel

Expansions	Order no.
Selector switch boards U-A10, U-MU, U-TH2	(see page 01.46)
Relay / trigger / analog board, 2 slots Per system up to 7 boards are supported. (see chapter "Output modules")	ES5690RTA5

Options	Order no.
Internal data memory sufficient for 100,000 values	OA5690S
Multi-point adjustment, special linearization, management of calibration data	OA5690KL
Temperature ranges for 8 refrigerants (see 10.08)	SB0000R2
Measuring rate for 1 measuring channel, 500 mops (SD card required)	SA0000Q5

Standard delivery

Precision measuring instrument, data acquisition system with graphics display and operating controls, master measuring circuit board MM-A9, micro SD card, USB card reader, mains plug assembly ZB1212NA11, operating instructions, manufacturer's test certificate

DAkkS or works calibration KE90xx, electrical, for measuring instrument (see chapter "Calibration certificates"). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

ALMEMO® Measuring Instruments

ALMEMO® 5690-2M09TG3



Dimensions: 179 x 158 x 232 mm (WxHxD)

Data acquisition system in desktop housing TG3, 9 inputs, MA56902M09TG3 6 free slots Expansion with 3 U-A10 boards or U-TH2 (30 inputs) or 6 U-MU boards (60 inputs)

or 3 RTA5 boards

ALMEMO[®] 5690-2M09WG3



Dimensions: 209 x 207 x 153 mm (WxHxD) (width includes fastening strips)

Data acquisition system in wall-mounted housing WG3, 9 inputs, 6 free slots MA56902M09WG3 Expansion with 3 U-A10 boards or U-TH2 (30 inputs) or 6 U-MU boards (60 inputs)

or 3 RTA5 boards

The boards have their connections facing downwards. To facilitate wall-mounting four holes (5.3 mm) are provided on the protruding strips to the left and right of the housing's backplate (which cannot itself be removed).

ALMEMO[®] 5690-2M09TG8



Dimensions: 444 x 158 x 232 mm (WxHxD)

Data acquisition system in desktop housing TG8, 9 inputs, 19 free slots MA56902M09TG8 Expansion with 9 U-A10 boards or U-TH2 or U-MU (90 inputs) or 7 RTA5 boards

ALMEMO® 5690-2M09BT8



483 x 132 x 273 mm (WxHxD)

Data acquisition system in 19-inch rack housing, 9 inputs, 19 free slots MA56902M09BT8 Expansion with 9 U-A10 boards or U-TH2 or U-MU (90 inputs) or 7 RTA5 boards

ALMEMO® Measuring Instruments

Master measuring circuit board, selector switch boards, and expansions for the ALMEMO[®] 5690-1M09 and 5690-2M09 systems



circuit board MM-A9

Selector switch boards for ALMEMO[®] 5690-1M09 and 5690-2M09

Technical data and functions of selector switch boards

- Selector switch boards for expanding the ALMEMO[®] 5690-1M09 and 5690-2M09 systems by additional inputs
- There are several design variants for different installations / input plugs.

Selector switch boards U-A10

10 inputs for ALMEMO[®] single connectors For flexible applications with individual sensors and measuring signals.

Selector switch boards U-MU

10 inputs for ALMEMO[®] 10 MU connectors For permanently installing groups of 10, especially temperature sensors.

Technical data

Measuring inputs	10 ALMEMO [®] input sockets, electrically isolated	
Measuring ranges	All ranges (see page 01.05)	
Sensor supply	12 V, max. 0.3 A (per system max. 2.5 A)	
Footprint	2 slots	

Standard delivery

Selector switch board U-A10

```
Order no.
ES5690UA10
```

ALMEMO[®] connector must be ordered separately.

Technical data

Measuring inputs	10 inputs, electrically isolated, socket strip for ALMEMO [®] 10-way MU connector	
Measuring ranges all thermocouples, Pt100, Ni100, NTC, e 2.6 V, 260 mV, 55 mV, 26 mV		
Sensor supply	None	
Footprint	1 slot	

Standard delivery

Selector switch board U-MU ALMEMO[®] 10-way MU connector Order no. ES5690UMU ZA5690MU

Selector switch boards U-TH2

10 inputs for miniature thermal connectors For any individual thermocouple temperature sensors with miniature thermal connector.

Order no.

Technical data

Measuring inputs	10 miniature thermal sockets, electr. isolated ALMEMO [®] sensor parameters are saved in the measuring instrument.	
Measuring ranges	all thermocouples	
Sensor supply	None	
Footprint	2 slots	

Selector switch board U-TH2ES5690UTH2Miniature thermal connectors must be ordered separately.

ZA1904SD

ALMEMO[®] Measuring Instruments

ALMEMO[®] 5690-1CPU

Technical data and functions

- Technical data and functions, as for $ALMEMO^{\circledast}$ 5690 series
- CPU board with measuring circuit (without measuring inputs) and output sockets
- Up to 100 measuring inputs / 100 measuring channels via selector switch boards
- Option XU up to 190 measuring inputs / 250 measuring channels via selector switch boards
- Option XM high-speed measuring operations, up to 190 measuring inputs / 250 measuring channels via active measuring circuit boards The measuring circuit boards operate in parallel, thus ensuring short scanning times for a large

number of channels. The scanning time is determined by the measuring circuit board with the highest number of active measuring channels - or, at conversion rate 50 Hz, also by the processing time of the CPU.

- Option 5 ALMEMO[®] output sockets for digital interfaces, analog outputs, trigger, alarm contacts, socket P0 for integrated relay outputs
- Data logger with internal RAM (standard) or FeRAM (option) or external ALMEMO[®] memory connector with micro SD card

Technical data

Technical data, as for ALMEMO [®] 5690 series		External memory (accessory)	ALMEMO [®] memory connector	
CPU board	Measuring circuit (without measuring inputs) input boards (see page 01 54)	Outputs	with micro SD card	
Measuring inputs / measuring channels		Outputs	output modules (analog / data / trigger /	
Standard up to 100 inputs / 100 meas. channels via selector switch boards			relay cables, etc.) . Alarm signal transmitter, internal Socket P0	
Option XU	up to 190 inputs / 250 meas. channels via selector switch boards		for integrated relay outputs (option) Or trigger and analog output	
Option XM up to 190 inputs via active measu	up to 190 inputs / 250 meas. channels		(by request)	
	via active measuring circuit boards	Operation	1 key, 5 LEDs, 2 coding switches	
Memory, internal	sufficient for 400,000 values, linear or ring memory			
Standard	RAM (buffered by battery)			
Option SF	FeRAM (non-volatile)			

Accessories

|--|

Input boards / expansions	Order no.
Option XM - selector switch boards and active measuring circuit boards	(see page 01.54)
Relay / trigger / analog board, 2 slots Per system up to 4 boards are supported. (see chapter "Output modules")	ES5690RTA5

Options	Order no.
Up to 190 measuring inputs / 250 measuring channels	OA5690XU
For active measuring circuit boards, up to 190 measuring inputs / 250 measuring channels	OA5690XM
Data memory, internal FeRAM, non-volatile (instead of battery-buffered RAM)	OA5690SF
Multi-point adjustment, special linearization, management of calibration data	OA5690KL
Temperature ranges for 8 refrigerants (see 10.08)	SB0000R2
Measuring rate for 1 measuring channel, 500 mops (SD card required) This cannot be combined with option XM.	SA0000Q5
For output socket P0	
SH2 2 semiconductor relays (normally open) internal, 0.5 A, 50 V	OA5690SH2
OH2 2 additional relays (normally closed) for option SH2 (thus 2 changeover relays)	OA5690OH2

Standard delivery

Precision measuring instrument, data acquisition system with CPU board Measuring circuit (without measuring inputs) Input boards must be ordered separately. (see page 01.54) Mains plug assembly ZB1212NA11, Operating instructions, manufacturer's test certificate

DAkkS or works calibration KE90xx, electrical, for measuring instrument (see chapter "Calibration certificates"). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

ALMEMO® 5690-1CPUTG1



Dimensions: 77 x 145 x 218 mm (WxHxD)

Data acquisition system in desktop housing TG1CPU board, 1 free slotMA56901CPUTG1Messeingänge über:Messuring inputs via 1 MU board (10 inputs)

ALMEMO[®] 5690-1CPUTG8



Dimensions: 444 x 158 x 232 mm (WxHxD)

Data acquisition system in desktop housing TG8 CPU board, 19 free slots MA56901CPUTG8 Measuring inputs via nine A10 or TH2 boards (90 inputs) or 19 MU boards (190 inputs) or four RTA5 output boards

ALMEMO® 5690-1CPUTG3



Dimensions: 179 x 158 x 232 mm (WxHxD)

Data acquisition system in desktop housing TG3 CPU board, 6 free slots MA56901CPUTG3 Measuring inputs via three A10 or TH2 boards (30 inputs) or 6 MU boards (60 inputs) or three RTA5 output boards

ALMEMO® 5690-1CPUBT8



Dimensions: 483 x 132 x 273 mm (WxHxD)

Data acquisition system in 19-inch rack housing CPU board, 19 free slots MA56901CPUBT8 Measuring inputs via nine A10 or TH2 boards (90 inputs) or 19 MU boards (190 inputs) or four RTA5 output boards



Carry case, aluminum profile frame ZB5600TK3 for ALMEMO[®] 5690-1/-2



Rack case with handle ZB5090RC for ALMEMO[®] 5690-xxBT8 in 19-inch rack housing

Order no.

ALMEMO[®] Measuring Instruments

ALMEMO[®] 5690-2CPU

Technical data and functions

- Technical data and functions, as for ALMEMO® 5690 series
- CPU board with measuring circuit (without measuring inputs) and output sockets
- Up to 100 measuring inputs / 100 measuring channels via selector switch boards
- \bullet Option XU up to 190 measuring inputs / 250 measuring channels via selector switch boards
- Option XM high-speed measuring operations, up to 190 measuring inputs / 250 measuring channels via active measuring circuit boards The measuring circuit boards operate in parallel, thus ensuring short scanning times for a large number of channels. The scanning time is determined by the measuring circuit board with the highest number of active measuring channels or, at conversion rate 50 Hz, also by the processing time of the CPU.
- Option 5 ALMEMO[®] output sockets for digital interfaces, analog outputs, trigger, alarm contacts, socket P0 for integrated relay outputs
- Generously dimensioned graphics display, bright illumination, large display of measured values
- Measured values can be displayed graphically in line chart or bar chart form or numerically in various sizes.
- 3 user-defined menus can be freely configured from a range of 50 functions.
- Easy to operate by means of 4 soft-keys and cursor block, menu-guided with wizards and context-sensitive help windows
- Choice of languages : German, English, French
- Data logger with internal RAM (standard) or FeRAM (option) and with micro SD card (standard).

Technical data

Technical data, as for A	ALMEMO [®] 5690 series	Memory	Micro SD card, integrated drive
CPU board	Measuring circuit (without meas. inputs) Input boards (see page 01.54)	Outputs	5 ALMEMO [®] sockets, suitable for all output modules (analog / data / trigger /
Measuring inputs / measuring channels Standard up to 100 inputs / 100 measuring channels via selector switch boards		relay cables, etc.) Alarm signal transmitter, ir Socket P0 for integrated re	relay cables, etc.) Alarm signal transmitter, internal Socket P0 for integrated relay outputs
Option XU	up to 190 inputs / 250 measuring channels via selector switch boards		(option) Or trigger and analog output (by request)
Option XM	up to 190 inputs / 250 measuring channels via active measuring circuit boards	Display Graphics display	128 x 128 pixels, 16 rows
Memory, internal	sufficient for 400,000 values, linear	Illumination	5 white LEDs, 3 brightness levels
Standard	or ring memory RAM (buffered by battery)	Operation	9 keys (4 soft-keys and cursor block) 9 status LEDs on front panel
Option SF	FeRAM (non-volatile)		

Input boards / expansions	Order no.
Option XM - selector switch boards and active measuring circuit boards	(see page 01.54)
Relay / trigger / analog board, 2 slots Per system up to 4 boards are supported. (see chapter "Output modules")	ES5690RTA5

Options

Up to 190 measuring inputs / 250 measuring channels	OA5690XU
For active measuring circuit boards, up to 190 measuring inputs / 250 measuring channels	OA5690XM
Data memory, internal FeRAM, non-volatile (instead of battery-buffered RAM)	OA5690SF
Multi-point adjustment, special linearization, management of calibration data	OA5690KL
Temperature ranges for 8 refrigerants (see 10.08)	SB0000R2
Measuring rate for 1 measuring channel, 500 mops (SD card required) This cannot be combined with option XM.	SA0000Q5
For output socket P0	
SH2 2 semiconductor relays (normally open) internal, 0.5 A, 50 V	OA5690SH2
OH2 2 additional relays (normally closed) for option SH2 (thus 2 changeover relays)	OA5690OH2

Standard delivery

Precision measuring instrument, data acquisition system with graphics display and operating controls, CPU board Measuring circuit (without measuring inputs) Input boards must be ordered separately. (see page 01.54) Micro SD card, USB card reader, mains plug assembly ZB1212NA11, Operating instructions, manufacturer's test certificate.

DAkkS or works calibration KE90xx, electrical, for measuring instrument (see chapter "Calibration certificates"). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

ALMEMO® 5690-2CPUTG3



Dimensions: 179 x 158 x 232 mm (WxHxD)

Data acquisition system in desktop housing TG3 CPU board, 6 free slots MA56902CPUTG3 Measuring inputs via three A10 or TH2 boards (30 inputs) or 6 MU boards (60 inputs) or three RTA5 output boards

ALMEMO[®] 5690-2CPUWG3



Dimensions: 209 x 207 x 153 mm (WxHxD) (width includes fastening strips)

Data acquisition system in wall-mounted housing WG3 CPU board, 6 free slots MA56902CPUWG3 Measuring inputs via three A10 or TH2 boards (30 inputs) or 6 MU boards (60 inputs) or three RTA5 output boards The boards have their connections facing downwards. To fa-

cilitate wall-mounting four holes (5.3 mm) are provided on the protruding strips to the left and right of the housing's backplate (which cannot itself be removed).

ALMEMO[®] 5690-2CPUTG8



Dimensions: 444 x H158 x T232 mm (WxHxD)

Data acquisition system in desktop housing TG8 CPU board, 19 free slots MA56902CPUTG8 Measuring inputs via nine A10 or TH2 boards (90 inputs) or 19 MU boards (190 inputs) or four RTA5 output boards

ALMEMO® 5690-2CPUBT8



Dimensions: 483 x 132 x 273 mm (WxHxD)

Data acquisition system in 19-inch rack housingCPU board, 19 free slotsMA56902CPUBT8Measuring inputsvia nine A10 or TH2 boards (90 inputs)or 19 MU boards (190 inputs)or four RTA5 output boards

ALMEMO® Measuring Instruments

CPU board, selector switch boards, active measuring circuit boards and expansions for CPU systems ALMEMO[®] 5690-1CPU and 5690-2CPU



Input boards for ALMEMO® 5690-1CPU and 5690-2CPU

Technical data and functions

- Selector switch boards U-xx for CPU systems without options XU / XM or with option XU
- Active measuring circuit boards M-xx with own A/D converter for CPU systems with option XM

Input board U-A10 / M-A10



10 inputs for ALMEMO[®] single connectors. For flexible applications with individual sensors and measuring signals. • There are several design variants for different installations / input plugs.

Input board U-MU

10 inputs for ALMEMO[®] 10 MU connectors. For permanently installing groups of 10, especially temperature sensors.

Technical data

Measuring inputs	10 ALMEMO [®] input sockets, electrically isolated
Measuring ranges	All ranges (see page 01.05)
Sensor supply	12 V, maximum 0.3 A (per system max. 2.5 A)
Footprint	2 slots

Standard delivery

, , , , , , , , , , , , , , , , , , ,	
Selector switch board U-A10	ES5690UA10
Active measuring circuit board M-A10	
(for CPU system with option XM)	ES5690MA10

Technical data

Measuring inputs	10 inputs, electrically isolated, socket strip for ALMEMO [®] 10-way MU connector
Measuring ranges	all thermocouples, Pt100, Ni100, NTC ohms, 2.6 V, 260 mV, 55 mV, 26 mV
Sensor supply	None
Footprint	1 slot

Standard delivery

Order no.

Selector switch board U-MU Active measuring circuit board M-MU (for CPU system with option XM) ALMEMO[®] 10-way MU connector Order no. ES5690UMU

ES5690MMU ZA5690MU

Input board U-TH2

10 inputs for miniature thermal connectors. For any individual thermocouple temperature sensors with miniature thermal connector.

Order no.

Technical data

Measuring inputs	10 miniature thermal sockets, electr. isolated ALMEMO [®] sensor parameters are saved in the measuring instrument.
Measuring ranges	all thermocouples
Sensor supply	None
Footprint	2 slots

Standard delivery

Selector switch board U-TH2	ES5690UTH2
Active measuring circuit board M-TH2	
(for CPU system with option XM)	ES5690MTH2
Miniature thermal connectors must be ordered a	separately

ALMEMO® 8590 /8690 series



ALMEMO[®] precision measuring instrument for measured data acquisition, with data logger function. Comprehensive range of functions for all application areas. Increased measuring accuracy, fast measuring rate 9 measuring inputs. Operates as data logger or PC interface, also with rechargeable batteries.

Technical data and functions, ALMEMO® 8590 /8690

- · Increased measuring accuracy and stability
- Fast measuring rate, up to 50 measuring operations per second With SD memory card, up to 100 mops, optional for 1 channel up to 500 mops
- 9 measuring inputs, electrically isolated
- Over 65 standard measuring ranges
- Support for ALMEMO[®] plugs with multi-point adjustment, special linearization, and special measuring ranges
- Option KL for independent multi-point adjustment or special linearization programmable in 30 points and management of calibration data saved in the sensor connector and the measuring instrument
- Higher measuring quality thanks to electrical isolation between measuring inputs and device power supply (device ground)

Technical data ALMEMO® 8590 /8690

- Improved cold junction compensation with 2 sensors
- Data logger option Internal EEPROM sufficient for 100,000 measured values (option S) configurable as linear or ring memory - or memory connector with micro SD (accessory)
- Sleep mode for long-term recording
- 2 ALMEMO[®] output sockets, suitable for digital interfaces, analog output, trigger input, alarm contacts, memory card
- 5 LEDs for indicating various operating states
- Key for switching on and start / stop measuring
- Complete sensor and device programming by means of AMR-Control software (included in delivery).

Precision class	AA (see page 01.04)	Operation	1 key, 5 LEDs, 2 coding switches
Measuring rate	(100), 50, 10 and 2.5 mops	Internal memory (option S)	Internal EEPROM sufficient for 100,000
Measuring inputs Electrical isolation	9 ALMEMO [®] input sockets with semiconductor relays (50 V)	_	measured values, configurable as linear or ring memory
for analog sensors Additional electrical isolation between measuring inputs and power supply		External memory (accessory) ALMEMO [®] memory connector with micro SD card
	(device ground)	Date and time-of-day	Real-time clock,
Additional channels	4 function channels, device-internal		buffered with lithium battery
Outputs 2 ALMEMO [®] sockets, suitable for all output modules (analog / data / trigger / relay cables, memory, etc.)		Current consumption (without input and output modules)Active modeapprox. 25 mASleep modeapprox. 0.05 mA	
		Environmental conditions an	nd general technical data

Environmental conditions and general technical data see page 01.04 onwards

ALMEMO [®] 8590 /8690, accessories	Order no.
Memory connector with micro SD, including USB card reader (see chapter "General accessories") DC adapter cable, 10 to 30 VDC, $12 \text{ V} / 1 \text{ A}$, electrically isolated	ZA1904SD ZB3090UK2

ALMEMO [®] 8590 /8690. connecting cable	Order no.
	7410100211
USB data cable, electrically isolated	ZAI9I9DKU
V24 data cable, electrically isolated	ZA1909DK5
Ethernet data cable, electrically isolated	ZA1945DK
Analog output cable, -1.25 to +2.0 V, 0.1 mV / digit	ZA1601RK
Trigger and alarm cable (2 relays, 0.5 A, 50 V)	ZA1006EKG
Network technology, Bluetooth modules (see chapter "Networking")	

ALMEMO® 8590-9



Precision measuring instrument, 9 measuring inputs

Data logger option with internal memory or external memory connector (accessory)

Technical data and functions

- Technical data and functions, as for $ALMEMO^{\circledast}\,8590$ / 8690

Technical data

Technical data, as for ALM	EMO® 8590 / 8690
Sensor power supply	Mains adapter 12 V, maximum 0.5 A
Power supply	
Mains adapter	ZB1212NA12 100 to 240 VAC
	to 12 VDC, 1.5 A, electrically isolated
DC adapter cable	ZB3090UK2 10 to 30 VDC, 1 A,
	electrically isolated
Housing	180 x 49 x 137 mm (LxWxH)
	Polystyrene (PS) Weight approx. 490 g

ALMEMO® 8690-9A



Precision measuring instrument, 9 measuring inputs

Data logger option with internal memory or external memory connector (accessory) Runs on rechargeable batteries, charging via the device itself

Technical data and functions

- Technical data and functions, as for ALMEMO® 8590 / 8690
- Runs on rechargeable batteries, high-speed charging in the device itself using mains unit, included in delivery

Technical data

Technical data, as for ALMI	EMO® 8590 / 8690
Rechargeable battery pack	8 rechargeable NiMH batteries, 9 to 11 V, 1600 mAh With intelligent high-speed charging (3.5 hours)
Sensor power supply	
Mains adapter Runs on rechargeable batt	12 V, maximum 0.5 A eries 9 to 11.5 V, maximum 0.5 A
Power supply	
Mains adapter	ZB1212NA12 100 to 240 VAC, to 12 VDC, 1.5 A
DC adapter cable	electrically isolated ZB3090-UK2 10 to 30 VDC, 12 VDC, 1 A
Housing	218 x 77 x 145 mm (LxWxH) Polystyrene (PS) Weight approx. 1.2 kg

Options	Order no.
Internal data memory sufficient for 100,000 values	OA8590S
Multi-point adjustment, special linearization,	
management of calibration data	OA8590KL
Temperature ranges for 8 refrigerants (see 10.08)	SB0000R2
Measuring rate for 1 measuring channel, 500 mops	
(SD card required)	SA0000Q5
DIN rail mounting	OA2290HS

Standard delivery

Mains plug assembly ZB1212NA12, operating instructions, manufacturer's test certificate

Precision measuring instrument ALMEMO® 8590-9 for measured data acquisition MA85909

Options	Order no.
Internal data memory sufficient for 100,000 values	OA8590S
Multi-point adjustment, special linearization, management of calibration data	OA8590KL
Temperature ranges for 8 refrigerants (see 10.08)	SB0000R2
Measuring rate for 1 measuring channel, 500 mops	\$ 1 000005
DIN rail mounting	OA2290HS

Standard delivery

Rechargeable batteries, mains plug assembly ZB1212NA12, Operating instructions, manufacturer's test certificate Precision measuring instrument ALMEMO® 8690-9A for measured data acquisition MA86909A

DAkkS or works calibration KE90xx, electrical, for measuring instrument (see chapter "Calibration certificates"). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Order no.

Order no.

ALMEMO® Measuring Instruments

Universal ALMEMO[®] transmitter 2490 with analog output



- 1 or 2 measuring inputs.
- Built-in analog output 2 x 10 V or 20 mA (programmable)
- Display and keybad.

Technical features

- Analog transmitter with built-in double analog output.
- · Analog output range and measuring channel assignment programmable via keyboard.
- Basic measuring instrument with over 65 standard measuring ranges.
- Good measuring accuracy, measuring rate up to 10 measurements/s.
- Support of ALMEMO® connectors with multipoint adjustment, special linearization and special ranges.
- · Measuring functions: Measured value, zeroing, sensor calibration, max. and min. value storage.
- · Full sensor and instrument programming via interface

Technical data

Precision class:	B, see page 01.06		16
Measuring rate	10 and 2.5 mops	0.0 to 10.0 V	0,
Measuring ranges:	over 65 measuring ranges, inter alia thermocouples, Pt100, Pt1000, NTC temperature / humidity, (capacitive or psychrometric)	0.0 / 4.0 to 20.0 mA	1 A 0. To
Measuring inputs: 2490-1R02U 2490-2R02U	via ALMEMO [®] connector 1 ALMEMO [®] socket 2 ALMEMO [®] sockets, electrically isolated with semiconductor relay (50 V).	Digital outputs: Power supply:	vi fc ar vi
Additional channels:	4 function channels internal to the device		1(
Sensor supply:	9 V, max. 80 mA for power supply operation	Standard equipment	L
Analog outputs.	via ALMEMO [®] socket P0:	Housing:	A
maiog outputs.	2 x 10 V or 20 mA (programmable), both outputs with common ground.	Environmental conditions see page 01.04 onwards	s and

6 bit DAC, electrically isolated. 5 mV/digit, load > 100 kOhm. μ A/digit, load < 500 Ohm. ccuracy: 1% of meas. v. +0.1% of final v emperature drift: 10 ppm/K. ime constant: 100 µs. ia ALMEMO[®] sockets A1 and A2 or PC cable USB or RS232 nd relay cable ia ALMEMO® socket DC 0 ... 30 V DC, electrically isolated to nalog outputs and measuring input CD screen, keypad BS, L127 x W83 x H42 mm general technical data

Programming the analog output (Example)



M Μ

Analog end

ALMEMO® 2490-1R02U



Analog transmitter, 1 measuring input Double analog output

ALMEMO® 2490-2R02U



Analog transmitter, 2 Measuring inputs Double analog output

Accessories	Order no.
Power supply: (via ALMEMO [®] socket DC)	
100 to 240 V AC via mains unit 12 V, 1.5 A, with ALMEMO [®] connector	ZA1312NA12
10 to 30 VDC, maximum 80 mA, electrically isolated, via ALMEMO [®] clamp connector ZA1000FSV	included in delivery
Digital interface: (via ALMEMO [®] socket A1)	
USB interface via ALMEMO [®] USB cable	ZA1919DKU
RS232 interface via ALMEMO® RS232 cable	ZA1909DK5
Limit value contact: (via ALMEMO [®] socket A2)	
(see chapter "Output modules")	
(Programming via digital interface, see above)	
2 normally open contacts, 50 VDC / 500 mA (can also be programmed as inverted)	
via ALMEMO [®] relay cable, V6, clamped connection	ZA1006EKG
ALMEMO® limit value cable with banana plugs (for electrical socket adapter)	ZA1006GK
Electrical safety socket adapter, 250 V / 6 A (for ALMEMO [®] limit value cable)	ZB2280RA
Installation :	
DIN rail:	ZB2490HS
Magnet	ZB2490MH

Standard delivery

Analogue transmitter, measuring input via ALMEMO[®] plug. Double analogue output incl. ZA1000KS clamping plug. Electrically isolated power supply incl. ZA1000FSV terminal plug. Operating instructions, manufacturer's test certificate. Analog transmitter ALMEMO[®] 2490-1R02U, 1 measuring input Analog transmitter ALMEMO[®] 2490-2R02U, 2 measuring inputs Order no.

MA24901R02U MA24902R02U

DAkkS or factory calibration KE90xx, electrical, for measuring instruments, see chapter Calibration certificates. The DAkkS calibration meets the requirements of DIN EN ISO/IEC 17025 for test equipment.

ALMEMO[®] 4390-2



ALMEMO[®] precision measuring instrument in fitted panel design with data logger function. Comprehensive range of functions for all application areas Increased measuring accuracy, fast measuring rate, 1 measuring input, 2 limit value relays, integrated. Option with double analog output.

Technical data and functions

- · Increased measuring accuracy and stability
- Fast measuring rate, up to 50 measuring operations per second With SD memory card, up to 100 mops, optional for 1 channel up to 400 mops
- 1 ALMEMO[®] input socket, suitable for all ALMEMO[®] sensors or 6-contact clamp connector socket, also for 26 V and 20 mA
- More than 65 standard measuring ranges
- Support for ALMEMO[®] plugs with multi-point adjustment, special linearization, and special measuring ranges Measuring functions : Measured value, dual display, smoothing, zero-setting, setpoint adjustment, maximum / minimum /
- Higher measuring quality thanks to electrical isolation between measuring inputs and device power supply (device ground)
- Data logger with internal EEPROM, sufficient for 16,000 measured values, configurable as linear or ring memory
- Memory connector with micro SD (accessory)
- As standard 2 limit value relays can also be driven via interface

- Option with double analog output can also be driven via interface
- 2 ALMEMO[®] output sockets, suitable for digital interfaces, analog output, trigger input, alarm contacts, memory card
- 8-character alphanumeric 14-segment display
- Programming functions displayed in normal text (3 languages)
 5 programming menus
- Measuring function, memory, sensor, device, output
- Measuring functions : Measured value, dual display, smoothing, zero-setting, setpoint adjustment, maximum / minimum / average values, temperature compensation, atmospheric pressure compensation
- Sensor programming: Measuring range, measured value correction, scaling, units, limit value monitoring, graduated locking of functions, scaling of analog output
- Device programming: Conversion rate, real-time clock with date, output cycle, baud rate, choice of languages

Order no.

Technical data

Precision class	AA (see page 01.04)	0.0 to 10.0 V	0.5 mV / digit, load >100 kilohms
Measuring rate	(100), 50, 10 and 2.5 mops	0.0 to 20.0 mA	0.1 mA / digit, load <500 ohms
Measuring inputs	1 ALMEMO [®] input socket, suitable for all ALMEMO [®] sensors or 6-contact screw connector with input for 26 V (integrated divider) or 20 mA	Accuracy Temperature drift Time constant	± 0.1 % of measured value ± 0.1 % of final value 10 ppm / K 100 μ s
Accuracy Channels Electrical isolation for and	(integrated divider) of 20 mA (integrated shunt) Divider / shunt ±0.1 % of measured value 4 channels for double sensors and function channels alog sensors	Standard equipment Display Keypad Date and time-of-day Memory, internal EEPRO	8-character 14-segment LED display 5 membrane keys Real-time clock, buffered with battery M sufficient for 16,000 measured values
Sensor power supply	between measuring input and power supply (device ground) 12 V / 0.1 A; 9 V / 0.15 A; 6 V / 0.2 A	Power supply Mains operation Option U	90 to 250 VAC, 50 / 60 Hz 10 to 30 V, 0.5 A, electrically isolated
Outputs	2 ALMEMO [®] sockets, suitable for all output modules (analog / data / trigger / relay cables, memory, etc.)	Housing Panel opening	Standard plastic housing 96 x 48 x 132 mm (WxHxD) 90 x 42.5 mm
2 limit value relays Option with double analog	Mechanical changeover, 230 V, 2 A putput 10 V or 20 mA (programmable) 16-bit DAC, electrically isolated	Environmental conditions at see page 01.04 onwards	nd general technical data

Ac	ces	SO	ries

Memory connector with micro SD, including USB card reader (see chapter "Output modules")	ZA1904SD
Options	Order no.
Measuring rate 400 mops (SD card required) Power supply 10 to 30 VDC, electrically isolated 2 analog outputs (common ground), electrically isolated 10 V or 20 mA (programmable) Temperature ranges for 8 refrigerants	SA0000Q4 OA4390U OA4390R02 SB0000R2
Standard delivery	Order no

Standard derivery	Order no.
Operating instructions, manufacturer's test certificate, Precision measuring instrument ALMEMO [®] 4390-2	MA43902

DAkkS or works calibration KE90xx, electrical, for measuring instrument (see chapter "Calibration certificates"). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Reference Measuring Instruments



High-precision measuring

ensure very high levels of resolution, precision, and linearity. They are thus ideally suitable as reference instruments in calibration laboratories and quality resolution up to 0.001 K. These devices are two output sockets which can be used instrument case.

The new reference measuring instruments are offered in a set including sensor. They come in a compact design (with an optional variant with protective class IP54), an illuminated graphics display, and easy and convenient operation by assurance procedures. They measure with soft-keys and the cursor block. There

for connection to a PC or for networking. There is also a plug-on measured value memory available as an option. Delivery includes evaluation software, data cable, temperature sensor, DAkkS calibration certificate, mains unit, and measuring

Calibration certificate for ALMEMO® 1020-2 with precision sheathed thermocouple sensor type N (Example)

the gsstelle GmbH bration laboratory in the nst	Kalibrierzeichen
ientfühler, angeschlossen an anzeigegerät nnected with 1 temp. measuring dev ss- und Regelungstechnik GmbH E: ALMEMO 1020-2 be : NICrSI-NISI, TYP N 2070031	Dieser Kalibrierschein dokume führung auf nationale jurgen eineren in jurgen Darstellung der Einheiten in jurgen Die DAKKS ist Unterzeichnen Übereinkommen der Euro for Accreditation (EA) um Laboratory Accreditation zur gegenseitigen Kalibrierscheine. Für die Einhaltung ein zur Wiederholung die Benutzer verantworti
ice: 1 obe: 1 Mess- und Regelungstechnik G	traceability to na traceability units of realize the units of the International Sy

Dbject of ca	<i>libration</i>	angeschloss H12070031 1 thermocol connected w Serial-No. H	sen an ein Temper uple probe NiCrSi- vith one temperatu I12070031	aturanzeigegerät AL NiSi, type N, Ø 6 mr re measuring deviće	MEMO 1020-2, Seri n length 760 mm, n ALMEMO 1020-2,
lessergebr	iisse / Test Re	<u>əsult</u>			
Kanal	Sorion Mr.	Dröftemperetur	Anzoigo	Aburoichung	Magaunaiaharhai
Kanal Channel	Serien-Nr. Serial No.	Prüftemperatur Test Temperature °C	Anzeige Indication °C	Abweichung Deviation K	Messunsicherhei Uncertainty K
Kanal Channel	Serien-Nr. Serial No.	Prüftemperatur Test Temperature °C	Anzeige Indication °C	Abweichung Deviation K	Messunsicherhei Uncertainty K
Kanal Channel M0	Serien-Nr. Serial No.	Prüftemperatur Test C °C 1150,00 1000.00	Anzeige Indication °C 1150,00 1000.00	Abweichung Deviation K 0,00 0.00	Messunsicherhei Uncertainty K 3,0 1,5
Kanal Channel M0	Serien-Nr. Serial No.	Prüftemperatur <i>Test</i> <i>Temperature</i> °C 1150,00 1000,00 500,00	Anzeige Indication °C 1150,00 1000,00 500,00	Abweichung Deviation K 0,00 0,00 0,00	Messunsicherhei Uncertainty K 3,0 1,5 1,0

The values are based on the International Temperature Scale of 1990 (ITS-90).

Die Korrektur der Messkette erfolgte über die Mehrpunktjustage-Funktion! The correction of the measuring system was realized by the multiple point function!

Reference Measuring Instruments

ALMEMO[®] 1020-2



Reference measuring instrument for temperature **High-precision measuring** by means of thermocouples Types N, S, R, B Resolution 0.01 K, up to 1800 °C

Technical features

- Temperature measurement with very high levels of resolution, Two output sockets for digital interface, ALMEMO® memory precision, and linearity, using thermocouples Types N, S, R, B
- Suitable as reference device in calibration laboratories and quality assurance procedures
- Very high accuracy thanks to multi-point adjustment of the Easy and convenient to operate by means of 4 soft-keys and thermocouple temperature sensor
- Each temperature sensor has its own cold junction stored in the ALMEMO[®] plug or externally. The cold junction temperature in the ALMEMO® plug is measured to a very high resolution of 0.001 K by means of an NTC sensor.
- Two electrically isolated measuring inputs for thermocouples, types N, S, R, B
- Resolution 0.01 K
- Units °C, °F, K
- High-resolution A/D converter, delta-sigma, 24-bit, 1.25 mops Choice of language : German, English, French (measuring operations per second)

- connector
- Compact, modern, ergonomic design
- · Graphics display, illuminated with white light
- cursor block
- Measured value display : 2 measured values, differential, measuring point list, cold junction temperature
- Measuring functions : Zero-setting, smoothing, maximum / minimum values, individual value memory for 100 values
- Data logger with ALMEMO[®] memory connector (accessory)
- Sensor programming : Smoothing, designation, units
- Device configuration : Illumination, contrast, device address, baud rate

Technical data ALMEMO[®] 1020-2

Measuring inputs	2 ALMEMO [®] input sockets for thermocouples	Outputs	2 ALMEMO [®] sockets for interface cable and ALMEMO [®] memory connector
Electrical isolation A/D converter Measuring ranges NiCrSi-NiSi Type N PtRh10-Pt Type S PtRh13-Pt Type R PtRh30-PtRh6 Type B Resolution Accuracy Type N Type S Type R Type B Nominal conditions	Semiconductor relay (50 V) Delta-sigma, 24-bit, 1.25 mops -200 to +1300 °C -50 to +1768 °C +250 to +1768 °C +250 to +1820 °C 0.01 K $\pm 0.1 \text{ K} \pm 1$ digit in range -200 to +1300 °C +50 to +1760 °C +100 to +1760 °C +500 to +1800 °C 23 °C ± 2 K, 1013 mbar, battery mode	Standard equipment Display Illumination Keypad Date and time-of-day Individual value memory, Power supply Battery set Mains adapter Current consumption (without) With illumination	Graphics display, 128 x 64 pixels, 8 rows 2 white LEDs 7 silicone keys (of which 4 soft-keys) Real-time clock, buffered by battery internal 100 measured values 3 AA alkaline batteries ZA1312NA12 100 to 240 VAC to 12 VDC, 1.5 A, electrically isolated out input and output modules) approx. 20 mA approx. 40 mA
Temperature drift Cold junction temperature	typical 10 ppm / K Measuring operations	Housing	127 x 83 x 42 mm (LxWxH) ABS, 290g
J i tomp or and o	with 0.001 K resolution	Environmental conditions se	ee page 01.04 onwards

Ethernet data cableZA1ALMEMO® memory connector with micro SDZARubberized impact protection, grayZB2DIN rail mountingZB2	Accessories	Order no.
	Ethernet data cable ALMEMO [®] memory connector with micro SD Rubberized impact protection, gray DIN rail mounting	ZA1945DK ZA1904SD ZB2490GS2 ZB2490HS
Variants

Complete set comprising reference measuring instrument for temperature plus accessories, evaluation software, thermocouple sensor, with DAkkS calibration certificate

Reference measuring instrument ALMEMO® 1020-2, including 3 AA alkaline batteries, mains unit ZA1312NA12, USB data cable ZA1919DKU, instrument case, and evaluation software ALMEMO® View SW5500AV (see page 06.16)

Set with high-precision sheathed thermocouple sensor type N



Technical data:

Sheathed thermocouple sensor type N FTAN926L0500P2		
Measuring element	NiCrSi-NiSi, type N, class 1	
Measuring tip	Mineral-insulated sheathed line, d = 6 mm, L = 500 mm	
Operative range	-200 to +1150 °C	
Connecting cable	1.5 meters, thermal line (stranded wire) FEP / silicone (-50 to +200 °C)	
ALMEMO [®] plug	Resolution 0.01 K with integrated cold junction	

Set with high-precision thermocouple sensor type S



Order no.

with thermocouple sensor type S FTAS916L0700P2 replacement ceramic protective tube, case for sensors ZB9000TK2 with DAkkS calibration certificate at 500/1000/1200 °C, including adjustment SP10202S1D

Technical data:

Thermocouple sensor type S FTAS916L0700P2

Measuring element	PtRh10-Pt, Type S, Class 1	
Measuring tip	Thermowire, $d = 0.5 \text{ mm}$ in ceramic protective tube diameter = 6 mm. length = 700 mm	
Operative range	up to +1400 °C	
Connection head	ceramic protective tube, screwed	
Connecting cable	1.5 meters, compensation line FEP / silicone (-50 to +200 °C)	
ALMEMO [®] plug	Resolution 0.01 K with integrated cold junction compensation sensor	

Set with precision thermocouple sensor type S, with external cold junction



Set

Set

Order no.

with thermocouple sensor type S, with external cold junction FTAS906L0700P2, replacement ceramic protective tube, Case for sensors ZB9000TK2 with DAkkS calibration certificate at 500 / 1000 / 1200 °C, including adjustment SP10202S2D

Technical data:

Thermocouple sensor type S, with external cold junction ETA COOCI 0700D

	F1A5906L0/00P2
Measuring element	PtRh10-Pt, Type S, Class 1
Measuring tip	Thermowire, $d = 0.5 \text{ mm}$
	in ceramic protective tube
	diameter = 6 mm , length = 700 mm
Operative range	up to +1600 °C
Connection head	ceramic protective tube, screwed
Connecting cable	0.75 meters, insulated, thermo-wires
	PtRh10-Pt as far as cold junction
Cold junction	Stainless steel protective tube
	diameter = 5 mm, length = 250 mm
Connecting cable	2 meters, stranded copper wire
ALMEMO [®] plug	Resolution 0.01 K

ALMEMO® 1030-2



Reference measuring instrument for temperature. High-precision measuring with Pt100 sensors Resolution 0.001 K

Technical features

- Temperature measurement with very high resolution, precision, Compact, modern, ergonomic design and linearity, using Pt100 sensors
- Suitable as reference device in calibration laboratories and Easy and convenient to operate by means of 4 soft-keys and quality assurance procedures
- Very high accuracy thanks to multi-point adjustment of the Measured value display 2 measured values and differential Pt100 temperature sensor
- 2 electrically isolated measuring inputs for Pt100 sensors
- Resolution : 0.001 K.
- Units °C, °F, K
- High-resolution A/D converter, delta-sigma, 24-bit, 1.25 mops (measuring operations per second)
- Two output sockets for digital interface, ALMEMO® memory Choice of language: German, English, French connector

- Graphics display, illuminated with white light
- cursor block
- Measuring functions: Zero-setting, smoothing, maximum / minimum values, individual value memory for 100 values
- Data logger with ALMEMO[®] memory connector (accessory)
- Sensor programming: Smoothing, designation, units, resolution
- Device configuration: Illumination, contrast, device address, baud rate

Measuring inputs	2 ALMEMO [®] input sockets for Pt100 sensors	Standard equipment Display	Graphics display, 128 x 64 pixels, 8 rows
Electrical isolation	Semiconductor relay (50 V)	Illumination	2 white LEDs
A/D converter	Delta-sigma, 24-bit, 2.5 mops	Keypad	7 silicone keys (of which 4 soft-keys)
Measuring range	Pt100, -200 to +400 °C	Date and time-of-day	Real-time clock, buffered by device battery
Resolution	0.001 K or 0.01 K	Individual value memo	ory, internal 100 measured values
Measuring current	1 mA	Power supply	
Accuracy	$\pm 0.010 \text{ K} \pm 1 \text{ digit}$	Battery set	3 AA alkaline batteries
	in range -50 to +400 °C	Mains adapter	ZA1312NA12 100 to 230 VAC
Nominal conditions	23 °C \pm 2 K, < 90 % r.H., battery mode		to 12 VDC, 1.5 A, electrically isolated
Temperature drift	typical 2 ppm / K	Current consumption (w	ithout input and output modules)
Outputs	2 ALMEMO [®] sockets for interface cable		approx. 20 mA
	and ALMEMO® memory connector	With illumination	approx. 40 mA
		Housing	127 x 83 x 42 mm (LxWxH) ABS, 290 g

Technical data ALMEMO® 1030-2

Ambient conditions see starting on page 01.04.

Accessories	Order no.
Ethernet data cable	ZA1945DK
ALMEMO [®] memory connector with micro SD	ZA1904SD
Rubberized impact protection, gray	ZB2490GS2
DIN rail mounting	ZB2490HS
Aluminum profile case for 1 sensor (up to 500 mm in length)	ZB9000TK1

ALMEMO[®] X6

Set with precision resistance temperature detector Pt100



Pt100-temperature sensor FPA923L0250

Technical data FPA923L0250

Measuring element Class	Pt100 wire-wound 1/10 B (DIN EN 60751) at 0 °C	Nominal length Sensor tube	250 mm Stainless steel, diameter 3 mm
Measuring tip	Operative range -50 to +400 °C	Connecting cable	2 meters, FEP / silicone
Response time T ₉₀	5 seconds	ALMEMO [®] plug	ZA9030FS7P3, resolution 0.001 K

Options

new: Added functions for ALMEMO 1030 and 1036:

1. Extension of the measurement range with resolution 0.001 K (P314): -200...560 °C.

2. New measurement range with resolution 0.01 K (P214): -200...850 °C.

3. The 4 sensor specific parameters R0 and A, B, C of the Callendar-Van Dusen equation

can be programmed for Pt 100 sensors by the user.

Standard delivery

Reference measuring instrument for temperature measurement with accessories, evaluation software, and Pt100 temperature sensor. Complete set including DAkkS calibration certificate:

Reference measuring instrument ALMEMO® 1030-2 including 3 AA alkaline batteries, Desktop mains unit ZA1312NA12, USB data cable ZA1919DKU, Instrument case, evaluation software ALMEMO® View SW5500AV (see page 06.06) and Pt100 temperature sensor FPA923L0250 with DAkkS calibration certificate (2 temperature points at 0 and 100 °C, including adjustment)

SP10302D

Order no.

OA1030FE

Order no.

new Accessories Precision resistance temperature sensor Pt100 FPA924L0500H for the operating range -100 ... +660 °C To achieve high precision, it is absolutely necessary . to calibrate the electrode incl. multi-point adjustment! Please order additionally! Technical data FPA924L0500H

Measuring element:	Pt100 resistor, class B	Handle:	up to 60 °C
Measuring tip:	Application range -100 +660 °C	Connection cable:	2 m cable
Sensor tube:	stainless steel, diameter 4 mm		in PTFE/fiberglass protection hose.
Nominal length:	465 mm (visible)	ALMEMO [®] connector:	ZA9030FS7P3, resolution 0.001 K

Standard delivery

Precision resistance temperature probe for the application range -100 ... +660 °C Measuring element Pt100, class B, probe diameter 4 mm, length 465 mm, with handle, 2 m cable and ALMEMO® connector for ALMEMO® 1030, 1033, 1036, 8036, storage case

Order no.

FPA924L0500H



ALMEMO® 1033-2



Reference measuring instrument for temperature. High-precision measuring with Pt100 sensors Resolution 0.001 K new: Measuring range up to 720 °C with highest resolution 1 mK

Technical data and functions

- new: Extended measuring range up to 720 °C with highest resolution 1 mK.
- *new*: Function expansion as standard. The 4 sensor-specific parameters R0 and A, B, C of the CvD equation (Callendarvan-Dusen equation) for any Pt100 sensor can be programmed by the user.
- Temperature measurement with very high resolution, precision, and linearity, using Pt100 sensors
- · Suitable as reference device in calibration laboratories and quality assurance procedures
- Very high accuracy thanks to multi-point adjustment of the Pt100 temperature sensor
- 2 electrically isolated measuring inputs for Pt100 sensors
- Resolution : 0.001 K, Units : °C, °F, K
- High-resolution A/D converter, delta-sigma, 24-bit, 1.25 mops (measuring operations per second)

- Two output sockets for digital interface, ALMEMO[®] memory connector
- Compact, modern, ergonomic design
- Graphics display, illuminated with white light
- Easy and convenient to operate by means of 4 soft-keys and cursor block
- Measured value display 2 measured values and differential
- Measuring functions: Zero-setting, smoothing, maximum / minimum values, individual value memory for 100 values
- Data logger with ALMEMO[®] memory connector (accessory)
- Sensor programming: Smoothing, designation, units, resolution, multi-point adjustment
- Device configuration: Illumination, contrast, device address, baud rate
- Choice of language: German, English, French

Technical data ALMEMO[®] 1033-2

Measuring inputs	2 ALMEMO [®] input sockets for Pt100 sensors	Standard equipment Display	Graphics display, 128 x 64 pixels, 8 rows
Electrical isolation	Semiconductor relay (50 V)	Illumination	2 white LEDs
A/D converter Measuring range	Delta-sigma, 24-bit, 2.5 mops	Keypad Date and time-of-day	7 silicone keys (of which 4 soft-keys) Real-time clock, buffered by device battery
P314 : Pt100, -200	to +720 °C resolution 0.001 K	Individual value mem	ory, internal 100 measured values
P214 : Pt100, -200 Measuring current	to +850 °C resolution 0.01 K 1 mA	Power supply Battery set	3 A A alkaline batteries
Accuracy P314 + 0.010 K + 1	digit in range $100 \text{ to } \pm 720 \text{ °C}$	Mains adapter	ZA1312NA12 100 to 230 VAC
P214 : $\pm 0.03 \text{ K} \pm 1$	digit in range -100 to + $850 ^{\circ}\text{C}$	Current consumption (w	to 12 VDC, 1.5 A, electrically isolated ithout input and output modules)
Nominal conditions Temperature drift	$23 \text{ °C} \pm 2 \text{ K}, < 90 \% \text{ r.H., battery mode}$ typical 2 ppm / K	With illumination	approx. 20 mA approx. 40 mA
Outputs	2 ALMEMO [®] sockets for interface cable	Housing	127 x 83 x 42 mm (LxWxH) ABS, 290 g
	and ALMEMO [®] memory connector	Ambient conditions see	starting on page 01.04

Accessories

Software WinControl for data acquisition

for 1 device up to 20 channels

Input connectors	Order no.
ALMEMO [®] input connector up to 720 °C, resolution 0.001 K (range P314) ALMEMO [®] input connector up to 850 °C,	ZA9030FS7P3
resolution 0,01 K (range P214)	ZA9030FS2P3

Standard delivery

Reference measuring instrument for temperature up to 720 °C. Batteries, operating instructions, manufacturer's test certificate, . Order no.

SW5600WC1

ZA1919DKU ZA1945DK

ZA1904SD ZA1312NA12

ZB2490GS2 ZB2490HS

ZB2490TK2

Precision resistance temperature sensor Pt100 FPA924L0500H for the operating range-100 ... +660 °C



Technical data FPA924L0500H

Measuring element:	Pt100 resistor, class B
Measuring tip:	Application range -100 +660 °C
Sensor tube:	stainless steel, diameter 4 mm
Nominal length:	465 mm (visible)



Precision RTD temperature sensor Pt100 FPA924L0500H in case (Measuring device and accessories not included)

Handle:	up to 60 °C
Connection cable:	2 m cable in PTFE/fiberglass protection hose.
ALMEMO [®] plug:	ZA9030FS7P3, resolution 0.001 K

 To achieve a high precision, it is absolutely necessary to calibrate the electrode incl. multi-point adjustment!
 Please order additionally!

Standard delivery

Precision resistance temperature probe for the application range -100 ... +660 °C Measuring element Pt100, class B, probe diameter 4 mm, length 465 mm, with handle, 2 m cable and ALMEMO[®] connector for ALMEMO[®] 1030, 1033, 1036, 8036, storage case Order no.

FPA924L0500H

Precision resistance temperature probe Pt100 FPA923L0250 for the operating range -50 ... +400 °C



To achieve a high precision, it is absolutely necessary to calibrate the measuring chain incl. multi-point adjustment! Please order additionally!

Accessories	Order no.
Aluminum profile case for 1 probe	
(up to 500 mm length)	ZB9000TK1

Technical data

Measuring element	Pt100 wire-wound	Nominal length	250 mm
Class	1/10 B (DIN EN 60751) at 0 °C	Sensor tube	Stainless steel, diameter 3 mm
Measuring tip	Operative range -50 to +400 °C	Connecting cable	2 meters, FEP / silicone
Response time T90	5 seconds	ALMEMO [®] plug	ZA9030FS7P3, resolution 0.001 K

Standard delivery

High-precision temperature sensor, measuring element Pt100 1/10 DIN class B Sensor diameter 3 mm, length 250 mm Measuring tip -50 to +400 °C with 2-meter FEP / silicone cable and ALMEMO[®] plug Resolution 0.001 K for ALMEMO[®] 1030, 1033, 1036, 8036

Order no.

FPA923L0250

DAkkS or factory calibration KT90xx temperature for sensor or measuring chain (sensor + device) (see chapter Calibration certificates) DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

ALMEMO® 1036-2



Reference measuring instruments for humidity and temperature **High-precision measurement** with the Pt100 psychrometer and Pt100 sensors **Resolution Temperature 0.001 K** Relative humidity 0.01 % Dew point 0.01 K

Technical features

- Humidity measurement with very high resolution, precision, Two electrically isolated measuring inputs for Pt100 sensors and linearity, using Pt100 psychrometer
- · Suitable as reference device in calibration laboratories and quality assurance procedures
- Very high level of accuracy using the Pt100 psychrometer thanks to multi-point adjustment of the two temperature sensors
- Pt100 psychrometer optimized for measuring operations involving high humidity levels performed over long periods
- Automatic atmospheric pressure compensation is provided for pressure-dependent humidity variables by means of a digital atmospheric pressure sensor integrated in the ALMEMO® device.
- · Humidity calculation on the basis of formulae as per Dr. Sonntag and the enhancement factor as per W. Bögel (correction factor fw(t,p) for real mixed gas systems). This substantially widens the measuring range and improves the accuracy of humidity variable calculations.
- Resolution Temperature Pt100 0.001 Κ, Relative humidity 0.01%, Dew point 0.01 K
- The humidity variables are calculated from the three primary measuring channels (real measurable variables). Drv temperature (°C), humid temperature (°C), atmospheric pressure (mbar)
- Three humidity variables displayed simultaneously, freely selectable: Relative humidity(%), dewpoint(°C), mixture(g/kg), Absolute humidity (g/m3), vapor pressure (mbar), enthalpy (kJ/ kg)

- High-resolution A/D converter, delta-sigma, 24-bit, 1.25 mops (measuring operations per second)
- Two output sockets for digital interface, ALMEMO[®] memory connector
- Compact, modern, ergonomic design
- Graphics display, illuminated with white light
- · Easy and convenient to operate by means of 4 soft-keys and cursor block
- Measured value display : Sensor display (up to 4 measured values), measuring points list, atmospheric pressure
- Measuring functions : Zero-setting, smoothing, maximum / minimum values, individual value memory for 100 values
- Data logger with ALMEMO[®] memory connector (accessory)
- Sensor programming : Smoothing, designation, measuring range selection, locking
- Device configuration : Illumination, contrast, device address, baud rate, atmospheric pressure
- Choice of language : German, English, French
- Humidity measurement in temperature range -100 to +200 °C. with precision digital capacitive temperature / humidity sensors FHAD 36 Rx, with ALMEMO® D6 connector (Accessories, see chapter "Atmospheric humidity"). Configuration of ALMEMO[®] D6 sensors on ALMEMO[®] device itself. For the digital sensors FHAD 36-Rx, it is not possible to program the multi-point adjustment via the measuring instrument.

Measuring inputs Two ALMEMO® input sockets Outputs Two ALMEMO® sockets for interface for Pt100 psychrometer FPA 836-3P3 cable and ALMEMO® memory connector or Precision digital capacitive tempera-Standard equipment ture / humidity sensors FHAD 36 Rx Graphics display, 128 x 64 pixels, 8 rows Display Electrical isolation Semiconductor relay (50 V) Illumination 2 white LEDs Delta-sigma, 24-bit, 1.25 mops A/D converter Keypad 7 silicone keys (of which 4 soft-keys) Measuring range Pt100, -200 to +400 °C Date and time-of-day Real-time clock, buffered by battery Resolution 0.001 K Individual value memory, internal 100 measured values Measuring current 1 mA Power supply ±0.010 K ±1 digit Accuracy 3 AA alkaline batteries Battery set in range -50 to +400 °C Mains adapter ZA1312NA12 100 to 240 VAC 23 °C ±2 K, 1013 mbar, battery mode Nominal conditions to 12 VDC, 1.5 A, electrically isolated Temperature drift typical 2 ppm / K Current consumption (without input and output modules) Calculated humidity quantities Analytic equation approx. 20 mA (not an approximation) approx. 40 mA With illumination Digital atmospheric pressure sensor (integrated in the device) Housing 127 x 83 x 42 mm (LxWxH) 700 to 1100 mbar Measuring range ABS, 290g ±2.5 mbar (at 23 °C ±5 K) Accuracy Ambient conditions see starting on page 01.04.

Technical data ALMEMO[®] 1036-2

ALMEMO[®] X6

Reference Measuring Instruments

Accessories	Order no.
Ethernet data cable	ZA1945DK
ALMEMO [®] memory connector with micro SD	ZA1904SD
Rubberized impact protection, gray	ZB2490GS2
DIN rail mounting	ZB2490HS
Spare wicks (2 pieces)	ZB98462ED
Extension cable for mains units, 3-pin bayonet coupling, length 5 meters	ZB5090VK05

Set with Pt100 psychrometer FPA 836-3P3



Psychrometer FPA 836-3P3

Technical data Pt100 psychrometer FPA 836-3P3

Operating temperature	up to +90 °C (no ice)	Housing	Plastic PMMA
Humidity measuring range approx. 10 to 100 % RH		Dimensions	175 x 50 x 75 mm (LxWxH)
Measuring system	psychrometric	Ventilator power supply	12 VDC via mains unit
Accuracy	$<\pm1$ % RH under nominal conditions		cable, approx. 1.5 meters
Nominal conditions	23 °C ±2 K, 1013 mbar, 50 % RH		(included in delivery)
Femperature sensors sheet resistance 2 x Pt100 closs P. ALMEMO® adjusted	Connecting cables	2 cables, each 5 meters, FEP / silicone	
	2 x Pt100 class B, ALMEMO ⁻ adjusted	ALMEMO [®] plug	Pt100, resolution 0.001 K

Options

Added functions for ALMEMO 1030 and 1036:

- 1. Extension of the measurement range with resolution 0.001 K (P314): -200...560 °C.
- 2. New measurement range with resolution 0.01 K (P214): -200...850 °C.
- 3. The 4 sensor specific parameters R0 and A, B, C of the Callendar–Van Dusen equation
- can be programmed for Pt 100 sensors by the user

Standard delivery

Order no.

Order no.

OA1030FE

Reference measuring instrument for humidity measurement with accessories, evaluation software, and Pt100 psychrometer, Complete set including DAkkS calibration certificate

Reference measuring instrument ALMEMO® 1036-2, with integrated digital atmospheric pressure sensorincluding 3 AA alkaline batteries, mains unit ZA1312NA12, USB data cable ZA1919DKU, instrument case,and evaluation software ALMEMO View SW5500AV (see page 06.16) and Pt100 psychrometer FPA 836-3P3including mains unit, water bottle, pair of wicks with DAkkS calibration certificateTemperature at approx. +25 °C, relative humidity at approx. 30 % / 75 % RH,and atmospheric pressure in range 700 to 1100 mbar (5 points)SP10362D

Precision resistance temperature detector Pt100 (Accessories)	Order no.
Precision temperature sensors for ALMEMO [®] 1030, 1033, 1036, 8036. Technical data see chapter 01, ALMEMO [®] 1033	
for the operating range -50 +400 °C	FPA923L0250

for the operating range -100 ... +660 °C

FPA923L0250 FPA924L0500H

ALMEMO® 8036-9



Reference measuring instrument for temperature and humidity

Multi-channel measuring instrument with nine measuring inputs for Pt100 sensors and Pt100 psychrometers. High-precision measuring with resolution of 0.001 K For calibration laboratories, quality assurance procedures, and monitoring of test and measuring rooms For use either as PC interface or with external memory connector as data logger

Technical data and functions

Multi-channel instrument for high-precision measuring

Reference measuring instrument ALMEMO[®] 8036-9 ensures very high levels of resolution, precision, and linearity when measuring temperature, using up to nine Pt100 sensors - or alternatively up to four Pt100 psychrometers.

This reference measuring instrument is suitable for use as calibration standard in calibration laboratories, for quality assurance procedures, or as a multi-channel instrument for high-precision measuring operations, e.g. in test and measuring rooms or climate chambers.

With the Pt100 the measuring ranges have been expanded considerably, up to +670 °C at the highest resolution of 0.001 K and up to +850 °C at a resolution of 0.01 K. The measured value units can be programmed to either °C / K / °F.

Reference measuring instrument ALMEMO[®] 8036-9 operates with special ALMEMO[®] plugs incorporating expanded programming possibilities. These plugs, it should be noted, cannot be interchanged with the ordinary plugs used with ALMEMO[®] V6 / V7 measuring instruments.

Very high precision thanks to multi-point adjustment and input of coefficients for the Pt100 characteristic

This very high level of precision is achieved by calibrating the measuring chain comprising Pt100 sensor and measuring instrument. For each individual sensor there are two error correction methods available.

- 1. Multi-point adjustment in up to 35 temperature points
- 2. Input of coefficients R0 and A, B, C for the Pt100 characteristic as per the Callendar / Van Dusen equation

Linearization is then performed using the sensor-specific Pt100 characteristic.

Both correction procedures can be used for any sensor simultaneously. The correction values from multi-point adjustment and the coefficients of the Pt100 characteristic are saved in the sensor connector.

Sensors are identified by means of a programmable 10-character alphanumeric designation stored in the sensor connector and a serial number. Similarly, for the purpose of monitoring the calibration interval, the date of the next calibration due and the calibration interval can be programmed and saved in the sensor connector.

High-precision humidity measuring with atmospheric pressure compensation and calculation as per Dr. Sonntag and W. Bögel

The Pt100 psychrometer incorporates two temperature sensors assigned to two measuring inputs.

The digital atmospheric pressure sensor integrated in the ALMEMO[®] device ensures that any pressure-dependent humidity variables are pressure-compensated automatically.

Humidity is calculated on the basis of formulae as per Dr. Sonntag and the enhancement factor as per W. Bögel (correction factor fw(t,p)) for real mixed gas systems). This substantially widens the measuring range and improves the accuracy of humidity variable calculations.

Temperature is measured to a resolution of 0.001 K, relative humidity to 0.01% RH, and dewpoint temperature to 0.01 K.

Humidity variables are calculated from the three primary measuring channels (real measurable variables) - dry temperature (TD $^{\circ}$ C), wet temperature (TW $^{\circ}$ C), and atmospheric pressure (mbar).

In the second ALMEMO[®] plug (dry sensor) there are up to three humidity variables, simultaneously programmable : relative humidity (%), dewpoint (°C), and mixture (g/kg). Abs. humidity (g/m³), vapor pressure (mbar), enthalpy (kJ/kg)

Other equipment

- Five LEDs for indicating various operating states
- One pushbutton for switching the device on / off and to start / stop a measuring operation
- Data logger mode with plug-in ALMEMO[®] memory connector with micro SD card (accessory)
- Two ALMEMO $^{\mbox{\tiny \$}}$ output sockets for simultaneously connecting a PC or network and an ALMEMO $^{\mbox{\tiny \$}}$ memory connector

ALMEMO[®] Control configuration software

The ALMEMO[®] Control software (included in delivery) can be used on a PC to program all sensor parameters in the Pt100 sensor or in the Pt100 psychrometer : measuring range / resolution, units, smoothing, text description, calibration date and calibration interval, multi-point adjustment, locking level.

The ALMEMO[®] Control software also be used to completely program the device.

WinControl software for measured data acquisition

The WinControl software (accessory) can be used to acquire and document measured values from the reference measuring instrument. In the calibration laboratory the reference measuring instrument (reference standard) and the ALMEMO[®] device (test item) can be networked together and evaluated using WinControl.

ALMEMO® 8036-9



Technical data

Measuring inputsNine ALMEMO® measuring inputs for Pt100 sensors and Pt100 psychrometersElectrical isolationSemiconductor relay (50 V)	Outputs	Two ALMEMO [®] sockets for interface cable and ALMEMO [®] memory connector	
A/D converter Measuring range	D converter Delta-sigma, 24-bit, 1.25 mops asuring range Pt100, 4 conductors, -200 to +670 °C Resolution 0.001 K Pt100, 4 conductors, -200 to +850 °C	Standard equipment Operation Date and time-of-day	1 key, 5 LEDs, 2 coding switches Real-time clock, buffered by lithium battery
Measuring current Accuracy	Resolution 0.01 K 1 mA $\pm 0.010 \text{ K} \pm 1 \text{ digit in range } -50 \text{ to } +560^{\circ}\text{C}$ Resolution 0.001 K $\pm 0.05 \text{ K} \pm 1 \text{ digit in range } -100 \text{ to } +850^{\circ}\text{C}$ Resolution 0.01 K $\pm 223^{\circ}\text{C} + 28^{\circ}\text{ L}$ 1012 mban	Power supply Mains adapter Current consumption Active mode Sleep mode	ZB1212NA12 100 to 240 VAC to 12 VDC, 1.5 A, electrically isolated without input and output modules approx. 35 mA (with memory connector approx. 45 mA) approx. 0.05 mA
Temperature drift Calculated humidity va	typical 2 ppm / K ariables Analytic equation	Housing	180 x 049 x 137 mm (LxWxH) Polystyrene (PS), approx. 490 g
5	(not an approximation)	Ambient conditions see s	tarting on page 01.04.
Digital atmospheric pre Measuring range Accuracy	essure sensor (integrated in the device) 700 to 1100 mbar ±2.5 mbar (at 23 °C ±5 K)		

Input connector ALMEMO [®] 8036-9	Order no.
ALMEMO [®] input connector for the user's own third party high-precision sensors, Pt100, 4 conductors, 0.001 K resolution, for ALMEMO [®] 1030, 1033, 1036, 8036	ZA9030FS7P3
ALMEMO [®] input connector for the user's own third party high-precision sensors, Pt100, 4 conductors, 0.01 K resolution, for ALMEMO [®] 1030, 1033, 1036, 8036	ZA9030FS2P3

Accessories	Order no.
Memory connector with micro SD, including USB card reader (see chapter ,General accessories')	ZA1904SD
WinControl software for measured data acquisition per device up to 20 channels for any number of devices and channels	SW5600WC1 SW5600WC2

Connecting cables	Order no.
USB data cable, electrically isolated	ZA1919DKU
Ethernet data cable, electrically isolated	ZA1945DK

Standard delivery

Reference measuring instrument ALMEMO[®] 8036-9, nine inputs for Pt100 sensors and Pt100 psychrometers, integrated atmospheric pressure sensor, including mains unit ZB1212NA12

Order no.

MA80369

DAkkS / DKD calibration KD92xxD, atmospheric pressure, for measuring chain (sensor and device), see catalog chapter Calibration certificate. The DAkkS calibration meets the requirements of DIN EN ISO/IEC 17025 for test equipment.

Order no.

ZB9000TK1

Order no.

Pt100 high-precision sensor FPA923L0250 for reference measuring instrument ALMEMO® 1030-2/1036-2/8036-9



To achieve a high precision, it is absolutely necessary to calibrate the measuring chain incl. multi-point adjustment! Please order additionally!

Technical data

Measuring element	Pt100 wire-wound	Nominal length	250 mm
Class	1/10 B (DIN EN 60751) at 0 °C	Sensor tube	Stainless steel, diameter 3 mm
Measuring tip	Operative range -50 to +400 °C	Connecting cable	2 meters, FEP / silicone
Response time T90	5 seconds	ALMEMO [®] plug	Resolution 0.001 K

Accessories

Aluminum profile case for 1 sensor (up to 500 mm in length)

Standard delivery High-precision temperature sensor, measuring element Pt100 1/10 DIN class B Sensor diameter 3 mm, length 250 mm Measuring tip -50 to +400 °C with 2-meter FEP / silicone cable and ALMEMO® plug Resolution 0.001 K for ALMEMO® 1030, 1033, 1036, 8036 FPA923L0250 **Other version :**

new: Pt100 precision sensor FPA924L0500H for the operating range -100 ... +660 °C see chapter 01, ALMEMO® 1033.

DAkkS or factory calibration KT90xx temperature for sensor or measuring chain (sensor + device) (see chapter Calibration certificates) DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Pt100 high-precision psychrometer FPA 836-3P3 for reference measuring instrument ALMEMO® 1036-2/8036-9



To achieve a high precision, it is absolutely necessary to calibrate the measuring chain! Please order additionally!

Technical data

Operating temperature	up to +90 °C (no ice)	Housing	Plastic PMMA
Humidity measuring range approx. 10 to 100 % RH		Dimensions	175 x 050 x 075 mm (LxWxH)
Measuring system	psychrometric	Ventilator power supply	12 VDC via mains unit
Accuracy	$<\pm1$ % RH under nominal conditions		Cable, approx. 1.5 meters
Nominal conditions	+23 °C +2 K 1013 mbar 50 % BH		(included in delivery)
	chast maisternas	Connecting cables	2 cables, each 5 meters, FEP / silicone
Temperature sensors	2 x Pt100 class B. ALMEMO [®] adjusted	ALMEMO [®] plug	Pt100, resolution 0.001 K
	ý J		

Accessories	Order no.
Spare wicks (2 pieces)	ZB98462ED
Extension cable for mains units, 3-pin bayonet coupling, length 5 meters	ZB5090VK05

Standard delivery

Psychrometer with two Pt100 sensors Fitted cable, with two ALMEMO® plugs Resolution 0.001 K forALMEMO® 1036-2/8036-9, mains unit, water bottle, 1 pair of wicks, carry case ZB2490TK2

Order no.

FPA8363P3

DAkkS / DKD calibration KD92xxD, atmospheric pressure, for measuring chain (sensor and device), see catalog chapter Calibration certificate. The DAkkS calibration meets the requirements of DIN EN ISO/IEC 17025 for test equipment.

Content

ALMEMO [®] Input connectors	02.02
Multi-point adjustment for precisely correcting measuring chains	02.03
Digital ALMEMO [®] D7 measuring connector for thermocouple	02.06
Connector for thermocouple	02.07
Digital ALMEMO [®] D7 measuring connector for Pt100 / Pt1000	02.09
Digital ALMEMO [®] D6 measuring connector for Pt100	02.10
Digital ALMEMO [®] D7 Precision measuring connector for Pt100	02.11
Connector for Pt100	02.13
Digital ALMEMO [®] D6 measuring connector for NTC	02.14
Connector for NTC	02.15
Digital ALMEMO [®] D7 measuring connector for potentiometric	02.16
Connector for potentiometric	02.17
Digital ALMEMO [®] D7 measuring connector for bridge	02.18
Connector for bridge	02.19
Digital ALMEMO [®] D7 measuring connector for DC	02.20
Connector for DC	02.22
Digital ALMEMO [®] measuring module for DC	02.25
Adapter Cables for AC	02.27
Digital ALMEMO [®] measuring module for AC	02.28
Adapter Cables for Frequency / Pulse / Rotational Speed	02.30
Adapter Cable for Digital Input Signals	02.30
Universal Adapter Cables with Free Ends	02.31
MU Connector for ALMEMO [®] Plug-In Boards	02.31
Connector Adapter Cable, Digital Input of Third Party Device	
to ALMEMO [®] Device	02.32



ALMEMO[®] Input connectors

The intelligent ALMEMO[®] input connector turns every measuring setup into an exceptionally flexible measuring system. Instead of preconfigured ALMEMO[®] sensors you can take your own existing sensors. We supply ALMEMO[®] plugs specially pre-programmed for this purpose with the necessary sensor parameters and the appropriate measuring range. These plugs have six screw terminals and can be easily and conveniently connected.

All devices and plugs offer the following functions:

- Each measuring point can be assigned a specific designation
- Sensor signals can be scaled
- Measured values can be corrected for zero-point and gain

Several measuring instruments offer the following options with the ALMEMO[®] plug:

- Multi-point calibration data can be saved in the plug.
- User-defined linearization with up to 30 points can be programmed in the plug.

- Control points with actual / setpoint value can be entered easily via the AMR-Control software.
- Any special measuring ranges programmed in the plug can be processed.
- Calibration schedules can be managed in the plug and are detected automatically
- The plug's exact designation can be called up.

The overall performance quality and the already high level of precision provided by ALMEMO[®] measuring technology is thus raised even further.

New: Digital ALMEMO® D6- and D7-plugs

Numerous analog sensors and measurable variables can be digitized via the digital ALMEMO[®] D6 and D7 plugs. Thus, the ALMEMO[®] system is open for any desired extension of measured variables, measured values, and applications:

• Digital ALMEMO[®] D6 and D7 plugs enable new measuring ranges

and linearization independent of the ALMEMO[®] device.

• The overall accuracy of the digital ALMEMO[®] sensor is independent from the ALMEMO[®] display device / data logger and from the extension cables used. The complete measuring chain, consisting of sensor and

connected ALMEMO[®] D6 or D7 plug (with integrated A/D converter), is calibrated (DAkkS / factory) and can be replaced or exchanged as and whenever necessary.

• The pluggable digital extension cables (see chapter General accessories) provide high transmission reliability.

New: Digital ALMEMO[®] D7-measurement plugs: Special applications / features

Important! ALMEMO[®] D7 measurement plugs can only be connected to ALMEMO[®] measuring instruments of the V7 generation, i.a. ALMEMO[®] 500, ALMEMO[®] 710, ALMEMO[®] 809, ALMEMO[®] 202.

- Every ALMEMO[®] D7 plug features up to 10 display and function channels.
- Digital ALMEMO[®] D7 plugs enable high measuring speeds or a high level of precision. Thus these plugs can be used for a vast variety of measuring tasks
- The ALMEMO[®] D7 plug measures dynamic processes using the setting High Speed Measuring Options at high sampling rate. In case high resolution and stable values are needed (e.g. for accuracy transducers), the ALMEMO[®] D7 measurement plug measures with reduced sampling rate, if the setting High Resolution is selected.
- The digital ALMEMO® D7 measurement plug comes with an integrated A/D converter. The measuring rate is solely determined by

the A/D converter. All D7 measurement plugs run in parallel on the ALMEMO[®] V7 measuring instrument with their own measuring rate. This makes it possible to obtain high measuring speeds.

- The measured values can be provided with a unit featuring up to 6 characters. To designate a sensor it is possible to program comments with up to 20 characters.
- The user can easily perform the configuration via the ALMEMO® V7 measuring instrument.

ALMEMO[®] multi-point adjustment for precisely correcting measuring chains

1. Individual sensor linearization

(e.g. range, dimension, scaling- and limit values, comments) it is now possible to save complete characteristic curves of a sensor in the ALMEMO® plug. This offers the great opportunity to connect also non-linear sensors to the ALMEMO® system whose linearizations (measuring ranges) are not saved to the device itself. Consequently, the variety of sensors

immensely increased.

Usage

The user is able to carry out the special linearization by himself. By means of the free software ALMEMO® CONTROL a linearization table is converted to an interpolation table containing over 30 basic values and saved onto the ALMEMO® plug. Using the function "consider

In addition to the sensor characteristics compatible with ALMEMO® devices is correction value zero and gradient" the linearization with the already pre-scaled readouts is carried out for a pre-scaled measuring range. This procedure requires an ALMEMO® device (e.g. ALMEMO® 2690-8) featuring the option "KL" (multipoint adjustment and special measuring ranges).



Special linearisa	ation						
<u>F</u> ile <u>T</u> able							
Meas point:	00	specialNtc					
Range:	D260	Include correction v	al. (zero,slope)				
Interpolation points:	5 💌						
Next calibration		Interval	0 Months				
Reference/	Setpoint	Indicated/Act	ual value				
Dimension:	ê 🔻	Dimension:	°C				
Decimal places:	2 🔻	Decimal places:	2 👻				
Interpolatio	on point	Setpoint	Actual value	SP	IP	м	
	1.	0.54	-6.00	54	0	5024	
	2.	1.46	0.00	146	600	3058	
	з.	2.30	9.00	230	1500	5571	
	4.	3.83	18.00	383	2400	6413	
	5.	5.20	25.00				
Insert line		Program					
Delete line							



Measuring instrument ALMEMO[®] 2690-8 with programming option KL



The linearization table programmed on linearizations at all times. the ALMEMO[®] plug can be saved as a file to the PC and additionally as an Excel table for archiving purposes. O course, it is possible to load the linearization table again from the archived file as well as from the ALMEMO[®] plug. Consequently, the user is able to access his special

Hand units from series ALMEMO® 2470, 2490 as well as 2590 are already able to process ALMEMO® plugs with a programmed characteristic curve as standard. Individual linearizations are possible in all measuring ranges of the ALMEMO[®] measuring instruments.

2. Maximum precision due to multi-point adjustment

Measurement deviations from a reference To adjust a device, the readout of the the ALMEMO® plug as fine adjustment. or a measurement standard, which were measurement instrument (actual value) is In this way it is possible to significantly identified during the calibrating of the as well as possible leveled to the reference increase the measurement accuracy of e.g. device, can be used to permanently correct value (setpoint) to obtain a correct readout. inexpensive standard sensors. a sensor or a measurement chain. In this Measurement case, we speak about adjustment.

deviations concerning several measuring points are saved to

Two-point adjustment

Sample table Two-point adjustment at 0°C and 100°C

(using the parameters ZPC = zero-point correction / SC = slope correction) example given: ZPC = -0,20 / SC = 1.0010

Measuring range PT100 204 (-200.00°C to 400.00 °C)					
basic value	setpoint	actual value	corrected value (= readout on test device)		
1. Start of meas. range	-200	-200			
2.	-20	-20.25	-20.07		
3.	0.00	-0.20	0.00		
4.	50.00	49.80	50.05		
5.	100.00	99.75	100.00		
6.	150.00	149.60	149.95		
7. End of meas. range	400.00	400.00			

Readout values concerning zero point and slope are corrected.

Multi-point adjustment

Sample table multi-point adjustment at all five meas. points

Measuring range PT100 204 (-200.00°C to 400.00 °C)					
basic value	setpoint	actual value	corrected value (= readout on test device)		
1. Start of meas. range	-200	-200			
2.	-20	-20.25	-20.00		
3.	0.00	-0.20	0.00		
4.	50.00	49.80	50.00		
5.	100.00	99.75	100.00		
6.	150.00	149.65	150.00		
7. End of meas. range	400.00	400.00			

Multi-point adjustment allows to exactly correct the readout values to the reference values.

- 1. By default, a linear interpolation between the endpoints of the adjusted range and the devicespecific upper and lower measuring range limits is carried out.
- 2. Optionally it is possible to disable any measurement outside the adjusted range (i.e. no incorrect measurements outside the adjusted range). The device will only signalize whether the result is exceeding or falling below the measurement range.

Usage

In case reference or correction values are available, the user can carry out the multithe free software ALMEMO® CONTROL value zero and gradient" the readouts of special measuring ranges).

a correction table is converted to an a pre-scaled sensor are corrected. This interpolation table containing over 30 basic procedure requires an ALMEMO[®] device values and saved to the ALMEMO® plug. (e.g. ALMEMO® 2690-8) featuring the point adjustment by himself. By means of Using the function "consider correction option "KL" (multi-point adjustment and



ALMEMO® plug with 4K EEPROM. Characteristic curve and sensor characteristics are saved to the plug

The correction table programmed on the from the ALMEMO® plug. Consequently, programmed multi-point adjustment as ALMEMO[®] plug can be saved as a file to the PC and additionally as an Excel table for archiving purposes. Of course, it is possible to load the correction table 2470, 2490 as well as 2590 are already again from the archived file as well as able to process ALMEMO® plugs with a

the user is able to access his multi-point adjustments at all times.

Hand units from series ALMEMO® 2450,

standard. For sensors that have special linearizations saved on the ALMEMO® plug, a multi-point adjustment is not possible.

Multipoint calibration						
<u>File</u> <u>I</u> able						
Meas point: 00	_5_point!					
Range: D260	Include correction v	al. (zero,slope)				
Interpolation points: 5 🗾 🗹	with range limits		Start of range	5.00 💌	End of range	5.00 💌
Next calibration 12.02.2012	Interval	12 Month	5			
Interpolation point	Setpoint	Actual value	SP	IP	M	
Start of range	-5.00	-5.00	0	0	34614	
1.	-3.50	-3.58	150	142	30341	
2.	-1.50	-1.42	350	358	40289	
3.	0.00	-0.20	500	480	27927	
4.	1.50	1.56	650	656	31508	
5.	3.50	3.64	850	864	36141	
End of range		5.00				
Insertline	Program					



Measuring instrument ALMEMO® 710 a precision measuring instrument with touchscreen

Calibration

During the calibration of the ALMEMO® measuring technology, the sensor deviation is determined in every calibration point and saved as correction value to the ALMEMO[®] plug. The measured values

for such multi-point adjusted sensors are then listed in the calibration certificate. Compared to the reference values, the identified sensor deviations are close to zero. Measurements within the calibrated interval can then be carried out with minor deviations. The measured value displayed on the ALMEMO® measuring instrument is the already corrected value and can be used directly. It is not necessary anymore to correct the displayed measured value on the basis of the calibration certificate.

Input connectors for thermocouples

Digital ALMEMO[®] D7 measuring connector for thermocouple sensors of type K, N, T, J, R, S, B, E

Measure dynamic temperature changes with up to 100 measurement operations per second. One single connector for different thermocouple types (programmable).

Optimal linearization accuracy of the thermocouple characteristic by calculation methods as per the DIN IEC 584. Increased accuracy thanks to multi-point adjustment of the thermocouple sensor during calibration. For current measuring instruments ALMEMO[®] V7, i.a. the precision measuring instruments ALMEMO[®] 710 or ALMEMO[®] 202.



Technical data and functions

- The digital ALMEMO[®] D7 measuring connector for thermocouples can be used for a variety of thermocouple types. Once connected, the thermocouple type is programmed via the ALMEMO[®] V7 measuring instrument.
- *new*: the range for thermocouple type E. For use at lowest temperatures.
- The thermocouple is connected via 2 screw terminals integrated in the measuring connector. Every measuring connector has an integrated temperature sensor directly in the screw terminals for measurement and automatic compensation of the cold junction temperature.
- The input of the ALMEMO[®] D7 measuring connector is galvanically isolated from the ALMEMO[®] V7 measuring instrument. Therefore the connected thermocouple sensor is galvanically isolated from the other connected ALMEMO[®] sensors as well.
- The digital ALMEMO[®] D7 measuring connector operates with its own integrated A/D converter. The linearization of the thermocouple characteristic is calculated using method in compliance with DIN IEC 584 (not an approximation).
- For measuring dynamic temperature changes, the ALMEMO® D7 measuring connector operates at a fast conversion rate. The

measuring rate is determined exclusively by the integrated A/D converter.

- On the ALMEMO[®] V7 measuring instrument all D7 measuring connectors operate in parallel - each at its own measuring rate. The measuring instrument's very short scan cycle is determined by the measuring rates of the D7measuring connectors - nearly irrespective of their number. The ALMEMO[®] V7 measuring instrument saves the measured values; the measuring software WinControl displays them graphically.
- The overall accuracy of the measuring operation is unaffected by the presence of an ALMEMO[®] V7 display device / data logger. In case the measuring chain - consisting of a thermocouple sensor and the connected ALMEMO[®] D7 measuring connector - is calibrated, the measuring chain can be connected to any ALMEMO[®] V7 measuring device without any additional measuring uncertainties.

At constant ambient conditions, an increased system accuracy is achieved by calibrating the thermocouple sensor using multipoint adjustment.

• To designate a sensor it is possible to program comments with up to 20 characters.

Technial data

Sensor type: Measuring input:	Thermocouple type: K, N, T, J, R, S, B, E galvanically isolated, dielectric strength 50V	System accuracy at conve type K, K2, N, N2, J, T type E type R S B	rsion rate 10 mops: $\pm 0.2K \pm 0.02\%$ of measured value $\pm 0.1K \pm 0.02\%$ of measured value $\pm 0.8K \pm 0.02\%$ of measured value	
Measuring ranges:	K -200.0 to +1370.0 °C N 200.0 to +1300.0 °C	Temperature drift	0.003 %/K (30 ppm)	
	J -210.0 to +1100.0 °C	Cold junction compensation	on sensor: NTC 10K at 25°C	
пеж:	E $-270.0 \text{ to } +800.0 \degree \text{C}$ T $-200.0 \text{ to } +400.0 \degree \text{C}$ S $-50.0 \text{ to } +1760.0 \degree \text{C}$ R $-50.0 \text{ to } +1760.0 \degree \text{C}$ B $+250.0 \text{ to } +1820.0 \degree \text{C}$ K2 $-200.00 \text{ to } +1370.00 \degree \text{C}$ N2 $-200.00 \text{ to } +1300.00 \degree \text{C}$	Cold junction compensati System accuracy: Nominal temperature: Supply voltage: Current consumption:	on effective in the range -10 °C to +60 °C: -30°C to +100°C ±0,2K ± 0,01K/°C 23 °C ± 2 K 6, 9, 12 V from ALMEMO [®] device approx, 5 mA	
Resolution:	0.1 K* respectively 0.01 K	Environmental conditions see page 01.04 onwards		
	for measuring range K2 / N2	 * Factory setting. The desired measuring range can be programmed 		
Conversion rate:	2.5*, 10, 50, 100 mops			
Linearization	calculation method (not an approximation)	on the ALMEMO [®] V7 device		

Types:

ALMEMO® D7 measuring connector for thermocouples.Fast measuring rate. Integrated galvanic isolation. ZTD70

Input connectors for thermocouples

ALMEMO® Connector for Thermocouple Types K, N, J, T



Variants (with thermal material)

Model	Meas. Range	Resolution	
NiCr-Ni (K)	-200.0 to +1370.0°C.	0.1 K	ZA9020FS
NiCroSil-NiSil (N)	-200.0 to +1300.0°C.	0.1 K	ZA9021FSN
Fe-CuNi (J)	–200.0 to +1000°C.	0.1 K	ZA9021FSJ
Cu-CuNi (T)	-200.0 to +400°C.	0.1 K	ZA9021FST

ALMEMO[®] measuring module for thermocouples, types K, J, T, electrically isolated, up to 1000 V Type ZAD 950 AB



• Electrically isolated measurement of thermocouples (in particular bare thermo-wire types) on live parts

Order no.

- Digital transfer of measured values to the ALMEMO[®] measuring instrument
- Connecting cable, fitted with ALMEMO[®] plug

Technical data

Sensor	Thermocouple			
Measuring range				
ZAD950ABK	NiCr-Ni (K) -200 to 1370 °C			
ZAD950ABJ	Fe-CuNi (J) -200 to 1000 °C			
ZAD950ABT	Cu-CuNi (T) -200 to 400 °C			
Resolution	0.1 K			
Linearization accuracy	$\pm 0.05 \text{ K} \pm 0.05 \%$ of measured value			
Precision class	C (see page 01.05)			
Measuring rate	2.5 measurements/sec.			

Electrical isolation	1 kV DC/AC permanent, 4 kV for 1s	
Sensor connection	4-mm safety sockets and safety plugs (with screw terminals)	
Power supply	6 to 13 VDC via ALMEMO® device	
Current consumption	approx. 30 mA	
Connecting cable	1.5 meters with ALMEMO [®] plug	
Housing	Dimensions (LxWxH) 127x83x38mm, ABS (acrylonitrile butadiene styrene)	

Types:

ALMEMO® measuring module for NiCr-Ni (K), including 1.5 meters ALMEMO® connecting cable	ZAD950ABK
ALMEMO® measuring module for Fe-CuNi (J) including 1.5 meters ALMEMO® connecting cable	ZAD950ABJ
ALMEMO® measuring module for Cu-CuNi (T) including 1.5 meters ALMEMO® connecting cable	ZAD950ABT
Please note : thermocouple must be ordered extra; e.g. thermo-wires see Chapter Temperature	

DAkkS- or Factory calibration KE90xx, electrically, for digital measuring module, see Chapter Calibration. DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Order no.

Input connectors for thermocouples

ALMEMO[®] Connector for Thermocouple Types U, L, S, R, B, AuFe-Cr



Types			Order no.
Model	Meas. Range	Resolution	
Cu-CuNi (U)	-200.0 to +600.0°C	0.1 K	ZA9000FSU
Fe-CuNi (L)	-200.0 to +900°C.	0.1 K	ZA9000FSL
PtRh10-Pt (S)	0.0 to +1760.0°C	0.1 K	ZA9000FSS
PtRh13-Pt (R)	0.0 to +1760.0°C	0.1 K	ZA9000FSR
PtRh30-PtRh6 (B)	+400.0 to +1800.0°C	0.1 K	ZA9000FSB
AuFe-Cr (A)	-270.0 to +60.0°C	0.1 K	ZA9000FSA

ALMEMO® Connector with integrated cold junction sensor for all thermocouples



For especially exacting applications demanding the highest possible level of precision or performed under unfavorable conditions (e.g. subject to thermal irradiation) **Programming:** 1st channel, NTC, integrated cold junction sensor, resolution 0.01 K 2nd channel, thermocouple, resolution 0.1 K; please specify type !

Types:			Order no.
Model	Meas. Range	Resolution	
NiCr-Ni (K)	–200.0 to +1370.0°C.	0.1 K	ZA9400FSK
NiCroSil-NiSil (N)	–200.0 to +1300.0°C.	0.1 K	ZA9400FSN
Fe-CuNi (L)	–200.0 to +900°C.	0.1 K	ZA9400FSL
Fe-CuNi (J)	–200.0 to +1000°C.	0.1 K	ZA9400FSJ
Cu-CuNi (T)	–200.0 to +400°C.	0.1 K	ZA9400FST
Cu-CuNi (U)	–200.0 to +600.0°C	0.1 K	ZA9400FSU
PtRh10-Pt (S)	0.0 to +1760.0°C	0.1 K	ZA9400FSS

Digital ALMEMO® D7 measuring connector for Pt100 / Pt1000 temperature sensor

High-level resolution of 0.01 K across the entire measuring range up to 850 °C Linearization of the Pt100 / Pt1000 characteristic calculated Calibration with greater accuracy by subjecting the temperature sensor to multi-point adjustment Only for latest ALMEMO[®] V7 measuring instruments, including ALMEMO[®] 500, 710, 809, 202.





The new ALMEMO[®] D7 measuring connector provides even greater precision!

Technical data and functions

- The digital ALMEMO[®] D7 measuring connector uses its own integrated A/D converter. It provides a high-level resolution of 0.01 K across the entire measuring range up to 850 °C. Linearization of the Pt100 / Pt1000 characteristic is calculated in compliance with DIN IEC 751 (not an approximation).
- The overall accuracy of the measuring operation is unaffected by the presence of an ALMEMO[®] V7 display device / data logger. The whole measuring chain, comprising e.g. a Pt100 / Pt1000 sensor and the connected ALMEMO[®] D7 measuring connector, can be calibrated end-to-end. Calibration can be performed with greater accuracy by subjecting the temperature sensor to a process of multi-point adjustment.
- The measuring rate is determined entirely and exclusively by the integrated A/D converter. On the ALMEMO[®] V7 measuring instrument all D7 measuring connectors operate in parallel at their own measuring rate. The measuring instrument's very short scan cycle is determined by the measuring rates of the D7 measuring connectors irrespective of their number.
- Sensor identification can be programmed with designations up to 20 characters in length.

Technical data

Sensor type	Pt100, 4 conductors or	Linearization	calculated
	Pt1000, 4 conductors		(not an approximation)
Measuring input	electrically interconnected with the power supply (ALMEMO [®] device ground)	Accuracy Pt100 Pt1000	0.07 K +2 digits 0.08 K +2 digits
Measuring range	-200 to +850 °C	Nominal temperature	+22 °C ±2 K
Resolution	0.01 K	Temperature drift	0.003 % / K (30 ppm) (resistance)
Conversion rate	10 mops	Supply voltage	from 6 V up. from ALMEMO [®] device (sensor supply voltage)
Pt100	approx. 1 mA	Current consumption	approx. 9 mA
Pt1000	approx. 0.1 mA	Environmental condition	s see page 01.04 onwards

Types:				Order no.
Туре	Measuring range	Range	Resolution	
Pt100, 4 conductors	-200+850 °C	DP04	0.01 K	ZPD700FS
Pt1000, 4 conductors	-200+850 °C	DP14	0.01 K	ZPD710FS

Digital ALMEMO® D6 measuring connector for Pt100 temperature sensor

Digital temperature sensors now also for ALMEMO® V6 measuring instruments, e.g. ALMEMO® 5690, 2690, 2590 Resolution of 0.01 K across the entire measuring range up to 400 °C Linearization of the Pt100 characteristic calculated

Calibration with greater accuracy by subjecting the temperature sensor to multi-point adjustment





The new ALMEMO[®] D6 measuring connector provides even greater precision!

Technical data and functions

- The digital ALMEMO[®] D6 measuring connector uses its own integrated A/D converter. It provides a high-level resolution of 0.01 K across the entire measuring range up to 400 °C. Linearization of the Pt100 characteristic is calculated in compliance with DIN IEC 751 (not an approximation).
- The overall accuracy of the measuring operation is unaffected by the presence of an ALMEMO[®] display device / data logger. The whole measuring chain, comprising e.g. a Pt100 sensor

and the connected ALMEMO[®] D6 measuring connector, can be calibrated end-to-end. Calibration can be performed with greater accuracy by subjecting the temperature sensor to a process of multi-point adjustment.

• The ALMEMO[®] D6 measuring plug operates with its own refresh rate. The measured values are scanned digitally at the conversion rate of the ALMEMO[®] measuring device.

Sensor type	Pt100, 4 conductors or	Accuracy	
Measuring input	electrically interconnected	Pt100	0.07 K +2 digits
	with the power supply	Nominal temperature	+22 °C ±2 K
	(ALMEMO [®] device ground)	Temperature drift	0.003 % / K (30 ppm) (resistance)
Measuring range	-200 to +400 °C	Supply voltage	from 6 V up. from ALMEMO [®] device
Resolution	0.01 K		(sensor supply voltage)
Refresrate:	0,1 s	Current consumption	approx. 9 mA
Measuring current		Environmental condition	s see page 01.04 onwards
Pt100	approx. 1 mA		
Linearization	calculated		
	(not an approximation)		

Technical data

Types:

Type Pt100, 4 conductors Measuring range -200...+400 °C Resolution 0.01 K Order no.

ZAD030FS



Digital ALMEMO[®] D7 Precision measuring connector for Pt100 temperature sensor, resolution 0.001 K

Digital precision measuring connector with highest resolution of 0.001 K across the entire measuring range up to 400 °C Linearization of the Pt100 characteristic calculated Calibration with greater accuracy by subjecting the temperature sensor to multi-point adjustment For ALMEMO[®] V7 measuring instruments, including ALMEMO[®] 500, 710, 809, 202, 204.



The new ALMEMO[®] D7 measuring connector provides even greater precision!



Digital precision resistance sensor Pt100 FPD723L0250A3D (example)

Technical data and functions

- *new:* The digital ALMEMO[®] D7 precision measuring connector becomes a reference sensor with highest accuracy when used with a suitable Pt100 sensor (see following page).
- *new:* The digital ALMEMO[®] D7 precision measuring connector uses its own integrated A/D converter. It provides a highest resolution of 0.001 K across the entire measuring range up to 400 °C.
- Linearization of the Pt100 characteristic curve in the measuring connector is calculated in compliance with DIN IEC 751 (not an approximation).
- The overall accuracy of the measuring operation is unaffected by the presence of an ALMEMO® V7 display device / data logger. The whole measuring chain, comprising e.g. a Pt100

sensor and the connected ALMEMO[®] D7 measuring connector, can be calibrated end-to-end. Calibration can be performed with greater accuracy by subjecting the temperature sensor to a process of multi-point adjustment.

- The measuring rate is determined entirely and exclusively by the integrated A/D converter. On the ALMEMO® V7 measuring instrument all D7 measuring connectors operate in parallel at their own measuring rate. The measuring instrument's very short scan cycle is determined by the measuring rates of the D7 measuring connectors irrespective of their number.
- Sensor identification can be programmed with designations up to 20 characters in length.

Technical data

Sensor type	Pt100, 4 conductors	Accuracy	± 0.015 K ± 2 digits
Measuring input	electrically interconnected	Nominal temperature	+22 °C ±2 K
	with the power supply	Temperature drift	0.003 % / K (30 ppm) (resistance)
	(ALMEMO [®] device ground)	Supply voltage	starting at 6 V from ALMEMO [®] device
Measuring range	-200 to +400 °C	Supply voltage	(sensor supply voltage)
Resolution	0.001 K	Current consumption	approx. 9 mA
Conversion time:	3.4 seconds	Ambient conditions see fr	om page 01.04
Measuring current	approx. 1 mA		
Linearization	calculated		
	(not an approximation)		

Types:

Type Pt100, 4 conductors Measuring range -200...+400 °C

Resolution 0.001 K

Order no.

ZPD730FS

Input connectors for Pt100

Note on suitable sensors:

The sensor determines the accuracy, stability, hysteresis and long-term stability of the measuring chain consisting of sensor and digital connector. For the sensor, the following must be taken into account:

- The type of Pt100 sensor element determines, among other things, the achievable measurement uncertainty / stability.
- The design (sensor diameter, installation of the sensor element, powdered or with thermal paste) influences the selfheating and the hysteresis for the measurement uncertainty.

The self-heating must be included in the measurement uncertainty: If the self-heating is NOT known for the sensor design at hand, a lump sum must be charged.

Example: For a sufficiently long sheath element, an amount of 17 mK is recommended. In comparison: For the Ahlborn precision probe FPA923/FPD723 the self-heating was determined and is included in the measurement uncertainty with typ. 2 mK. The hysteresis must be described in addition to the measurement uncertainty:

If the hysteresis is not determined, a lump sum of up to 0.2 % of the span is recommended in international regulations.

Example: Calibration range 0 to 400 °C, hysteresis lump sum up to 0.8 K or calibration range 0 to 100 °C up to 0.2 K (200 mK).



Digital precision resistance sensor Pt100 up to 400 °C with resolution of 0.001 K as reference sensor, with ALMEMO® D7 connector for ALMEMO® V7 measuring devices / data logger

Digital precision resistance sensor with highest accuracy and linearity for temperature measurements in a wide temperature range. Application as reference probe for comparison measurements in research, development, quality assurance and production processes.

For ALMEMO® V7 measuring instruments: ALMEMO® 500, 710, 809, 202, 204.



Digital precision resistance sensor Pt100 FPD723L0250A3D (example)



see chapter 07 Temperature

Types	Order no.
Digital precision resistance sensor Pt100 as reference sensor, with cable and ALMEMO® D7 connector.	
Incl. DAkkS calibration certificate (2 temperature points at 0°C and 100°C incl. multi-point adjustment).	FPD723L0250A3D

Input connectors for Pt100

ALMEMO® Connector for Pt100 Sensors/Pt1000 Sensors



Types:			Order no.
Model	Meas. Range	Resolution	
Pt100 4-conductor	-200.0 to +850.0°C	0.1 K	ZA9030FS1
Pt100 4-conductor	–200.0 to +400.0°C *	0.01 K	ZA9030FS2
Pt1000 4-conductor	-200.0 to +850.0°C *	0.1 K	ZA9030FS4
Pt1000 4-conductor	–200.0 to +400.0°C *	0.01 K	ZA9030F85
			* Data may vary depending on device: (see data sheet per devic

ALMEMO® Connector for Ni100 Sensors/Ni1000 Sensors



Types:			Order no.
Model	Meas. Range	Resolution	
Ni100	-60.0 to +240.0°C	0.1 K	ZA9030FS3
Ni1000	-60.0 to +240.0°C	0.1 K	ZA9030FS6

ALMEMO[®] Connector for Resistance



Technical Data ZA9003SS4:

Connection	2-wire
Linearization accuracy:	$\pm 0,2 \% \pm 0,02$ kOhm
	Linearization is saved in the
	ALMEMO [®] connector; (this is not
	available with ALMEMO® 2450, 8390)

Types:

Model	Meas. Range
Ohm	0.00 to 500.00
Ohm	0.0 to 5000.0*
kOhm	0 to 110.00 kOhm

ZA9003FS
ZA9003FS2
ZA9003SS4

Order no.

* Data may vary depending on device; (see data sheet per device)

10/2021 • We reserve the right to make technical changes.

Digital ALMEMO[®] D6 measuring connector for temperature sensors NTC

High levels of precision and resolution 0.001 K across measuring range -20 to +65 °C Linearization of the NTC characteristic - calculated using Galway Steinhart coefficients Increased measured value accuracy - thanks to multi-point adjustment of the NTC sensor during calibration For all ALMEMO[®] V6 and V7 measuring instruments, including ALMEMO[®] 2490 and ALMEMO[®] 202.





Technical data and functions

• The digital ALMEMO[®] D6 measuring connector uses its own integrated A/D converter. Linearization of the NTC characteristic is calculated using the Galway Steinhart coefficients (not an approximation). Across measuring range -20 to +65 °C this produces the very high resolution of 0.001 K. • The digital temperature sensor reaches this high level of precision irrespective of any extension cables used and of any processing in the ALMEMO[®] display device / data logger. Overall accuracy is determined exclusively by the NTC sensor and the ALMEMO[®] D6 measuring connector. This increased measured value accuracy is achieved by subjecting the NTC sensor to multi-point adjustment during calibration.

New:

With the ALMEMO[®] D6 measuring plug, customer-specific NTC sensors can be connected to the Almemo[®] system after the corresponding Steinhart-Hart coefficients have been configured via the sensor menu. When using own sensors with 10 kOhm resistance at 25 °C, no additional adjustment of the connector is necessary (sensors with different resistance values on request).

Technical data

Sensor type	NTC type N		
Measuring input	Electrically interconnected with the power supply (ALMEMO [®] device ground)	Accuracy Range DNtc / DNt2 Range DNtc3	±0.05 K at -50 to +100 °C ±0.02 K at -20 to +65 °C
Measuring ranges	see variants	Nominal temperature	23 °C ±2 K
Resolution	see variants	Temperature drift	0.004 % / K (40 ppm)
Refresh rate	0.3 seconds for up to two channels	Supply voltage	from 6 V up, from ALMEMO [®] device (sensor supply voltage)
Linearization	(not an approximation)	Current consumption	approx. 4 mA
		Environmental condition	s see page 01.04 onwards

Types:				Order no.
Type / input	Measuring range	Range	Resolution	
NTC, 1 input	-50+125 °C	DNtc	0.01 K	ZAD040FS
NTC, 2 inputs	-50+125 °C	DNtc/DNt2	0.01 K	ZAD040FS2
NTC, 1 input	-20+65 °C	DNt3	0.001 K	ZAD040FS3

ALMEMO[®] Connector for Ntc Sensors



Types:			Order no.
Model	Meas. Range	Resolution	
Ntc Typ N	-50.0 to +125.0°C	0.01 K	ZA9040FS
2xNtc Typ N	-50.0 to +125.0°C	0.01 K no electrical isolation	ZA9040FS2

Digital ALMEMO[®] D7 measuring connector for potentiometric sensors (displacement transducers, etc.)

For displacement transducers and other potentiometric sensors High-speed measuring at 100 measuring operations per second (mops) and a resolution of 10,000 digits Only for the latest ALMEMO[®] V7 measuring instruments, including ALMEMO[®] 500, 710, 809, 202.





This new, innovative ALMEMO[®] D7 measuring connector successfully combines high precision and high speed. The user can set the preferred configuration quickly and easily on the AL-MEMO[®] V7 measuring instrument itself.

Technical data and functions

- The ALMEMO® D7 digital measuring connector operates with its own integrated A/D converter. Overall measuring accuracy is unaffected by the presence of an ALMEMO® V7 display device / data logger. The whole measuring chain, comprising e.g. a displacement transducer and the connected ALMEMO® D7 measuring connector, can be adjusted end-to-end.
- The measuring rate is determined exclusively by the integrated A/D converter. On the ALMEMO® V7 measuring instrument all D7 measuring connectors operate in parallel each at its own measuring rate. The measuring instrument's very short scan cycle is determined by the measuring rates of the D7 measuring connectors more or less irrespective of their number.
- For measuring dynamic processes the ALMEMO[®] D7 measuring connector operates at a fast conversion rate. The ALMEMO[®] V7 measuring instrument saves the measured values; the measuring software WinControl displays them in graphical form.
- The voltage drop is measured at the potentiometer. The 2-volt reference voltage is supplied via the ALMEMO[®] D7 plug.
- The sensor is scaled to the physical quantity (e.g. displacement in mm); this is performed via the ALMEMO® V7 device (on the device itself or using ALMEMO® Control software) - with zero-point adjustment and final value adjustment. The measured value's assigned units can be up to 6 characters in length. Sensor identification can be programmed with a comments text up to 20 characters in length.

Sensor type	Potentiometer	Reference voltage	2 V
Measuring input	Electrically connected to the power	System accuracy	0.02 % ?*? ±2 digits
	supply	Nominal temperature	22 °C ±2 K
(ALMEMO [®] device ground)	Temperature drift	0.003 % / K (30 ppm)	
Input range	-2 to +2 V	Supply voltage	from 6 V up via the AI MEMO [®] device
Display range	0.00 to 100.00 %	Supply voltage	itself (sensor supply)
Resolution	0.01 %	Current consumption	approx. 8 mA (without sensor)
Conversion rate	100 mops	Environmental conditions see page 01.04 onwards	

Technical data

Types:

Type Potentiometer Display range 0...100 % Resolution 0.01 %

Order no.

Input connectors for potentiometer

ALMEMO® Connector for Potentiometer pickoffs



Technical Data

Sensor supply:	2.5 V
Temperature coefficient:	< 50 ppm/K

Types:			Order no.
Model	Meas. Range	Resolution	
2.6 V DC Differenz	-2.6 to +2.6*	0.1 mV	ZA9025FS3
	* Data may vary depending on	device; (see data sheet per device)	

Digital ALMEMO[®] D7 measuring connector for bridge differential mV

For force transducers (tension / compression), torque transducers, or strain gauges High-speed measuring at 1000 measuring operations per second (mops) and resolution 50,000 digits or high-level resolution at up to 200,000 digits and 10 mops Only for latest ALMEMO[®] V7 measuring instruments, including ALMEMO[®] 500, 710, 809, 202.





The new ALMEMO[®] D7 measurement plug enables high measuring speeds or high measuring accuracy applicable for a vast variety of measuring tasks.

The user can select the preferred configuration quickly and easily on the ALMEMO[®] V7 measuring instrument itself.

Technical data and functions

- The digital ALMEMO® D7 measuring connector uses its own integrated A/D converter. The overall accuracy of the measuring operation is unaffected by the presence of an ALMEMO® V7 display device / data logger. The whole measuring chain, comprising e.g. a force transducer and the connected ALMEMO® D7 measuring connector, can be calibrated end-to-end.
- The measuring rate is determined entirely and exclusively by the integrated A/D converter. On the ALMEMO® V7 measuring instrument all D7 measuring connectors operate in parallel at their own measuring rate. The measuring instrument's very short scan cycle is determined by the measuring rates of the D7 measuring connectors irrespective of their number.
- For measuring dynamic processes the ALMEMO[®] D7 measuring connector operates in the high-speed range at a fast conversion rate. The ALMEMO[®] V7 measuring instrument saves the measured values; the measuring software WinControl

displays them in graphical form. If high-level resolution and stable values are required, e.g. precision transducers for force, the ALMEMO[®] D7 measuring connector operates in the "High-level resolution" range but at a reduced conversion rate.

- Measurements are taken using a full bridge with a 4-conductor circuit. The bridge is powered from the ALMEMO[®] D7 plug.
- The sensor is scaled to its actual physical quantity (e.g. end value 1 kN with characteristic 2 mV / V); this is performed via the ALMEMO[®] V7 device (device itself or ALMEMO[®] Control software). zero-point adjustment, scaling of end value by entering characteristic mV / V or adjustment by loading the bridge with end value The assigned units can be up to 6 characters in length. Sensor identification can be programmed with designations up to 20 characters in length.

Technical data

Sensor type	Full bridge, 4 conductors	System accuracy	0.02 % +2 digits at 10 measurements / second	
Measuring input	with the power supply	Nominal temperature	+22 °C ±2 K	
	(ALMEMO [®] device ground)	Temperature drift	0.003 % / K (30 ppm)	
Input range	-29.3 to +29.3 mV	Supply voltage	from 6 V up. from ALMEMO® device	
Display range, Conversion rate, see variants			(sensor supply voltage)	
Bridge power supply	5 V, self-calibrating with divider chain Accuracy 0.01 %	Current consumption	approx. 15 mA (without force transducer)	
Temperature drift 10 ppm / K		Environmental conditions	see page 01.04 onwards	

Types:			Order no.
Range	Display range	Conversion rate	
DMS1*	±200 000 digits	10 mops	
or			
DMS2	±50 000 digits	1000 mops	ZKD700FS
* Factory setting : T	he desired measuring range can b	e programmed on the ALMEMO [®] V7 device itself.	
Option: Configura	ation of ALMEMO® D7 measu	uring connector; measuring rate 1000 mops	OA9007PRM1000

Input connectors for measuring bridges

ALMEMO® Connector for measuring bridges, millivolt / volt differential

With zero-symmetrical voltage supply of ± 2.5 V stabilized from the ALMEMO[®] device



Technical Data

Sensor supply	
Voltage U _F :	$5V\pm0.05V$
Temperature coefficient:	<50ppm/°C
Output current:	25 mA at $U_{G} = 12 V$ 30 mA at $U_{G} = 9 V$ 50 mA at $U_{G} = 6 V$
Ruhestrom:	approx. 3 mA
Energy saving	So long as the measuring point is not selected, the bridge voltage remains switched OFF.

Types:			Order no.
Model	Meas. Range	Resolution	
55mV DC	-10.0 to +55.0	1 µV	ZA9105FS0
26mV DC	-26.0 to +26.0	1 µV	ZA9105FS1
260mV DC	-260.0 to +260.0	10 μV	ZA9105FS2
2.6V DC	-2.6 to +2.6*	0.1 mV	ZA9105FS3
	* Data may vary dependin	g on device; (see data sheet per device)	

Input connectors for DC

Digital ALMEMO[®] D7 measuring connector for DC voltage differential (volt) / DC current differential (mA)

Fast measuring rate, up to 1000 measuring operations per second (mops) at resolution up to $1 \text{ mV} / 10 \mu \text{A}$ (2,000 digits) or High resolution up to 0.001 mV / 0.1 μA (200,000 digits) at 5 mops Only for latest ALMEMO[®] V7 measuring instruments, including ALMEMO[®] 500, 710, 809, 202.

U+ Signal+ U-U-Without supply voltage

with supply voltage

Technical data and functions

- The digital ALMEMO[®] D7 measuring connector uses its own integrated A/D converter. The overall accuracy of the measuring operation is unaffected by the presence of an ALMEMO[®] V7 display device / data logger. The measuring rate is determined entirely and exclusively by the integrated A/D converter. On the ALMEMO[®] V7 measuring instrument all D7 measuring connectors operate in parallel at their own measuring rate. The measuring instrument's very short scan cycle is determined by the measuring rates of the D7 measuring connectors irrespective of their number.
- For measuring dynamic processes the ALMEMO[®] D7 measuring connector operates in the high-speed range at a fast

The new ALMEMO[®] D7 measurement plug enables high measuring speeds or high measuring accuracy applicable for a vast variety of measuring tasks.

The user can select the preferred configuration quickly and easily on the ALMEMO[®] V7 measuring instrument itself.

conversion rate. The ALMEMO[®] V7 measuring instrument saves the measured values; the measuring software WinControl displays them in graphical form. If high-level resolution and stable values are required, e.g. precision transducers for pressure, the ALMEMO[®] D7 measuring connector operates in the high-resolution range but at a reduced conversion rate.

Measuring transducers without their own mains unit and needing a power supply are powered from the ALMEMO® D7 plug. Each signal is scaled to its actual physical quantity (e.g. pressure 25 bar at voltage 10 volts); the assigned units can be up to 6 characters in length. Sensor identification can be programmed with designations up to 20 characters in length.

Technical data

Measuring input	electrically interconnected with the power supply	Nominal temperature	+22 °C ±2 K
	(ALMEMO [®] device ground)	Temperature drift	0.003 % / K (30 ppm)
Measuring range	see variants	Supply voltage	6 / 9 / 12 V, from ALMEMO [®] device
Conversion rate, resolu	tion see variants		(sensor supply voltage)
Overload	see variants	Current consumption	approx. 8 mA (without transducer)
Internal resistance	see variants	Sensor supply	6 / 9 / 12 V, from ALMEMO® device
Input current	100 pA	ZED70xFSV15: 15±0),6 V, max. 50 mA at device voltage 12 V
		ZED70xFSV24: 24 ±	1 V, max. 30 mA at device voltage 12 V
System accuracy	0.02 % +2 digits	Environmental conditions see page 01.04 onwards	
5	at 5 measurements / second		



Input connectors for DC

Types:

Measuring range	Resolution Conversion rate (mops)	Internal resistance	Overload	Order no.
-2.2+2.2 Volt	0.01 mV, 5 mops* / 0.1 mV, 500 mops / 1 mV, 1000 mops	110 kOhm	±3 V	ZED700FS
-64+64 mV -250+250 mV*	0.001 mV, 5 mops*	5 GOhm	±2.8 V	ZED700FS2
-20+20 Volt	0.1 mV, 5 mops* / 1 mV, 500 mops / 10 mV, 1000 mops	110 kOhm	±30 V	ZED702FS ZED702FSV15** ZED702FSV24**
-60+60 Volt	1 mV, 5 mops* / 10 mV, 500 mops / 10 mV, 1000 mops	103 kOhm	±60 V	ZED702F82
-20+20 mA	00.1 $\mu A,5$ mops* / 1 $\mu A,500$ mops / 10 $\mu A,1000$ mops	100 Ohm	±28 mA	ZED701FS ZED701FSV15** ZED701FSV24**
* Factory setting : The desired measuring range can be programmed on the ALMEMO® V7 device itself ** Sensor supply see above: Technical data				

Option:

Configuration of ALMEMO[®] D7 measuring connector measuring rate 500 mops measuring rate 1000 mops

OA9007PRM500 OA9007PRM1000

Accessories	Order no.
Galvanic isolation up to 50 V for ALMEMO [®] D7 sensors. pluggable cabel, length = $0,2$ m	ZAD700GT

ALMEMO[®] Connector for Voltage Millivolt



Types:			Order no.
Model	Meas. Range	Resolution	
55 mV DC	-10.0 to +55.0	1 μV	ZA9000FS0
26 mV DC	-26.0 to +26.0	1 μV	ZA9000FS1
260 mV DC	-260.0 to +260.0	10 µV	ZA9000FS2

ALMEMO[®] Connector for Volt DC

Technical Data	
Accuracy divider:	only 5.5 / 26 V connector, ±0.1% of measured value Temperature coefficient: <10 ppm/K Nominal temperature: 23°C ±2 K

Types:			Order no.
Model	Meas. Range	Resolution	
2.6 V DC	-2.6 to +2.6*	0.1 mV	ZA9000FS3
5.5 V DC (divider 100:1)	-1.0 to 5.5	0.1 mV	ZA9602FS4
26 V DC (divider 100:1)	-26.0 to +26.0	1 mV	ZA9602FS
2 mal 26 V DC (2 x divider)	-26.0 to +26.0	1 mV no electrical isolation	ZA9602FS2
		* Data may vary depending on device; (see	data sheet per device)

ALMEMO® Connector for DC voltage difference millivolts / volt

for sensors / transmitters, Supply from $ALMEMO^{\circledast}\;$ device



Tec	hnic	cal C)ata

Sensor supply	(for voltage see technical data of ALMEMO [®] device)
Accuracy divider:	only 26V connector ±0,1% of meas. value Temperature coefficient: <10 ppm/K Nominal temperature: 23°C ±2 K

(Connection diagram for connectors with 4 clamps, see next page)

Types:			Order no.
Model	Meas. Range	Resolution	
55 mV DC	-10.0 to +55.0	1 μV	ZA9000FS0D
26 mV DC	-26.0 to +26.0	1 μV	ZA9000FS1D
260 mV DC	-260.0 to +260.0	10 µV	ZA9000FS2D
2.6 V DC	-2.6 to +2.6*	0.1 mV	ZA9000FS3D
26 V DC (divider 100:1)	-26.0 to +26.0	1 mV	ZA9602FS3
	* Data may vary depending of	n device; (see data sheet per device)	

Input connectors for DC

ALMEMO® Connector for DC Millivolt / Volt Differential

for sensors / transmitters, Supply : 12 V from the ALMEMO $^{\mbox{\tiny \ensuremath{\mathbb{R}}}}$ device



Technical Data

Sensor supply U_F : Device voltage U_G :	12.2 12.5V (15V/24V on request) 8 12 V
Output current:	$100 \text{mA} \text{ at } \text{U}_{\text{G}} = 9 \dots 12 \text{V}$
Accuracy divider:	only 26V connector $\pm 0,1\%$ of meas. value Temperature coefficient: <10 ppm/K Nominal temperature: 23°C ± 2 K

Types:			Order no.
Model	Meas. Range	Resolution	
55mV DC	-10.0 to +55.0	1 µV	ZA9600FS0V12
26mV DC	-26.0 to +26.0	1 µV	ZA9600FS1V12
260mV DC	-260.0 to +260.0	10 μV	ZA9600FS2V12
2.6V DC	-2.6 to +2.6*	0.1 mV	ZA9600FS3V12
26V DC (divider 100:1)	-26.0 to +26.0	1 mV	ZA9602FS3V12
	* Data may vary dependin	g on device; (see data sheet per device).	

for sensors / transmitters, Supply : 5 V from the ALMEMO[®] device Technical Data



Bulu	
Sensor supply U _F :	5 V ±2 % (max.)
Device voltage U_{g} :	8 12 V
Output current:	50 mA at $U_{g} = 9 \dots 12V$
Accuracy divider:	±0,1% v. Mw.
	Temperature coefficient: <10 ppm/K
	Nominal temperature: $23^{\circ}C \pm 2 K$

Types:			Order no.
Model	Meas. Range	Resolution	
5.5 V DC (divider 100:1)	-1.0 to 5.5	0.1 mV	ZA9602FS5V05

DAkkS- or Factory calibration KE90xx, electrically, for digital measuring module, see Chapter Calibration. DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Input connectors for DC

ALMEMO[®] Connector for DC Current mA



Technical Data

Accuracy shunt:	$\pm 0,1\%$ of measured value
	Temperature coefficient: <25 ppm/K
	Nominal temperature: 23°C ±2 K

Types:			Order no.
Model	Meas. Range	Resolution	
32 mA DC	-32.0 to +32.0*	1 μΑ	ZA9601FS1
4/20 mA DC	0 to 100%	0.01 %	ZA9601FS2
2 mal 32 mA DC	-32.0 to +32.0*	1 μA no electrical isolation	ZA9601FS3
2 mal 4/20 mA DC	0 to 100%	0.01 % no electrical isolation	ZA9601FS4
		* Data may vary depending on	device; (see data sheet per device)

ALMEMO[®] Connector for DC mA Differential

for sensors / transmitters, Supply from the $ALMEMO^{\circledast}\,$ device



data
<25 ppm/K
PC + 2K
2

Types:			Order no.
Model	Meas. Range	Resolution	
32 mA DC	-32.0 to +32.0*	1 μΑ	ZA9601FS5
4/20 mA DC	0 to 100%	0.01 %	ZA9601FS6
			* Data may vary depending on device; (see data sheet per device)

ALMEMO[®] for DC mA Differential

for sensors / transmitt	itters, Supply 12V from the ALM	MO [®] devi	دہ Technical Data		
	U+ I _M / GND		Sensor supply U _F : Device voltage U _G :	12,2 12,5V (15V/24V on request) 8 12V	
			Output current:	100mA at $U_{g} = 9 \dots 12 \text{V}$	
	(3-wire transmitter can also be connected)	Accuracy shunt:		±0,1% of measured value Temperature coefficient: <25 ppm/K Nominal temperature: 23°C ±2 K	
Types:				Order no.	
Model	Meas. Range	Resolut	ion		
32mA DC	-32.0 to +32.0*	1 μΑ		ZA9601FS5V12	
4-20mA DC	0 to 100%	0.01 %		ZA9601FS6V12	
	* Data may vary depending on	device; (see	e data sheet per device)		

Fast digital ALMEMO[®] D7 measuring module for DC voltage / DC current / DC power

Dynamic measurement of DC signals with 1000 mops (measuring operation per second). Overvoltage proof measuring input. Galvanically isolated up to 6 kV. For connecting current ALMEMO[®] V7 measuring instruments: ALMEMO[®] 500, 710, 809, 202, 204



Technical data

see chapter Electrical variables

Types

Measuring module including touch-proof connecting cable, ALMEMO[®] connection cable permanently connected to the ALMEMO[®] D7 plug

DC voltage

1 ALMEMO[®] measuring channel: voltage

Measuring range	Resolution	Overload	Input resistance	Order no.
±60 V DC	0.01 V	±90 V	1 MOhm	ZED700AB3
±400 V DC	0.1 V	$\pm 400 \text{ V}$	4 MOhm	ZED700AB5

DC current

1 ALMEMO® measuring channel: current

Measuring range	Resolution	Overload	Input resistance	Order no.
±20 mA DC	0.01 mA	±500 mA	4.7 Ohm	ZED701AB1
±200 mA DC	0.1 mA	$\pm 500 \text{ mA}$	1 Ohm	ZED701AB2
±2 A DC	0.001 A	$\pm 4 \text{ A}$	100 mOhm	ZED701AB3
±20 A DC*	0.01 A	±20 A	8 mOhm	ZED701AB5
* ~	(C10A E	· · · · ·		10

* Continuous operation up to a maximum of 10A. For currents exceeding the maximum of 10 A, the measuring period is 10 minutes. After that, the device needs to cool down to room temperature.

DC power

3 ALMEMO® measuring channels: voltage, current, power

Measuring range current**	Measuring range power (calculated)	Resolution power	Order no.
±2 A DC	120 W	0.1 W	ZED707AB33
$\pm 20 \text{ A DC}^*$	1.2 kW	0.01 kW	ZED707AB35
$\pm 2 \text{ A DC}$	800 W	0.1 W	ZED707AB53
$\pm 20 \text{ A DC}^*$	8 kW	0.01 kW	ZED707AB55
	Measuring range current** ±2 A DC ±20 A DC* ±2 A DC ±20 A DC*	Measuring range current**Measuring range power (calculated)±2 A DC120 W±20 A DC*1.2 kW±2 A DC800 W±20 A DC*8 kW	Measuring range current**Measuring range power (calculated)Resolution power±2 A DC120 W0.1 W±20 A DC*1.2 kW0.01 kW±2 A DC800 W0.1 W±20 A DC*8 kW0.01 kW

* Continuous operation up to a maximum of 10A. For currents exceeding 10 A, the maximum measuring period is 10 minutes. After that, the device needs to cool down to room temperature.

** Resolution, Overload, Input resistance see further above.



Digital ALMEMO® D6 measuring module for DC voltage and DC current

Overvoltage proof measuring input. Galvanically isolated up to 6 kV. For connection to all ALMEMO[®] V6 / V7 measuring instruments.



Technical data

see chapter Electrical variables

Types

Measuring module including touch-proof connecting cable, ALMEMO[&] connection cable permanently connected to the ALMEMO[&] D6 plug

DC voltage

4 ALMEMO® measuring channels: voltage, maximum value, minimum value, average value

Measuring range	Resolution	Overload	Input resistance	Order no.
±60 V DC	0.01 V	$\pm 90 \mathrm{V}$	1 MOhm	ZAD900AB3
±400 V DC	0.1 V	$\pm 400 \text{ V}$	4 MOhm	ZAD900AB5

DC current

4 ALMEMO® measuring channels: current, maximum value, minimum value, average value

Measuring range	Resolution	Overload	Input resistance	Order no.
±20 mA DC	0.01 mA	±500 mA	4.7 Ohm	ZAD901AB1
±200 mA DC	0.1 mA	±500 mA	1 Ohm	ZAD901AB2
±2 A DC	0.001 A	$\pm 4 \mathrm{A}$	100 mOhm	ZAD901AB3
$\pm 20 \text{ A DC}^*$	0.01 A	±20 A	8 mOhm	ZAD901AB5

* Continuous operation up to a maximum of 10A. For currents exceeding the maximum of 10 A, the measuring period is 10 minutes. After that, the device needs to cool down to room temperature.
ALMEMO[®] Adapter Cable for AC Voltage



Technical Data

Frequency range: 50 Hz to 10 kHz	
Accuracy:	\pm 0.2% of final val. \pm 0.5% of meas. val.
	(40Hz 2kHz sinusoidal),
Crest factor:	3 (add. error 0.7%), 5 (add. error 2.5%)

NEVER connect voltages higher than 50V! DANGER!

Types:		Order no.
Meas. Range	Resolution	
5 to 260mV_{eff}	0.1 mV	ZA9603AK1
0.05 to $2.6V_{eff}$	0.001 V	ZA9603AK2
0.5 to 26.0 $V_{\rm eff}$	0.01 V	ZA9603AK3

Measuring module for AC

10/2021 • We reserve the right to make technical changes.

Fast digital ALMEMO[®] D7 measuring module for AC voltage / AC current / AC power

For acquiring the true root mean square (RMS) value of a sinusoidal AC signal. Sampling rate of 1000 mops. Overvoltage proof measuring input. Galvanically isolated up to 6 kV. For connecting current ALMEMO[®] V7 measuring instruments: ALMEMO[®] 500, 710, 809, 202, 204



Technical data

see chapter Electrical variables

Types

Measuring module including touch proof connecting cable, ALMEMO® connection cable permanently connected to the ALMEMO® D7 plug

AC voltage

2 ALMEMO® measuring channels: voltage, frequency

Measuring range	Resolution	Overload	Input resistance	Order no.
25 V _{RMS} AC	0.01 V	$\pm 60 \text{ V}_{\text{RMS}}$	1 MOhm	ZED730AB3
400 V _{RMS} AC	0.1 V	$\pm 400 \text{ V}_{\text{RMS}}$	4 MOhm	ZED730AB5

AC current

2 ALMEMO® measuring channels: current, frequency

Measuring range	Resolution	Overload	Input resistance	Order no.
1,8 A _{rms} AC	0.001 A	$\pm 4 A_{RMS}$	100 mOhm	ZED731AB1
20 A _{RMS} AC*	0.01 A	$\pm 20 \text{ A}_{\text{RMS}}$	8 mOhm	ZED731AB3
* Continuous operation un	to a maximum of 10A DMS For	auronta avagading 10 A PI	AS the maximum maggining part	ad is 10 minutes

* Continuous operation up to a maximum of 10A RMS. For currents exceeding 10A RMS, the maximum measuring period is 10 minutes. After that, the device needs to cool down to room temperature.

AC power

5 ALMEMO® measuring channels: voltage, current, effective power, frequency, performance factor cos p

Measuring range voltage**	Measuring range current**	Measuring range power (calculated)	Resolution power	Order no.
25 V _{RMS} AC	1.8 A _{rms} AC	45 W	0.1 W	ZED737AB31
400 V _{RMS} AC	1.8 A _{rms} AC	720 W	1 W	ZED737AB51
400 V _{RMS} AC	$20 A_{RMS} AC^*$	8 kW	0.01 kW	ZED737AB53
* ~	· · · · · · · · · · · · · · · · · · ·			· 1 · 10 · ·

* Continuous operation up to a maximum of $10 A_{RMS}$. For currents exceeding $10 A_{RMS}$, the maximum measuring period is 10 minutes. After that, the device needs to cool down to room temperature.

** Resolution, Overload, Input resistance see further above.

ALMEMO® D6



Digital ALMEMO® D6 measuring module for AC voltage and AC current

For acquiring the true root mean square (RMS) value of a sinusoidal AC signal. Sampling rate of 1000 mops. Overvoltage proof measuring input. Galvanically isolated up to 6 kV. For connection to all ALMEMO[®] V6 / V7 measuring instruments



ZAD 903-ABx

ZAD 904-ABx

Technical data

see chapter Electrical variables

Types

Measuring module including touch proof connecting cable, ALMEMO[®] connection cable permanently connected to the ALMEMO[®] D6 plug

AC voltage

2 ALMEMO® measuring channels: voltage, frequency

Measuring range	Resolution	Overload	Input resistance	Order no.
25 V _{RMS} AC	0.01 V	$\pm 60 \text{ V}_{\text{RMS}}$	1 MOhm	ZAD903AB3
400 V _{RMS} AC	0.1 V	$\pm 400 \text{ V}_{\text{RMS}}$	4 MOhm	ZAD903AB5

AC current

2 ALMEMO® measuring channels: current, frequency

Measuring range	Resolution	Overload	Input resistance	Order no.
1,8 A _{rms} AC	0.001 A	$\pm 4 A_{RMS}$	100 mOhm	ZAD904AB1
20 A _{RMS} AC*	0.01 A	$\pm 20 \text{ A}_{\text{RMS}}$	8 mOhm	ZAD904AB3
* Continuous operation un	to a maximum of 10A DMS For	ourrants avaading 10A Pl	AS the merimum measuring period	ad is 10 minutes

* Continuous operation up to a maximum of 10A RMS. For currents exceeding 10A RMS, the maximum measuring period is 10 minutes. After that, the device needs to cool down to room temperature.

Input connectors and adapter cables

ALMEMO® Adapter Cable for Frequency / Pulse / Rotational Speed

for sensors, Supply : 5 V or direct from ALMEMO $^{\ensuremath{\mathbb{R}}}$ device



Technical Data

Frequency range:	0 to 15000 Hz (Resolution 1 Hz)
	0 to 3200.0 Hz (Resolution 0.1 Hz)
Speed range:	8 to 32000 rpm (Resolution: 1 rpm)
Max. pulse count:	65000
Pulse length:	> 50 ms
Input voltage	6 to 40 V, square-wave via optocoupler
Current consumption:	3 mA
Sensor supply	direct from ALMEMO® device
(for voltage s	ee technical data of ALMEMO® device)
Option V12	
Sensor supply:	12,2 to 12,5 V
Output current:	$100 \text{mA} \text{ at } \text{U}_{\text{G}} = 9 \text{ to } 12 \text{ V}$
	$(U_{G} = device sensor voltage)$

Types: (Cable leng	gths, 1.5 meters)		Order no.
Model	Meas. Range	Resolution	
Frequency	0 to 15000 Hz	1 Hz	
Frequency	0 to 3200,0 Hz	0.1 Hz (can, by inserting wire jumper, be switched to)	ZA9909AK1U
Pulses / Cycle	0 to 65000 Imp	1 Imp	ZA9909AK2U
Speed	8 to 32000 UpM	1 UpM	ZA9909AK4U
Option sensor supply	12 V		OA9909V12

ALMEMO[®] Adapter Cable for Digital Input Signals



Types: (cable length, 1.5m each)
3 digital inputs, (optocoupler), for floating contacts, 5V auxiliary voltage led out
4 digital inputs, electrically isolated (optocoupler) for external voltage, 4 to 30 V

Order no. ZA9000ES2 ZA9000EK2

Input connectors and adapter cables

ALMEMO® Universal Adapter Cable with Free Ends



Types:

Order no.

The ALMEMO[®] universal connector ZA 9000-FS is also available with connecting cable and free ends, as adapter cable ZA9000AK. The sensor supply voltage is present on terminal U+; it is supplied by the ALMEMO[®] device (sensor supply voltage 5 V, can be stabilized on request). Connecting cable : 8-wire, 8 x 0.14 mm², black, Length 1.5 m The wiring diagram and color code of the wires are consistent for all ALMEMO[®] sensors and cables, so that any pin configuration can be quickly and easily identified. ZA9000AK

ALMEMO[®] 10-Fold MU Connector for ALMEMO[®] Plug-In Boards with 64-Pin Spring Contact Strip



NOT suitable for sensors needing interface circuitry (e.g. 26 V, AC voltage, mA, humidity sensors, rotating vanes, frequency, pulse, rotational speed) no sensor supply possible)



The current MU connector version, ZA5690MU, can only be used in conjunction with the new ALMEMO[®] 5690 systems. The old MU connector version, ZA5590MU, can of course be used in conjunction with the old AL-MEMO[®] 5590/5990 systems but is subject to certain restrictions with the current 5690 systems (e.g. only 1 measuring channel per input, no multi-point adjustment or connector linearization)

Types:	Order no.
ALMEMO® 10-fold connector (64-pin) with EEPROM sensor memory	
for connecting 10 sensors; on request pre-programmed to your specifications	
for Data acquisition systems ALMEMO® 5690 and 500 (not for ALMEMO® 5590 / 5990)	ZA5690MU
For Data acquisition systems ALMEMO® 5590 und 5990	ZA5590MU

Input connectors and adapter cables

ALMEMO® Connector Adapter Cable, Digital Input of Third Party Device to ALMEMO® Device Type ZA 1000A KSW / ZAD 919A Kxx



Description:

- Data acquisition from external devices with digital interface • (RS232, Modbus RTU) and integration in the data acquisition with ALMEMO® devices.
- The digital connector of the adapter cable provides an electrically isolated serial interface and includes an interface processor for protocol conversion.
- Value-adding to existing measuring technology at a very interesting price-performance ratio.

Examples:

Scales and weighing equipment •

ching ALMEMO® connector.

Dial gauges and displacement transducers

Existing equipment incorporating a digital interface can, thanks to our flexible ALMEMO® system, continue being used. For this purpose, we can offer you the following

service : 1. We program a device type protocol for you, which matches the output interface of your device. 2. We fit the interface cable for your device with the mat-

- Multimeters
- Incremental displacement transducers
- Flue gas analysers

Types:

For the purposes of programming the interface, please provide us with a detailed description of the output interface of the third-party device you want to have integrated, or a matching cable, or a connector including the pin configuration, plus the third-party device itself for the purposes of testing and checking.

Interface programming for the device type protocol of the device to be integrated

ALMEMO[®] connector adapter cable

Order no.

ZA1000AKSW **ZAD919AK**

ALMEMO® Output modules

Content

ALMEMO [®] trigger cable ZA1000ET/ZA1006EK2	03.03	
ALMEMO [®] trigger / relay cable V6 Typ ZA1006EKG/ETG	03.03	
ALMEMO [®] relay cable, V6, ZA 1006 GK		
and electrical socket relay adapter ZB2280RA	03.04	
ALMEMO [®] analog output cable ZA1601RK	03.04	
ALMEMO [®] relay trigger adapter, analog ZA8006-RTA3	03.06	
ALMEMO [®] trigger output interface ES5690-RTA5	03.07	
ALMEMO [®] trigger output interface ES500-RTA6	03.08	



ALMEMO[®] Output modules

A modern measuring instrument must be able to communicate with its environment, i.e. transfer its measured data to peripheral equipment, execute commands from a computer, trigger alarm signals, and respond to switching pulses.

To cover all possibilities while also keeping the hardware needed to a minimum all necessary interfaces have been integrated in our ALMEMO[®] output connector. This concept allows the user - with one and the same ALMEMO[®] measuring instrument - to choose freely from a wide variety of output interfaces to best suit the particular task in hand .

For the purposes of connecting the modules virtually all ALMEMO[®] devices are equipped with two output sockets A1 and A2; these also allow the devices to participate in digital networking. The

output modules, just like the sensors, are detected automatically; no extra programming is required.

Please note that many ALMEMO[®] output modules can only be operated in conjunction with ALMEMO[®] devices version 6 and above (not 2390, 8390). Labeled V6 (device firmware update may be needed).

Describing all the many options provided by the ALMEMO® system with output modules would be beyond the scope of this catalog.

Please ask for our ALMEMO[®] Manual. It will provide you with valuable tips and a detailed description of our ALMEMO[®] output modules.

We shall of course be pleased to offer you competent advice and support to help you solve your particular measuring tasks. Or you can arrange a date for a demonstration. Our experts will be pleased to visit you - to introduce and explain the numerous application options that the ALMEMO[®] system offers.

ALMEMO® Output modules

ALMEMO® trigger cable V6 ZA 1006 ET / ZA 1006 EK2



Technical Data

Trigger input	
ZA1006ET	Trigger variants can be programmed with key
ZA1006EK2	For external zero-potential contact
	(not electrically isolated) and for external
	voltage 4 to 30 VDC (optocoupler),
	trigger variants can be programmed
Current consumptio	n approx. 3 mA
Cable length	1.5 meters
Connection	(see variants)

Variants	Order no.
ALMEMO [®] trigger cable, V6, with 1 key	ZA1006ET
ALMEMO [®] trigger cable, V6, with 2 trigger inputs for external contacts or voltages, with clamp connector	ZA1006EK2

ALMEMO® trigger / relay cable V6 ZA 1006 EKG / ETG



Technical Data:

Trigger input	For external zero-potential contact (not electrically isolated) or for external voltage 4 to 30 VDC (optocoupler) Trigger variants - can be programmed (V6 only)	
Relay	Normally open contact (semiconductor relay) Can also be programmed as inverted (V6 only) Load capacity: 50 VDC, 0.5 A, 1 ohm	
Current consumption approx. 3 mA		
Cable length	1.5 meters	
Connection	Clamp connector	

Variants	Order no.
ALMEMO [®] trigger / relay cable, V6, with 2 trigger inputs (programmable trigger variant) for external voltages and 2 normally open contacts	ZA1006EKG
ALMEMO [®] trigger / relay cable, V6, with 2 trigger inputs (programmable trigger variant) for external zero-potential contacts and 2 normally open contacts	ZA1006ETG

ALMEMO® relay cable, V6, ZA 1006 GK and electrical socket relay adapter, ZB 2280 RA





Technical Data

Relay cable, V6, type ZA 1006 GK		
Relay	Normally open (semiconductor relay)	
	Can also be programmed as inverted	
	(V6 only)	
	Load capacity 50 VDC, 0.5 A, 1 ohm	
Current consumption	approx. 3 mA	
Cable length	1.5 meters	
Connection	Banana plugr	

Technical Data

Relay adapter ZB2280RA		
Control input	for optocoupler output	
_	or switching contact R <10 kW	
Output	Electrical safety socket, mechanical	
	Telay, Ioau capacity 250 V, 0 A	
Switching status	OFF idle; ON alarm	

Variants	Order no.	Variants	Order no.
ALMEMO [®] relay cable, V6, with 1 normally open contact	ZA1006GK	Relay adapter for switching mains suppli- combined with relay cable ZA1006GK/Z	ed devices A1000GK ZB2280RA

ALMEMO[®] analog output cable ZA 1601 RK



- Measured values can be recorded using a chart recorder or a similar output device.
- A signal converter is integrated in the connector.
- The device signal is converted into voltage corresponding to the linearized measured value.
- To obtain a high response speed a conversion rate of 10 mops can be set in the ALMEMO $^{\mbox{\tiny (B)}}$ device.
- The output signal can be scaled as required.

Technical Data:

Output voltage	-1.250 to 2 000 V, not electr. isolated	
Gain	0.1 mV / digit	
Load	>100 kΩ	
Accuracy	$\pm 0.1\% \pm 6$ digits	
Temperature drift	1 digit / K	
Time constant	100 ms	
Current consumption approx. 3 mA		
Cable length	1.5 meters	

03.04

Order no. ZA1601RK



ALMEMO® analog output cable ZA 1601-RI and ZA 1602-RU



Technical data

- The analog signal is controlled internally by the measured value of a measuring channel, arbitrarily scalable.
- Respectively, the analog signal is controlled externally via the device interface with the WinControl software.

 Only suitable for the following device types: ALMEMO[®] 2590-xA, 2690-8A, 2890-9, 202, 204, 710, 809 devices manufactured from 2020 onwards (for older devices, a firmware update is necessary).

Output signal:	via clamping connector,	Temperature drift:	10 ppm/K
ZA1601RI ZA1602RU	galvanically isolated 1 x 0 to 20 mA, load >100 kOhm 2 x 0 to 10 V, load < 500 Ohm (common mass)	Power supply:	12 V via ALMEMO [®] plug the sensor voltage 12V is set on the ALMEMO [®] device.
Resolution:		ZA1601RI	max. 50 mA (at 12 V)
ZA1601RI	1 μA/digit	ZA1602RU	max. 20 mA (at 12 V)
ZA1602RU	0.5 mV/digit	Cable:	0.25 m
Accuracy:	0.1% of measured value +0.1 % of final value		

Order no.
ZA1601RI
ZA1602RU

ALMEMO® relay trigger adapter, analog ZA 8006 RTA3 for connecting to ALMEMO® devices

ZA 8006 RTA3



- Universal trigger output interface for connecting to output sockets on ALMEMO[®] devices from version V6 up (not 2390, 8390). device firmware update may be needed.
- Up to 10 peripheral elements (relays, trigger inputs, analog outputs) each with individually configurable function
- Relay functions, total alarm, assignment to particular limit values, or addressing via interface
- Integrated alarm signaling device can be assigned to all relay functions.
- Inverse relay addressing for alarm in the event of power failure
- Programmable messages to be issued when relays are activated
- Comprehensive trigger features with the aid of command macros, addressing via 2 keys or electrical signals
- Either 2 or 4 analog outputs (10 V or 20 mA) can be assigned to any measuring channels, scalable sub-areas, or alternatively addressing via interface.
- Analog output type 10 V or 20 mA (programmable)
- All programming and peripheral states shown on illuminated graphics display
- Keypad for selecting menu and port
- Watchdog function in the event of a failure of ALMEMO®

Technical Data

Trigger inputs	Optocoupler, 4 to 30 V, Ri >3 kohms		
Relay	Semiconductor relay 50 V, 0.5 A, 1 ohms	Power supply	via ALMEMO®
Analog outputs	10 V or 20 mA (programmable) 16-bit DAC, electrically isolated	Comment	or mains adapter (recommended f
0.0 to 10.0 V 0.0 to 20.0m \wedge	0.5 m V / digit, Load > 100 kohms	(with 9V supply)	2 analog outputs
Accuracy Temperature drift	$\pm 0.1\%$ of meas. val. $\pm 0.1\%$ of final val.	Display	Graphics 128 x 6 Lighting 2 white
remperature unit	10 ppm / K	Keynad	7 silicone keys (

All Ports Port: 01 23 Type: R.R. R.R 45 67 89 -- AA T T Single Ports Device Configuration Activ: v ν ν x923: 17 71 UΑ TR8 MENU P *ON TR9 Þ *ON menu selection all peripherals ZA 8006 RTA3 Socket: A2 Messages: 2 Port: 0 Relay:) Adr: 20 Normally oPen - 0.5A Port: 0.3 Port 3: -8: external steered inv Furnace overheated State: active Contact: x2-x3 oPen Tel: 08024-3007-99 TR8 MENU P *ON TR9 OFF *0N P relais messages device or computer addressing ZA 8006 RTA3 Socket: A2 ZA 8006 RTA3 Socket: A2 Adr: 26 0-10 V M01 Adr: 28 Port: 6 Port: 8 Trigger: Key + Optokoppler AnalogoutPut: 2: int. assigned Analogue value: 0: Start-StoP State: 3.4560 V inactive ×3: - ×2: + ×3: - ×2: + Connection: Connection: TR8 MENU P *ON TR9 TR8 MENU P *ON TR9 trigger inputs analog outputs

V6.01

ZA 8006 RTA3

Socket: A2

• Connection of peripherals via ALMEMO[®] clamp connectors, cable with anti-kink protective sleeve and strain relief

- Power supply via the ALMEMO[®] device; in case of the analog output option a mains adapter may also be required.
- Modern, compact housing also suitable for DIN top-hat rail mounting

On request: ALMEMO[®] output interface ZA8006RTA4 for connection to the PC (directly or via network).



Power supply	via ALMEMO [®] device or mains adapter ZA1312NA12
Current consumption	(recommended for analog output option) approx. 10 mA, Lighting approx. 15 mA
(with 9V supply)	2 analog outputs approx. 30 mA + 1.6 I_{Out}
Display	Graphics 128 x 64 (55 x 30 mm) Lighting 2 white LEDs
Keypad	7 silicone keys (4 soft-keys)
Housing	127 x 83 x 42 mm (LxWxH) ABS (maximum 70°C), 290 g

Basic version 2 trigger inputs and 4 normally open relaysOptions 2 additional relays (normally open)OA8006SH2Per normally open pair 2 additional normally closed relays
(with normally open relays 2 changeover relays)OA8006OH22 analog outputs (common ground), electrically isolated
10 V or 20 mA (programmable)OA8006R02

Possible combinations

1x OA8006SH2 (+2 relays) or 1x OA8006SH2 (+2 relays) + 1x OA8006R02 (+2 analog outputs) or 2 x OA800R0H2 (+4 analog outputs)

AccessoriesMains unit, 12 V, 1.5 ADIN tophat rail mountingZB2490HS

Order no.

ALMEMO[®] relay trigger adapter with 2 trigger inputs, 4 normally open relays, DC socket, graphics display, and keypad, including 1.5-meter ALMEMO[®] connecting cable and 3 ALMEMO[®] clamp connectors Z

ZA8006RTA3

Variants

ALMEMO[®] trigger output interface, ES 5690-RTA5, for data acquisition system ALMEMO[®] 5690



Technical Data:

Trigger inputs	Optocoupler 4 to 30 V, Ri > 3 kohms
Relays	Semiconductor relays 50 V, 0.5 A, 1 ohm
Analog outputs	10 V or 20 mA (programmed)
	16 bit DAC. electrically isolated
0.010.0 V	0.5 mV/Digit. Load > 100 kohms
0.020.0 mA	1 µA/Digit. Load < 500 ohms
Accuracy	$\pm \ 0.1\%$ of meas. val. $\pm \ 0.1\%$ of final val.
Temperature drift	10 ppm/K
Power supply	via ALMEMO [®] measuring system
Current consumption	Standard: approx. 10 to 20 mA
	2 analog outputs: approx. 15 mA + 1.8·IOut
Module	19" 8-DU (2 slots)

- Universal trigger output interface for ALMEMO $^{\ensuremath{\mathbb{R}}}$ 5690 data acquisition systems
- System (master measuring circuit or CPU module) addressed via an internal SPI bus
- Up to 10 peripheral elements (relays, trigger inputs, analog outputs) each with individually configurable function
- Relay functions, total alarm, assignment to particular limit values, or addressing via interface
- Inverse relay addressing for alarm in the event of power failure
- Relay states shown via LEDs
- Watchdog function in the event of a failure of ALMEMO[®] device or computer addressing
- Comprehensive trigger features with the aid of command macros, addressing via electrical signals
- Either 2 or 4 analog outputs (10 V or 20 mA programmable) can be assigned to any measuring channels, scalable sub-areas, or alternatively addressing via interface.
- On request : 10 analog outputs per plug-in module (without trigger inputs, without relays)
- Connection of peripherals via ALMEMO[®] clamp connectors, cable with anti-kink protective sleeve and strain relief
- Power supply via ALMEMO[®] system.



Basic version 2 trigger inputs and 4 normally open relaysOptions 2 additional relays (normally open)OA8006SH2Per normally open pair 2 additional normally closed relays

(with normally open relays 2 changeover relays) OA8006OH2

2 analog outputs (common ground), electrically isolated 10 V or 20 mA (programmable) OA8006R02

Possible combinations

2x OA8006SH2 (+4 relays)

or 1x OA8006SH2 (+2 relays) + 1x OA8006R02 (+2 analog outputs) or 2 x OA8006R02 (+4 analog outputs)

Variants

10/2021 • We reserve the right to make technical changes.

Order no.

ALMEMO[®] relay trigger module for data acquisition system ALMEMO[®] 5690 with 2 trigger inputs, 4 normally open relays, and 3 ALMEMO[®] clamp connectors

ES5690RTA5



Technical Data

ALMEMO® V7

10/2021 • We reserve the right to make technical changes

ALMEMO[®] trigger output interface, ES 500-RTA6, for data acquisition system ALMEMO[®] 500 V7



iecinical Dala.	
Trigger inputs	Optocoupler 4 to 30 V, Ri > 3 kohms
Relays	Semiconductor relays 50 V, 0.5 A, 1 ohm
Analog outputs	10 V or 20 mA (programmed)
	16 bit DAC. electrically isolated
0.010.0 V	0.5 mV/Digit. Load > 100 kohms
0.020.0 mA	1 μ A/Digit. Load < 500 ohms
Accuracy	$\pm \ 0.1\%$ of meas. val. $\pm \ 0.1\%$ of final val.
Temperature drift	10 ppm/K
Output rate:	in total up to 100 actions/s for a system
	with 1 RTA6 plug-in module
Power supply	via ALMEMO [®] measuring system
Current consumption	Standard: approx. 10 to 20 mA
	2 analog outputs: approx. 15 mA + 1.8 · IOut
Madula	10° 8 DU (2 slots)

- Universal trigger output interface for ALMEMO[®] 500 V7 data acquisition systems
- Control from the CPU slot via internal SPI bus.
- Up to 4 RTA6 plug-in units are supported per ALMEMO[®] 500.
- Up to 10 peripheral elements (relays, trigger inputs, analog outputs) each with individually configurable function
- Relay functions, total alarm, assignment to particular limit values, or addressing via interface
- Inverse relay addressing for alarm in the event of power failure
- Relay states shown via LEDs
- Watchdog function in the event of a failure of ALMEMO[®] device or computer addressing
- Comprehensive trigger features with the aid of command macros, addressing via electrical signals
- Either 2 or 4 analog outputs (10 V or 20 mA programmable) can be assigned to any measuring channels, scalable sub-areas, or alternatively addressing via interface.
- On request : 10 analog outputs per plug-in module (without trigger inputs, without relays)
- Connection of peripherals via ALMEMO[®] clamp connectors, cable with anti-kink protective sleeve and strain relief

The ALMEMO[®] Trigger Output Interface RTA6 can be used in ALMEMO[®] 500 data acquisition systems

manufactured as of 4th quarter 2021, (cannot be retrofit-

• Power supply via ALMEMO[®] system.

ted for older devices).



Basic version 2 trigger inputs and 4 normally open relays **Options** 2 additional relays (normally open) OA500SH2 Per normally open pair 2 additional normally closed relays

(with normally open relays 2 changeover relays) OA5000H2 2 analog outputs (common ground), electrically isolated

10 V or 20 mA (programmable) OA500R02

Possible combinations

2x OA500SH2 (+4 relays)

or 1x OA500SH2 (+2 relays) + 1x OA500R02 (+2 analog outputs) or 2 x OA500R02 (+4 analog outputs)

Variants

Note:

ALMEMO[®] relay trigger module for data acquisition system ALMEMO[®] 500 V7 with 2 trigger inputs, 4 normally open relays, and 3 ALMEMO[®] clamp connectors

Order no.

ES500RTA6

Ţ

Content

ALMEMO [®] networking technology	04.02
ALMEMO [®] PC connection using USB data cable ZA 1919 DKU	04.05
ALMEMO [®] PC connection using Ethernet data cable ZA1945-DK	04.05
Data cable for digital ALMEMO [®] D6 / D7 probe	04.05
Wireless link between PC and WLAN module	04.06
ALMEMO [®] Network Interface Cables	04.07
ALMEMO [®] Network Interface Cables with Fiber Optics	04.07
Wireless data links using ALMEMO [®] Bluetooth modules	04.08
Wireless PC link with Bluetooth	
Bluetooth USB CPU module ZA 1719 BCU	04.09
Bluetooth measuring instrument ALMEMO [®] 2790	
with integrated Bluetooth module	04.10
Mobile communications modem ZA 1709 GPRS	04.11
Mobile Internet and Cloud with ALMEMO® measurement technology	04.12



ALMEMO[®] networking technology

The ALMEMO[®] system provides optimal support for networked, decentralized measured data acquisition. Measured data can be acquired locally on site using short sensor signal lines and small modular measuring instruments and can then be evaluated all together on a central computer. This not only minimizes wiring requirements but also goes a long way to solving EMC problems (especially if optic fiber cables are used).

Via the cascadable interface provided by ALMEMO[®] devices it is possible, thanks to our ALMEMO[®] networking technology, to manage up to 100 ALMEMO[®] measuring instruments from just one computer. User-friendly software packages (see Chapter 05) are available for automatically scanning measuring points within the network, for evaluating

the measured values, and for graphically representing results in line chart or bar chart form. This permits measuring setups in which devices can be used with such high operational reliability and with such great flexibility that even the most demanding measuring tasks can be solved. For example:

- Data connection from the PC to ALMEMO[®] devices via USB, Ethernet, WLAN, RS232, Bluetooth, mobile communications, modem.
- Can be combined in a wide variety of ways via the output sockets A1 and A2 on the ALMEMO[®] measuring instrument
- Various networking arrangements can be implemented.
- Measuring instruments can be installed in separate rooms; considerable distances can be bridged.

- ALMEMO[®] devices / networks can be connected to the PC via an existing Ethernet / WLAN network.
- *New* Wireless connection between the wireless ALMEMO[®] sensor respectively wireless ALMEMO[®] interface for ALMEMO[®] D7 sensor and the wireless ALMEMO[®] data logger 470-1, see chapter ALMEMO[®] Measuring Instruments.
- PC and devices can be connected over a wireless link using Bluetooth modules.
- Measured data can be acquired and also read out from the measured value memory on an ALMEMO[®] data logger - all online - using the WinControl software package



Ethernet

Wi-F

ALMEMO[®] 500

PC connection via USB

(over a wireless Bluetooth link, see page 04.03) Inexpensive for relatively short distances (up to 5 m) several connections in parallel (star-configured network) for mobile use, e.g. notebook

Necessary component ZA 1919 DKU see page 04.05

PC connection via Ethernet / WLAN

(over a wireless Bluetooth link, see page 04.03) Measured data acquisition, on a decentralized basis, using existing LAN cabling / WLAN, relatively long distances, via Internet worldwide. Necessary component(s) ZA 1945 DK see page 04.05







Wi-Fi

LAN/ Wi-Fi

Corporate Network

Connection between ALMEMO® measuring instruments over ALMEMO® network cable (over a wireless Bluetooth link, see page 04.03) Inexpensive linear network solution, flexible, plug-and-play, easy to expand. Necessary component ZA 1999 NK5 see page 04.06



ALMEMO[®] PC connection using USB data cable ZA 1919 DKU RS232 data cable, type ZA 1909 DK5



- ALMEMO[®]-USB data cable for data connection between an ALMEMO[®] device and a PC with a USB interface
- ALMEMO[®] RS232 data cable with a DSUB socket for data connection between an ALMEMO[®] device and a PC with a COM interface
- ALMEMO[®] optic fiber cable (RS232) for absolute electrical isolation and extensive protection against lightning.

Types:	Order no.
USB data cable, electrically isolated, maximum 115.2 kbaud, cable length 1.5 meters,	
including CD with Windows driver	ZA1919DKU
As above but cable length 5 meters	ZA1919DKU-05
RS232 data cable electrically isolated, max. 115.2 kbaud,	
Current consumption : approx. 1 mA, cable length : 1.5 m	ZA1909DK5
As above, but cable lengths 5m / 10m / 15m	ZA1909DK5-05 /-10 /-15
RS232 data cable with optic fiber, max. 115.2 kbaud, Cable length 1,5 m	ZA1909DKL
Longer optic fiber (up to 50 m) for interiors, Duplex plastic 2.2 x 4.3mm, per meter	LL2243L

ALMEMO® PC connection using Ethernet data cable ZA 1945 DK



- For connecting almost any ALMEMO[®] measuring instrument to an Ethernet PC network.
- Linking up to the Internet now possible.
- Terminal operation using our AMR-Control software, available free-of-charge.
- Device-Installer configuration software also included on the AMR CD.
- Measured data acquisition via several Ethernet modules using our Win-Control software. (Version SW5600WC2 and above, see chapter Software).

Technical data

Ethernet:	Socket RJ45 (10/100 base-T) Automatic switchover 10 / 100 MHz	Power supply
ALMEMO®	ALMEMO [®] connector for socket A1 Baud rate standard 9600 bd, max. 115.2 kbd (can be changed via Device-Installer and browser)	Current consumpti

Power supply	12 V DC via measuring instrument (suitable mains supply unit recommended)
	(
Current consumption <60 mA (10 MHz), <90 mA (100 MHz)	

AccessoriesOrder no.Patch cable RJ45, plug / plug, 2 metersZB1904PK2TypeOrder no.Ethernet data cable, RJ45 socket on ALMEMO® connector, cable length 1.5 metersZA1945DK

Data cable for configuring digital ALMEMO® D6 / D7 sensors

Types	Order no.
ALMEMO [®] USB adapter cable length 1.5 meters for connecting an ALMEMO [®] D6 sensor to the USB port on a PC (power supply via USB)	ZA1919AKUV

Wireless link between PC and ALMEMO® WLAN module ZA 1719-WL

Wireless link between a PC connected to a local WLAN radio network and an ALMEMO[®] measuring instrument connected to an ALMEMO[®] WLAN module.



WLAN-module ZA 1719-WL

- WLAN module ZA 1719-WL, equipped with an active internal antenna, can be plugged into the A1 socket of any ALMEMO[®] measuring instrument (instead of the data cable) and thus be linked into a local WLAN radio network.
- Use of the existing infrastructure
- Range up to 400 meters (unobstructed)
- LEDs showing status of the power supply and data traffic
- All the usual encryption and authentication protocols can be configured.
- Configuration on the PC via USB adapter cable ZA 1919-AKUVW using configuration software
- Quick and easy incorporation in the WinControl data acquisition software via an Ethernet port.



Technical data

Standard features	WLAN 802.11a/b/g/e/i/h/j
Frequency band	2.4 GHz, channels 1–13
	5.0 GHz, channels 36– -165
	(U-NII band 1, 2, 2e, 3)
Output power	100 mW (20 dBm)
Throughput	500 kbit/s
Operating range	400 meters (unobstructed)
Encryption and authentication	
	WPA-PSK, WPA2-PSK, PEAP, LEAP
	WEP64/128, TKIP, AES (CCMP)
Protocol	TCP/UDP
Ethernet port	10001 (default)
Power supply	via ALMEMO [®] device
Current consumption	approx. 70 mA with 9V supply
Module housing	61 x 30 x 12 mm (LxWxH)
	ABS PC GF (-20 to +70 °C)
ALMEMO® data rate	1200 baud up to 115.2 kbaudd

Advisory note

Inside a building the operating range of the wireless link will be substantially lower.

	Order no.
Accessories	
USB adapter cable for configuring an ALMEMO® WLAN module ZA 1719-WL	ZA1919AKUVW
Option	
Cable between ALMEMO [®] plug and module, Length = 1 meter	OA1719BK
Variants	Order no.
Wireless PC link (WLAN) for one ALMEMO® measuring instrument	
ALMEMO [®] WLAN module for output socket A1 on the ALMEMO [®] device.	ZA1719WL

ALMEMO[®] Network Interface Cables ZA 1999 NK5

Ÿ.	The device network will be blocked if the measuring instrument fails to operate. No further peripheral devices can be connected (analog output, alarm relay etc.)	 Uses: Especially suitable for short distances and mobile measuring setups. Up to 100 ALMEMO[®] measuring instruments can be networked. Advantages: Devices can be quickly and easily interconnected and networked. Low power consumption (approx. 1 mA) without additional power supply. You can easily assemble the network cable yourself, up to 50m in length, using just two single network connectors ZA1999FS5 (a couple) and one four-wire cable.
Тур	Des	Order no.
Netv	work cable for cascading several devices for baud rates up t	to 115.2 kbaud
curr	ent loop, electrically isolated, 1.5 m long	ZA1999NK5
As a	above, but cable lengths 5m / 10m / 15m	ZA1999NK5 -05/ -10 / -15/ -xx

2 Network connectors (a couple) with screw terminals for local self-assembly

ZA1999FS5

ALMEMO® Network Interface Cables with Fiber Optics ZA 1999 NKL



The device network will be blocked if the measuring in-

No further peripheral devices can be connected

strument fails to operate.

(analog output, alarm relay etc.)

Uses:

- Especially suitable for safe and reliable data transmission in industrial environments with high levels of interference.
- Up to 10 ALMEMO® measuring instruments can be networked (at 9600 baud, double this number, if the transmission rate is halved).

Advantages:

- · Devices can be quickly and easily interconnected and networked.
- No EMC problems, highest possible immunity to interference, absolute electrical isolation of the instruments - even under high voltages.
- No additional voltage supply is required.
- · You can easily assemble the network cable with plastic optic fiber yourself, up to 50m in length, using just two single network connectors ZA1999FSL, without needing any special tools.

Types

Network cable with optic fiber for cascading several devices 1.5 m long for baud rates up to 115.2 kbaud As above, but cable lengths 5m / 10m / 15m Longer optic fiber cable for interiors, Duplex plastic 2.2 x 4.3 mm Network connector with optic fiber converter for local self assembly

Order no.

ZA1999NKL ZA1999NKL -05/ -10 / -15/ -xx LL2243L (please specify length L) **ZA1999FSL**

Wireless data links using ALMEMO[®] Bluetooth modules

Various types of connection are possible

Wireless PC connection see page 04.09

Wireless connection from a PC with ALMEMO[®] Bluetooth CPU to one ALMEMO[®] measuring instrument each with Bluetooth slave

Wireless sensor connection see page 04.12

Wireless sensor connection from a Bluetooth measuring device to a measuring input of a receiving ALMEMO[®] device with Bluetooth sensor module. Up to 4 measuring channels can be transmitted per connection..

Common technical data

Bluetooth	class 1 with active antenna
Protocol	SPP (sequence packet protocol) (128-bit encryption)
Operating range	300 meters (free field)*
ALMEMO® data rate	1200 baud up to 115.2 kbaud
Module housing ZA 1719-Bx	(LxWxH) 61 x 30 x 12 mm Polystyrene (-10 to +70 °C)
Cable length	for plug-in module ZA 1719-Bx with option OA1719BK Length = 1 meter

Inside a building the operating range of the wireless link will be substantially lower.

Advantages of ALMEMO[®] connections using Bluetooth compared with other wireless technologies

- Bluetooth wireless technology is industrial standard in compliance with IEEE 802.15.1; it ensures high transmission reliability.
- The frequency hopping procedure used ensures robustness against interference. The Bluetooth partners move continually to and from among the 79 wireless channels available.
- Any number of Bluetooth connections can operate in parallel with complete reliability.

Common technical features

- Bluetooth links are supplied already paired, i.e. simply plug in and start measuring. The plug-in module variant with a 1-meter cable can, in order to optimize the wireless link, be positioned away from the
- In the event of interruption to the Bluetooth connection the USB / COM interface in the PC remains available for the software being used. For continuous monitoring purposes this ensures very high transmission reliability. Advisory note : The Bluetooth links integrated in some laptops / PCs cannot be used for these purposes because in the event of interruption the operating system deactivates the COM interface and this must then be reactivated manually each time.
- Any ALMEMO[®] measuring instrument with a Bluetooth slave module connected can be used.

- The multi-digit PIN code ensures that all Bluetooth participants are identified reliably and unequivocally.
 These links once configured will, as soon as the device is
- These links once configured will, as soon as the device is switched ON, be automatically setup - and, in the event of interruption, be automatically restored.
- These powerful new Bluetooth class 1 wireless modules incorporate an integrated active antenna ensuring an especially wide operating range (up to 300 meters free field); there is no need for an extra antenna.
- The plug-in module variant with a 1-meter cable can, in order to optimize the wireless link, be positioned away from the measuring instrument between the ALMEMO[®] connector and the module (option OA1719BK) and specially aligned (using Velcro fastener).
- The connection can be configured end-to-end quickly and easily either with the AMR-Control software.
- To search through and select from the Bluetooth slave partner the user simply enters the appropriate PIN codes.

Wireless PC link with Bluetooth

Bluetooth USB CPU module ZA 1719 BCU

Wireless connection from a PC with ALMEMO[®] Bluetooth CPU to one ALMEMO[®] measuring instrument with Bluetooth slave



Technical data

Common technical data see page 04.07		
Cable	ZA1719BCU Length = 1.5 meters	
Voltage supply		
ZA1719BCU	via USB interface on the PC	
ZA1719BT1XS	via ALMEMO® measuring	
	instrument, approx. 35 mA (9 V)	



- ZA 1719 BCU ZA 1719 BT1XS
- Connection of the CPU module to the USB interface on a PC
- Connection of the plug-in slave module to socket A1 on an ALMEMO[®] device

OA1719BK

Order no.

Option for plug-in module ZA1719BT1XS Cable between ALMEMO[®] connector and module Length = 1 meter

Variants

Paired wireless PC connection (USB) for 1 ALMEMO® measuring instrument (configured and ready-to-operate)Bluetooth CPU module with USB (ZA1719BCU)and plug-in Bluetooth slave module (ZA1719BT1XS)ZA1719BPVU

10/2021 • We reserve the right to make technical changes.

04.09

Wireless sensor connection via Bluetooth

Wireless sensor connection from a Bluetooth measuring device to a measuring input of a receiving ALMEMO[®] device with Bluetooth sensor module. Four measuring channels per connection can be transmitted. Any number of sensor connections in parallel is possible.



Sensor connection via Bluetooth sensor measuring device ALMEMO[®] 2790 with built-in Bluetooth module





MA 2790-BTFM

ALMEMO[®] 2790 ZA 1729-BTFS with sensors for humidity, temperature, atmospheric pressure option OA 2790-RHA

- Connection of an ALMEMO[®] sensor to the measuring input M0 of the ALMEMO[®] Bluetooth device.
- Connection of the plug-in sensor module to the input socket Mxx of a receiving ALMEMO[®] device.

Technical features:

- 1 measuring input for all ALMEMO[®] sensors.
- Optional: Integrated digital sensor for humidity, temperature, atmospheric pressure. Sensors can be plugged in, replaced and individually calibrated (without any measuring instrument).
- Power supply with 3 AA rechargeable NiMH batteries, with charging via the device itself. (Please order the mains unit separately)
- Power saving sleep mode (save-to-memory cycle starting at one minute). Operating time (per charged battery) up to 200 hours with memory cycle of 1 minute, respectively 1 year with memory cycle of 1 hour.
- modern, compact housing, also for DIN rail mounting housing
- Generously dimensioned 2-row static 7 / 16 segment display including units
- Operating functions: cycle, keys can be locked via password, atmospheric pressure compensation.

Technical data MA 2790-BTFM

Measuring input:	1 ALMEMO [®] input socket	
A/D converter, measuring ranges, standard equipment,		
housing: as for ALMEM	O [®] 2490-1, see page 01.14, but:	
Sensor supply:	6 / 9 / 12 V (depending on the programmed	
	minimal sensor supply voltage-	
	in the ALMEMO [®] plug), max. 150 mA	
Power supply:	5 to 13V DC not galvanically isolated.	
Rechargeable battery:	3 AA rechargeable NiMH batteries.	
6 ,	integrated charge circuitry	
Current consumption:	approx. 14 mA with radio link	
	(without sensor)	
ALMEMO [®] socket DC:	for mains unit /interfaces	
Bluetooth connection:	master module integrated	

Accessories: mains unit 12V/2A	Order no. ZA1312NA10
DC adapter cable 10 to 30 V DC, 12V/0.25A galvanically isolated	ZA2690UK
DIN rail mounting	ZB2490HS
Option: Integrated digital sensor for humidity, temperate, pressure, (technical data FHAD 46-C2	Order no. atmospheric
see chapter Air humidity)	OA2790RHA

Technical data ZA 1729-BTFS

Common technical data	see page 04.07
Power supply:	via ALMEMO [®] measuring instrument,
	approx. 25 mA (9 V)
Module housing:	ALMEMO [®] plug, 61 x 20 x 8 mm (LxWxH), ABS

Variants

Paired wireless sensor connection (configured and ready-to-operate) with Bluetooth sensor measuring device ALMEMO[®] 2790, comprising:

Bluetooth sensor measuring device ALMEMO[®] 2790, 1 measuring input, integrated Bluetooth, including 3 AA rechargeable NiMH batteries (MA2790BTFM), and Bluetooth sensor plug-in module (ZA1729BTFS) MA2790BTFV

Order no.

Mobile communications modem ZA 1709 GPRS



- Remote interrogation and remote control of ALMEMO® devices
- Ideal for measuring operations at remote sites
- Automatic memory readout or inexpensive 24-hour online measuring thanks to a charges structure according to actual data usage.

Technical data

Frequency range	GPRS 850 / 900 / 1800 / 1900 MHz LTE: Bands 1, 3, 8, 20 (800, 900, 1800, 2100 MHz)
Connections	RS-232 (9600 baud, 9-contact. sub-D socket) FME antenna connection (male) Power supply, SIM card reader
Power supply	10 to 30 V, via mains unit, included in delivery or via cable for external voltage
Current consumption	maximum 1.2 A at 12 V
Operating temp.	-30 to +75 °C (mains unit 0 to +40 °C)
Dimensions	65 x 74 x 33 mm
Weight	approx. 110 g
Mains unit	Input voltage 110 to 240 VAC Output voltage 10.5 to 13.5 VDC Operating temperature 0 to +40 °C

Advisory note:

For technical reasons a special data tariff and a VPN access are required; these can be arranged via "akrobit software GmbH". Akrobit software GmbH offers various tariffs for VPN and mobile communications; depending on the tariff chosen, the Mobile communications modem can be used within Germany, within Europe, or worldwide.

A VPN client software must also be installed on the computer used for evaluation. The VPN client software is included in delivery free-of-charge. For automatic memory readout the software AMR WinControl is required together with additional module "Automatic ALMEMO[®] memory readout" SW5600WCZM9.

Accessories	Order no.
Additional protocol "Automatic memory readout" for WinControl (SW5600WC1/2/3/4)	SW5600WCZM9
for external voltage 10 to 30 V DC, minimum of 1.2 A for 12 V DC	ZB1709EK

Variants:

Order no.

Mobile communications modem for connecting to ALMEMO[®] devices, including data cable ZA1909DK5, adapter ZA1709AS, mains unit, documentation, antenna with magnetic base Cable approx. 2.5 meters.

ZA1709GPRS



Mobile internet, combined with keywords such as cloud computing and web access, is a topical issue. Thanks to our solutions, you can connect your ALMEMO[®] measuring technology via the internet and record it centrally. It is irrelevant where the measuring technology is located. You have worldwide access to the recorded data of all the measuring devices via the browser on your PC in your office.

It is possible to connect via LAN, WLAN, or via mobile communications. Requirement for this setup is a corresponding data cable (ZA 1945-DK), WLAN module (ZA 1719-WL), or modem (ZA 1709GPRS), and an internet connection respectively a sufficient coverage for mobile communication on site



The akrobit[®] cloud server (responsible for the acquisition of measured data) queries the data from the measuring devices, saves the data and provides the data in a variety of formats to be downloaded or sent via email. RMT WinControl is recommended to display and evaluate the data (e.g. with arithmetic channels).

In the access-protected area, current measured values and measurement processes can be viewed in a browser. It is possible to set an alarm email that is triggered by a component failure or a limit value infringement





Alternatively, a direct connection to the measuring device is provided as well. In that case, the user himself is responsible for data acquisition, data storage and the alerting procedure. To manage this, the AMR WinControl software is recommended since this software has been specially developed for the convenient handling of ALMEMO[®] devices. The measuring device can be accessed via a secure VPN connection

Cloud service	C1	C2	C3	C4	CD
Measured value files available for download (can also be sent by email)	✓	✓	✓	✓	
Online-Visualization via web browser		✓		✓	
Alert in case of component failure or a limit value infringement (email)			✓	✓	
Customer can directly access the measuring device					 ✓
Contract with akrobit (24 month/ extension 12 month)					
Customer software (recommended)					
AMR WinControl					✓
RMT WinControl	✓	✓	✓	✓	

The cloud service is provided by the akrobit software GmbH. The actual prices depend on the number of devices and the desired services. Data acquisition via the mobile communications implies additional costs for the SIM card and for the transmitted data. The customer can either provide a suitable SIM card himself or the akrobit software GmbH can offer one. In case the modem is used outside Europe, it is mandatory that the customer himself provides the SIM card.

On request, we will be pleased to provide a demo version.

Content

AMR WinControl the software for all ALMEMO [®] instruments RMT WinControl software for evaluating, monitoring, networking	05.04 05.17
WinControl Client OCX and Simple ASCII Server	05.18
ALMEMO [®] View	05.19



State-of-the-art measuring instruments must be able to interconnect with their environment.

Special ALMEMO® software programs give you complete The "AMR WinControl" package has been specially developed control of the whole measuring setup and ensure convenient device handling.

Once measured values have been acquired by the ALMEMO® measuring instrument, this data can be transmitted to a computer via modem, data line, optic fiber, or radio link.

"ALMEMO® Connect", the WINDOWS configuration software, is included free-of-charge with all ALMEMO® devices. This software package lets you program all the device parameters and scan all measured data via a single computer.

for data acquisition and measured data processing with ALMEMO® equipment.

Acquired measured values can be displayed, arithmetically processed, stored, printed out, and exported to other software applications for further processing. ALMEMO® measuring instruments can thus be addressed in an already established corporate network.

A demo version of AMR WinControl can be downloaded free-ofcharge from www.ahlborn.com



ALMEMO[®] Connect : Full Control over the Instrument Setup and Convenient Device Handling

The ALMEMO[®] Connect software allows complete programming As a result, you can keep a constant overview and can completely of the sensors, configuration of the measuring device and reading of the measured value memory via the serial interface (COM) or via network TCP/IP.

control your measuring task!

The latest program version is available for download from www.ahlborn.com.



Functions

- For all ALMEMO® devices V6 and V7 (incl. ALMEMO® 470 and 500)
- For all ALMEMO® connectors analog, digital, D6, D7
- Programming ALMEMO[®] devices
- · Configure device user menus
- · Read out measured value memory and transfer to spreadsheet
- Programming ALMEMO® plugs/measuring points
- Load/save ALMEMO[®] connector/measuring point programming
- Create/store/readout multipoint adjustment
- · Scale/adjust/calibrate measured values
- Display measured values
- Configure ALMEMO[®] output modules (relay/analog/trigger)

AMR WinControl the software for all ALMEMO® measuring instruments

Software Description:

- Software for acquiring, displaying and processing measured data of the ALMEMO[®] device series (V5, V6, V7, A500 and A470)
- Convenient programming and operation of the devices.
- Graphical display, mathematical processing and printing (measurement report) of current and saved data.
- Appropriate for long term measurements (GMP) or for control and monitoring tasks. Can be easily adapted to every project.
- Fast familiarization and safe operation thanks to Windows interface and the context-sensitive help.
- Further information and the current demo version are available under www.akrobit.de.



Software	Versions:	Order no.
Light:	For 20 measuring points and one instrument	SW5600WC1
Standart	: For any number of measuring points and instruments	SW5600WC2
Profi:	For any number of measuring points and instruments, all options included (except Data server, Web server and additional modules)	SW5600WC3
Server:	For any number of measuring points and devices, all options included (except add-on modules), with an integrated data server (simultaneous access by several RMT WinControl clients). (see 05.12 - 05.13)	SW5600WC4
Update:	of the latest software version for older versions	SW5600WCU3
-	of the latest software version for newer versions	SW5600WCU4

Options:

optionst	<u> </u>
Network capability (for addressing several ALMEMO® devices)	SW
Automatic generation of measured data files (daily files / weekly files)	SV
Alarm function (alarm record, output to ALMEMO® relays, starting other applications)	SW
Data server see 05.12	SW
Web server see 05.13	SW
Extended evaluation functions see page 05.08	SW
Fast scanning of measured values for V7 devices (up to 1000 mops online)	SV
PIMEX Player: combined measured value display and video display(see 05.14)	SV
Additional modules:	Or
Thermal comfort and air-conditioning calculations (as per DIN 1946, EN ISO 7730); (see 05.11)	SV
Password protection (see 05.12)	SV
Test bench manager (prerequisite : WC3 / WC4 or WC1 / WC2 + WCO2) (see 05.11)	SV
Thermal transmittance (U) wizard (see 05.09 and chapter Building physics)	SV
Thermal quantity wizard (see 05.10)	SV
OPC export (see 05.11)	SV
Additional protocol (selectable, requires WC3 / WC4) (see system integration, page 05.12)	SV
The memory is read out automatically (see 05.07 connecting options)	SV
Automated printing (line diagrams, tables) (needed: WC3/WC4 oder WC1/WC2 + WCO2)	SV
ODBC-Support (export to SQL-databases) (see 05.11)	SV
Assistant for calibrating measuring sensors (needed: WC3/WC4) (see 05.09)	SV
Assistant for calibrating climate cabinets (needed: WC3/WC4) (see 05.10)	SV
PIMEX Recorder: combined measured value recording and video recording (requirement: WC3/WC4)	SV
<i>new:</i> Assistant for A0/F0 value (see 05.14)	SV
new: Assistant for refrigerant (see 05.14)	SV
new: Assistant for process sequence and setpoint generator (needed: WC3/WC4) (see 05.16)	SV
Complete packages (see 05.13 - 05.14):	Or
Long-term / continuous monitoring	SV
CAN Trace: combined measured data recording and CAN data recording as well as evaluation functions	SV
Hardware copy protection (see 05.15):	Or
USB dongle	SV
USB network dongle	SV

Order no. SW5600WCO1 SW5600WCO2 SW5600WCO5 SW5600WCO9 SW5600WCO10 SW5600WCO11 SW5600WCO12

Order no.

V 5600 WCZM1 V 5600 WCZM2 V 5600 WCZM3 V 5600 WCZM4 V 5600 WCZM5 V 5600 WCZM6 V 5600WCZM7 V 5600 WCZM9 V5600WCZM10 V5600WCZM11 V5600WCZM12 V5600WCZM13 V5600WCZM14 V5600WCZM15 V5600WCZM16 V5600WCZM17

Order no. SW 5600 WCV SW5600WCCAN

Order no.

SW 5600 HL SW5600NHL

Member of measuring points supportedNumber of measuring points supportInitial valuationunitianityunitianityunitianityunitianitySurport for ALMIXMO* networkIIUIIUII <th>Function overviewy</th> <th>WC1</th> <th>WC2</th> <th>WC3</th> <th>WC4</th> <th>WCV</th>	Function overviewy	WC1	WC2	WC3	WC4	WCV
Number of measuring points supported20valuatedvaluatedvaluatedvaluatedvaluatedNumber of connections supportedII	Measured values - scanning					
Number of consistions apported1ulminalulminalulminalSupport for ALMEMOY network <t< td=""><td>Number of measuring points supported</td><td>20</td><td>unlimited.</td><td>unlimited.</td><td>unlimited.</td><td>unlimited.</td></t<>	Number of measuring points supported	20	unlimited.	unlimited.	unlimited.	unlimited.
Support for ALMENO* network. </td <td>Number of connections supported</td> <td>1</td> <td>unlimited.</td> <td>unlimited.</td> <td>unlimited.</td> <td>unlimited.</td>	Number of connections supported	1	unlimited.	unlimited.	unlimited.	unlimited.
Fast saming of measured values for V7 devices (up to 1000mops online)VVVVVConnection typesVVV <t< td=""><td>Support for ALMEMO[®] network</td><td></td><td>✓</td><td>✓</td><td>✓</td><td>✓</td></t<>	Support for ALMEMO [®] network		✓	✓	✓	✓
Connection types V V V V Serial (COM), TCPIP V V V V V Schedule-controlled connection stup Image: Control of Connection Stup V V V V Measured values (numeric, ber chart, wind rose, round gauges) V<	Fast scanning of measured values for V7 devices (up to 1000mops online)			✓	✓	✓
Serial (COM), TCP/IP<	Connection types	•				
Nodem, GSM, and wireless modem supportin<	Serial (COM), TCP/IP	✓	✓	✓	✓	✓
Schedule-controlled connection setup </td <td>Modem, GSM, and wireless modem support</td> <td></td> <td></td> <td>✓</td> <td>✓</td> <td>✓</td>	Modem, GSM, and wireless modem support			✓	✓	✓
Measured values (numric, bar chart, wind rose, round gauges)VVVVDisplay of measured values (numric, bar chart, wind rose, round gauges)VVVVVSave / load presentation characteristics as format typeVVVVVVSave / load presentation characteristics as format typeVV	Schedule-controlled connection setup			✓	✓	✓
Display of measured values (numeric, har chart, wind rose, round gauges)✓✓✓ <th< td=""><td>Measured values - display</td><td></td><td></td><td></td><td></td><td></td></th<>	Measured values - display					
Line graph (YT), XY graph </td <td>Display of measured values (numeric, bar chart, wind rose, round gauges)</td> <td>✓</td> <td>✓</td> <td>✓</td> <td>✓</td> <td>✓</td>	Display of measured values (numeric, bar chart, wind rose, round gauges)	✓	✓	✓	✓	✓
Save / load presentation characteristics as format typeÝÝÝÝÝÝÝTable, overview✓✓✓ </td <td>Line graph (YT), XY graph</td> <td>✓</td> <td>✓</td> <td>✓</td> <td>✓</td> <td>✓</td>	Line graph (YT), XY graph	✓	✓	✓	✓	✓
Table, overview<	Save / load presentation characteristics as format type	✓	✓	✓	✓	✓
Zoom functionsYYYYProjecti consYYYYYProjecti consYYYYYMessured values - savingXYYYYSaving to hard disk - automaticYYYYYSaving to hard disk - automaticYYYYYSaving to hard disk - automaticYYYYYSaving to hard disk - automaticYYYYYAutomatic generation of diliy, weekly, monthly filesIIYYYYAutomatic ally saved files - sent by e-mailIIIIYYYYAutomatic ally saved files - sent by e-mailIIIIIYYYYAutomatic ally saved files - backed up automaticallyIIIIIYY <td>Table, overview</td> <td>✓</td> <td>✓</td> <td>✓</td> <td>✓</td> <td>✓</td>	Table, overview	✓	✓	✓	✓	✓
Project icons✓✓✓✓Work surfaces✓✓✓✓✓Measured values - saving✓✓✓✓✓✓Saving to hard disk - natural✓✓✓✓✓✓✓Saving to hard disk - natural✓✓✓	Zoom functions	✓	✓	✓	✓	✓
Work surfacesVVVVMeasured values - savingVVVVVSaving to hard disk - automaticVVVVVVAutomatic generation of daily, weekly, monthly filesVVVVVVAutomatic generation of daily, weekly, monthly filesVVV<	Project icons	✓	✓	✓	✓	✓
Measured values - savingVV<	Work surfaces			✓	✓	✓
Saving to hard disk - manualImage: start of the start of t	Measured values - saving	1	II			<u></u>
Saving to hard disk - automaticImage: Automatic generation of daily, weekly, monthly filesImage: Automatic generation of daily, weekly, filesImage: Automatic generation of daily, weekly, filesImage: Automatic generation of daily, weekly, filesImage: Automatic generation of daily,	Saving to hard disk - manual	✓	✓	✓	✓	✓
Automatic generation of daily, weekly, monthly filesImage: Constraint of the set of t	Saving to hard disk - automatic	✓	✓	✓	✓	✓
Automatic asving on an event-controlled basisImage: Second Se	Automatic generation of daily, weekly, monthly files			✓	✓	✓
Automatically saved files - sent by e-mailII <th< td=""><td>Automatic saving on an event-controlled basis</td><td></td><td></td><td>✓</td><td>✓</td><td>✓</td></th<>	Automatic saving on an event-controlled basis			✓	✓	✓
Automated printing of files as line diagram or tableImage: Constraint of the set of t	Automatically saved files - sent by e-mail			✓	✓	✓
Automatically saved files - backed up automaticallyImage: Constraint of the state o	Automated printing of files as line diagram or table					✓
Tail-safe (only devices with failsafe mode and internal memory)Image: The transmit of transmit of the	Automatically saved files - backed up automatically					 ✓
Measured values - analysisTwo measuring cursors with statistics functionImage: Constraint of the statistics of the statistics is a line graphImage: Constraint of the statistics is a line graphLoading comparative characteristics in a line graphImage: Constraint of the statistics is a line graphImage: Constraint of the statistics is a line graphArithmetic channelsImage: Constraint of the statistics is a line graphImage: Constraint of the statistics is a line graphImage: Constraint of the statistics is a line graphArithmetic channelsImage: Constraint of the statistics is a line graphImage: Constraint of the statistics is a line graphImage: Constraint of the statistics is a line graphLocal arithmetic channelsImage: Constraint of the statistics is a line graphImage: Constraint of the statistics is a line graphImage: Constraint of the statistics is a line graphLocal arithmetic channelsImage: Constraint of the statistics is a line graphImage: Constraint of the statistics of the statistics of the statistics of the statistic of the statistic of the statistic o	Fail-safe (only devices with failsafe mode and internal memory)					 ✓
Two measuring cursors with statistics functionImage: Constraint of the statistics of the statis	Measured values - analysis	I				
Displaying local maximum and minimum values in a line graphImage: Constraint of the second secon	Two measuring cursors with statistics function	✓	✓	✓	✓	✓
Loading comparative characteristics in a line graphImage: Constraint of the second	Displaying local maximum and minimum values in a line graph			✓	✓	✓
Arithmetic channelsImage: Channels of the second secon	Loading comparative characteristics in a line graph			✓	✓	✓
Global arithmetic channelsImage: Channels of files already savedImage: Channels of files of files already savedImage: Channels of files o	Arithmetic channels	1				
Local arithmetic channels for files already savedImage: style sty	Global arithmetic channels	✓	✓	✓	✓	✓
Calculations based on external table valuesImage: style sty	Local arithmetic channels for files already saved	✓	✓	✓	✓	✓
Formeleditor mit Syntax-HervorhebungImage: Constraint of the syntax-Hervorhebung faileImage: Constraint of the syntax-Hervorhebung faileImage: Constraint of the syntax Hervorhebung faileImage: Constraint of the syntax Hervor	Calculations based on external table values	✓	✓	✓	✓	✓
Formelvorlagen für viele AnwendungsfälleImage: Constraint of the state	Formeleditor mit Syntax-Hervorhebung	✓	✓	✓	✓	✓
Measured values - processingImage: Constraint of the set of third particular folder (wild card search)Image: Constraint of the set of third particular folder (wild card search)Image: Constraint of the set of third particular folder (wild card search)Image: Constraint of the set of third particular folder (wild card search)Image: Constraint of the set of third particular folder (wild card search)Image: Constraint of the set of third particular folder (wild card search)Image: Constraint of the set of third particular folder (wild card search)Image: Constraint of the set of third particular folder (wild card search)Image: Constraint of the set of third particular folder (wild card search)Image: Constraint of the set of third particular folder (wild card search)Image: Constraint of the set o	Formelvorlagen für viele Anwendungsfälle	✓	✓	✓	✓	✓
Linking /splitting of filesImage: constraint of the second of	Measured values - processing	1				
Grouping measured value files in a particular folder (wild card search)Image: Constraint of the second of timeImage: Constraint of timeImage: Constrain	Linking /splitting of files	✓	✓	✓	✓	✓
Grouping measured value files over a particular period of timeImage: Constraint of the particular period of timeImage: Constraint of the particular period of timeExporting measured valuesImage: Constraint of the particular period of timeImage: Constraint of the particular period of timeImage: Constraint of the particular period of timeClipboardImage: Constraint of the particular period of timeImage: Constraint of the particular period of timeImage: Constraint of the particular period of timeImage: Constraint of the particular period of timeClipboardImage: Constraint of the particular period of timeImage: Constraint of the particular period	Grouping measured value files in a particular folder (wild card search)			✓	✓	✓
Exporting measured valuesClipboard✓✓✓✓File formats (MS-Excel XLS / XLSX, TXT / CSV, FAMOS, QS-STAT, DIAdem, binary)✓✓✓✓Dynamic data exchange (DDE, OLE)✓✓✓✓✓Online data transmission to MS-Excel✓✓✓✓✓Measured values - import✓✓✓✓✓ASCII (list, columns, table formats)✓✓✓✓✓ALMEMO® View files✓✓✓✓✓Programming of measuring points and devices✓✓✓✓Avtermented excline of third metry emeans✓✓✓✓	Grouping measured value files over a particular period of time			✓	✓	✓
ClipboardImage: Clipb	Exporting measured values	1				
File formats (MS-Excel XLS / XLSX, TXT / CSV, FAMOS, QS-STAT, DIAdem, binary)Image: Constraint of the state of	Clipboard	✓	✓	✓	✓	✓
Dynamic data exchange (DDE, OLE)Image: Constraint of the sector of the sect	File formats (MS-Excel XLS / XLSX, TXT / CSV, FAMOS, OS-STAT, DIAdem, binary)	✓	✓	✓	✓	✓
Online data transmission to MS-Excel Image: Constraint of the second	Dynamic data exchange (DDE, OLE)	1	\checkmark	✓	✓	\checkmark
Measured values - import Measured values - import ASCII (list, columns, table formats) Image: stable formats) ALMEMO® View files Image: stable formats) Programming of measuring points and devices Image: stable formats) Programming the characteristics of measuring points and devices Image: stable formats) Autempted acquire of third porty segments Image: stable formats)	Online data transmission to MS-Excel	√	✓	✓	✓	 ✓
ASCII (list, columns, table formats) \checkmark \checkmark \checkmark \checkmark \checkmark \checkmark \checkmark ALMEMO® View files \checkmark \checkmark \checkmark \checkmark \checkmark \checkmark \checkmark Programming of measuring points and devices \checkmark \checkmark \checkmark \checkmark \checkmark \checkmark \checkmark	Measured values - import					
ALMEMO® View files Image: Alticle for the second secon	ASCII (list. columns, table formats)	✓	 Image: A second s	✓	✓	✓
Programming of measuring points and devices Image: Constraint of the second s	ALMEMO [®] View files	· •	· •	·	· •	· •
Programming the characteristics of measuring points and devices Image: Characteristic of the second secon	Programming of measuring points and devices	1 -	•	-		
Automated applies of third mantu appage	Programming the characteristics of measuring points and devices	✓	 ✓ 	✓	✓	1
Automated scaling of inite-darky sensors $ \mathbf{v} \mathbf{v} $	Automated scaling of third-party sensors	✓	✓	✓	✓	✓
Measuring points programming - save to file / load from file	Measuring points programming - save to file / load from file	✓	✓	✓	✓	✓

Editing the programmed file (similar to Excel tables)	\checkmark	✓	✓	✓	✓
Data reduction					
Averaging function (ONLINE and OFFLINE)	✓	✓	✓	✓	✓
Smoothing (over time / over number of values, ONLINE and OFFLINE)	✓	✓	✓	✓	✓
Data logger functions					
Programming the data logger (including averaging functions)	✓	✓	✓	✓	✓
Read out from device memory (all / selective measured values)	✓	✓	✓	✓	✓
Display of memory occupancy status	✓	✓	✓	✓	✓
Alarm functions					
Alarm value display in measuring points list and in all measured value displays	✓	✓	✓	✓	✓
Alarm report with confirmation and comments text			✓	✓	✓
Events list (audit trail)			✓	✓	✓
Start a program in the event of a particular fault			✓	✓	✓
Send e-mail / SMS in the event of an alarm			✓	✓	✓
Switch ALMEMO® output relays (specific to measuring point).			✓	✓	✓
In case of an alarm, tones and sound recording are played back (via a sound card)			✓	✓	✓
Control commands dependent on measured values (KwikScript)			✓	✓	✓
Advance warning alarm					✓
Alarm log printout					✓
Schedules for alarm processing					✓
Automatic checking of system configuration					✓
Password protection					
Protection against unauthorized access					✓
Protection against operator error by assigning individual access rights					✓
Traceability of activities by means of an events list					✓
Alarm confirmation with user identification					✓
Control and regulation					
Two-point controller with ALMEMO® output relay?*?s			✓	✓	✓
Proportional controller with ALMEMO® analog output modules			✓	✓	✓
PID controller with ALMEMO [®] analog output modules and arithmetic channels			✓	✓	✓
Automation by means of user-defined operating controls					
Keys and buttons in project icons and as a toolbar	\checkmark	✓	✓	✓	✓
Setting constants	✓	✓	✓	✓	✓
Starting / stopping a measuring operation	✓	✓	✓	✓	✓
Switching relays			✓	✓	✓
Setting analog output values			✓	✓	✓
Configuration management					
Save / load interface configuration		✓	✓	✓	✓
Printout					
Diagrams, meas. value tables, meas. point list, file overview including comments	✓	✓	\checkmark	✓	✓
Network server functions					
Displaying measured values and diagrams on Intranet or Internet				✓	✓
Embedding diagrams and project icons on your own Internet pages				✓	✓
Accessing the integrated web server via any browser				✓	✓
Accessing measured data and history data via TCP/IP (open text protocol)				✓	✓
Forwarding measured data to RMT WinControl				✓	✓
Availability of already acquired measured data even after program restart				✓	✓
Alarm confirmation via web server					✓

After initial installation AMR WinControl will run in demo mode - comprising the full functionality of the professional version (WC3) - for a trial period of 30 days, after which time it will have to be registered. All the functions incorporated in the professional version can be tried without restriction and without engagement. If further functions (additional modules) are needed for test purposes, these can also be enabled on a temporary basis. Users can thus try the software for the duration of the trial period with the full range of functions normally needed and then place an order after the system has been running to their complete satisfaction. Registration does not need reinstallation.

Main Window/General View



- The main window is the platform for all operations with AMR WinControl. All actions run within this window and can be minimised to a symbol, within the window or together with the window, and run in the background.
- The measuring data can be presented as follows: Numeric presentation of measured values, bar diagram, wind rose, round instruments, line diagram, XY diagram, table, file overview.
- Windows can be distributed over various work surfaces between which it is possible to switch by means of tabs.
- The program can be operated by means of menu commands. Only those commands, which can be executed in the corresponding situation, will be available. For a faster operation context-sensitive menus, keyboard commands and symbols in the tool bar are available.
- Comprehensive help information is available via the function descriptions in the status line, notes in the tool bar and a context-sensitive help system.

List of Measuring Points, devices and connections

🛛 🗧 Channel:	s, Devices ani	d Conn	ection	iŝ							_ 0	83	
	Comment	Channel	Unit	Sensor	Low Lin.	Upr. Lin	. Base	Factor	Exp	Averag.	Monitor	^	
1 1	emperature	0.0	*C	NCr	-10	10			0				
2 /	Vir Temperature	0.1	*C	NCr	22				0				
📕 Channels, D	evices and C	onnecti	ons						0				
Device Address	0	1		1	-	120)		0				
Device Type	A2290-8 5	.73	A265	10-8 V6 6	.39				0			18	
Label	AMR ALMEMO	2290-8	AMR AI	LMEMO 2	690-8				0			1	
Sensor Votage	11.7 V		n a	annaí	Davis		6000	-				_	-
Alarm State				anner	s, Devic	es ano	Conr	rection	15				
Sampling Rate	3 M/s					Ne	twork	(intrane	f)	L	ocal CO	м	
Scan Continuously	no		Protoc	ol			alneno			aineno			-1
Store Continuously	no		Port				192.168	92.168.100.105			COMI		
ALMEMO V6 Suppor	t no		Settin	Settings			TCP Port: 10001		Baud Rate: 9600				
Total Memory	509.4 K8	3	Conne	- ction Sta	tus		Conn	toted		4	Connecte	d	
Free Memory	509.4 K	3	Data 1	ransfer			1	~			10		_
Measuring Cycle			Autor	atic Reco	nnect		30	5			30 s		
Print Cycle			Device	Number	(2)		0				1		
Start Time			Allow	CRC Prot	ocol		n	0			00		
End Time			Stand	ard Timec	ut		180) ms			1800 ms		
Available Channels	20		Scan Timeout			4500 ms			4500 ms				
Active Channels	8		Device Select Delay			0 ms			0 ms				
Pressure Compens.	1013 mb	ir 🛛	Secur	e device	initialisation		VRS			yes			
Hysteresis	10 Digit:	5	Poll de	nices in			every cycle			every cycle		le	
A2 Function			Lost N	fessage									
A Dandson (Connections (Last E	rror			_	_	- 1	15.09.20	06, 11:23	:36	
A Noswices V	Connections /	1 ·	4 >	& Device	es λ Conr	ections	1	11	_				11

- As soon as the program is started and the serial interface is assigned, all sensors that are programmed and connected to the measuring instrument(s) will be recognized automatically and displayed in the list of measuring points.
- Apart from sensor specific data regarding the measuring range, comment, limit values, correction values the list also contains symbols for limit value exceeding, sensor breakage and online storage.
- Device-specific information, e.g. device type, memory occupancy, and settings for operating the data logger are also displayed.
- Measuring instruments can be connected via various interfaces (COM, TCP, modem) simultaneously; mixed-mode operation over various connections is possible. Information regarding the current status of connections is displayed here.

Arithmetic channels / new formula editor

f(x)	Mexandreiding Messinglein, Reinstrading Magneting, Reinstrading, Reinstrad, Reinstrading, Reinstrading, R
Formeleditor 80.17 - Status	(Demetrien) Enferen Hingsfigen Beenden Hile
Static Bearborten Formel einfügen Meter if(m("ProTung aktiv") > 0.5; if(m if(m("Minimalwert") < limitmin("Minimalwert") < limitmin("Minimalwert") < limitmin("Minimalwert") > -0.5; if(m("Dauer")	state entities,statum "Maximalivent") =inimitrat("Maximalivent"); -1; if(m alwert"), -2,inimitrat("Maximalivent"); -0.5 and m 60; 1; -3), m("Status") }))

- Acquired measured values can be further processed and displayed via arithmetic channels during as well as after the measuring operation.
- The arithmetic channel feature of the program offers the possibility to calculate further variables from the measured data, to derive statuses, and to verify conditions.
- The new formula editor facilitates the color highlighting and checking of the syntax (syntax highlighting) as well as the convenient selection and integration of measuring points.
- For common calculations and tasks there are now formula templates available that can be directly entered and combined in the formula editor.
- Depending on the definition, an arithmetic channel is available either globally in the entire program as a virtual measuring point or just locally in one data record (line diagrams or XY diagrams, table).
- It is also possible to extend already saved data records by any desired number of arithmetic channels.
- Arithmetic channels can be saved together in one file and can be loaded again at any time. This enables a convenient evaluation of saved data with just a few clicks.

Line graph, measuring cursors and statistics function



- The line graph displays the temporal evolution of the values of ongoing measurement operations or of saved data.
- Customer specific settings for the line graph can be saved as a template and can be applied in two clicks to other files. Alternatively it is also possible to create a new diagram with the saved template.
- The zoom function and the possibility to shift the axes with the mouse enable an easy navigation through the data.
- Two measuring cursors help to analyze the acquired data.
- The integrated statistics function calculates differences, minimum, maximum, average value and standard deviation of the range defined by the cursors and displays the data in a table.
- The diagram and the table can be printed, or can be copied to the clipboard..

Work spaces

- Better overview and fast navigation between different views thanks to tabs as used in a web browser.
- Division of projects into different views with clear designations of the tabs done by the user himself.
- It is no longer necessary to minimize a window to enable the user to see what he wants to see.
- Automatic switching on an event controlled basis or via active elements in a project illustration that e.g. serves as an overview.
- The navigation between work spaces can be restricted by password protection in order to oblige user to one particular view.
- The structural division of the windows into work spaces can also be fetched via the web server.

Data logger functions

- Settings necessary for operating the data logger can also be programmed via the AMR WinControl software.
- The memory can be read out and deleted. The time of the data logger can be synchronized with the one of the system.
- Important information regarding the memory and the set cycles of the device are displayed in the overview of the measuring device.
- The readout of the memory devices can occur individually or combined for all data loggers in the measuring network, whereat a preview of already read values is displayed in a line diagram.
- Optionally it can be determined that only a selection of the saved values (not all measured values) shall be read out of the device memory.

The memory is read out automatically

- This module greatly facilitates the task of reading out from the device memory of an autonomous data logger.
- Saving data to the data logger is interrupted, its memory is read out, and, if this is successful, the memory content is deleted. The time-of-day is synchronized and saving data to the data logger is resumed.
- Reading out from memory can be completely automated in the form of schedules.
- All steps and possible errors are documented in the events list..

Monitoring Functions

- An alarm can be triggered by a component failure or a limit value infringement.
- Alarm processing can be activated individually for each measuring point.
- Alarms are reported visually and / or acoustically.
- The cause and the duration of events responsible for triggering the alarm are documented in an events list.
- Alarm reports can be confirmed either individually or all together.
- If the cause of an alarm persists uncorrected an alarm reminder is issued to ensure that the alarm is not forgotten after it has been confirmed.
- A line graph with settable history can be generated for the variable triggering an alarm.
- In the event of an alarm being triggered e-mails can be sent, ALMEMO[®] output relays can be switched, and programs or scripts can be executed.
- Alarm reports can be forwarded via the network.
- In the event of a limit value being infringed program control commands can be executed (KwikScript).







Control and regulation



Automatic saving-to-memory



- Two-point controllers, proportional controllers, and time-based controls are available.
- It is also possible, using arithmetic channels, to define PID controllers. Setpoint curves und process sequences can be specified by means of files with
- coordinates pairs.
 Values can be specified and process sequences can be modified all via command buttons in project icons or the toolbar.
- Measured data can be saved to memory manually or on a time-controlled or eventdriven basis.
- Not only daily / weekly / monthly files can be specified but also files with any random periods of time.
- Data is saved to memory automatically in the background irrespective of any opened diagrams, tables, or displays.
- Measured value files can be exported automatically on completion of a save-tomemory cycle and be sent by e-mail (as an option with the events list).

Extended evaluation functions



- Measured value files can be incorporated in new or already existing line charts in the form of comparative characteristics.
- Folders containing a large number of measured value files can be conveniently grouped using various patterns based on file names and filters according to time and measuring point.
- Local maximum and minimum values can be shown in a line chart as any measured value curve required. The search radius between maximum and minimum can be freely set.

Project illustrations



- Project illustrations allow for visualizing the setup of measurements and processes by using individually designed graphics and/or photographs (bitmaps).
- The presentation of the acquired data is provided in measured value fields that can be freely positioned; size and colors (including limit value violation) can be freely selected.
- Text fields can be filled with legend information and descriptions and can be freely positioned.
- By means of dynamic text fields it is possible to display texts in relation to measured values or conditions.
- All opened diagrams (line diagram, bar diagram, etc.) and displays can be inserted as a live element and arranged as desired.
- Command buttons (keys and switches) can be freely positioned in the project icon and allow changes to values for performing calculations or controlling processes (switching of relays or valves, etc.).
- The design of the command buttons can be changed in any way in the form of icons; the measurement setup can thus be visualized in a completely integrated way.
- Any number of project illustrations can be opened at the same time, allowing, for example, to give a presentation of the total view and detailed views of a project.
05.09

Individual operation and display panels

- · Combination of the operations and display elements into a clearly structured overall entity, focusing on fundamental aspects.
- Direct control and programming of devices, test procedures, and software features.
- Display of conditions visually or in form of predefined, explanatory, changing texts.
- Integration of opened line diagrams, bar diagrams, and displays directly in the panel.
- Interaction also possible via web server in browser from other computer. Password protection is additionally recommended.
- The user is able to create the operation and display panels according to his own needs by means of the project illustration.
- · We offer the service to create panels in case a visually appealing and sophisticated solution is desired.

Thermal transmittance (U) wizard

- The thermal transmittance (U) wizard is available for Online and Offline calculations; it guides the user through all the required steps.
- The user can choose from a selection of calculation methods for the experimental thermal transmittance value, for the thermal transmittance value according to DIN 4108, and for the official calculated value.
- Determination of the currently calculated value and the sliding average value.
- The calculation methods will be described and the allocation of the corresponding measuring variables will be provided.
- After completing all steps a line diagram will be created, which will then be filled with the measuring data and the calculated variables.
- The cursor function can be used to open the statistic table, which provides further evaluation options (see above).

PPD / PMV wizard (comfort index measurement)

- Calculation of thermal comfort as per DIN 1946 Part 2 and ISO 7730
- User guidance by means of a wizard and easy-to-understand evaluation
- Output in the form of "predicted mean vote" (PMV) and "predicted percent of dissatisfied" (PPD)
- Online and offline calculation of PMV and PPD in real time or on the basis of measured values already existing
- Graphical representation of measured data and calculated values in a format suitable for export (e.g. ASCII, MS Excel, DiaDEM, etc.)
- Calculation parameters can be saved as a model for subsequent calculations.
- Additional PMV / PPD functions are available for use in arithmetic channels.

Assistant for calibrating measuring sensors

- · Multilevel calibration via self-defined calibration programs with set point lists and stability criterion
- · Hardware profile with set point, reference and calibration measuring points.
- · Automated procedure with measured value recording
- Drive a calibrator (set point specification)
- · Any desired number of measuring points can be calibrated simultaneously
- Saving the values as AMR, CSV or Excel file
- Saving a configurable number of values per calibration step in case the stability criterion is met
- Overview window with progress bar

10/2021 • We reserve the right to make technical changes.

• The price for the module depends on the number of calibration station and calibrators that are to be supported simultaneously.

The U-Value is calculated using the fi m the DIN 4108. The s Air and Wall Temp < Back Next > Cancel Help









Assistant for the calibration of climate chambers



- Calibration according to directive DAkkS-DKD-R 5-7
- Support of methods A and B with 9 and more measuring points
- Intuitive user navigation
- Analysis is possible online as well as offline
- Direct involvement of the climate chambers in the online measurement operation
- Online visualization of the calibration process for all measuring points
- Calculation of local humidity measured on the temperature monitoring points
- Determining measurement uncertainties
- Logging of deviations from the display value
- Automatic, convenient analysis with protocol creation in PDF format.

Thermal quantity wizard



Password protection



- The thermal quantity is calculated automatically from the volume flow and the temperature difference.
- You can enter settings easily and conveniently using the wizard.
- Data tables for water are included in delivery; users can define their own extensions for other media themselves.
- The thermal quantity can be calculated in real time or on the basis of existing measured value files.

$$\delta Q = c_v \cdot m \cdot dT$$

- Thanks to the integrated user management system, unauthorized access to AMR WinControl is impossible. This policy reduces the security risks to a minimum.
- Every change of user is logged in the events list for subsequent evaluation.
- Access rights can be defined individually per user or can be copied.
- *new:* Authentication can be done as WinControl user or Windows user (local or Active Directory). Windows groups are supported.
- Access limitations can be defined for every single program feature.
- Alarm confirmations can be assigned unequivocally to particular users.
- The password protection is the minimum requirement for the system validation according to FDA 21 CFR Part 11.

Data Export:



- The data files can be, Online and/or at any later point in time, stored in the following formats Excel (XLS / XLSX), ASCII (TXT / CSV), WK1, FAMOS, QS-STAT, DIAdem.
- With ODBC measured data can be exported in SQL databases (structured query language). This supports all data sources for which an ODBC driver is installed and set up on the system.
- The line and XY diagrams and the tables can be copied to the clipboard and, for example, be inserted into a protocol text.
- Via dynamic data exchange (DDE) it is possible to transfer measured values Online to other applications, for example MS-EXCEL.
- Furthermore, line diagrams can be embedded into text documents (e.g. a MS Word document) via the OLE function.

OPC Client/Serve

OPC export: Process control system connection

- "Openness, Productivity, and Collaboration"
- OPC is an established industrial standard for access procedures on a multi-vendor basis irrespective of manufacturer.
- · AMR WinControl operates as an OPC client; it writes current measured values to the global variables provided by an OPC server.
- Data can be transferred in parallel to several OPC servers.
- Data from AMR WinControl can, with the aid of OPC, be visualized online in LabView[™].

ODBC support: SQL database connection

- Open database connectivity
- ODBC is a standardized database interface used by SQL as its database language.
- Recorded measured values can thus be transferred to a database.
- Current measured values can be interrogated from a database per measuring cycle.
- A suitable ODBC driver for the database must be installed and set up on the system.

Test bench manager

- Several autosave managers can be operated and organized via a convenient, easy-touse graphical user interface.
- Measured data can thus be saved simultaneously to different files.
- · Autosave managers can be started and stopped independently of one another and according to various criteria (time-driven or event-driven).
- Different measuring locations (operating in parallel) can thus be treated separately.
- · Measured value files can be indicated as write-protected already during recording.
- Including 10 autosave managers (optionally more available)
- If required, we offer to implement individual automations of test stations including input of test parameters, test procedure, signaling (optical/acoustic), and protocol printout.



- AMR WinControl can handle single measuring instruments as well as a network of measuring instruments of the ALMEMO® series.
- The connection to the measuring instrument(s) can be established via serial interface, USB, Bluetooth, or mobile modem.
- In a similar way, the measuring instruments can be addressed via a computer network (TCP/IP address) and VPN.
- · Connections can be set up on a time-controlled basis. Reading out from the memory on ALMEMO® devices can be automated. The memory can on request be cleared and saving to memory can be resumed automatically. Any problems encountered are noted in the events list.
- Via mobile radio it is possible to establish connections to devices that have been installed in remote locations. The connection can be established inexpensively and permanently, as the billing is volume-oriented.



Process control (e.g. Lab







Protocol printout



System integration



- With a few clicks, recorded measured values can be printed out as a protocol.
- The customer can create his own individual templates or customize the available sample templates.
- The protocol may include the line graph, measured values, calculated variables, times, and comments.
- Ideal for compiling measurement reports or protocols for customers without having to bother with Excel and data export
- Optionally, AMR WinControl offers support for protocols for measured value enquiry from devices from other manufacturers simultaneously for any number of connections.
- MODBUS: flexible protocol and industry standard
- CAN Bus: with PEAK-CAN or USB2CAN adapter
- OPC DA: measured data acquisition from measuring devices/systems or data transfer to an OPC server (e.g. LabView)
- MQTT: Inclusion of topics of an MQTT server (broker) as measuring points and sending of acquired measured values as topics to an MQTT server.
- ODBC: SQL data base (Oracle, MSSQL, MySQL, ...)
- Climate chambers: Feutron[®], CTC, Binder, Memmert, Vötsch, and Weiss Umwelttechnik, ESPEC, ATT
- Dew point mirror: DPM 373, DewMaster
- Gas analyzers: ECO Physics CLD 8xx, ABB, MRU Nova H8, as well as Emerson devices X-Stream, MLT, CLD, and NGA
- Power meters & energy meters: Yokogawa WT230 & WT310, Janitza[®], Infratek 106A & 108A, Simeas-T, and Hioki
- Calibrators: Julabo, ISOTECH, AMETEK® (JofraTM), JOFRA (ATC/RTC)
- Precision measuring device: Fluke 8508A (with full precision)
- Barcode scanner protocol: network-compatible and serial scanners
- Simple ASCII: implementation of your own measuring devices
- The use of AMR WinControl for acquiring measured data of further devices is possible upon request.

Barcode scanner protocol



• Acquisition of barcodes in text format via USB, TCP/IP or Bluetooth by using appropriate scanners.

- Analysis of the barcode to control program features (e.g. automatic saving) and test procedures.
- The barcode is automatically imported into the name of the file.
- Display of the scanned barcode in text format and storage of numeric barcodes in measured value files.
- Several scanners can be operated in parallel.

Measured value server



- With the measured value server up to 200 users simultaneously can access current measured values and the measured values history via a TCP network (Intranet / Internet).
- · Interface to any data acquisition and process control system
- Online transmission of measured data to other operating systems (e.g. LINUX, WINDOWS CE, UNIX, etc.)
- Data distribution according to any specified criteria
- Customized solutions can be implemented using straightforward ASCII commands issued via the TCP protocol; all these commands are fully documented.
- Open "read-only" interface for any user-defined connection software
- "REMOTE WinControl" and "WinControl Client OCX" provide powerful standard solutions for the measured value clients.

Web server

- AMR WinControl provides a full range of web server functions for publishing web pages (HTML) in the Intranet / Internet. It also incorporates additional functions that can be used to output the contents of AMR WinControl windows directly onto web pages.
- Current measured values and measured value histories can be displayed in a variety of ways (line diagrams, XY diagrams, project illustrations) in the Intranet / Internet.
- Visualization of processes and systems
- Visual remote monitoring
- Confirmation of alarms via the browser (only with alarm function and password protection)
- · Linking presentation and real-time data on web pages
- The way in which measured values are displayed does not depend on the operating system; only a browser is needed (MS Internet Explorer, Firefox, Chrome, Opera, etc.).
- Diagrams and measured values can also be displayed on smartphones and tablet PCs.
- · Security provided by SSL / TLS and user authentication
- Very easy to use : Images generated from the contents of a window can be transmitted as soon as the program starts without needing any further settings. For particularly demanding tasks the HTML pages must first be adapted and connected to the web server.
- The wide variety of image formats and special parameters make for transparency and loss-free scaling and permit automatic updating. Powerful real-time compression algorithms minimize the volume of data to be transmitted.
- All the layout facilities available in HTML, DHTML, and CSS can be exploited; combining with JavaScript is also possible.
- Graphics, text, and measured value displays can be combined and merged completely seamlessly.
- The web designer is free to specify, more or less independently of AMR WinControl, how the measured value displays are to appear.
- The user receives current measured data without being exposed to any sort of security risk because there is no need for Java or special plug-ins.

SW5600WCV Package for long-term / continuous monitoring

This package, based on the AMR WinControl "professional" version, contains all the options and modules needed to implement long-term and continuous monitoring of critical measurable variables.

- Integrated user management with individually settable access rights and password protection
- · Tamper-proof event list with sort and filter functions
- Trend monitoring pre-alarm for signaling trend developments
- Signaling of alarms and events with user-specific confirmation and comments
- Alarm confirmation per web server (authentication and SSL / TLS available)
- Schedules : Automatic switching ON / OFF of alarm treatment for each measuring point, e.g. alarm treatment on working days between 06 and 18 o'clock only.
- Temporarily withdrawing certain measuring points from alarm treatment, e.g. for defrosting a cold room
- In the event of alarm an MS-Excel log can be printed out automatically. Users can modify the log provided or create their own.
- Failsafe : Automatic reading out of the device memory after loss of connection to the device
- Requirements: ALMEMO® device with failsafe mode and internal memory
- System configuration
- Integrity check on all measuring points and measuring instruments after program start
- Processing of measured and calculated variables in control and regulation functions
- Automatic printout and / or e-mail with daily files and event lists
- Including security package.

Security package

- Data security : Automatic backup of all automatically recorded data (daily and weekly files, measured values recorded on an event-controlled basis, event lists, etc.)
- Fail-safe : In the event of failure a watchdog is triggered for PC restart and / or signaling via relay.
- Including watchdog card



Ereignislistel						
Messstellen	Alarme	Ereignisse	4 Uhrzeit	Meldungsty	Messstelle	
Messstelle	Kommentar	Er	eignis	Beginn	Ende	T
0.0	KOMM					
0.8						
0.69	123					
5.0	sensor					
5.1						
5.2	messtelle					
5.3						1
5.9						
80.0						
81.0						
		Systemkonfigu	uration erfolgreich	15.01.2009, 18:05:1	3	
		Messwertabfr	rage gestartet	15.01.2009, 16:06:0	2	
5.1		GW-Unterschr	rebung	15.01.2009, 16:08:0	3 15.01.2009, 16.06.07	
-		Alarm quittert		15.01.2009, 16:08:0	5	
_		Inesswertabf	rage beendet	15.01.2009, 16:06:0	8	
-			Access Rights			x
11 Bezeichmunn o 5 - Vählaam er 21 Beschreibung Interj Hegin des Ereigni untier aus: 08 01 onen edas Noas 10 Kommentan zu 20 Bud tevete u. de 10 Kommentan zu 20 Bud tevete u. de 10 Rofermation de Budgestelle	der Alem neistung for Monsetolitet in der Bahmerhodingungen sess (prenzwerklichersdreic 00, 13152 von Palus ein behadung punkt der Guffung- smit Statumg im Statumg i	en der Massweiterte AMR WinControl b bung: 08.01.00, 12: -18,5 °C en genuen		pen pprt sport sport sport sport sport sport sport set Set Set Set Set Set set Calculation Channe set Calculation Channel set Calculat	te Te	E Hop
D.	histor	lo sture	Lines I	10		
attelungsleter	Slinde	NIK 200	r 1411			
uslišit skontrolle						
5) Best Migung der	Kenntnisnahme der Störu	nasmeliking.	_			
iensthebender:	(East)	Datum:	Utrzet Alarm			
a second de						
		Unterschrift	34-47	Time:	20.05.2008, 08:24:41	
			· · · · ·	Channet	0.0 - Input	
4am e:	Rain	Unterschrift	aw	Event:	Limit value exceeded	
Demerkungen	the Vagang mark is da	Betrieledenskad nige		Stop Alarm	Hel	
		akrobit software - testcenter -				

new

Software

PIMEX: combined measured value recording and video recording



- Simultaneous acquisition of measured values from ALMEMO[®] devices together with video data from a digital source
- The measured data and video signal are synchronized and displayed together.
- The modes available are preview, record, and playback.
- PIMEX player is included in the professional version (WC3). The recording function is available as module (ZM14).
- Possible applications : Documentation / visualization of the process environment (e.g. for safety in the workplace, quality management, etc.)

CAN trace: combined measured value recording and CAN data recording



- Synchronous recording and display of measured data and CAN messages
- Navigation with cursor in the line graph and display of the associated CAN messages in a table
- Configurable decoding and color highlighting of the CAN data
- Search and filtering of the CAN data
- Export of CAN data to a TRC file
- Import of CAN data from a TRC file to measured data
- Support of PEAK-CAN adapter (USB or PCIe)

Assistant for A0/F0 value





- Calculation of the A0 or F0 value during sterilization in AMR WinControl.
- Wizard for creating the appropriate calculation channels with specification of the temperature measuring points, the reference temperature and the z-value.
- Any number of independent calculations in parallel.
- Calculations can be performed live (online) or subsequently for recorded values.

Assistant for refrigerant



- new
- Calculations of dew point or boiling temperature.
- Wizard for creating the appropriate calculation channels with specification of pressure measuring points and data tables for desired refrigerant.
- Refrigerants can be added by the user.
- Any number of independent calculations in parallel.
- Calculations can be performed live (online) or afterwards..

Automation of test stations

- Management of up to 150 independent test stations (basic configuration: 10).
- Storage of assigned measurement data in separate files for each test station.
- Input of test parameters (DUT, tester, etc.) and data for controlling the test when starting a test station.
- Control of the test station and the test item via calculation channels and the setpoint generator.
- Export and archiving of test results.
- Output of test reports as PDF or to a printer.
- E-mail dispatch after the test.
- Optional: Control of the test station with barcode scanner.
- Optional: Output of test results to an SQL database (ODBC).
- On request complete test station automation by akrobit Software GmbH..

Assistant for process sequence and setpoint generator

- Creation of time-controlled value and switching sequences via a graphical user interface.
- Tabular specification of times and values with repetitions
- Continuous progressions (ramps) as well as abrupt changes of values
- Waiting for signals
- Representation of the total course in a line diagram
- Parallel operation of several process sequences
- Support for all ALMEMO[®] analog and relay outputs, as well as supported third-party devices with setpoint specification such as climatic chambers and furnaces.

Copy protection

- AMR WinControl incorporates a copy protection system which requires a PCdependent code to enable it. To receive this code the user must first register the software by telephone, fax, or e-mail. Per licence purchased the software may be installed and operated on one computer.
- It is also possible as an option to request a hardware copy protection mechanism, a dongle; with this the software can be installed on any number of computers but will only run on that PC into which the dongle is currently plugged.
- A network dongle may contain more than one licence; with this it is possible without the inconvenience of moving the dongle to run the software simultaneously on as many computers in a company network as there are licences encoded in the dongle.

AMR WinControl system requirements

Components :

Computer Operating system

Memory Free hard-disk capacity Interfaces Minimum configuration

Windows-PC (x86/x64) Windows 8.1, 10, 2012 R2, 2016 (32 and 64 bit) 4096 MB 30 MB USB Recommended configuration

Windows-PC Windows 10

8192 MB 100 MB COM (RS232), USB, network card



1	
	and the second
	A COLORING



new

RMT WinControl software for evaluating, monitoring, networking



Program description

- Access to measured values on one or more AMR WinControl data servers in a local network or via the Internet
- Access to one measuring system by any number of users simultaneously
- Open and evaluate AMR files
- Same range of functions as AMR WinControl except for device access
- At our site (www.akrobit.de) you can find all the latest information regarding software versions and updates and also download the most recent trial version of the software.



RMT WinControl can perform the following:

- Monitoring of measured data from WinControl data servers at various locations
- Evaluation of acquired measured data / files independent of the recording computer
- Safe and secure access to the data acquisition system by "read-only" protocol
- Additional alarm handling and recording independent of the recording computer
- By accessing automatically stored files of an AMR WinControl and querying the measured value history, the evaluation computer does not have to run continuously.

SW5600NHL

Software versions Basic version (like SW5600WC2 except for device access and maximum 1 connection) Professional version (like SW5600WC3 except for device access and maximum 1 connection) Web server (like SW5600WC4 except for device access and any number of connections) Update to the latest software version	Order no. SW5600WCR2 SW5600WCR3 SW5600WCR4 SW5600WCRU
Options	Order no.
Automatic generation of measured data files (daily files / weekly files) Modem support Alarm function (event list, alarm e-mail / SMS, switching of ALMEMO [®] output relays) Data server see page 05.13 Web server see page 05.14 Extended evaluation functions see page extended evaluation 05.11	SW5600WCRO2 SW5600WCRO3 SW5600WCRO5 SW5600WCRO8 SW5600WCRO9 SW5600WCRO10
Additional modules Thermal comfort calculations as per DIN 1946, EN ISO 7730 see page 05.12, 12.14 Password protection see page 05.12 Test bench manager (prerequisite : WCR3 / WCR4 or WCR2 + WCRO2) see page 05.15 Thermal transmittance (U) wizard see page 05.11, 13.03 Thermal quantity wizard see page 05.12 OPC export see page 05.12	SW5600WCRZM1 SW5600WCRZM2 SW5600WCRZM3 SW5600WCRZM4 SW5600WCRZM5 SW5600WCRZM6
Hardware copy protection see page 05.15 Hardlock USB dongle	SW5600HL

Hardlock USB dongle Hardlock USB network dongle

Minimum system requirements

Component	Minimum configuration	Recommended configuration
Computer:	Windows-PC (x86/x64)	Windows-PC (x86/x64)
Operating system	Windows 8.1, 10, 2012 R2, 2016 (32 and 64 bit)	Windows 10
RAM	4096 MB	8192 MB
Free hard-disk capacity	25 MB	100 MB
Interfaces	Network card TCP/IP	Network card TCP/IP, Internet or VPN

WinControl client OCX and SimpleASCII server

WinControl Client OCX

- Access to measured values on a WinControl data server in a local network or via Internet
- \bullet MS ActiveX® universal components for integrating in your own applications
- Client licence for data server included
- Including documentation and simple application example for MS Excel
- This requires an AMR WinControl WC4 or option WC08.
- Measured values from a WinControl data server can be transferred to your own applications by the WinControl client OCX.
- Current values and the measured value history can be scanned.
- Using OCX shortens development times appreciably because it relieves the developer of tasks involving communication with the data server.
- It can be incorporated in any application supporting OLE (Object Linking and Embedding) (e.g. MS Excel, Matlab, MS Access, MS SQL Server, etc.).
- Any programming language can be used for this purpose (C++, C#, Visual Basic (VB, VBA, VBS), Delphi, etc.).
- Since multiple objects can be used simultaneously, data from various data servers can be acquired and recorded. OCX needs to be installed on the system only once.

Simple ASCII server

- Server component for sending data to AMR WinControl using the SimpleASCII protocol via TCP/IP
- \bullet MS ActiveX® universal components for integrating in your own applications
- including SimpleASCII protocol licence .
- Including documentation and simple application example for MS Excel.
- Using the SimpleASCII server measured values or data can be transferred to AMR WinControl from another source (application or measuring instrument).
- Using this component shortens development times appreciably because it relieves the developer of tasks involving the programming of a TCP/IP server; (in programming languages (e.g. VBA, VBS) this is not possible without additional components).
- It can be incorporated in any application supporting OLE (Object Linking and Embedding) (e.g. MS Excel, Matlab, MS Access, MS SQL Server, etc.).
- Any programming language can be used for this purpose (C++, C#, Visual Basic (VB, VBA, VBS), Delphi, etc.).
- With ActiveX-Control you can e.g. develop your own driver for incorporating an additional measuring instrument in AMR WinControl.

Software version

Client licence with OCX (client licence for the AMR WinControl server and OCX developer's licence) SimpleASCII server (SimpleASCII protocol licence for AMR WinControl with ActiveX-Control)

Minimum system requirements

The configuration actually needed depends on the software in which ActiveX-Control is integrated.









ALMEMO[®] View



ALMEMO[®] View is a software package that can be used to evaluate and display measured data on one ALMEMO[®] device with up to four measurement channels.

ALMEMO[®] View runs under MS-Windows and can be used to drive an ALMEMO[®] device with up to four measuring points.

As soon as the connection between the computer and the measuring instrument has been established the program detects and lists these measuring points automatically.

The measured values are then read at a sampling rate selected by the user.

Datenlogger

The measured value memory on an ALMEMO[®] data logger (maximum four measuring points) can be read out, displayed as a line chart or table, and saved to a file. The parameters needed to operate the measuring instrument can be set via a dialog and programmed with **ALMEMO[®] View**

Display of measured values

The recorded data can be displayed in numeric form, in a table, and as a line chart. It is possible to display just one measuring point or several measuring points at the same time in different modes.

Saving measured values

Measured values can be archived in line chart or table form.

Printing out

ALMEMO[®] View can also be used directly to print out diagrams, tables, or a list of all measuring points with their associated correction values, e.g. for the purposes of technical documentation. The results can be viewed in advance before printing out in the print preview. The program supports all printers that can normally be installed under MS-Windows.

Documentation

To compile protocols using some other software the line charts, tables, and lists in **ALMEMO®** View can be copied via the MS-Windows clip-board to other application programs.

Please note: The ALMEMO[®] View does NOT work with ALMEMO[®] V7 devices.

Software versionen	Order no.
Basic ALMEMO® View software for maximum four measuring channels	
(recommended for 1 measuring instrument with a maximum of 4 measuring channels, connection via 1 COM interface)	SW5500AV

System requirements:

ALMEMO® View can be run on a computer (x86/x64) with Windows XP or newer

Content

ALMEMO [®] memory connector with micro-SD ZA 1904 SD	06.02
Extension cable	06.03
Accessories for measuring instruments	06.06
Rechargeable Batteries	06.06
Mains Adapter, Power Supply Cables	06.07
Carry cases, Rack case	06.08

ALMEMO® memory connector with micro-SD ZA 1904 SD



- for ALMEMO® data loggers, as of version 6
- Large memory
- High data security
- Measured values can be saved to a text file.
- The memory card in the data logger can be replaced quickly and easily on site.
- Files can be transferred to a PC quickly and easily via a card reader

Technical data

Measuring instruments	for ALMEMO [®] 202, 204, 710, 809, 1020, 1030, 1033, 1036, 2470-2S, 2590-2A/-4AS, 2690, 2890, 4390, 5690, 8036. 8590, 8690 Memory connector on device output socket A2
ALMEMO [®] memory conne	ector
	Integrate drive for micro-SD card
Memory card	MicroSD industry standard
	(Industrial Grade SSD SLC Technology)
	with high performance, reliability and
	durability, possible up to 2 GB,
	standard FAT16 format

Measured values	With 512 MB approx. 30 million measured values
Ring memory	no
File format	ASCII text file, measured values in table format, separated by semi-colons
Reading device	USB card reader for removable storage media
Measuring software	WinControl (as of version 6), see Chapter Software

Variants	Order no.
ALMEMO® memory connector with micro-SD memory card (512 MB) including USB card reader	ZA1904SD
Micro-SD memory card (512 MB as replacement)	ZB1904SD



Micro-SD memory card (as replacement)

ALMEMO® extension cable up to 4 meters length for all ALMEMO® devices (V5, V6, V7)

Passive extension cable ZA 9060-VK for all ALMEMO[®] sensors (analog, DIGI, D6, D7) except for thermocouple sensors.



Technical data and functions

- The passive ALMEMO[®] extension cables ZA 9060-VK are used for all ALMEMO[®] sensors (analog, DIGI, D6, D7) except for thermocouple sensors and for all ALMEMO[®] devices (V5, V6, V7).
- The extension cables have an ALMEMO[®] connector/ coupling and are plugged between the ALMEMO[®] sensor plug and the ALMEMO[®] measuring instrument.
- The measuring signal or the digital measured values and the parameters saved in the ALMEMO[®] sensor plug are evaluated by the ALMEMO[®] measuring instrument via the extension cable.

Variants:

Passive extension cable for all ALMEMO[®] sensors (analog, DIGI, D6, D7) except for thermocouple sensors, for all ALMEMO[®] devices (V5, V6, V7).

1 meter long 2 meters long 4 meters long

Passive extension cable ZA 9020-VK up to 4 m length for ALMEMO® sensor NiCr-Ni



Technical data and functions

- The passive ALMEMO[®] extension cables NiCr-Ni ZA 9020-VK are used for ALMEMO[®] sensors NiCr-Ni and for all ALMEMO[®] devices (V5, V6, V7).
- The extension cables NiCr-Ni feature a specific cable with integrated compensating cable NiCr-Ni, have an ALMEMO[®] connector / coupling, and are plugged between the ALMEMO[®] sensor plug and the ALMEMO[®] measuring instrument.
- The measuring signal and the parameters saved in the ALMEMO[®] sensor plug are evaluated by the ALMEMO[®] measuring instrument via the extension cable
- Note: ALMEMO[®] extension cables are only available for

Variants:

Passive extension cable for ALMEMO® sensor NiCr-Ni and for all ALMEMO® devices (V5, V6, V7).

1 meter long

- 2 meters long
- 4 meters long

• Note: Many ALMEMO[®] sensors can be delivered with a longer connecting cable. Please do not hesitate to ask!

Please note:

Connecting cables must not be plugged together!

ZA9060VK1 ZA9060VK2 ZA9060VK4

Order no.

thermocouple type K, NiCr-Ni. Many ALMEMO* thermocouple sensors can be delivered with a longer thermal line / compensation line. Please do not hesitate to ask.

Please note: Connecting cables must not be plugged together!

Order no.

ZA9020VK1 ZA9020VK2 ZA9020VK4

ALMEMO[®] extension cable up to 100 meters in length for all ALMEMO[®] devices (V5, V6, V7)

Intelligent extension cable ZA 9090-VKC up to 100 meter in length for all ALMEMO[®] sensors, analog, D6, except for D7, except for thermocouple sensors.



Technical data and functions

- The intelligent ALMEMO[®] extension cables ZA 9060-VKC are used for analog ALMEMO[®] sensors, D6, except for D7, except for thermocouple sensors and for all ALMEMO[®] devices (V5, V6, V7).
- The extension cables have an ALMEMO[®] connector/ coupling (each with a microcontroller) and are plugged between the ALMEMO[®] sensor plug and the ALMEMO[®] measuring instrument. The current consumption of the extension cable is approximately 8 mA.
- The analog measuring signals are transferred analogy via the intelligent extension cable, the digital measured values and the

parameters saved on the ALMEMO[®] sensor plug are digitally transferred via CRC and evaluated by the ALMEMO[®] measuring instrument.

- The ALMEMO[®] sensors can be exchanged arbitrarily. The intelligent extension cable does not influence the measurement operation even in case calibrated sensors with adjustment / multi-point adjustment or sensors with special linearizations (saved on the ALMEMO[®] sensor plug) are used.
- Note: Many ALMEMO[®] sensors can be delivered with a longer connecting cable. Please do not hesitate to ask!
- Please note:

The intelligent extension cables ZA 9090-VKC are **not suitable for:**

- ALMEMO[®] plug for frequency, pulse, rotational speed ZA 9909-AKx,
- ALMEMO® rotational speed sensor FU A919-2,
- ALMEMO[®] plug for digital signals (voltage) ZA 9000-ES2/EK2,
- ALMEMO[®] measuring module for DC voltage / DC ZA 9900-AKx, ZA 9901-AKx (no average value),
- ALMEMO[®] flow sensors FV A915-Vx,
- ALMEMO[®] vane anemometer FV A915-x (new variant FVAD 15-x can be used),
- Meteorological transducer FM A510.

Connecting cables must not be plugged together! If the intelligent extension cable ZA 9090-VKC is used, the device cannot operate in sleep mode.

Variants:

Order no.

Intelligent extension cable for ALMEMO® sensors, analog, D6, except for D7, except for thermocouple sensors*, for all ALMEMO® devices (V5, V6, V7).
5 meters long
10 meters long
2A9090VKC10
20 meters long
30 meters lo

ALMEMO[®] D7 extension cable, up to 100 meters in length and electrically isolated, for ALMEMO[®] V7 devices and ALMEMO[®] D7 sensors

Digital extension cable ZAD7 00-VK, up to 100 meters in length, for ALMEMO® D7 sensors



Technical data and functions

- ALMEMO[®] digital extension cable ZAD7 00-VK is used for ALMEMO[®] V7 devices and for ALMEMO[®] D7 sensors.
- Each such extension cable incorporates an ALMEMO[®] plug / coupling (each with integrated microcontroller); it should be connected between the ALMEMO[®] sensor plug and the ALMEMO[®] measuring instrument. Current consumption for this extension cable is approx. 2 mA.
- The digital measured values and the parameters saved in the ALMEMO[®] sensor plug are transferred in digital form via an RS485 link with CRC to the ALMEMO[®] measuring instrument, which then evaluates them.
- The ALMEMO® sensors can be freely interchanged. The digital extension cable has no effect on the measuring operation; this also applies to calibrated sensors with adjustment / multi-point adjustment.
- With digital extension cable ZAD7 00-VK device operation in sleep mode is possible; (sleep delay must be programmed in the sensor plug).

Please note:

Connecting cables must not be plugged together!

Variants:

Digital extension cable for ALMEMO® V7 devices and for ALMEMO® D7 sensors.

5 meters long 10 meters long 20 meters long 30 meters long 50 meters long 100 meters long

ALMEMO[®] D7 electrical isolation element ZAD7 00-GT



Technical data and functions

- Electrical isolation element ZAD7 00-GT is used to isolate the ALMEMO[®] V7 device and the ALMEMO[®] D7 sensor from one another. This also electrically isolates the ALMEMO[®] D7 sensor with respect to the other connected ALMEMO[®] sensors.
- The electrical isolation element is a short pluggable cable with ALMEMO[®] plug / coupling. The ALMEMO[®] coupling incorporates an integrated 12V DC/DC converter ensuring electrical isolation between the power supply to the ALMEMO[®] electronics and that to the connected sensor. The digital data link is electrically isolated via an optocoupler. The maximum insulation voltage is 50V (continuous).
- The electrical isolation element is plugged directly onto the ALMEMO® V7 device. Current consumption for this electrical isolation element is approx. 8 mA. It is also possible to use an ALMEMO® D7 extension cable between the electrical isolation

element and the ALMEMO® D7 sensor.

- As with the ALMEMO[®] D7 extension cable, the ALMEMO[®] sensors can be freely interchanged. The electrical isolation element has no effect on the measuring operation; this also applies to calibrated sensors with adjustment / multi-point adjustment.
- As with the ALMEMO® D7 extension cable, device operation in sleep mode is possible; (sleep delay must be programmed in the sensor plug).

Please note:

It is not permitted to connect several electrical isolation elements in series.

Variants:

Electrical isolation element for ALMEMO[®] V7 devices and for ALMEMO[®] D7 sensors Plug-in cable Length = 0.2 meters

.. .

Order no.

ZAD700VK05 ZAD700VK10 ZAD700VK20 ZAD700VK30 ZAD700VK50 ZAD700VK100

Order no.

ZAD700GT

Accessories for measuring instruments ALMEMO[®] 2450, 2490, 2590 and output interface ZA 8006 RTA

Manual Works	Rubber safety holster, green Rubber safety holster, gray including carry strap	Order no. ZB2490GS1 ZB2490GS2
	Vent plug with handle, to close unneeded ALMEMO [®] sockets, suitable for ALMEMO 2450, 2490, 2470, 2590 710, 1020, 1030, 1036, output interface RTA3/4), 2690, 202, 4 G R2400BAG
	Top hat rail mounting 1 battery compartment cap with top hat rail hol including top hat	ider fitted, ZB2490HS
	Magnetic fastening 2 pot magnets, including 2 screws (for battery compartment cap)	ZB2490MH

Batteries and Rechargeable Batteries



1.0

Rechargeable batteries

Types:Order no.AA battery, 1.5 VZB2000B1AA NiMH rechargeable battery, 1.2 V, 1900 mAh, coded
for charging in ALMEMO® unit
(e.g. ALMEMO® 2690-8)ZB2000A1NM

CHARGE CHARGE CHARGE CHARGE DC-A DC-A INPUT 12V DC AP CHARGE

Types

Order no.

Rechargeable battery, 9 ... 11 V, 1600 mAh, NiMH with intelligent high-speed charging housed in case 180 x 49 x 137 mm (LxWXH) (without plug connections) voltage output via 3-pin socket ZB5690AP

Connector mains unit, 100 to 240 VAC for charging the battery

ZB1212NA11

Connecting cable from battery to ALMEMO[®] device length = 1.5 meters, with ALMEMO[®] plug for ALMEMO[®] 2490, 2470, 2590, 2690, 202, 204 ZA1012AKA

With 3-pin bayonet coupling for ALMEMO [®] 5690, 8590, 8690, 809	ZB5090EKA
With hollow connector for ALMEMO [®] 2890	ZB2290EKA

Environmental conditions see page 01.04 onwards

Mains Adapter



ZB1000UA

DC Power Supply Cables



Supply cables for DC voltages

- Usage for car and electric fence batteries.
- For instruments that need to be supplied from the car battery.

Order no.

Switching power supply / connector variant 100 to 240 VAC with EU adapter (Types NA11 and NA12 with UL marking) Type NA12, output 12 V 1,5 A, with ALMEMO[®] plug, e.g. for ALMEMO[®] handsets 2490, 2470, 2590, 2690, 202, 204, ZA1312NA12 Type NA11, output 12 V 2,5 A, with ALMEMO[®] plug, e.g. ZA1312NA11 Type NA12, output 12 V 1,5 A, with 3-pin bayonet coupling, e.g. for ALMEMO® 809, 8590, 8690, 8036 ZB1212NA12 Type NA11, output 12 V 2,5 A, with 3-pin bayonet coupling, e.g. for ALMEMO[®] 5690, 500 ZB1212NA11 US adapter (for typs NA11 and NA12) **ZB1000PUS**

Type NA10, output 12 V 2 A, with hollow connector, e.g. for ALMEMO® 2890, 470 **ZB1112NA10**

Conversion connector for mains-powered devices Euro-plug to US standard (flat-pin) **ZB1000UA**

Environmental conditions see page 01.04 onwards

Variants

Adapter cable with

universal car connector

Order no.

ZA2690UK2

10 to 30 V DC, electrically isolated, with DIN hollow connector for ALMEMO® 2890-9, 6290-7B2

Output: 12V DC / 1 A (max.) **ZB2590UK** 10 to 30 V DC, electrically isolated, with ALMEMO® con-

nector for ALMEMO® 2490, 2590, 2690-8, 202, 204 Output: 12 V DC / 250 mA (max.) **ZA2690UK**

Output: 12 V DC / 1 A (max.)

10 to 30VDC, electr. isol., with bayonet coupling for ALMEMO® 8590, 8036, 809 Output: 12VDC/250mA (max.)

ZB3090UK 10 to 30VDC, electr. isol., with bayonet coupling, for ALMEMO® 5690-9, 8690, 500 output: 12V DC / 1.25A (max.) **ZB3090UK2**

ZB1000AKU

New ALMEMO[®] power supply plug, 9 to 12 VDC, not electr. isolated, with clamp connector for ALMEMO® DC socket on hand-held devices ALMEMO® 2490, 2590, 2690, 710, 202, 204 Programming 0.2 A ZA1312FS1 Programming 1 A ZA1312FS8

New: ALMEMO[®] power supply cable with USB plug. NOT galv.getr., 5 V DC via USB power bank or PC. USB plug with 1.5 m cable and ALMEMO[®] supply plug ZA 1312-FS8. For ALMEMO® devices (from model year 2014) 2490, 2470, 2590-2A/4AS, 2690, 202, 204 ZA1312U



Instrument Cases



ZB 2590 TK2



Types

ble insert)

Carry cases (approx. dimensions in cm)

e.g. for ALMEMO® 5690 measuring systems

6 cm (removable insert)

ments, see photograph)

sories, or laptop)

Carry case, large, aluminum profile frame / ABS (acrylonitrile butadiene styrene) - e.g. for ALMEMO[®] 710, 2690, 2890 data logger, Inside dimensions 48 x 35 (WxD) x 6 (H) +

Carry case, universal, high, aluminum profile frame / ABS,

Inside dimensions 48 x 25 (WxD) x 16 (H) + 10 cm (remova-

Instrument case for all ALMEMO[®] handheld devices, inside dimensions (WxDxH) 42 x 30 x 9 (divided into compart-

ZB 5600 TK3



ZB 2490 TK2



Rack case (approx. dimensions in cm) Rack case with carrying handle, for ALMEMO[®] MA5690xxBT8 and MA500xxBT8x measuring systems, in 19-inch sub-rack, 84 DU, height 5 HU Outside dimensions (WxDxH) 54 x 50 x 27, with integrated lockable rack draw, inside dimensions (WxDxH) 40 x 37 x 7 (for cables, acces-

ZB5090RC





ALMEMO[®] input connector also for existing sensors (see Chapter Input Connectors)

ALMEMO® output modules (analog, relay, trigger) (see Chapter Output Connectors)

ALMEMO[®] data connection, network technology, Bluetooth modules Wireless and modem transmission (see Chapter Network Technology).

Software for the presentation and evaluation of measuring data, including many notes, is described in Chapter Software.

Order no.

ZB2590TK2

ZB5600TK3

ZB2490TK2

infrared meas. Temperature technology

Content

Temperature Sensors and accuracy Types and Fields of Application	07.02	
Sheathed sensors Accessories for Sheathed sensors	07.06 07.09	
Low-cost universal sensors	07.10	
NiCr-Ni sensors in various designs Thermowires and compensation lines Connectors for thermocouples	07.11 07.18 07.20	
Pt100 temperature sensors for special applications Digital precision resistance sensor Pt100	07.21 07.22	
Pt100 sensors and NTC sensors in various designs Plug-in laboratory sensor Pt100 cable sensors	07.23 07.27 07.28	
Pt100 glass thermometer with immersion depths as per ASTM Insertable sensor	07.29 07.30	
Infrared measuring technology Emissivity values for different materials Digital infra-red sensor for measuring surface temperature Compact infra-red probe head AMiR FIA 844	07.33 07.36 07.37 07.39	_
Infra-red transmitter for measuring surface temperature Infrared Measuring Heads in Two-Wire Design AMiR 7838	07.41 07.43	





Selecting the right type of temperature sensor depends on your measuring task. For example, thermocouples, resistor-based sensors (Pt100 and Ntc) and pyrometers (infrared sensors) are available.

Rule of Thumb:

- Thermocouples are very fast and provide a large measuring range.
- Resistor-based sensors are more accurate but slower.
- Ntc sensors are very fast, accurate, but they have a limited measuring range.
- Infrared sensors do not contact the device under test and they have very small time constants, but they depend on the emission grade.
- The larger the measuring range, the more universal the possible range of applications.

Selection Criteria:

Select the temperature sensor that suits your measuring task according to the criteria below:

- Meas. range
- Accuracy
- Response time
- Stability
- Type of construction

Thermocouples

Thermocouples consist of two spotwelded wires of different metals or alloys. The thermoelectric effect at the contact surface is used to measure temperatures. A relatively small thermoelectric voltage is caused, which depends on the temperature difference between the measuring point and the connecting terminals.

Accuracy, Operating Temperatures:

The basic values for the thermoelectric voltages and for the permissible tolerances of thermocouples are specified in standard

DIN/IEC 584. Our thermocouple sensors are available in two tolerance classes as per DIN/IEC 584-2.

According to DIN/IEC 584-2, the thermocouple sensors are available in different accuracy classes.

Accuracy classes for the thermocouples type K or type N (extract)

class	range of validity	limiting deviation		
		(in each case the greater value applies)		
1 -	40 to 1000°C	± 1.5 K or ± 0.004 x t K		
2 -	40 to 1200°C	±2.5 K or ±0.0075 x t K		

The accuracy class is specified for every thermocouple sensor. The accuracy applies within the above specified range of validity. The operative range is specified for every sensor – depending on its construction. These values refer to the sensor tip. Additionally, the operative ranges of the connecting cable and the transition sleeve (or similar) have to be considered.

The sensor handles and cables are usually resistant to temperatures up to +80 °C. Heat-resistant cables are also available on

request. Various types of thermocouples are available; these can be distinguished in terms of their temperature range, sensitivity, and in particular their compatibility with the test substance. The most popular thermocouple is the NiCr-Ni (type K)

Connecting cable with thermal line (stranded wire) There is no adverse temperature effect at the juncture from measuring element to cable

With immediate effect, the sensor connecting cables for many sensor types will use a new thermal line (stranded wire, thermal line class 2) instead of the conventional compensation line. The transition from measuring element (sensor tip) to connecting cable (in the cable sleeve or in the handle) thus remains, even over a wide temperature span (up to 200 °C), unaffected by temperature error; the usual measuring errors caused by temperature differences at the juncture when using a conventional compensation line can thus with the new thermal line be avoided.

For just a few sensor types and extension cables a compensation line will continue to be used as previously. The compensation lines generally comply with Class 2 as per DIN 43722. For type K the operating temperature range of the compensation line is 0 to $150 \,^{\circ}$ C.

Resistor-Based Sensors (Pt100 Sensors)

When measuring the temperature the increase in resistance at increasing temperatures is utilised at the Pt100 sensors. The measuring resistor is fed with a constant current and the voltage drop at the resistor is measured as a function of the temperature. Due to the

small resistance variation (0.3 to $0.4\Omega/^{\circ}C$) the 4-conductor circuit should always be used to exclude any influences from the lead wires.

Accuracy, operating temperatures:

According to DIN/IEC 751, measuring resistors are used for the Pt100 sensors. Several accuracy classes are defined for the Pt100 sensor.

Accuracy classes of the Pt100 sensors (extract)					
class	range of validity		limiting deviation		
	wire-wound resistors	film resistor			
В	-196 to +600 °C	-50 to +500 °C	$\pm (0.3 + 0.005 \mid t \mid) \text{ K}$		
А	-100 to +450 °C	-30 to +300 °C	±(0.15 + 0.002 t) K		

The accuracy class is specified for every Pt100 sensor. Depending on the construction of the sensor, the higher

accuracies class A and1/5 DIN class B are available on request. The accuracy applies within in the above specified range of validity. Regarding the accuracy 1/5 DIN class B, the range of validity is sensor specific.

temperature	limiting deviations		
	DIN class B	DIN class A	1/5 DIN class B*
0°C	±0.3 K	±0.15 K	±0.06 K
100°C	±0.8 K	±0.35 K	
200°C	±1.3 K	±0.55 K	
300°C	±1.8 K	±0.75 K	
	Higher accuracies available at extra cost	order no. OPG2**	order no. OPG5**

Examples of Pt100 limiting deviations

*range of validity is sensor specific

** On request, depending on the construction of the sensor

The operative range is specified for every sensor – depending on its construction. These values refer to the sensor tip. Additionally, the operative ranges of the connecting cable and the transition sleeve (or similar) have to be considered. The sensor handles and cables are usually resistant to temperatures up to +80 °C. Heat-resistant cables are available on request.

Measuring ranges, resolution:

PT100 probes FP Axxx are by default

assigned measuring range PT100-1 (resolution 0.1 K). Measuring range PT100-2 (resolution 0.01K) can be programmed as alternative on the 1st channel or in addition on the 2nd channel.

Thermistors (NTC Sensors)

NTC sensors (thermistors) have a significantly higher resistance than Pt100 sensors. When measuring temperatures their negative temperature coefficient is utilised, i.e. the resistance is decreasing with increasing temperatures.

Accuracy, operating temperatures:

The accuracy of the sensor element is manufacturer-specific. The sensor element is installed in a sensor and provided with a connecting cable and an ALMEMO[®] plug. Processing, crossing points, terminal points and connecting cable influence the accuracy of the temperature sensor.

The following accuracy is specified for the NTC temperature sensor with a cable length of 2 meters:

Accuracy of the NTC sensors		
Range of validity	limiting deviation	
-20 to < 0 °C	±0.4 K	
0 to 70 °C	±0.2 K	
>70 to 100 °C	±0.6 K	
The accuracy applies within in the above specified range of validity.	These values refer to the sensor tip. Addi- tionally, the operative ranges of the con-	The handle of the sensor and the cable are heat resistant up to 80 °C.

The operative range is specified for every sensor – depending on its construction.

necting cable and the transition sleeve (or the like) have to be considered.

Types and Fields of Application

The construction variants of temperature sensors are as many and diverse as the measuring tasks.

- $T_{_{\rm max}}$ is the maximum operating temperature of the sensor tip.
- T_{90} is the time required by the sensor to reach 90% of the step response after a jump in temperature .
- The specified T_{00} times refer to measuring operations in a moving liquid.

The temperature sensors listed are also available, on request, with other lengths and diameters

Surface sensors with flat measuring tip	For measurements on good heat conductors, on even and plain surfaces.	
Surface sensor	For quick measurements, also on non-plain surfaces.	
with spring-type thermocouple band		
Immersion probes	For measurements in liquids, as well as powdery substances, air and gases.	
Sensors with heat-resistant measuring tip	For measurements at extremely high temperatures.	
Sensor with penetrating tip	For measurements in plastic and pasty substances.	
Sword probe	For measurements in paper, cardboard and textile stacks.	
Transducer with free sensor	For measurements in air and gases	

ALMEMO[®] temperature measurement

Every ALMEMO[®] sensor can be adjusted, i.e. correction values of the sensor can be stored in the connector.

Thus, the measuring accuracy can be significantly increased.

During DAkkS/DKD or factory

calibrations performed by the Ahlborn Company, the correction values are recorded, stored in the sensor plug and locked. The adjustment can be realized in 2 points (zero, gradient) or in over 30 points as multi-point adjustment. Thanks to this procedure the slightest deviations are archived on the calibrated temperature points.

The multi-point adjustment is described in detail in chapter "Input connectors" and in chapter "Calibration certificates".

Precise temperature measurement thanks to digital ALMEMO[®] sensors

Digital ALMEMO[®] sensors are used to measure temperatures with high precision. Any Pt100 and NTC sensor can become a digital sensor with the appropriate ALMEMO[®] measurement plug.

For Pt100 sensors, the digital ALMEMO[®] D7 measurement plug is used in combination with an ALMEMO[®] D7

measuring instrument. For NTC sensors, the digital ALMEMO[®] D6 measurement plug is used in combination with any current ALMEMO[®] measuring device.

The overall accuracy is determined only by the temperature sensor with the connected ALMEMO[®] measurement plug, independent from the ALMEMO[®] display device / data logger. The complete measuring chain, consisting of temperature sensor and the connected ALMEMO[®] measurement plug can be calibrated. An increased accuracy can be achieved by a multi-point adjustment of the sensor during the calibration process.

Temperature sensor Pt100 with digital ALMEMO[®] D7 measurement plug

High resolution 0.01 K within the complete measuring range up to 850°C. Linearization of the Pt100 characteristic with accurate calculation method. Increased accuracy for calibrated sensors thanks to multi-point adjustment of the Pt100 sensor.

The digital ALMEMO[®] D7 measurement plug works with an own, integrated A/D converter. The high resolution of 0.01 K can be achieved within the complete measuring range going up to 850°C. The linearization of the Pt100 characteristic is calculated accurately according to DIN IEC 751 (no approximation procedure). To designate a sensor it is possible to program comments with up to 20 characters in the ALMEMO[®] D7 measurement plug

For technical data regarding the ALMEMO[®] D7 measurement plug Pt100 ZPD700FS, see chapter "Input connectors".

Temperature sensor NTC with digital ALMENO[®] D6 measurement plug

High precision. High resolution 0.001K within the measuring range of -20 to +65°C. Linearization of the NTC characteristic according to Galway Steinhart with accurate calculation method. Increased accuracy thanks to multi-point adjustment of the NTC sensor during the calibration process.

The digital ALMEMO[®] D6 measurement plug works with an own, integrated A/D converter. The linearization of the NTC characteristic is calculated accurately with the Galway Steinhart coefficient (no approximation procedure). For the measuring range of -20 to $+65^{\circ}$ C, a high resolution of 0.001 K can be achieved. The high precision of the digital temperature sensor is independent from connected

extension cables.

For technical data regarding the ALMEMO[®] D6 measurement plug, see chapter "Input connectors".

If you do not find a suitable sensor in this catalogue, we can manufacture it according to your specifications (technical drawing or detailed specification) and supply you with a customised sensor!

Sheathed sensors

- 10/2021 We reserve the right to make technical changes.
- These reasonably priced sensors are for universal use (-200 to +1100 °C) and suitable for immersion measurements in liquids, air, and gases. The sheathed line, depending on diameter, can be bent within certain limits.
- Different connection variants :
- With cable and $ALMEMO^{\circledast}$ connector Order no. FxAxx,

with cable and free ends, Order no. Fx0xx.

- Connector options :
- With THERM circular connector : Option T9020RS, with miniature Thermo flat connector : Option OT9020FS.

Thermocouple sheathed sensors FTAxx and FTANxx

Accuracy:	FTAxx; NiCr-Ni thermocouple, type K, DIN class 1* FTANxx; NiCrSi-NiSi thermocouple, type N, DIN class 1*
Sensor tip, sheathed line :	diameter, length, operating temperature; see table; material Inconel 2.4816 Here the sensor tip and sheathed line are of the same diameter. These types are therefore also suitable for mounting with clamped screw connections.
Cable sleeve :	Brass, hexagonal, $L = 65$ mm, circumdiameter = 9 mm, operating temp40 to +160 °C
Standard cable :	1.5 meter FEP / silicone thermal line (stranded wire)* Operating temp50 to +200°C There is no adverse temperature effect at the juncture from measuring element to cable.
Cable options :	Compensation line, PVC / PVC, insulated, operating temperature –20 to +105 °C The compensation line is also available, on request, with FEP / FEP, insulated.
ALMEMO [®] connector	FTAxx NiCr-Ni ZA9020FS with resolution 0.1 K FTANxx NiCrSi-NiSi ZA9021FSN with resolution 0.1 K

Pt100 sheathed sensors FPAxx

Accuracy :	Pt100 film resistor, DIN class B*
Options :	DIN class A, 1/5 DIN class B
	Pt100 wire wound measuring resistor
Sensor tip :	diameter, length, operating temperature; see table; material stainless steel
Sheathed line :	diameter, length; see table; material stainless steel
	On certain types the sensor tip and sheathed line are of different diameter; (i.e. the sensor tip is thicker). These types are therefore not suitable for mounting with clamped screw
	connections. Types suitable for clamped screw connections are available on request.
Cable sleeve :	Brass, hexagonal, $L = 65$ mm, circumdiameter = 9 mm, operating temp40 to +160 °C
Standard cable :	1.5 meters line, FEP / silicone, insulated, operating temperature -50 to $+200$ °C
Cable options :	Line, PVC / PVC, insulated, operating temperature -20 to +105 °C
	The line is also available, on request, with FEP / FEP, insulated.
ALMEMO [®] connector	Pt100, ZA9030FS1, with resolution 0.1 K
	Option: Pt100 ZA9030FS2 with resolution 0.01 K (standard with 1/5 DIN class B)

NTC sheathed sensors FNAxx

Accuracy :	NTC type N (see 07.04)
Sensor tip :	diameter, length, operating temperature; see table; material stainless steel
Sheathed line :	diameter, length; see table; material stainless steel
	On certain types the sensor tip and sheathed line are of different diameter; (i.e. the sensor tip
	is thicker). These types are therefore not suitable for mounting with clamped screw connections. Types suitable for clamped screw connections are available on request
~ 11 1	connections. Types suitable for champed serve connections are available on request.
Cable sleeve :	Brass, hexagonal, $L = 65$ mm, circumdiameter = 9 mm, operating temp. -40 to $+160$ °C
Standard cable :	1.5 meters line, PVC / PVC, insulated, operating temperature -20 to +105 °C
Cable options :	Line, FEP / silicone, insulated, operating temperature -50 to $+200$ °C
	The line is also available, on request, with FEP / FEP, insulated.
ALMEMO [®] connector	NTC, ZA9040FS, with resolution 0.01 K.

* Range of validity see page 07.03

** No temperature influence at the transition from the measuring element to the cable (see page 07.03)

DAkkS or factory calibration KT90xx temperature for sensor or measuring chain (sensor + device) (see chapter Calibration certificates) DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Sheathed sensors



Sensor with :

Sensor tip, dimensions d1, sheathed line, dimensions d2, overall length (including sensor tip) L, Cable sleeve, dimensions length = 65 mm, circumdiameter = 9 mm, Cable

Thermocouple sheathed sensors NiCr-Ni, type K Typical Application: universal, in range -40 ° C to 900 ° C

Diameter d1=d2	Operat	ting temperature Sensor tip	Length L	Order no
0.5 mm	-2	200900°C	50 mm	FTA05L0050
0.5 mm	-1	200900°C	100 mm	FTA05L0100
0.5 mm	-1	200900°C	250 mm	FTA05L0250
0.5 mm		200900°C	500 mm	FTA05L0500
0.5 mm	-1	200900°C	1000 mm	FTA05L1000
1.5 mm	-2	2001100°C	100 mm	FTA15L0100
1.5 mm	-2	2001100°C	250 mm	FTA15L0250
1.5 mm	-2	2001100°C	500 mm	FTA15L0500
1.5 mm	-2	2001100°C	1000 mm	FTA15L1000
3.0 mm	-2	2001100°C	100 mm	FTA30L0100
3.0 mm	-2	2001100°C	250 mm	FTA30L0250
3.0 mm	-2001100°C		500 mm	FTA30L0500
3.0 mm	-2	2001100°C	1000 mm	FTA30L1000
Connection cal	ole	Operative range	Length	Order no
FEP/silicone		-50200°C	1.5 m	default
Thermal line				
(stranded wire)				
			5 m	OTK01L0050
PVC/PVC -20105°C		-20105°C	1.5 m	OTK02L0015
Compensation line				
			5 m	OTK02L0050

Thermocouple sheathed sensors NiCrSi-NiSi, type N Typical application: in the range -200 ° C to 1150 ° C, long-term stability at high temperatures

Diameter d1=d2	Operating temperature Sensor tip	Length L	Order no
1.5 mm	-2001150°C	500 mm	FTAN15L0500
1.5 mm	-2001150°C	750 mm	FTAN15L0750
1.5 mm	-2001150°C	1000 mm	FTAN15L1000
3.0 mm	-2001150°C	500 mm	FTAN30L0500
3.0 mm	-2001150°C	750 mm	FTAN30L0750
3.0 mm	-2001150°C	1000 mm	FTAN30L1000
6.0 mm	-2001150°C	500 mm	FTAN60L0500
6.0 mm	-2001150°C	750 mm	FTAN60L0750
6.0 mm	-2001150°C	1000 mm	FTAN60L1000
		1	
Connection cs	able Onerative range	Length	Order no

Connection cable	Operative range	Length	Order no
FEP/silicone Thermal line (stranded wire)	-50200°C	1.5 m	default
		5 m	OTNK01L0050

DAkkS or factory calibration KT90xx temperature for sensor or measuring chain (sensor + device) (see chapter Calibration certificates) DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Resistor-based sensors Pt100 4L

Typical Application: universal, in range -40°C to 400°C

Diameter d1 Sensor tip	Diameter d2, Sheathed line	Operating temp. Sensor tip	Length L	Order no.
1.5 mm	1.5 mm**	-40400°C	100 mm	FPA15L0100
1.5 mm	1.5 mm**	-40400°C	250 mm	FPA15L0250
1.5 mm	1.5 mm**	-40400°C	500 mm	FPA15L0500
2.2 mm*	2.0 mm	-40400°C	100 mm	FPA22L0100
2.2 mm*	2.0 mm	-40400°C	250 mm	FPA22L0250
2.2 mm*	2.0 mm	-40400°C	500 mm	FPA22L0500
3.2 mm*	2.8 mm	-40400°C	100 mm	FPA32L0100
3.2 mm*	2.8 mm	-40400°C	250 mm	FPA32L0250
3.2 mm*	2.8 mm	-40400°C	500 mm	FPA32L0500

* This sensor type (reinforced tip) is not suitable for clamped screw connections. Suitable types FPA20Lx or FPA30Lx with same end-to-end diameter are available on request.
 ** Too strong bending of / kinking of the sheathed line should be avoided.

Options	Order no.
Accuracy class B Accuracy class A Accuracy class 1/5 DIN Class B* Wire-wound measuring resistor operating range -200 450 ° C	default OPG2 OPG5 OPM1
* at 0 °C	or hir

Connection cable	Operative range	Length	Order no.
FEP/silicone	-50200°C	1.5 m 5 m	default OPK01L0050
PVC/PVC	-20105°C	1.5 m 5 m	OPK02L0015 OPK02L0050

Resistor-based sensors NTC Typical Application: universal, in range 0°C to typ. 70°C

Diameter d1 Sensor tip	Diameter d2, Sheathed line	Operating temp. Sensor tip	Length L	Order no.
2.0 mm	2.0 mm	-20100°C	100 mm	FNA20L0100
2.0 mm	2.0 mm	-20100°C	250 mm	FNA20L0250
2.0 mm	2.0 mm	-20100°C	500 mm	FNA20L0500
3.2 mm*	2.8 mm	-20100°C	100 mm	FNA32L0100
3.2 mm*	2.8 mm	-20100°C	250 mm	FNA32L0250
3.2 mm*	2.8 mm	-20100°C	500 mm	FNA32L0500

This sensor type (reinforced tip) is not suitable for clamped screw connections. Suitable types with same end-to-end diameter are available on request.

Connection cable	Operative range	Length	Order no.
PVC/PVC	-20105°C	1.5 m 5 m	default OPK02L0050

DAkkS or factory calibration KT90xx temperature for sensor or measuring chain (sensor + device) (see chapter Calibration certificates) DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Handle for sensors with hexagonal cable sleeve



Clamp srew connection ZT943xKV



Operative range For sheath elements

Option: Notched steel ring (once fitted, cannot be removed), $T_{max} = 800 \text{ °C}$ For ZT9431KV Order no. OT9431ST For ZT9432KV Order no. OT9432ST

Variants (with PTFE clamping ring)	Order no.
for types FTA15Lxxxx, FPA16Lxxxx	ZT9431KV
for types	
FTA30Lxxxx, FPA30Lxxxx and FNA30Lxxxx	ZT9432KV

Technical data

Operating temperature	up to maximum 250 °C with option up to 800 °C
Thread	M8x1, 14 AF

Heat-conducting paste ZB9000WP

For surface measurement.	operative range	-30 to +200 °C.	heat-conducting paste.	tube, 12 ml
	operative range	2010 200 29	near concorning public,	

Order no. ZB9000WP

NiCr-Ni-sensor FTA 15 P1

	Accuracy: Measuring tip: T ₉₀ : * Cable:	NiCr-Ni class 1* Operative range -200+1100 °C 200x1.5 mm, sheathed line, Inconel 1.5 s 1.5 m FEP/silicone thermal line** with AL MEMO [®] connector
For immersion measurement	L = 200 mm (No variants ava: Option: Handle r	Order no. FTA15P1 ilable) nounted Order no. OFH1
Pt100-sensor FPA 32 P1		
	Accuracy: Measuring tip:	Pt100 film resistor, class B* Operative range -40+400 °C 200 x 2.8 Measuring tip reinforced 3.2 mm, sheathed line stainless steel
	T ₉₀ : * Cable:	10 s 1.5 m PVC / PVC with ALMEMO [®] connector
For immersion measurement	L = 200 mm (No variants ava: Option: Handle r	Order no. FPA32P1 ilable) nounted Order no. OFH1
NTC-sensor FNA 305		
ELANS LANNE CONTROL IN THE INPORTANT AT LAND LAND AND A LAND A LA	Accuracy: Measuring tip	NTC, see page 07.04 Operative range -10 to +60 °C (non-condensing) Protective tube in stainless steel Diameter = 3.0mm, length = 50 mm mounted directly on ALMEMO [®] connector
For Indoor air measurements	L = 50 mm (No variants av	o s Order no. FNA305 ailable)

* Range of validity see page 07.03
** There is no adverse temperature effect at the juncture from measuring element to cable. see page 07.03

DAkkS or factory calibration KT90xx temperature for sensor or measuring chain (sensor + device) (see chapter Calibration certificates) DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

NiCr-Ni sensor with handle FTA 120x



Accuracy: Measuring tip: T ₉₀ : * Handle: * Cable:	NiCr-Ni class 1* Operative range -200+400 °C Silver rivet, level, spring-loaded, not electrically isolated 3 s 138 mm 1.5 m PVC
L = 30 mm	Order no. FTA1201
L = 150 mm	Order no. FTA1202

For surface measurement and immersion measurement

NiCr-Ni sensor with handle FTA 122 LxxxxH



For surface measurement and immersion measurement

Accuracy:	NiCr-Ni class 1*
Measuring tip:	Operative range -200+400 °C
	Silver rivet, level, not electr. isolated
T ₉₀ : *	3 s
Handle: *	127 mm
Cable:	1.5 m FEP/silicone thermal line**
L = 50 mm	Order no. FTA122L0050H
L = 100 mm	Order no. FTA122L0100H
L = 200 mm	Order no. FTA122L0200H

NiCr-Ni sensor with handle FTA 121 LxxxxH



For surface measurement and immersion measurement

Accuracy: Measuring tip:	NiCr-Ni class 1* Operative range -200+400 °C
	Silver rivet, level, angled, not electrically isolated
T ₀₀ : *	3 s
Handle: *	127 mm
Cable:	1.5 m FEP/silicone thermal line**
L = approx. 50	mm Order no. FTA121L0050H
L = approx 200	mm Order no. FTA121L0200H

NiCr-Ni sensor with handle FTA 150 LxxxxH



* Range of validity see page 07.03

** There is no adverse temperature effect at the juncture from measuring element to cable. see page 07.03

10/2021 • We reserve the right to make technical changes.

DAkkS or factory calibration KT90xx temperature for sensor or measuring chain (sensor + device) (see chapter Calibration certificates) DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

NiCr-Ni sensor FTA 109 P NiCr-Ni class 2* Accuracy: Measuring tip: Operative range -50...+500 °C Thermal ribbon, not electr. isolated Measuring head approx. 15 mm diameter T₉₀: * 1 s 1.5 m FEP/silicone thermal line** Cable: For surface measurement L = approx. 180 mm Order no. FTA109P Sensor with handle Order no. FTA109PH (No variants available) NiCr-Ni sensor FTA 104 P Accuracy: NiCr-Ni class 2* Measuring tip: Operative range -50...+500 °C Thermal ribbon, not electr. isolated Measuring head approx. 15 mm diameter T₉₀: * Cable: 1 s1.5 m FEP/silicone thermal line** L = approx. 180 mm,For surface measurement with 90° angle, approx. 50 mm Order no. FTA104P Sensor with handle Order no. FTA104PH (No variants available) NiCr-Ni sensor with handle FTA 153 LxxxxH NiCr-Ni class 2* Accuracy: Measuring tip: Operative range -200...+250 °C Thermal ribbon, crossed, not electrically isolated T₉₀: * 1.5 s Handle: * 127 mm 1.5 m PVC Cable: L = 100 mmOrder no. FTA153L0100H For surface measurement NiCr-Ni sensor with handle FTA 1535 LxxxxH NiCr-Ni class 2* Accuracy: Measuring tip: Operative range -200...+250 °C 100 Thermal ribbon, not electr. isolated T₉₀: * 25 Handle: * 127 mm Cable: 1.5 m PVC L = 100 mmOrder no. FTA1535L0100H For surface measurement

* Range of validity see page 07.03

** There is no adverse temperature effect at the juncture from measuring element to cable. see page 07.03

DAkkS or factory calibration KT90xx temperature for sensor or measuring chain (sensor + device) (see chapter Calibration certificates) DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

NiCr-Ni sensor with handle FTA 420 LxxxxH



For surface measurement on level surfaces

NiCr-Ni sensor FTA 025 P



Magnet sensor for surface measurement



Magnet sensor with Velcro fastener e.g. for pipework

Accuracy: Measuring tip:	NiCr-Ni class 1* Operative range -50+500 °C Silver disc, spring-loaded, not electrically isolated
T ₉₀ : *	2 s
Handle: *	12/ mm
Cable:	1.5 m FEP/silicone thermal line**
L = 150 mm	Order no. FTA420L0150H

Accuracy:	NiCr-Ni class 2*
Measuring tip:	Operative range -50+300 °C
0 1	Thermal ribbon, not electr. isolated
	Fastened by magnet
T ₉₀ : *	1.5 s
Cable:	2 m silicone thermal line**

Magnet sensor (No variants available) Order no. FTA025P

Klettband: approx. 400 mm, for pipe diameter appr. 10 to 75 mm Operating range: -10 ... +110 °C mounted on sensor tip

Magnet sensor, including Velcro fastener Order no. FTA025PKB

10/2021 • We reserve the right to make technical changes.

* Range of validity see page 07.03

** There is no adverse temperature effect at the juncture from measuring element to cable. see page 07.03

DAkkS or factory calibration KT90xx temperature for sensor or measuring chain (sensor + device) (see chapter Calibration certificates) DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

NiCr-Ni sensor FTA 131



Magnet sensor For surface measurement

NiCr-Ni sensor FTA 026 P



For surface measurement

Accuracy:	NiCr-Ni class 1*
Measuring tip:	Operative range -50+250 °C
	Thermal ribbon,
	not electrically isolated
T ₀₀ : *	1.5 s
Cable:	0.9 m line, PTFE compensating cable

NiCr-Ni class 2*

3 m FEP/silicone

Order no. FTA131

Silver rivet, level, spring-loaded,

not electrically isolated Fastened by magnet

Measuring tip: Operative range -50...+100 °C

3 s

Accuracy:

T₉₀: *

Cable:

Magnet sensor

Ribbon sensor **Order no. FTA026P** (No variants available)

NiCr-Ni sensor FTA 8068



For surface measurement on pipes

DAkkS or factory calibration KT90xx temperature for sensor or measuring chain (sensor + device) (see chapter Calibration certificates) DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

^{*} Range of validity see page 07.03

NiCr-Ni film thermocouple FTA 683



For surface measurement

Accuracy: NiCr-Ni class 2* Measuring tip: Operative range -100 to +200°C Folie, Insulation Kresol T₉₀: * 2 s

with permanently connected FEP / silicone thermal line (stranded wire)**

-50 to +200°C, 2 meters, with ALMEMO® connector Order no. FTA683 Measuring element without cable, free ends (for your own sensors) Order no. FT0683

NiCr-Ni class 2*

3 s

Operative range -200...+205 °C

1.5 m

Thermowire, welded, not electrically isolated

NiCr-Ni sensor FTA 390 x



For surface measurement

Operative range -25...+350°C (short time up to 400 °C) Insulation FEP,

* Range of validity see page 07.03

** There is no adverse temperature effect at the juncture from measuring element to cable. see page 07.03

Digital infra-red sensor for measuring surface temperature FIAD43



Operative range: -40...600 °C, Miniature probe head, with cable and ALMEMO® D6 plug and 1 mounting nut

Cable length = 1 mCable length = 3 mFor technical data, see page 07.34 Order no. FIAD4332 Order no. FIAD4332L3

Order no. FTA3900

Order no. FTA39010

DAkkS or factory calibration KI9xxx temperature for digital sensor (see chapter Calibration certificates)

Compact infra-red probe head FIA844



Operative range: -20...500 °C, Probe head, with cable and ALMEMO® plug and 2 mounting nuts

Cable length = 1 mCable length = 3 mFor technical data, see page 07.36 Order no. FIA844 Order no. FIA844L3

Factory calibration KI9xxx temperature for sensor (see chapter Calibration certificates)

DAkkS or factory calibration KT90xx temperature for sensor or measuring chain (sensor + device) (see chapter Calibration certificates) DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

NiCr-Ni sensor with handle FTA 05 L0050H



For immersion measurement

Accuracy: Measuring tip:	NiCr-Ni class 1* Operative range -200+500 °C Sheathed line, Inconel
T ₉₀ : * Handle: * Cable:	0.8 s 127 mm 1.5 m FEP/silicone thermal line**
L = 50 mm	Order no. FTA05L0050H

NiCr-Ni sensor with handle FTA 125 LxxxxH



NiCr-Ni sensor with handle FTA 126 LxxxxH



NiCr-Ni sensor with handle FTA 1261 LxxxxH



Accuracy: Measuring tip:	NiCr-Ni class 1* Operative range -200+500 °C Sheathed line Inconel
T ₉₀ : *	3 s
Handle: *	127 mm
Cable:	1.5 m FEP/silicone thermal line**
L = 150 mm	Order no. FTA1261L0150H
L = 300 mm	Order no. FTA1261L0300H

For immersion measurement in plastic and pasty substances, e.g. bitumen

* Range of validity see page 07.03

** There is no adverse temperature effect at the juncture from measuring element to cable. see page 07.03

DAkkS or factory calibration KT90xx temperature for sensor or measuring chain (sensor + device) (see chapter Calibration certificates) DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

NiCr-Ni sensor with handle FTA 123 LxxxxH



Measuring point

For immersion measurement in plastic and pasty substances

Accuracy:	NiCr-Ni class 1*
Measuring tip:	Operative range -200+300 °C
	Penetrating tip
T ₉₀ : *	3 s
Handle: *	127 mm
Cable:	1.5 m FEP/silicone thermal line**
L = 50 mm	Order no. FTA123L0050H
L = 100 mm	Order no. FTA123L0100H

NiCr-Ni sensor with handle FTA 1231 LxxxxH



For immersion measurement in plastic and pasty substances

Accuracy:	NiCr-Ni class 1*
Measuring tip:	Operative range -200+400 °C
	Penetrating tip, cone
	stainless steel 1.4541
T ₉₀ : *	6 s
Handle: *	127 mm
Cable:	1.5 m FEP/silicone thermal line**
L = 250 mm	Order no. FTA1231L0250H

* Range of validity see page 07.03

** There is no adverse temperature effect at the juncture from measuring element to cable. see page 07.03

NiCr-Ni thermowire T 190-0

NiCr-Ni thermowire T 190-1	Accuracy: NiCr-Ni class 2* Insulation : Glass fiber (wires and sheath) Operating temp.: -25°C to +350°C (short time up to 400 °C) Wire diameter: 0.5 mm External diameter: approx. 1.3 x 2.1 mm NiCr-Ni thermowire per meter with glass fiber covering Order no. LT01900 NiCr-Ni thermowire sensor, welded tip, with ALMEMO [®] connector 1.5m long Order no. FTA3900 ALMEMO [®] connector 5m long Order no. FTA3900L05
NiCr-Ni thermowire T 190-2	Accuracy: NiCr-Ni class 2* Insulation : Glass fiber (wires and sheath) Operating temp.: -25°C to +350°C (short time up to 400 °C) Wire diameter: 0.2 mm External diameter: approx. 0.6 x 1.0 mm NiCr-Ni thermowire per meter with glass fiber covering Order no. LT01901 NiCr-Ni thermowire sensor, welded tip, with ALMEMO [®] connector 1.5 m long Order no. FTA3901 ALMEMO [®] connector 5m long Order no. FTA3901L05
	Accuracy:NiCr-Ni class 2*Insulation :PVC (wires and sheath)Operating temp.:-10°C to +105°CWire diameter:0.5 mmExternal diameter:approx. 2.2 x 3.4 mmNiCr-Ni thermowire per meterwith PVC insulationOrder no. LT01902NiCr-Ni thermowire sensor, welded tip, withALMEMO® connector 1.5 m longOrder no. FTA3902ALMEMO® connector 5 m longOrder no. FTA3902L05
NiCr-Ni thermowire T 190-3	
	Accuracy:NiCr-Ni class 2*Insulation :Silicone (wires and sheath)Operating temp.:-45°C to +200°CWire diameter:0.5 mmExternal diameter:approx. 4 mmNiCr-Ni thermowire per meter with silicone insulationOrder no. LT01903NiCr-Ni thermowire sensor, welded tip, with ALMEMO® connector 1.5 m long ALMEMO® connector 5 m longOrder no. FTA3903

* Range of validity see page 07.03

DAkkS or factory calibration KT90xx temperature for sensor or measuring chain (sensor + device) (see chapter Calibration certificates) DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.
	Accuracy:NiCr-Ni class 2*Insulation :FEP (Wires and sheath)Operating temp.:-200°C to +205°CWire diameter:0.5 mmExternal diameter:approx. 1.5 x 2.5 mm
	NiCr-Ni thermowire per meter with FEP insulationOrder no. LT019010NiCr-Ni thermowire sensor, welded tip, with ALMEMO® connector 1.5m longOrder no. FTA39010 Order no. FTA39010L05
NiCr-Ni thermowire T 190-11	
	Accuracy:NiCr-Ni class 2*Insulation :FEP (Wires and sheath)Operating temp.:-200°C to +205°CWire diameter:0.2 mmExternal diameter:approx. 1.3 x 2.0 mm
	NiCr-Ni thermowire per meter with FEP insulationOrder no. LT019011NiCr-Ni thermowire sensor, welded tip, with ALMEMO [®] connector 1.5m long ALMEMO [®] connector 5m longOrder no. FTA39011 Order no. FTA39011L05
NiCr-Ni thermowire T 190-7	
	Accuracy:NiCr-Ni class 2*Insulation :Ceramic fiber (Wires and sheath)Operating temp.:-40°C to +1200°CWire diameter:0.8 mmExternal diameter:approx. 3 x 4 mm
Nur für trockene, nicht agressive Umgebung!	NiCr-Ni thermowire per meter with ceramic fiber insulationOrder no. LT01907NiCr-Ni thermowire sensor, welded tip, with ALMEMO [®] connector 1.5m long ALMEMO [®] connector 5m longOrder no. FTA3907 Order no. FTA3907L05
NiCr-Ni compensation line T 191-1	
	compensation line:NiCr-NiInsulation :PVC (Wires and sheath)Operating temp.: -10° C to $+105^{\circ}$ CWire diameter:0.5 mmExternal diameter:approx. 3.6 mm
Other types are available on request. LT01912 Insulation Silicone/silicone/glass filament, up to 200°C LT01913 Insulation PVC / screening film / PVC, up to 105°C	NiCr-Ni bunched conductor with PVC insulation, for each meter Order no. LT01911
NiCr-Ni thermal line (Litze) T 191-6	
	Thermal line (stranded wire): NiCr-Ni*Insulation:Wires : FEP, sheath : siliconeOperating temp.:-50+200°CWire diameter:0.7 mmExternal diameter:approx. 3.8 mm
	NiCr-Ni thermal line (stranded wire) with FEP / silicone insulation, per meter Order no. LT01916
 * Range of validity see page 07.03 ** There is no adverse temperature effect at the juncture from measuring 	element to cable. see page 07.03

10/2021 • We reserve the right to make technical changes.

ALMEMO® connector for thermocouples (see Chapter Input connectors)



For Types K, N, L, J, T (no thermo-electric transition / with thermal material) NiCr-Ni (K) Order no. ZA9020FS NiCroSil-NiSil (N) Order no. ZA9021FSN Order no. ZA9021FSJ Fe-CuNi (J) Cu-CuNi(T) Order no. ZA9021FST For Types U, S, R, B, AuFe-Cr Cu-CuNi (U) Order no. ZA9000FSU PtRh10-Pt (S) Order no. ZA9000FSS PtRh13-Pt (R) Order no. ZA9000FSR PtRh30-PtRh6 (B) Order no. ZA9000FSB Order no. ZA9000FSA AuFe-Cr (A)

ALMEMO® adapter plug with miniature flat socket



For Types K, J, T, S NiCr-Ni (K) Fe-CuNi (J) Cu-CuNi (T) PtRh-Pt (S)

Order no. ZKA029RA Order no. ZJA029RA Order no. ZTA029RA Order no. ZSA029RA

Miniature flat connectors for thermocouples types K, J, T, S, E



- Connectors with thermo contacts for avoiding voltage corruption at thermocouple junctions.
- For ambient temperatures -183 to +200 °C.
- Locking plate for complete coupling.

Examples for NiCr-Ni (K):

NiCr-Ni flat socket	Order no. ZK9029FB
NiCr-Ni flat connector	Order no. ZK9029FS
Locking plate (10 pieces)	Order no. ZB9029VP
NiCr-Ni single built-in socket	Order no. ZK9029FE
1-row panel with NiCr-Ni socket	Order no. ZK9029FB1
6-row panel with NiCr-Ni socket	Order no. ZK9029FB6

Order numbers for the above examples are compiled from the following coding elements : Z①9029F②③. The coding elements can be taken from the table below.

The coding elements can be taken from the table below.

Туре ①	Color (IEC 584)	Variant 2	Panel ③	Panel dimensions
NiCr-Ni (K)	green	Male connector $=$ S	1-er (1-rhg)	38 x 38 x 2.5 mm
Fe-CuNi (J)	black	Female connector = B	6-er (1-rhg)	113 x 38 x 2.5 mm
Cu-CuNi (T)	brown		12-er (1-rhg)	203 x 38 x 2.5 mm
NiCr-CuNi (E)	lilac		24-er (2-rhg)	203 x 76 x 2.5 mm
PtRh-Pt (S)	orange			mounting depth: 25.4 mm

DAkkS or factory calibration KT90xx temperature for sensor or measuring chain (sensor + device) (see chapter Calibration certificates) DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Ordering:

Pt100 temperature sensors for special applications in humid conditions up to 150 / 250 °C

High-grade Pt100 resistance sensor For measuring operations in very humid atmospheric conditions Operative over a wide range of temperatures

Pt100 temperature sensors for applications in laboratories and medical engineering



Especially suitable for measuring temperatures in autoclaves, sterilizing units,, high-temperature steam applications, vacuum applications, and freeze drying units

Variants

Pt100 sensor, cable length = 5 m, ALMEMO[®] plug

Pt100 temperature sensors for industrial applications in air-conditioning / heat cabinets

Especially suitable for measuring temperatures in air-conditioning / heat cabinets with high atmospheric humidity Operative over a wide range of temperatures

Variants

Pt100 sensor, cable length = 5 m, ALMEMO[®] plug Pt100 sensor, cable length = 10 m, ALMEMO[®] plug **Technical data** Accuracy: Protective tube

Operative range Cable Working pressure Protective class ALMEMO[®] plug Pt100 film resistor, class A* Stainless steel, diameter 3 mm, length 20 mm -30 to +150 °C PFA, length 5 m maximum 3.0 bar IP69K Pt100 with resolution 0.01 K.

Order no. FPA30K20L0020

Technical data Accuracy: Protective tube

Operative range Cable Protective class ALMEMO[®] plug Pt100 film resistor, class B* Stainless steel, diameter 4 mm, length 50 mm -100 to +250 °C PFA IP68 Pt100 with resolution 0.01 K.

Order no. FPA40ST0050S01KL0050 Order no. FPA40ST0050S01KL0100



Digital Pt100 temperature sensor with ALMEMO[®] D7 connector

- The digital ALMEMO[®] D7 measuring plug works with its own built-in AD converter. The linearization of the Pt100 characteristic curve is calculated according to DIN IEC 751 (no approximation method).
- The overall accuracy of the measurement is independent of the ALMEMO[®] V7 display unit/data logger. The complete measuring chain, consisting of the Pt100 sensor and the connected ALMEMO[®] D7 measuring plug,

Variants

Digital Pt100 sensor, cable length = 5 m, with ALMEMO[®] D7 connector Digital double Pt100 sensor: 2 Digital Pt100 sensors, cable length 5 m each, mounted on 1 ALMEMO[®] D7 double connector

calibration by a multi-point adjustment of the temperature sensor.For all ALMEMO[®] V7 measuring instruments / data loggers

can be calibrated. Increased accuracy is achieved during

Technical data for the sensor: see above **Technical data for the ALMEMO® D7 measuring plug:** see chapter 2

> Order no. FPD740ST0050S01KL0050 Order no. FPD740ST0050S21KL0050

Accessories:

PTFE tube (high emissivity), open on both sides, length approx. 70 mm, for probe diameter 4 mm. Ord

DAkkS or factory calibration KT90xx temperature for sensor or measuring chain (sensor + device) (see chapter Calibration certificates) DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.



Order no.

ZB9000TK1

Digital precision resistance sensor Pt100 up to 400 °C with resolution of 0.001 K as reference sensor, with ALMEMO[®] D7 connector for ALMEMO[®] V7 measuring devices / data logger



Digital precision resistance sensor Pt100 FPD723L0250A3D For immersion measurements in air, gases and liquids

Technical data and functions

Digital precision resistance sensor with highest accuracy and linearity for temperature measurements in a wide temperature range.

Highest resolution 0.001 K over the entire measuring range.

Application as reference probe for comparison measurements in research, development, quality assurance and production processes.

For all ALMEMO[®] V7 measuring instruments/data loggers, including ALMEMO[®] 710, 809, 500.

The digital ALMEMO[®] D7 measuring plug operates with its own built-in AD converter. The linearization of the Pt100 characteristic is calculated according to DIN IEC 751 (no approximation method).

The overall accuracy of the measurement is independent of the ALMEMO[®] V7 display unit/data logger. The complete measuring chain, consisting of the Pt100 - sensor and the connected ALMEMO[®] D7 measuring plug, can be calibrated.

Highest accuracy is achieved during calibration by a multi-point adjustment of the temperature sensor.

The digital sensor is supplied with a DAkkS calibration certificate incl. multi-point adjustment.

Technical data

Measuring element:	Pt100 wire wound	AD converter:	Delta-Sigma
Class:	1/10 B (DIN EN 60751) at 0°C	Conversion time	3.4 seconds
Measuring tip:	Application range: -50°C+400°C	Measuring current:	approx. 1 mA
response time T90:	5 s	Linearization:	Calculation method
Nominal length:	250 mm		(no approximation method)
Sensor tube:	stainless steel, diameter 3 mm	Accuracy:	± 0.015 K ± 2 digits
Connection cable:	2 m FEP/silicone	Nominal temperature:	$22^{\circ}C + 2K$
ALMEMO® D7 measuring connector		Nommai temperature.	$22 \text{ C} \pm 2 \text{ K}$
		Temperature drift:	0.003 %/K (30ppm)
Measuring range:	see sensor range	Supply voltage:	starting at 6 V from ALMEMO [®] device
Resolution:	0.001 K	Current consumption:	approx. 9 mA

Accessory

Aluminum profile case for 1 probe (up to 500 mm length)

Standard deliveryOrder no.Digital precision resistance sensor Pt100 as reference sensor, with cable and ALMEMO® D7 connector.FPD723L0250A3DIncl. DAkkS calibration certificate (2 temperature points at 0°C and 100°C incl. multi-point adjustment).FPD723L0250A3D

DAkkS or factory calibration KT90xx temperature for sensor or measuring chain (sensor + device) (see chapter Calibration certificates) DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Pt100 sensor with handle FPA 106 LxxxxH



L = 100 mm	Order no. FPA106L0100H
Cable:	1.5 m FEP/silicone
Handle: *	127 mm
T ₉₀ : *	8 s
wiedsuning up.	Sheath element, stainless steel
Measuring tin	Operative range $-40 + 400 \circ C$
Accuracy:	Pt100 film resistor, class B*

For immersion measurement

Pt100 sensor with handle FPA 123 LxxxxH



For immersion measurement in plastic and pasty substances

Measuring tip:	Operative range -40+400 °C Penetrating tip
T ₉₀ : *	8 s
Handle: *	127 mm
Cable:	1.5 m FEP/silicone
L = 100 mm	Order no. FPA123L0100H

Pt100 sensor with handle FPA 124 LxxxxH



For surface measurement and immersion measurement

Accuracy: Measuring tip:	Pt100 film resistor, class B* Operative range -40+300 °C Silver rivet, level
T ₉₀ : *	10 s
Handle: *	127 mm
Cable:	1.5 m FEP/silicone

L = 100 mmOrder no. FPA124L0100H

10/2021 • We reserve the right to make technical changes.

* Range of validity see page 07.03

DAkkS or factory calibration KT90xx temperature for sensor or measuring chain (sensor + device) (see chapter Calibration certificates) DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

NTC sensor with handle FNA 106 LxxxxH



L = 100 mm	Order no. FNA106L0100H
Cable:	1.5 m PVC
Handle: *	127 mm
T ₀₀ : *	8 s
	Sheath element, stainless steel
Measuring tip:	Operative range -20+100 °C
Accuracy:	NTC, see page 07.04

For immersion measurement

NTC sensor with handle FNA 123 LxxxxH



For immersion measurement in plastic and pasty substances

NTC sensor with handle FNA 124 LxxxxH



For surface measurement and immersion measurement

Cable:	1.5 m PVC
L = 100 mm	Order no. FNA123L0100H
Accuracy: Measuring tip:	NTC, see page 07.04 Operative range -20+100 °C

]	L = 100 mm	Order no. FNA124L0100H
	Cable:	1.5 m PVC
	Handle: *	127 mm
	T ₉₀ : *	10 s
		Silver rivet, level
	Measuring tip:	Operative range -20+100 °C
	Accuracy:	NTC, see page 07.04

NTC sensor FNA 305

For room air measurement



Accuracy:	NTC, see page 07.04
Measuring tip:	Operative range -10+60°C
	(non-condensing), Protective tube
	in stainless steel
	diameter = 3.0 mm, length = 50 mm
	mounted directly on ALMEMO [®] connector
T ₉₀ :	8 s

L = 50 mm **Order no. FNA305** (No variants available)

DAkkS or factory calibration KT90xx temperature for sensor or measuring chain (sensor + device) (see chapter Calibration certificates) DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Pt100 sensor FPA 611 x



For surface measurement



Accuracy:	Pt100 film resistor, class B*
Measuring tip:	Operative range see below
0 1	Copper, level
	Improved thermal transfer thanks to innovative sensor element and new contact technology
T ₀₀ : *	20 s
Cable:	see below

Surface sensor -10...+90°C, Cable PVC, 2 m Order no. FPA611 -10...+110°C, Cable, PFA, 3m for more demanding mechanical stress ALMEMO[®] connector, resolution 0.01 K

Order no. FPA611S01

Accessories Fixture for fastening with cable ties

Best-Nr. ZB9611RM

Pt100 film sensor FPA 686



For surface measurement

Accuracy: Messfläche:	Pt100 wire-wound, class B* Operative range -50+200 °C, temperature-resistant foil,
T ₉₀ *: Cable:	15 x 40 mm, approx. 0.5 mm thick 2 s Stranded wire PFA, 4-wire twisted
Length 2 m Length 10 m	Order no. FPA686 Order no. FPA686L10

Pt100 ceramic chip sensor element FP 0802



Accuracy:Pt100 film resistor, class B*Measuring tip:Operative range -40...+400 °C
Ceramic chip sensorConnection wires:10 mm, bareCeramic chip sensorOrder no. FP0802

Unprotected sensor element for constructing your own sensors

* Range of validity see page 07.03

DAkkS or factory calibration KT90xx temperature for sensor or measuring chain (sensor + device) (see chapter Calibration certificates) DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

NTC sensor FNA 611



NTC sensor element FN 0001



Sensor		Order no. FN0001
Connection with	res	180 mm, fluoropolymer insulation
Measuring tip:	Sensor	re range -20+100 °C
Accuracy:	NTC, se	e page 07.04

Unprotected sensor element for constructing your own sensors

10/2021 • We reserve the right to make technical changes.

DAkkS or factory calibration KT90xx temperature for sensor or measuring chain (sensor + device) (see chapter Calibration certificates) DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Pt100 Plug-in laboratory sensor FPA 416



Measuring element integrated in the socket of a 6 mm laboratory connector made of brass (nickel-plated).

Accuracy:	Pt100 film resistor, class B*
Measuring tip:	Operative range -40+150 °C
T ₉₀ :*	15 s
Cable:	Silicone/FEP 3m
ALMEMO [®] con	nector: resolution 0.01 K

Plug-in laboratory sensor Order no. FPA416

Pt100 Plug-in laboratory sensor FPA 414



Measuring element integrated in the socket of a 4 mm laboratory connector made of brass (gold-plated).

Accuracy:	Pt100 film resistor, class B*
Measuring tip:	Operative range -40+150 °C
T ₉₀ :*	15 s
Cable:	Silicone/FEP 3m
ALMEMO® com	nector: resolution 0.01 K

Plug-in laboratory sensor Order no. FPA414



Plug-in laboratory sensor, examples of use Measuring object with hole for inserted PT100 plug-in laboratory sensor.

* Range of validity see page 07.03

DAkkS or factory calibration KT90xx temperature for sensor or measuring chain (sensor + device) (see chapter Calibration certificates) DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Pt100 cable sensor

Technical data

Accuracy:	Pt100 film resistor, class B* (no other variants in stock)	
Protective tube:	Diameter, length see Variants, stainless steel 1.4301	
Junction of protective tube / connecting cable: Direct, hard-crimped for dry uses		
Cables:	Length = 1.5 meters, Other lengths are available as options. Cable diameter is never larger than the diameter of the protective tube.	
Operating temperature:		
	see variants, Always for whole sensor (i.e. sensor tip and cable)	
ALMEMO [®] connector: resolution 0.01 K.		

Inexpensive resistance-based temperature sensors. For immersion measurements in air and gases. Rigid protective tube made from stainless steel A wide variety of cable variants. Operating temperature (depending on variant) -40 to +400°C.

Please note: Only for usage in a dry environment

Note:

For temperature sensors suitable for usage in humid environments (e.g. climatic chamber) see page 07.21

Variants

1

With FEP / FEP cable (black),

Operative range -40...+250°C:

Diameter	Length	Order no.
3.0 mm	50 mm	FPA30K03L0050
3.0 mm	100 mm	FPA30K03L0100
4.0 mm	50 mm	FPA40K03L0050
4.0 mm	100 mm	FPA40K03L0100

A longer cable is available as an option

Total length 5 m	OPK03L0050
Total length 10 m	OPK03L0100

With FEP / silicone cable (red),

Operative range -40+200°C:		
Diameter	Length	Order no.
5.0 mm	50 mm	FPA50K01L0050
5.0 mm	100 mm	FPA50K01L0100
6.0 mm	50 mm	FPA60K01L0050
6.0 mm	100 mm	FPA60K01L0100
A longer ca	hle is available as a	an ontion

Total length 5 m OPK01

Total length 10 m

OPK01L0050 OPK01L0100

Cable with glass-fiber / glass-fiber / VA wire shielding,

Operative ra	nge -40+400°C	
Diameter	Length	Order no.
5.0 mm	50 mm	FPA50K06L0050
5.0 mm	100 mm	FPA50K06L0100
6.0 mm	50 mm	FPA60K06L0050
6.0 mm	100 mm	FPA60K06L0100
A longer ca	ble is available a	is an option
Total length 5 m		OPK06L0050
Total length 10 m		OPK06L0100

* Range of validity see page 07.03

DAkkS or factory calibration KT90xx temperature for sensor or measuring chain (sensor + device) (see chapter Calibration certificates) DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Pt100 glass thermometer with immersion depths as per ASTM



2-meter FEP / silicone cable)

Pt100 glass thermometer with immersion depths as per ASTM specifications, with ALMEMO[®] connector (including

Variants

Operative range:

For immersion measurement in liquid media at low immersion depths.

Order no.

FPA910

Technical data

Accuracy:	Pt100 wire-wound, class A*	
Measuring tip	Operative range -50 to +310 °C	
	Glass, tapered	
	Diameter = 3 mm , length = 15 mm	
Shaft	Glass, Diameter = 6 mm	
	NL= 250 mm (total nominal length)	
	Labeling codes for immersion depths :	
	identification rings on the shaft as per	
	ASTM specifications (American Society	
	for Testing and Materials)	
T	2.5 seconds	
Cable junction sleeve		
	Stainless steel, 8 x 40 mm	
	Cable exit secured with shrink-fit sleeve	
Cable	2 meters, FEP / silicone	
ALMEMO [®] connector		
	Resolution 0.01 K	

* Range of validity see page 07.03

Insertable sensor NiCr-Ni with round mounting plug T 820-6



Operative range:

Measuring tip, spring-loaded, for surface and immersion measurement.

Technical data

Accuracy:	NiCr-Ni class 2*
Measuring tip	Operative range -40 to +400 °C Silver rivet, level, spring-loaded
	not electrically isolated
T*	3 s
Insert length	60 mm (see layout drawing)
Fixture	Plastic, Ø 20 mm,
	resistant up to +120 °C
Connection	Round mounting plug

Accessories: ALMEMO[®] connecting cable, 2 meters Order no. ZA9020BK2

TypesOrder no.Insertable sensor NiCr-NiFT98206with round mounting plugFT98206

Insertable sensor NiCr-Ni with terminal head FT 0477



Operative range:

Spring-loaded measuring tip, for surface and immersion measurement

Technical data:

Accuracy:	NiCr-Ni class 2*
Measuring tip:	Operative range -40 to +400°C Silver rivet, level, spring-loaded, electronically isolated
Thread:	M10
Insert length:	25 mm (see layout drawing)
Terminal head:	Clamp connector

Options:

3-meter compensation line PVC, mounted, free ends: Order no. OT9020K02L0030

ALMEMO[®] plug including assembly for NiCr-Ni-sensor Order no. OT9020AS

Types	Order no.
Screw-in sensor NiCr-Ni	
with terminal head	FT0477

* Range of validity see page 07.03

DAkkS or factory calibration KT90xx temperature for sensor or measuring chain (sensor + device) (see chapter Calibration certificates) DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Insertable sensor Pt100 with terminal head FP 0463



Operative range:

For immersion measurements, pressure-sealed up to 15 bar.

Options: 3 meters cable PVC, assembled, free ends OT9030K02L0030 ALMEMO[®] connector including assembly for Pt100 sensor OT9030AS

Tec	hnica	data

Accuracy:	Pt100 film resistor, class B*
Sensor tube	Stainless steel
Operative range:	-40+350°C
Thread	1/2", with copper ring seal, pressure-sealed up to 15 bar
Insert length	70 mm (see layout drawing)
Terminal head	Clamp connector
Variants Insertable sensor with	Order no.

Screw-in sensor Pt100, NiCr-Ni with fitted cable Fx 0710 L27M10



Operative range:

For immersion measurement

Option:

ALMEMO[®] connector including assembly for Pt100 sensors: Order no. OT9030AS

Technical data FP0710L27M10

Accuracy:	Pt100 film resistor, class B*
Sensor material:	stainless steel
Operative range:	-40 to +200 °C
Thread:	M10
Insert length:	27 mm (see layout drawing)
Cable:	3 meters, FEP / wire shielding, / FEP free ends
Variants	Order no.
Screw-in sensor Pt100	0
with cable, free ends	FP0710L27M10
Option cable length 5	meters OPK04L0050

Technical data FT0710L27M10

Accuracy:	NiCr-Ni class 2*
Sensor material:	stainless steel
Operative range:	-100 to +400 °C
Thread:	M10
Insert length:	27 mm (see layout drawing)
Cable:	3 meters, thermal line glass filament / glass filament / VA wire shielding, free ends
	
Variants	Order no.
Screw-in sensor NiCr	-Ni
with cable, free ends	FT0710L27M10

Option:

ALMEMO® connector including assembly NiCr-Ni sensor: Order no. OT9020AS

* Range of validity see page 07.03

DAkkS or factory calibration KT90xx temperature for sensor or measuring chain (sensor + device) (see chapter Calibration certificates) DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Insertable sensor PtRh-Pt (S) with terminal head FT 0426x

Operative range:

For immersion measurements, up to 1400 or 1600 °C.

Technical data

Accuracy:	Thermowire PtRh-Pt (S) class 1*
Measuring tip	Ceramic protection tube
Operative range	see under variants
Insert length	500 mm
Protective tube	Ceramic, C799, d= 6 mm, replaceable
Cable	2-meter compensation line FEP/Silikon, free ends

Accessories

Aluminum profile case for 1 sensor with connection head (up to 700 mm length) Order no. ZB9000TK2

Replacement ceramic protection tube d= 6 mm, for FT0426x Order no. ZB9006SR0500

Options

ALMEMO[®] connector with assembly Order no. OT9020AS

Variants

Order no.

Insertable sensor PtRh-Pt type S with terminal head and compensation lines, free ends)

$T_{max} = 1400^{\circ}C$, thermowire $\emptyset = 0.35$ mm,	FT04261
$T_{max} = 1600^{\circ}C$, thermowire $Q = 0.5$ mm,	FT04262

^{*} Range of validity see page 07.03

DAkkS or factory calibration KT90xx temperature for sensor or measuring chain (sensor + device) (see chapter Calibration certificates) DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.



Why Infrared Measurements?

Infrared measuring instruments provide large advantages with regard to measuring tasks that cannot be solved with conventional contact thermometers. Examples:

What is Infrared Radiation?

Every substance with a temperature above absolute zero emits an infrared radiation (spectral range of wavelengths from 0.7 to 1000µm) that corresponds to its temperature. This range is located below the longer red wavelength range and is not visible to the human eye. For measurements the most interesting range is located between 0.7 and 20µm.

The infrared radiation emitted by the test object follows the known optical rules and, therefore, can be deviated, bundled with lenses or reflected from catoptric ele-

ments.

les

thermal capacity.

The emissivity of a test object indicates how much infrared energy has been absorbed or released by radiation. The value can be between 0 and 1.0. The fact that the emissivity depends on the wavelength is relevant for measurements. With increasing object temperature the radiation maximum shifts to the short wave range. Therefore, IR thermometers are equipped with filters, which allow only one particular wavelength to pass through for the measurement. The spectral range for spe-

· Measurements of very high temperatu-

Measurements at surfaces with low

res not allowing the use of thermocoup-

thermal conduction and bodies with low



Measurements at moving, inaccessible

· Measurements at objects, which must

not be influenced by contact measure-

(<1s).

ments.

or live parts with a high rate of response

cific materials must be considered for the application.

How Infrared Thermometers Operate

The optical system of an infrared thermo- energy captured by the detector is elect-

meter captures the energy emitted from a ronically amplified and converted into an circular measuring spot and focuses it onto electrical signal. The optical resolution a detector. A material with a high trans- results from the ratio of the measuring di- resolution the smaller the measuring spots mission Partos is used rocality denses. The temperature for size of the animal further align are the animal further align are the size of the size of the animal further align are the size of the animal further align are the size of the size of the animal further align are the size of the size of the animal further and the size of t

The measuring spot must always be smaller than the test object or the measuring point of interest. The higher the optical DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

What is Intermittent Photometry?

the thermal drift and immunes devices mised signal processing, leads to an excelagainst thermal shock. The stability resul- lent temperature resolution and allows the

Using intermittent photometry eliminates ting from this, combined with noise-opti-

measurement of smallest test objects and fast response times.

Special Infrared Pyrometers

Ratio Pyrometers determine the temperature from the ratio of the energy radiated in each of two wavelength ranges. This method allows for exact measuring results, even in case of a limited view to the test object due to vapour, steam, dust, dirty windows or lenses (up to 95% reduction of meas. signal). Furthermore, test objects, which are smaller than the measuring spot ces), but can also be moved to pass above

(e.g. measurement at wires), or low or varying emissivities at fast moving objects, do not affect the measuring result.

Line Scanners measure the object temperature along a line. Fixed installed line scanners provide coloured heat flow charts from a product passing under the measuring head (e.g. conveyors, rotary furna-

objects (e.g. heat flow chart of a house wall). The infrared scanner measuring head AMiR 7880 scans up to 256 dots over an angle of 90°. 20 lines can be scanned within one second. One measuring tape can be divided into 3 sectors, side by side or overlapping.

What You Should Consider For Infrared Measurements

aerosols at the measuring point?

If the atmosphere at the measuring point is contaminated with dust, vapour and aerosols, the radiation energy impinging on the sensor can be influenced by contaminated lenses. This can be avoided by using an air blow attachment that keeps the lens clean.

What to do in case of high ambient temperatures?

If the ambient temperature exceeds the temperature specified for the measuring head of the IR sensor, the measuring head must be protected by mounting an air or water cooling system along with an air blow attachment (to avoid water condensing on the lens). Furthermore, cables and cable routings with high temperature stability must be used.

What to do in case of heat sources located next to the measuring object?

If heat sources are located next to the test object, these can transmit or reflect additional energy. Such ambience radiations occur, for example, at measurements in industrial furnaces where the wall temperature is often higher than the temperature of the test object. Many infrared instruments allow for a compensation of the ambient temperature.

What to do in case of dust, vapour and What to do in case of measurements in a vacuum?

In case of vacuum furnaces and similar applications it is necessary to mount the measuring head outside of the vacuum area and to perform the measurement through a window. When selecting the measuring window the transmission values of the window must match the spectral sensitivity of the sensor. Quartz glass or quartz are typically used for high temperatures. In case of low temperatures within the 8 to 14µm band the use of a special material, which is translucent for IR, is necessary, e.g. germanium, amtir, zinc selenide or sapphire. When selecting the window the temperature requirements, window thickness and pressure difference, as well as the possibility of keeping the window on both sides clean, must be considered. It might be advisable to consider an additional antireflective coating an the window on the window to increase the transmission capacity. Furthermore, it must be considered that not all window materials are translucent in the visible range.

Why is the emissivity so important?

In case of ideal radiators the reflected and transmitted energy equals zero and the emitted energy corresponds 100% to the characteristic temperature. However, many bodies emit less radiation at the same temperature (non-selective radiator). The ratio of real radiation value and that of the ideal radiator is defined as the

emissivity ε . For example, a mirror has an emissivity of 0.1 while a so-called 'black body' has an emissivity of 1.0. Many nonmetals such as wood, rubber, stone, and organic materials have only low reflecting surfaces and, as a result, high emissivities between 0.8 and 0.95. However, metals, especially if they have glossy surfaces, can have $\varepsilon = 0.1$. Therefore, IR thermometers provide an option for setting the emissivity. The emissivity should be known as exact as possible. If a too high emissivity has been set, the indicated temperature is lower than the actual temperature, given that the temperature of the test object is higher than the ambient temperature. For example, if 0.95 has been set, while the emissivity is actually only 0.9, a temperature that is lower than the actual temperature will be indicated.

How can the emissivity be determined?

Several methods can be used to determine the emissivity. As a first starting point, the following emissivity table can be consulted. The table data only represents average values, as the emissivity of a material is influenced by various factors. These include: temperature, angle of measurement, surface geometry (plane, concave, convex), thickness, surface quality (polished, rough, oxidised, sand-blasted), spectral range of the measurement and transmission capacity (e.g. in case of thin plastic foils)

Temperature Range	Spectral Sensitivity	Application Examples
appr. 0 800°C	8 to 14 μm 3 to 5 μm 7 to 15 μm 7 to 18 μm	All non-metals, wood, paper, textiles, floor coverings, asphalt, lime floor, edibles, pharmaceuticals, as well as use with print, coating, laminating, drying/hardening, wave soldering and reflow soldering, for indoor installations, fire control, dust tips etc.
appr. 10 360°C	nominal 7.9 μm	Fabrication and processing of polyester foil, fluoroplastics, fluoropolymer, acrylate, nylon (polyamide), acetylene cellulose, polyamides, polyurethanes, PVC, polycarbonates.
appr. 260 1650°C	nominal 5.0/5.2 µm	Surface measurement on glass for heating up, forming, sealing, laminating, bending.
appr. 200 1200°C	3.9 µm	Metal finishing, furnaces, melting furnaces, blast furnaces, measurements on thick glass. Measurements slightly influenced by CO ₂ atmosphere (combustion gases).
appr. 30 340°C	nominal 3.43 µm	Fabrication and processing of polyethylene, polypropylene, polystyrene and other foils.
appr. 400 3000°C	2 to 2.7 µm	Processing of ferrous and nonferrous metals, induction furnaces, glass production, melting furnaces, lab research.
appr. 200 1800°C	1.6 µm	Heat treatment of steel, bending, hardening, warming up.
appr. 500 3000°C	1 μm	Steel production, molten baths, for highest precision with shaping, casting and processing of metals, as well as the processing of glass, ceramics, semiconductors and chemicals.

Application Examples for Infrared Thermometers

Compact Glossary of Important Terms

Atmospheric Windows:	The wavelength ranges within the infrared spectrum, in which the atmospheric radiation energy is transmitted and the atmospheric absorption is minimal, approximately $3 \dots 5\mu m$ and $8 \dots 14\mu m$.
Focal Point, Focal Distance	e:Measuring distance where the maximum optical resolution is reached.
Far Field:	Measured distance, which is significantly larger than the focal length of a device, in most cases is larger than ten times the focal length.
Field of View:	The test object area, which is measured by the infrared thermometer; the diameter of the measuring spot is proportioned to the distance from the test object; often also specified as an angular variable at the focal point. Also see optical resolution.
Non-Selective Radiator:	Radiating body with an emissivity that, for all wavelengths, bears the same constant ratio to the emis- sivity of a full radiator at the same temperature, which is opaque to radiation of infrared energy.
Background Temperature:	From the view of the measuring instrument the ambient temperature or the temperature behind the test object.
Measuring Spot:	Diameter of the test object area, which is subject to a temperature measurement; the measuring spot is defined by the circular area, which typically allows to capture 90% of the infrared energy radiating from the test object to the optical receiving aperture of the measuring instrument.
Optical Resolution:	Also called the distance ratio: The 'measuring distance/measuring spot size' ratio (distance ratio E:M) of an IR measuring spot. The measuring distance is typically defined as the distance from the focal point and the measuring spot size as the diameter of the IR measuring spot measured at the focal point (typically the 90% energy measuring spot diameter). The optical resolution can be also defined for the far field, by using the values for the measuring distance and measuring spot size within the far field.
Degree of Reflection:	Ratio of the radiation energy reflected from a surface to the incident radiation of the same surface; for a perfect mirror the value is approximately 1, for a full radiator the reflection is zero.
Full Radiator:	Also: black body; ideal radiator. Body, which absorbs the whole impinging radiation energy of all wavelengths and which does not reflect nor transmit any radiation. The surface of a full radiator has a uniform emissivity of 1.
Spectral Sensitivity:	Wavelength range for which an infrared thermometer is sensitive.

Emissivities of Various Materials Depending on the Spectral Range **2.2** μm Metals 1 μm 5.1 µm 8–14 μm non-oxidised 0.1-0.2 0.02 - 0.20.02 - 0.20.02-0.1Aluminium 0.2-0.4 oxidised 0.4 0.2-0.4 0.2 - 0.4oxidised 0.4 0.3 Alloy A3003, 0.4 0.2-0.6 0.2-0.8 0.1-0.4 0.1-0.3 etched polished 0.1-0.2 0.02-0.1 0.02-0.1 0.02-0.1 0.05-0.2 polished 0.35 0.05-0.2 0.05-0.1 Lead etched 0.65 0.5 0.4 0.4 oxidised 0.3 - 0.70.2 - 0.70.2 - 0.60.4 0.05-0.3 0.03-0.3 Chromium 0.02-0.2 0.7-0.9 0.5-0.9 oxidised 0.4 - 0.80.6 - 0.9Iron 0.35 0.05-0.25 0.05-0.2 non-oxidised 0.1 - 0.3rusty 0.6-0.9 0.5-0.8 0.5 - 0.70.35 0.4-0.6 molten 0.7-0.9 0.7-0.95 0.65-0.95 0.6-0.95 oxidised Iron, cast non-oxidised 0.35 0.3 0.25 0.2 0.35 0.3-0.4 0.2-0.3 0.2-0.3 molten 0.9 0.95 09 0.9 Iron, wrought dull Gold 0.3 0.01-0.1 0.01-0.1 0.01-0.1 alloy Haynes 0.5 - 0.90.6 - 0.90.3 - 0.80.3 - 0.8Inconel oxidised 0.4-0.9 0.6-0.9 0.6-0.9 0.7-0.95 sand-blasted 0.3-0.4 0.3-0.6 0.3-0.6 0.3-0.6 electropolished 0.2-0.5 0.25 0.15 0.15 polished 0.05 0.03 Copper 0.03 0.03 0.05-0.2 0.05-0.2 0.05-0.15 0.05-0.1 etched 0.2-0.8 0.7-0.9 0.5-0.8 0.4-0.8 oxidised 0.3-0.8 0.05-0.2 0.03-0.15 0.02-0.1 Magnesium Brass polished 0.8-0.95 0.01-0.05 0.01-0.05 0.01-0.05 high polished 0.4 0.3 0.3 oxidised 0.6 0.5 0.5 0.6 0.4-0.9 0.5-0.9 Molybdenum 0.3-0.7 0.2-0.6 oxidised non-oxidised 0.25-0.35 0.1-0.3 0.1-0.15 0.1 Monel (Ni-Cu) 0.3 0.2-0.6 0.1-0.5 0.1 - 0.14Nickel oxidised 0.8 - 0.90.4 - 0.70.3-0.6 0.2 - 0.5electrolytic 0.2 - 0.40.1 - 0.20.1 - 0.150.05-0.15 Platinum black 0.95 0.9 0.9 0.05-0.15 0.05-0.15 0.05-0.15 Mercurv 0.04 Silver 0.02 0.02 0.02 0.8-0.9 0.8-0.9 0.7-0.9 Steel cold-rolled heavy plate 0.6-0.7 0.5-0.7 0.4-0.6 polished sheet metal 0.35 0.2 0.1 0.1 0.25-0.4 melt steel 0.35 0.1 - 0.2oxidised 0.8-0.9 0.8-0.9 0.7-0.9 0.7-0.9 stainless 0.35 0.2-0.9 0.15-0.8 0.1 - 0.8Titanium polished 0.5 - 0.750.2 - 0.50.1 - 0.30.05-0.2 oxidised 0.6-0.8 0.5 - 0.70.5 - 0.60.35-0.4 0.05-0.25 Tungsten polished 0.1 - 0.30.03-0.1 0.15 oxidised 0.6 0.1 0.1 Zinc polished 0.5 0.05 0.03 0.02 Tin (non-oxidised) 0.25 0.1 - 0.30.05 0.05 Nonmetals 2.2 µm 5.1 µm 8–14 µm 1 µm Asbestos 0.9 0.8 0.9 0.95 Asphalt 0.95 0.95 Basalt 0.7 0.7 0.65 0.9 Concrete 0.9 0.95 0.98 Ice 0.9-0.98 Soil _ _ _ 0.9 - 0.95Paint (non alkaline) _ 0.4-0.97 0.8-0.95 Gypsum _ 0.2 pane 0.98 0.85 Glass _ 0.4-0.9 0.9 molten mass _ 0.95 Rubber 09 _ _ 0.9-0.95 Wood, natural 0.9-0.95 _ _ 0.4-0.98 0.98 Limestone _ 0.95 Carborundum 0.9 0.9 Ceramics 0.4 0.8-0.95 0.85-0.95 0.95 Pebble stones 0.95 0.95 Carbon non-oxidised 0.8-0.95 0.8-0.9 0.8-0.9 0.8-0.9 graphite 0.8-0.9 0.8-0.9 0.7 - 0.90.7 - 0.80.95 0.95 Paper (any colour) (translucent, over 0.5mm) 0.95 Plastic 0.95 _ _ 0.95 0.95 Fabric (cloth) _ _ 0.9 0.9 Sand 0.9 Snow 0.8-0.95 0.95 0.85-0.95 _ Argil Water 0.93

Digital infra-red sensor for measuring surface temperature FIAD43 Miniature probe head, integrated electronics, ALMEMO[®] D6 plug



Measuring Field



Options fitted at our factory



Air blower attachment

OR7843LB

- Digital infra-red probe head with integrated signal processor
- All sensor characteristics and adjustment data are stored in the probe head itself.
- Digital transmission ensures that measured values are not affected by the sensor cable being moved, bent, or twisted.
- Surface temperature is measured over a wide range up to 600°C.
- Robust stainless steel housing, protection class IP65
- The probe head, thanks to its small dimensions, can be installed in cramped and restricted conditions.
- The probe head is threaded for quick and easy installation.
- The sensor cable in polyurethane (PUR) is suitable for industrial use and is resistant to oily, acidic, basic environments.
- The sensor can be connected directly via the cable's ALMEMO[®] D6 plug to any ALMEMO[®] device.
- One measuring channel is preprogrammed on leaving our factory surface temperature (°C).
- Emissivity 0.95 are preprogrammed (on leaving our factory).
- This can be programmed from 0.1 to 1.0 at the current ALMEMO[®] V6 devices via the device or via interface (some only via interface).
- Transmittance 1.0 is preprogrammed (on leaving our factory). When using the focal point lens attachment or the protective window, the transmittance of the focal point lens attachment or the protection window must be adjusted. Transmittance can be modified in the ALMEMO® D6 sensor menu directly on the PC using USB adapter cable ZA1919AKUV (see page 04.05) 35/5000 or with an ALMEMO® V7 measuring device..

General features and accessories, ALMEMO[®] D6 sensors see page 01.08



Deflecting mirror with integrated air blower attachment OR7843US1



DAkkS or factory calibration KI9xxx temperature for digital sensor (see chapter Calibration certificates). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Technical data

Digital infra-red probe head (including A/D converter)

Temperature measuring range	-40 to +600 °C
Spectral sensitivity	8 to 14 µm
Optical resolution (90 % energy)	10:1
	with focal point lens attachment 1 mm at distance of 10 mm
	Iransmittance can be programmed to 0.75. (see below)
Accuracy	± 1 % of meas. value or ± 1 K (whichever value is higher) ± 2 K for meas. values <20 °C
Reproducibility	± 0.5 % of measured value or ± 0.5 K (whichever value is higher)
Nominal conditions	23 °C ±5 K, emissivity 1.0
Temperature coefficient	± 0.05 K / K or ± 0.05 % of measured value / K (whichever value is higher)
Temperature resolution	0.1 K
Response time	130 ms (90 %)
Emissivity	0.95 (preprogrammed on leaving our factory) This can be programmed from 0.1 to 1.0
	at the current ALMEMO [®] V6 devices via the device (some only via interface).
Transmittance the focal point lens	attachment or the protective window :
	1.0 (preprogrammed on leaving our factory) This can be programmed from 0.1 to 1.0
	directly on the PC using USB adapter cable ZA1919AKUV. (please place a special order)
	(see "General accessories for ALMEMO [®] D6 sensors")
Protection class	IP65 (NEMA 4) (National Electric Manufacturers Association)
Ambient temperature	-10 to +120 °C with air-cooled housing -10 to +200 °C
Storage temperature	-20 to +120 °C
Relative atmospheric humidity	10 to 95 % non-condensing
Housing	Stainless steel
Dimensions	Probe head Length 28 mm x Ø 14 mm Thread M12 x 1
Weight	Probe head 50 grams with 1-meter cable
Connecting cable(s)	permanently fitted Polyurethane (PUR) For available lengths see variants.
	with ALMEMO [®] D6 plug
ALMEMO [®] D6 plug	Refresh time 0.25 seconds for all channels
	Supply voltage 6 to 13 VDC
	Current consumption 4 mA

Accessories



Focal point lens attachment (cannot be used together with air blower attachment or air-cooled housing) Transmittance 0.75

ZR7843CFL



Protective window (cannot be used together with air blower attachment or air-cooled housing) **ZR7843PW** Transmittance 0.75



Mounting bracket, rigid

ZR7842H

Mounting bracket, adjustable

0

5

10

Measuring field with focal point lens attachment

D:S = 10:1

ZR7842JH

24 30 mm

20

15

25

Compact infra-red probe head AMiR FIA 844 suitable for all ALMEMO® devices



- Compact inexpensive infra-red probe head for measuring surface temperature
- Other measuring ranges -20 to +500 °C
- High optical resolution Measuring spot 11.5 mm at distance 150 mm, in distant field 9:1
- Sturdy stainless steel housing Protection IP65
- Quick and easy to install thanks to screw-fit housing
- Integrated electronics, cable permanently fitted
- Can be connected directly to the ALMEMO[®] device using an ALMEMO[®] connector.





10/2021 • We reserve the right to make technical changes.

Accessories	Order no.
Mounting bracket, rigid	ZR7844FB
Mounting bracket, adjustable	ZR7844JB
Air blower attachment Thread M18x1	ZR7844APM
Variants (including 2 mounting nuts):	
ALMEMO [®] infra-red probe head Measuring range -20 to +500 °C	
with permanently fitted cable and $ALMEMO^{\text{(B)}}$ connector, Cable length = 1 meter	FIA844
Same as above Cable length $= 3$ meters	FIA844L3
Factory calibration KI9xxx temperature for sensor (see chapter Calibration certificates)	

Technical data

Temperature range	-20 to +500 °C
Spectral sensitivity	8 to 14 µm
Optical resolution (90 % energy)	13:1 (11.5 mm at 150 mm distance), distant field 9:1
Accuracy	± 1.5 % of measured value or ± 2 K (whichever value is higher)
	± 3.5 K for measured values <0 °C
Reproducibility	± 0.5 % of measured value or ± 1 K (whichever value is higher)
Nominal conditions	23 °C ±5 K, Emissivity 0.95
Temperature resolution	0.1 K
Response time	150 ms (95 %)
Emissivity	0.95, fixed setting
Voltage supply	via ALMEMO® connector (12 VDC)
Protection	IP65
Ambient temperature	-10 to +70 °C
Storage temperature	-20 to +85 °C
Relative atmospheric humidity	10 to 95 % non-condensing
Housing	Stainless steel
Dimensions	Length 94 mm Thread M18x1
Connecting cable	permanently fitted, 1 or 3 meters, -30 to $+105$ °C
	including ALMEMO® connector, programmed
Weight	approx. 160 g (1-meter cable)

Mounting bracket Order no. ZR7844FB





Mounting bracket, adjustable Order no. ZR7844JB





Air blower attachment Thread M18x1 Order no. ZR7844APM





Infra-red transmitter for measuring surface temperature AMiR 7843 Miniature probe head, transmitter box with display / operating controls, with analog output



- Surface temperature is measured over a wide range up to 600 / 1000 $^{\circ}\mathrm{C}.$
- The probe head, thanks to its small dimensions, can be installed in cramped and restricted conditions.
- Robust stainless-steel housing, protective class IP65
- The probe head is threaded for quick and easy installation.
- The sensor cable is suitable for industrial use and is resistant to oily, acidic, and alkaline environments.
- Transmitter box with display and operating controls
- Analog output 10 V / 20 mA, freely selectable and scalable.
- Infra-red sensor suitable for direct connection to ALMEMO[®] measuring instruments see Digital sensor FIAD43x with ALMEMO[®] D6 plug (see page 01.08)

Accessories MR7843 series			Order no.
Mounting bracket, rigid Mounting bracket, adjustable Protective window (cannot be used together with air blower attachment or air-cooled housing)	ZR7842H ZR7842JH ZR7843PW	Focal point lens attachment (cannot be used tog attachment or air-cooled housing) 10:1 optics Measuring spot diameter 1 mm at d 22:1 optics Measuring spot diameter 0.5 mm at	zether with air blower ZR7843CFL listance of 10 mm t distance of 10 mm.
Accessories for MR7843-12 / -32 /	-42		Order no.

Air blower attachment	ZR7842LB	90° deflecting mirror	
Air-cooled housing and T branch, including 0.8-meter		(only for air-cooled housing and air blower attachment)	ZR7842US
air hose, insulation, and air blower attachment	ZR7842KL1	90° deflecting mirror with integrated air blower attachme	nt
Same as above but with 2.8-meter air hose	ZR7842KL2		ZR7842US1

Options for MR7843-12 / -32 / -42

Factory test certificate (only with delivery of new devices) OR7843KZ1 DAkkSDKD or factory calibration KI9xxx, temperature, for sensors (see

chapter "Calibration certificates"). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Standard delivery

Probe head (including mounting nut) with cable, PUR, mounted on transmitter box

Temperature range	Optical resolution	Ambient tempera- ture, probe head	Order no. Probe head cable, 1 m	Order no. Probe head cable, 3 m*
-40 to 600°C	2:1	-10 to 120°C	MR784312	MR784312L03
-40 to 600°C	10:1	-10 to 120°C	MR784332	MR784332L03
0 to 1000°C	22:1	-10 to 120°C	MR784342	MR784342L03

* Available on request longer probe head cable, 8 / 15 / 30 meters

Options for MR7843-33 / -43

Air blower attachment, only fitted at our factory	OR7843LB1	Factory test certificate (only with delivery of new devices) OR7843KZ1
90° deflecting mirror		DAkkS or factory calibration KI9xxx, temperature, for sensors (see
(only with air blower attachment OR7843LB1)	OR7843KZ1	chapter "Calibration certificates"). DAkkS calibration meets all the requi-
		rements regarding test resources laid down in DIN EN ISO/IEC 17025.

Standard delivery

Probe head (including mounting nut) with cable, fluoropolymer, with separate electronics Ø14 mm, approx. 52 mm long, with 0.5 m cable, mounted on transmitter box

Temperature range	Optical resolution	Ambient tempera- ture, probe head	Order no. Probe head cable, 1 m	Order no. Probe head cable, 3 m*
-40 to 600°C	10:1	-10 to 180°C	MR784333	MR784333L03
0 to 1000°C	22:1	-10 to 180°C	MR784343	MR784343L03

* Available on request longer probe head cable 8 / 15 / 30 meters

Order no.

Order no.

Technical data Probe head

Temperature measuring rat	nge depending on type -40 to $+600$ °C or 0 to $+1000$ °C
Spectral sensitivity	8 to 14 um
Optical resolution (90 % e	nergy) depending on type 2:1 / 10:1 / 22:1 typical (21:1 guaranteed)
Response time (90%)	130 ms
Accuracy	+1% of measured value or $+1~K$ (whichever value is higher) $+2~K$ for measured values $<20~$ °C
Reproducibility	$\pm 0.5\%$ of measured value or ± 0.5 K (whichever value is higher)
Nominal conditions	at ambient temperature $\pm 23 \text{ °C} \pm 5 \text{ K}$. Emissivity factor 1.0 and calibration geometry
Temperature coefficient	$\pm 0.05 \text{ K} / \text{K} \text{ or } \pm 0.05 \% \text{ of measured value } / \text{K} \text{ (whichever value is higher)}$
Ambient temperature	depending on type -10 to $+120$ °C (with air cooling up to $+200$ °C) or -10 to $+180$ °C
Protective class	IP65 (NEMA-4) / IEC 60529
Relative humidity	10 to 95 % non-condensing
Housing	Stainless steel
Dimensions	$L = 28 \text{ mm}, \emptyset = 14 \text{ mm}, \text{ Thread } M12x1$
Probe head cable	depending on type polyurethane (PUR) or fluoropolymer
Electronics:	integrated in the measuring head. For type MR784333x / 784343x: separate electronics.
Weight	50 g (with 1-meter cable)
Transmitter box	
Output (selectable)	0 to 5 V / 0 to 10 V; 0 to 20 mA / 4 to 20 mA (Temperature range can be programmed in each case.)
	Thermocouple, type J, K, R, S Not electrically isolated from supply voltage
Temperature resolution	± 0.1 K for temperature range < 500 °C
Accuracy	± 1 K for output mA / V ± 1.5 K for output, thermocouple
Temperature coefficient	± 0.02 K / K for output mA / V, ± 0.05 K / K for output, thermocouple
Emissivity	0.100 to 1.100
Transmittance	0.100 to 1.000
Signal processing	Saving of maximum / minimum / average value retention period up to 998 seconds
Alarm output	zero-potential contact (semiconductor relays) 48 V / 300 mA
Power supply	8 to 32 VDC, maximum 6 W
Ambient temperature	-10 to +65 °C
Protective class	IP65 (NEMA-4) / IEC 60529
Relative humidity	10 to 95 % non-condensing
Housing	Zinc die casting
Dimensions	80 x 60 x 31.5 mm (LxWxH)
Weight	370 g

Dimensions









- · Precise measurement of the surface temperature in industrial processes.
- New: sturdy stainless steel housing, protection class IP65.
- Broad temperature range from -40 to 2000 °C.
- Several spectral ranges for a variety of materials and use cases. • Emissivity of the measuring surface can be manually adjusted on the probe head.
- Several optical resolutions and focal points.
- New: integrated laser (except 7834-10) for easy positioning of the probe head. Supply of the laser via the USB port.
- Analog output 4 to 20 mA in two-wire technology.
- New: USB port for configuring the analog output range, further probe head parameters and the signal processing (average value, maximum value, and minimum value).
- · Easy installation. Extensive range of accessories, i.a. a high temperature protective housing.
- Connection cable for ALMEMO® data logger. Sensor power supply via the ALMEMO[®] device.
 - On request: Intrinsically safe probe heads approved for various purposes in areas with potentially explosive atmosphere (gas/dust).

Туре	Measuring range	Spectral range	Optical resolution / focal point (refer to Measuring Field Diagrams)	Order no.
AMiR 7834-10x. without	t laser. with plastic l	ens. i.a. suitable for	food etc.	
AMiR 7834-10SF0	-20 to 600 °C	8 to 14 μm	15:1 / 101.3 mm at 1520 mm	MR783410SF0
AMiR 7834-10CF0	-20 to 600 °C	8 to 14 μm	7:1 / 7.1 mm at 50 mm	MR783410CF0
AMiR 7834-11x/-12x with laser, for low tempe	rature measurement	s, i.a. thick plastics,	asphalt, carpets, coated papers, thermo	forming etc.
AMiR 7834-11SF0	-20 to 600 °C	8 to 14 μm	33:1 / 46.1 mm at 1520 mm	MR783411SF0
AMiR 7834-11CF1	-20 to 600 °C	8 to 14 μm	33:1 / 2.3 mm at 76 mm	MR783411CF1
AMiR 7834-11CF2	-20 to 600 °C	8 to 14 μm	33:1 / 6.1 mm at 200 mm	MR783411CF2
AMiR 7834-12SF0	-40 to 1000 °C	8 to 14 μm	50:1 / 30.4 mm at 1520 mm	MR783412SF0
AMiR 7834-12CF2	-40 to 1000 °C	8 to 14 μm	50:1 / 4 mm at 200 mm	MR783412CF2
AMiR 7834-21x with las	ser, for blast furnace	lining, flame harden	ing, brazing etc.	
AMiR 7834-21SF0	200 to 1000 °C	3.9 µm	33:1 / 46.1 mm at 1520 mm	MR783421SF0
AMiR 7834-21CF1	200 to 1000 °C	3.9 µm	33:1 / 2.3 mm at 76 mm	MR783421CF1
AMiR 7834-21CF2	200 to 1000 °C	3.9 µm	33:1 / 6.1 mm at 200 mm	MR783421CF2
AMiR 7834-31x with las	ser, for surface temp	eratures of glass for	bending, hardening, glowing, sealing o	etc.
AMiR 7834-31SF0	250 to 2250 °C	5 µm	33:1 / 46.1 mm at 1520 mm	MR783431SF0
AMiR 7834-41x with las	ser, for foils PET, FE	P, acryl, nylon, PU,	PVC etc.	
AMiR 7834-41SF0	10 to 360 °C	7.9 μm	33:1 / 46.1 mm at 1520 mm	MR783441SF0
AMiR 7834-51x with laser, for ferrous metals / non-ferrous metals, induction heating, blast furnaces etc.			с.	
AMiR 7834-51SF0	500 to 2000 °C	2.2 μm	60:1 / 25.3 mm at 1520 mm	MR783451SF0
AMiR 7834-51CF1	500 to 2000 °C	2.2 μm	60:1 / 1.3 mm at 76 mm	MR783451CF1
AMiR 7834-51CF2	500 to 2000 °C	2.2 µm	60:1 / 3.3 mm at 200 mm	MR783451CF2

DAkkS- oder Factory calibration KI9xxx temperature for sensor (see chapter Calibration certificates). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Order no.

Infrared measuring technology

Technical data:

Accuracy:	$\pm 1\%$ of the measured value respectively ± 1.0 K for the measured temperature > 0°C,
	(whichever value is higher). for measured temperature $< 0^{\circ}$ C: $\pm(1.0 \text{ K} \pm 0.1 \text{ x})$
	$(0^{\circ}C - measured temperature))$. measured temperature in $^{\circ}C$
Reproducibility:	$\pm 0.3\%$ of measured value respectively ± 0.3 K (whichever value is higher).
Response time:	130 ms, for 7834-11 30ms, for 7834-31 60 ms
Nominal conditions:	$+23^{\circ}C \pm 5$ K, Emissivity factor 1.0 and calibration geometry
Emissivity:	0.10 to 1.00 manually adjustable on the probe head
Signal processing: tion, compensation of back	Averaging, maximum and minimum value retention, extended maximum and minimum value reten- ground temperature
Power supply:	12 to 24 VDC
Analog output:	via terminals, 4 to 20 mA linear, two-wire technology, load < 500 Ohm. Analog output range can be configured via USB
ALMEMO [®] application:	To acquire and save measured values, we recommend our ALMEMO [®] 4390-2 panel meters. For further ALMEMO [®] devices, see chapter ALMEMO [®] Measuring Instruments
Alarm relay:	via terminals, load capacity 24 V 150 mA 1 limit value configurable via USB
Digital interface:	USB 2.0, micro B-plug (only for sensor set-up)
Laser:	for positioning of the probe head, power supply via USB.
Operating temperature:	
	without cooling: -20 to 85°C,
	with air-cooling: 10 to 120°C
	with water-cooling: 10 to 175°C
	with Thermo jacket protection housing and water cooling: 10 to 315°C
Air humidity:	10 to 95 % RH at 30°C, non-condensing during operation and storage.
Material:	stainless steel (housing)
Protection class:	IP 65 (IEC 60529)
Dimension:	without water cooling housing: Length 186 mm, Ø 42 mm
Weight:	without water cooling housing: 500 g

Accessories

ALMEMO[®] connecting cable, directly mounted on the probe head, length 2 meters, with ALMEMO[®] connector, programmed for the probe head's temperature range, sensor supply via ALMEMO[®] device (use of the device mains unit is recommended) ZA7838AK

For further accessories (protective window, cooling housing, thermo jacket etc.), see the following pages

OptionOrder no.Factory test certificate (only with delivery of new devices).OR7834KZ1

Measuring Field Diagrams





AMiR 7834-10SF0



AMiR 7834-11SF0 AMiR 7834-21SF0 AMiR 7834-31SF0 AMiR 7834-41SF0



AMiR 7834-11CF2 AMiR 7834-21CF2

AMiR 7834-10CF0



AMiR 7834-11CF1 AMiR 7834-21CF1





AMiR 7834-12SF0

AMiR 7834-12CF2





AMiR 7834-51SF0



AMiR 7834-51CF2

AMiR 7834-51CF1

Accessories for the probe heads AMiR 7834 without the use of the thermo jacket protection housing



Accessories	Order no.
Protective window attached for probe head MR 7834-10x, material: plastic foil	ZR7834SFLTPF
Protective window attached for probe head MR 7834-11x/-12x, material: zinc sulfide	ZR7834SFLT
Protective window attached for probe head MR 7834-21x, material: sapphire	ZR7834SFMT
Protective window attached for probe head MR 7834-31x/-41x, material: calcium fluoride	ZR7834SFG5P7
Protective window attached for probe head MR 7834-51x, material: glass	ZR7834SFHT
Water cooling housing including air blower attachment	ZR7834KL
Air blower attachment	ZR7834LB
Deflecting mirror 90°	ZR7834US
Mounting bracket, adjustable	ZR7834JH
Mounting bracket, rigid (spare)	ZR7834H
Securing nut (spare)	ZR7834BM
Tube adapter for protective tubes	ZR7834RA
Stainless steel protective tube, 30 cm	ZR7834RE
Ceramic protective tube, 30 cm	ZR7834RK

Accessories for the probe heads AMiR 7834 using the thermo jacket protection housing



Accessories	Order no.
Thermo jacket protection housing	ZR7834SH
Mounting flange for thermo jacket	ZR7834TJMF
Adjustable mounting flange for thermo jacket	ZR7834TJMB
Adjustable tube adapter for thermo jacket	ZR7834JR
Mounting flange for protective tubes for thermo jacket	ZR7834TJFR
Stainless steel protective tube, 30 cm	ZR7834RE
Ceramic protective tube, 30 cm	ZR7834RK

Air humidity

Content

Air Humidity	08.02
Calibrating climatic chambers	08.03
Miniature multi-sensor module	08.07
Digital sensor for temperature, humidity, and atm. pressure FHAD 46-Cx	08.08
Digital sensor for temperature, humidity, and atm. pressure FHAD 46-C4xAx	08.09
Digital sensor for temperature, humidity, and atm. pressure FHAD 46-C2	08.10
High-precision sensor for temperature, humidity, atm. pressure FHAD 36 Rx	08.11
Capacitive humidity sensor FHA 646 R, miniature sensor	08.15
Digital sensor for measuring temperature and humidity FHAD 46-C7 compact screw fit sensor	08.16
Digital sensor for dew point, air humidity, temperature FHAD 46-DTC2	08.17
Digital psychrometer, FPAD 36-3	08.18
Digital psychrometers, FNAD 46	08.20
Digital temperature / humidity transmitter MH8D46	08.22

The Right Humidity Sensor for Any Measuring Task

For humidity measurements various methods are used that differ from each other mainly with regard to their accuracy and their suitability for long term measurements and the substance used for the measurement:

• Capacitive Air Humidity Measurement,

Capacitive Air Humidity Measurement

Capacitive sensors contain a glass substrate with a moisture sensitive polymer layer between two metal layers. By absorption of water, corresponding to the relative humidity, the dielectric constant and, as a result, the capacity of the thin-film capacitor are changing. The measuring signal is directly proportional to the relative humidity and does not depend on the atmospheric

Psychrometric Air Humidity Measurement

Psychrometers are precision devices containing a dry and a moistened temperature sensor. As a result of the evaporation the humidity sensor cools down, with a wind velocity of a minimum of 2m/s being required for the cool down process. The humidity values are calculated from the temperature difference (psychrometric difference). The calculation formulae for AL-MEMO[®] devices correspond to those used

Dew Point Determination with Dew Point Mirrors

An optically monitored mirror is mounted on a cascaded Peltier element. The sensor unit is also connected to a control circuit that regulates the operating current of the cooling element so that a defined condensate is established. The dew point temperature will be directly measured within

- Psychrometric Air Humidity Measurement,
- Hygrometric Air Humidity Measurement,
- Dielectric Measurement of Moisture in Materials,
- Measurement of the Moisture in Ma-

pressure.

Advantage:

- maintenance-free measurement over longer periods,
- can withstand temperatures below 0°C
- atm. pressure-independent, works when pressure is applied
- flexible use of the sensor

by the German Weather Authority related to 1013mbar. Differences regarding to the atmospheric pressure can be corrected to achieve precise measurements.

Advantage:

- no ageing of the sensor exception: contamination of the wick
- high accuracy

Advantage:

cibility

• high quality regarding the measuring technology

the sensor and can be output in a format,

· high accuracy, reliability and reprodu-

independent from atmospheric pressure

which allows for an evaluation.

terials According to the Principle of Conductivity,

- Dew Point Determination with CCC Dew Point Probes,
- Dew Point Determination with Dew Point Mirrors.

Disadvantage:

- limited long term stability
- sensitive to dewing and certain aggressive substances
- usable without problems up to 100% r.H. in all substances

Disadvantage:

- long term measurement limited by the required water reserve and wick maintenance
- difficult to use with temperatures below 0°C and with low humidities
- depending on the atmospheric pressure
- wide measuring range
- suitable for temperatures below 0°C

Disadvantage:

- high sophisticated measuring method
- high current consumption
- risk of contamination

Small Glossary for Humidity/Moisture Measurement Variables

Absolute Humidity	The absolute humidity indicates the weight of the water vapour contained in one m ³ of a mixture of air and water vapour.
Enthalpy	The enthalpy indicates how much heat is stored within the humid air. This value is important for calculating the cooling and heating performance, e.g. when checking heat exchangers.
Mixture Ratio	The absolute humidity related to 1kg dry air.
Relative Humidity	The relative humidity indicates the percentage of air, which is saturated with water vapour, i.e. how much percent of the maximum possible amount of water vapour is currently contained in the air. Owing to the dependence on temperature the relat. humidity can only ever be indicated for one specific temperature.
Saturation Vap. Pressure	Air can only ever contain a certain maximum amount of water vapour. This is called the saturation vapour pressure, specified as g water vapour per kg of humid air. The saturation vapour pressure strongly depends on the air temperature. At low temperatures it will be low and at high temperatures it will be high. Therefore, warm air can accept large amounts of vapour pressure and cold air only small amounts.
Dew Point	The dew point is the temperature where the relative humidity equals 100%. If the dew point is not reached the water vapour will start condensing.
Water Vap. Partial Press.	The total pressure in the room determined by the water vapour.
08.02	

Calibrating climatic chambers

ALMEMO[®] measuring system for calibrating climatic chambers as per guideline DAkkS-DKD-R 5-7



- Guideline DAkkS-DKD-R 5-7 lays down minimum requirements for the calibration procedure and for the determination of measurement uncertainties when calibrating climatic chambers.
- This guideline describes inter alia the objectives, procedures, and methods of calibration, and the uncertainty components involved.
- The full text of this guideline is available as a PDF document on the home

page of the Physikalisch-Technische Bundesanstalt (www.ptb.de --> Metrologische-Dienstleistungen --> DKD --> Publikationen) and can be downloaded free-of-charge.

Calibration of relative atmospheric humidity at nine points in the climatic chamber using precision measuring instrument ALMEMO[®] 710

The ALMEMO[®] measuring system, comprising precision measuring instrument ALMEMO[®] 710, one humidity sensor, and eight temperature sensors, can be used to acquire all relevant measurable variables prevalent in the climatic chamber. The relative atmospheric humidity at the nine points in the climatic chamber is calculated in the ALMEMO[®] 710 itself. Climatic chambers can thus be calibrated in full and on site quickly and easily.

Humidity is calculated in the ALMEMO[®] 710 on the basis of formulae as per Dr. Sonntag and the enhancement factor as per W. Bögel (correction factor Fw(t,p)) for real mixed gas systems). This substantially widens the measuring range and improves the accuracy of humidity variable calculations.

The determination of the radiation influence on the air temperature measurement is done with 2 temperature sensors with different sensor surface (different emissivity e.g. stainless steel and PTFE). With an ALMEMO[®] double sensor the 2 temperatures can be measured simultaneously (additionally) with the 8 temperatures of the corner points.

All values, both measured and calculated, are shown in a clear and easy-tounderstand way on the ALMEMO[®] 710's large touch display. The ALMEMO[®] 710 also operates as a data logger. Measuring series can be saved either to the internal memory (capacity for over 400,000 measured values) or via the ALMEMO[®] memory connector to an SD card (capacity for several millions of measured values).

WinControl can be used to display and document values e.g. as a line graphic - either online those measured values actually being acquired during a measuring operation or offline after a measuring operation those measured values previously saved. It also provides various evaluation and statistical functions.

Calibrating climatic chambers



The ALMEMO[®] measuring system comprises:

Precision measuring instrument ALMEMO® 710



10 inputs for any ALMEMO[®] sensors, atmospheric pressure sensor integrated in the measuring instrument.

Precision measuring instrument ALMEMO[®] 710 including USB cable, mains unit, instrument case, and configuration software ALMEMO[®] Control

MA710

Precision measuring instrument ALMEMO® 500

Data acquisition system, Tablet control via app. 20 measuring inputs for any ALMEMO[®] sensors (expandable).

Data logger ALMEMO® 500

CPU card including interfaces and web service. 4GB SD memory card. 2 active measuring circuit cards MA10 featuring 20 input sockets for all ALMEMO[®] sensors (standard, DIGI, D6, D7). Mains adapter Control unit with preinstalled app.In desktop housing TG6, 9 free slots MA500CPUA20TG6B

Calibrating climatic chambers

Digital Pt100 psychrometer with DAkkS calibration certificate	eN
Operative range 0 (not ice) to 90 °C, 10 to 100 % RH Built-in digital air pressure sensor: 700 to 1100 mbar The psychrometer is positioned at the center of the useful volume. From the measured values - dry temperature (t) and wet temperature (t_w) - and atmospheric pressure (p) (atmospheric pressure sensor integrated in the ALMEMO [®] connec- tor) we can calculate the relative humidity (U_w) at the center and the dewpoint (t_d).	
Digital Pt100 psychrometer FPAD 36-3 with ALMEMO [®] D6 connector, air pressure sensor installe including mains unit, water bottle, one pair of wicks, carrying case Programming for digital psychrometer: Dew point td DAkks calibration certificate for atmospheric humidity	rd, FPA8363 OA9000PRTD
Two climate points at 25°C, 30%RH and 25°C, 75%RH (other points available on request) DAkkS calibration certificate for air pressure sensor, 5 points in the range 7001100 mb	KH9146D KD9213D
Eight Pt100 temperature sensors with DAkkS calibration certificate	
for operation in the climatic chamber stainless steel protective tube with PFA cable. Operative range -100 to +250 °C, Protective class IP68 The eight temperature sensors are positioned at the corners of the cuboid spanning the useful volume. From the eight measured values for temperature (t) and the humidity variables from the psychrometer we can calculate the relative humidity values (U_w) at the corners of the cuboid	
Eight Pt100 temperature sensors, diameter 4mm, for operation in the climatic chamber,IP68, Cable length = 5 meters8 x	: FPA40ST0050S01KL0050
DAkks calibration certificate for temperature, three points at 0, 50, 100 °C (other points available on request) for 1st sensor for 2nd to 8th sensor Multi-point adjustment for eight sensors (in certificate, sensor deviation virtually reduced to zero)	1 x KT9021D 7 x KT9021D2 8 x KT9001DW
Programming for eight Pt100 temperature sensors for calculating humidity using ALMEMO [®] 710 including labeling of the sensor connector	OA9000PRKS
Cube for positioning temperature sensors: Wire cube, VA wire Ø4 mm. edge length 300 mm, vertices welded. Including spiral hoses to fix the sensor cables.	ZB1002Q01
Determination of the influence of radiation	ew
Two temperature sensors with different surfaces to determine the radiation effects on air temperatur (different emissivity e.g. stainless steel and PTFE)	re measurement operations.
Cover for Pt100 temperature sensor, diameter 4mm, PTFE, large emissivity	ZT9000TS41
With an ALMEMO [®] double sensor, the 2 temperatures can be measured simultaneously (additional of the corners.	lly) with the 8 temperatures
2 Digital Pt100 temperature sensors, diameter 4 mm each, for use in climatic cabinet, IP68, cable length 5 m each, mounted on 1 ALMEMO® D7 double connector IDAkkS calibration certificate for temperature, 3 points at 0 / 50 / 100 °C (other points on request) for 1st sensor for 2nd sensor Multi-point adjustment for 2 probes (with certificate probe deviation towards zero)	FPD740ST0050S21KL0050 KT9021D KT9021D2 2 x KT9001DW
Measuring software WinControl	

WinControl software, for measured value processing and documentation for any number of channels	
(i.a. arithmetic channels, statistic channels),	
all options included (except Data server, Web server, and additional modules)	SW5600WC3
Assistant for the calibration of climate cabinets.	
Automatic, convenient evaluation with protocol generation. (needed: WC3/WC4)	SW5600WCZM13
Additional protocol for direct integration of climate chambers into online measurement	SW5600WCZM7

Air humidity

Sensor posi- tion	Measuring point	Variable	Note
Spatial center	0.0	t (dry temperature)	measuring channel -psychrometer
	0.1	U _w (humidity)	arithmetic channel (psychrometer)
	0.2	t _d (dewpoint)	arithmetic channel (psychrometer)
	0.3	p (atmospheric pressure)	device-internal atmospheric pressure sensor
Corner 1	1.0	t (temperature Pt100)	measuring channel (Pt100)
	1.1	U _w (humidity)	arithm. channel (humidity from Pt100 and psychrometer)
Corner 2	2.0	t (temperature Pt100)	measuring channel (Pt100)
	2.1	U _w (humidity)	arithm. channel (humidity from Pt100 and psychrometer)
Corner 3	3.0	t (temperature Pt100)	measuring channel (Pt100)
	3.1	U _w (humidity)	arithm. channel (humidity from Pt100 and psychrometer)
Corner 4	4.0	t (temperature Pt100)	measuring channel (Pt100)
	4.1	U _w (humidity)	arithm. channel (humidity from Pt100 and psychrometer)
Corner 5	5.0	t (temperature Pt100)	measuring channel (Pt100)
	5.1	U _w (humidity)	arithm. channel (humidity from Pt100 and psychrometer)
Corner 6	6.0	t (temperature Pt100)	measuring channel (Pt100)
	6.1	U _w (humidity)	arithm. channel (humidity from Pt100 and psychrometer)
Corner 7	7.0	t (temperature Pt100)	measuring channel (Pt100)
	7.1	U _w (humidity)	arithm. channel (humidity from Pt100 and psychrometer)
Corner 8	8.0	t (temperature Pt100)	measuring channel (Pt100)

Guideline DAkkS-DKD-R 5-7 The following section includes extracts from the guideline.

U, (humidity)

U_ (humidity)

t (temperature Pt100)

Guideline DAkkS-DKD-R 5-7 Calibration of climatic chambers

(...)

4 Objectives of calibration

The calibration of a climatic chamber determines any deviation between the values displayed by the chamber indicators and the climatological variables, air temperature and relative humidity, measured in those parts of the chamber volume provided for use or at individual points in the chamber volume. (...)

arithm. channel (humidity from Pt100 and psychrometer)

measuring channel (Pt100), low emissivity (e.g. stainless steel surface)

measuring channel (Pt100), high emissivity (e.g. surface PTFE)

The objectives of calibration are thus the following :

8.1

9.0

9.1

Calibration of the indicators for temperature and relative humidity by comparison with values for air temperature and atmospheric humidity measured in the useful space using reference equipment (also specifying any such deviation and the necessary corrections. (...)

6 Calibration methods

(...)

(A) Calibration refers to the useful volume as spanned by the measuring locations in the unloaded climatic chamber. (...) (B) Calibration refers to the useful volume as spanned by the measuring locations in the unloaded climatic chamber. The climatic chamber can be loaded in line with the user's typical application or by filling at least 40 percent of the useful volume with test pieces.

(...)

7 Calibration procedures

7.1 Arrangement of measuring locations

(...) For chamber volumes of up to 2000 liters the requirements regarding the number and spatial positioning of the measuring points are as per DIN EN 60068, 3-5; i.e. the measuring locations are the corner points and the spatial center of the cuboid spanning the useful volume. (...)

The calibration result is only valid for that volume spanned by the measuring points. (...)

7.6 Humidity calibration

For the purpose of calibrating relative humidity in a climatic chamber subject to air circulation the absolute humidity and dewpoint Td or frost point Tf can be determined in the center of the useful volume and the spatial distribution of relative humidity can be calculated on the basis of the measured air temperature distribution. (...)
Miniature multi-sensor module for measuring temperature, humidity, and pressure with integrated EEPROM FH0D 46-C



Our new plug-in digital multi-sensor module - with its miniature design and extremely low energy consumption - combines the measurable variables - temperature, atmospheric humidity, and atmospheric pressure. It takes a complete reading of all these ambient parameters and can thus accurately determine all humidity-related and pressure-dependent variables, e.g. the frequently needed mixture ratio (r).

It communicates its findings via an I²C interface; the user can selectively access individual sensor variables and data saved to the integrated EEPROM.

Before leaving our factory the sensor module is adjusted and assigned an electronic identification code that can be read out on

receipt of the appropriate command. The integrated EEPROM can be used to save the user's own adjustment data, fine tuning, or electronic ID data (ID number, comments text, etc.). Since the saved parameters are retained in the EEPROM, a multisensor module can only be exchanged or replaced with modules that are identically calibrated and have all the same data.

The module is specially designed with very good thermal isolation to withstand temperature influence / thermal conduction and thus ensure that all variables are measured precisely. This system - unlike analog measured value processing - virtually excludes the risk of varying line lengths or disturbance factors adversely affecting the accuracy of measured results.

Technical data

Temperature range	-40 to +85 °C
Accuracy	+5 to +60 °C, typical ±0.2 K +5 to +60 °C, maximum 0.4 K -20 to +85 °C, maximum 0.7 K
Reproducibility	typical ±0.1 K
Humidity range Accuracy	5.0 to 98.0 % RH 10 to 90 % RH, maximum ±2 % RH at 23 °C ±5 K 5 to 98 % RH, maximum ±4 % RH at 23 °C ±5 K
Hysteresis	typical ±1 % RH
Pressure range Accuracy	300 to 1100 mbar 700 to 1100 mbar, ±2.5 mbar at 23 °C ±5 K
Internal memory	two-wire serial EEPROM 4 kbit (512 x 8 bit)

I ² C interface			
Data rate	0 to 400 kHz		
Sampling rate	2/sec at highest resolution		
Electrical data			
Power supply	2.1 to 3.6 V, typical 3.3 V		
Current consumption	during measuring typical 310 µA		
	in standby typical 0.35 µA		
Energy consumption	during measuring typical 1.02 mW		
	in standby typical 1.16 μW		
Connection	male strip connector, 4-pin,		
	spacing 1.27 mm see pin assignment		
lead-free, halogen-free, and RoHS-compliant			
(restriction of hazardous substances)			

Pin assignment

1
1 SDA
2 VCC
3 GND
 4 SCL

Dimensions



Variants

packaging unit 100 pieces

Miniature multi-sensor module for, humidity, temperature, and pressure with integrated EEPROM packaging unit 1 piece packaging unit 10 pieces Order no.

FH0D46C FH0D46CVE0010 FH0D46CVE0100

Digital sensor for temperature, humidity, and atmospheric pressure FHAD 46-Cx



Example: ALMEMO[®] D6-sensor FHAD 46-C41

Common technical features FHAD 46-Cx

- All sensors in 1 multi-sensor module: capacitive digital sensor for humidity and temperature, digital atmospheric pressure sensor. Additional EEPROM data storage medium in the sensor module.
- The sensor module is thoroughly adjusted. All sensor characteristic and adjustment data are stored on the data storage medium of the sensor module itself. In the process of readjusting the individual sensors the adjustment values are directly saved on the data storage medium of the sensor module.
- *new:* Every sensor module has an unique serial number saved on the humidity sensor. The serial number is either displayed in the sensor menu of the measuring instrument or in the ALMEMO[®] Control software. Hence, calibrated sensor modules can clearly be assigned to the calibration certificate.
- Replacement sensor modules are inexpensive: The sensor module is pluggable and can simply be exchanged on-site. Full accuracy without any adjustment, especially with calibrated sensors. The ALMEMO[®] connecting cable and the ALMEMO[®] measuring instrument have no influence on the calibration.
- new: The atmospheric pressure is measured directly at the measuring point in the sensor tip. Hence, the atmospheric pressure dependent humidity variables are automatically pressure compensated.

Digital sensor for temperature, humidity, and atmospheric pressure FHAD46-Cx, with ALMEMO[®] D6 plug *new:* atmospheric pressure sensor integrated in the multi-sensor module, for automatic atmospheric pressure compensation

• All relevant ambient parameters are measured with just one sensor.

- Humidity calculation on the basis of formulae as per Dr. Sonntag and the enhancement factor as per W. Bögel (correction factor fw(t,p) for real mixed gas systems) This substantially widens the measuring range and improves the accuracy of humidity variable calculations.
- *new:* Humidity variable : Absolute humidity in g/m³
- The humidity variables are calculated from the three primary measuring channels (real measurable variables). temperature, relative humidity, atmospheric pressure
- Freely selectable measurable variables
- Four measuring channels are programmed (at our factory). temperature (°C, T, t), relative humidity (%H, RH, Uw), dewpoint (°C, DT, td), atmospheric pressure (mbar, AP, p) Other humidity variables can also be selected. mixture (g/kg, MH, r), absolute humidity (g/m³, AH, dv), vapor pressure (mbar, VP, e), enthalpy (kJ/kg, En, h) The configuration is performed on the ALMEMO[®] V7 measuring instrument or directly on the PC using the USB adapter cable ZA1919AKUV (see chapter "ALMEMO[®] Network technology").

Digital temperature / humidity sensor (including A/D converter)		Accuracy	typical ± 0.2 K at 5 to 60 °C	
Operative range	depending on sensor type	_	maximum ±0.4 K at 5 to 60 °C	
Humidity		_	maximum ± 0.7 K at -20 to +80 °C	
Measuring range	0 to 98 % RH	Reproducibility	typical ± 0.1 K	
Sensor	CMOSens [®] technology	Response time T ₆₃	typical 20 seconds (without filter)	
Accuracy	± 2.0 % RH in range 10 to 90 % RH ± 4.0 % RH in range 5 to to 98 % RH at nominal temperature typical ± 1 % RH ± 23 °C ± 5 K re Atmospheric pressure	ALMEMO [®] connecting cable PVC; Length (see variants) with ALMEMO [®] D6 plug <i>new</i> FHAD 46-C4xAx silicone		
Hysteresis Nominal temperature Sensor operating pressure		Digital atm. pressure sens Measuring range Accuracy	or (integrated in the multi-sensor module) 700 to 1100 mbar ±2.5 mbar (at 23 °C ±5 K)	
Response time I_{63}	(without filter)	ALMEMO [®] D6 plug	1 seconds for all four shannals	
Temperature Sensor	CMOSens® technology	Supply voltage Current consumption	6 to 13 VDC 3 mA	

DAkkS or factory calibration KH9xxx temperature, humidity for digital sensor (see chapter "Calibration certificates"). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Digital sensor for temperature, humidity, and atm. pressure FHAD 46-C4AG in protective all-weather housing cable length up to 100 meters with ALMEMO[®] D6 plug



Common technical data FHAD 46-Cx

10/2021 • We reserve the right to make technical changes

Air humidity

Digital sensor for temperature, humidity, and atm. pressure FHAD 46-C4xAx Version in stainless steel, with protective cap with ALMEMO[®] D6 plug





Replacement multi-sensor module FH0D 46-C

Technical features

• *new* extended operating temperature range.

• new Silicone connecting cable.

• Four measuring channels are programmed (at our factory). temperature (°C, T, t), relative humidity (%H, RH, Uw), dewpoint (°C, DT, td), atmospheric pressure (mbar, AP, p)

Technical data

Operative range	-40+85 °C / 598 % RH		Length (see variants)
Mechanical design	Stainless steel, diameter 12 mm	Protective cap Screw-fit cable gland	slotted, open cap, SK10 Splash-protected
	,	General description and o	common technical data see FHAD 46 Cx

Variants including manufacturer's test certificate

Digital sensor for temperature, humidity, and atmospheric pressure, protective cap, stainless steel tube, with fitted cable and ALMEMO® D6 plug.

Sensor length 160 mm, Connecting cable, length 2 meters Sensor length 160 mm, Connecting cable, length 5 meters Sensor length 160 mm, Connecting cable, length 10 meters Sensor length 270 mm, Connecting cable, length 2 meters Sensor length 270 mm, Connecting cable, length 5 meters Sensor length 270 mm, Connecting cable, length 10 meters Sensor length 530 mm, Connecting cable, length 2 meters Sensor length 530 mm, Connecting cable, length 5 meters Sensor length 530 mm, Connecting cable, length 10 meters Replacement multi-sensor module, digital, adjusted, plug-in

FHAD46C41A FHAD46C41AL05 FHAD46C41AL10 FHAD46C42A FHAD46C42AL05 FHAD46C42AL10 FHAD46C43A FHAD46C43AL05 FHAD46C43AL10 FH0D46C

Order no.

Prote	ective caps		SK10	SK7	SK6	SK8
Dimens length a	sions : approx. 33 mm, diameter 1	12 mm				
	Designation	Pore size	max. temp.*	Typical Application		Order no.
SK10	slotted, open cap without filter	open	100°C	short response time, no dirt load		ZB9600SK10
SK7	Metal-mesh filter in PC-housing	100 µm	120°C	Universal, for medium, contamination, also high	h humidity	ZB9600SK7
SK6	PTFE-Sinterfilter	50 µm	180°C	High chemical resistance	ce	ZB9600SK6
SK8	Stainless steel sinter filter	10 µm	180°C	For severe mechanical s heavy contamination, st	stress, trong air flow	ZB9600SK8

* Observe application range

Accessories

ZB9600W

Brackets for wall mounting, distance from wall approx. 40 mm



with plastic sealing ring ZB9600KV20 Connecting flange for screw connection, hole circle 38 mm Ø ZB9600F20



Digital sensor for temperature, humidity, and atmospheric pressure FHAD 46-C2 Version in plastic, with slotted sensor cap with ALMEMO[®] D6 plug



• Four measuring channels are programmed (at our factory). Temperature (°C, T, t), Relative humidity (%H, RH, Uw)

Technical data

Operative range	-20 to +60 °C / 5 to 98 % RH	Extension tube	Ø 8 mm, length 97 mm
Mechanical design			
Sensor cap Plug connection	Ø 8 mm, length 36 mm Ø approx. 9 mm, IP40	General description and common technical data see Fl	

Variants including manufacturer's test certificate

Digital sensor for temperature, atmospheric humidity, and atmospheric pressure, with multi-sensor module in slotted sensor cap, plug connector, including ALMEMO® connecting cable with coupling and ALMEMO® D6 plug. Connecting cable, length 2 meters Connecting cable, length 5 meters Connecting cable, length 10 meters FHAD46C2L10 Cable stub approx. : 80 mmFHAD46C2L00(incl. multi-sensor module)FHAD46C2L00Spare sensor element for FHAD462, digital, enclosed in slottedsensor cover, adjustedFH0D46C2Extension tube, Ø 8 mm, length 97 mm,plug-in, for FHAD 46-C2ZB0D462VR

Replacement multi-sensor module FH0D 46-C2

Dewpoint (°C, DT, td)

Atmospheric pressure (mbar, AP, p).

Extension tube

Order no.

Digital sensor for temperature, humidity, and atm. pressure FHAD 46-C0 Uncovered multi-sensor module with ALMEMO[®] D6 plug

FHAD 46-C0 Uncovered multi-sen most compact design	sor module , short response time	Replacement multi-sensor module FF	10D 46-C
• Four measuring ch Temperature (°C, 1	annels are programmed (at our factory). ', t), Relative humidity (%H, RH, Uw)	Dewpoint (°C, DT, td), Atmospheric pressure (mbar, AP, p).	
rechnical data			
Operative range	-20 to +80 °C / 5 to 98 % RH	_ Multi-sensor module (dimensions over all) a	pprox. 6 x 14 x 3 mm
Mechanical design		Plug connection Width approx.	7 mm
Variants includi	ng manufacturer's test certificate		Order no.
Digital sensor for te pressure, with unco	mperature, humidity, and atmospheric vered multi-sensor module, plug connec-	Connecting cable, length 10 meters Replacement multi-sensor module.	FHAD46C0L10
tor, including ALMI ALMEMO [®] D6 plu	EMO^{e} connecting cable with coupling and \underline{g} .	digital, adjusted, plug-in	FH0D46C
Connecting cable, le	Ength 2 meters FHAD46C0		
Connecting cable, le	ength 5 meters FHAD46C0L05		

High-precision sensor for temperature, humidity, atmospheric pressure FHAD 36 RAx Wide operating temperature range Automatic atmospheric pressure compensation Digital sensor with ALMEMO[®] D6 plug



(example FHAD 36 RAS)

General features. ALMEMO® D6 sensors see page 01.08

Common technical features FHAD 36 RAx

- Digital capacitive humidity sensor with integrated signal processor, designed to meet the highest accuracy requirements in humidity measurement
- Unique correction and adjustment process All sensor characteristics and adjustment data are saved in the humidity sensor itself.
- A digital atmospheric pressure sensor integrated in the ALMEMO[®] D6 plug itself provides automatic pressure compensation for all pressure-dependent humidity variables.
- Humidity calculation on the basis of formulae as per Dr. Sonntag and the enhancement factor as per W. Bögel (correction factor fw(t,p) for real mixed gas systems) This substantially widens the measuring range and improves the accuracy of humidity variable calculations.
- Humidity variable, Absolute humidity in g/m³

- All relevant ambient parameters are measured with just one sensor.
- The humidity variables are calculated from the three primary measuring channels (real measurable variables). temperature, relative humidity, atmospheric pressure
- Freely selectable measurable variables
- Four measuring channels are programmed (at our factory). temperature (°C, T, t), relative humidity (%H, RH, Uw), dewpoint (°C, DT, td), atmospheric pressure (mbar, AP, p) Other humidity variables can also be selected: mixture (g/kg, MH, r), absolute humidity (g/m³, AH, dv), vapor pressure (mbar, VP, e), enthalpy (kJ/kg, En, h) This device can be configured directly on a PC using USB adapter cable ZA 1919 AKUV. (see chapter "Networking").
- The recommended application range for capacitive sensors is up to dew point temperatures in the range of 80°C td. Measurements at high humidity and high temperatures can lead to a larger sensor drift with capacitive sensors. Permanent changes in sensor characteristics can be caused by chemical / physical processes. Contamination in the measuring medium and falling below the dew point temperature (in extreme climates), can further intensify this effect.

Common technical data FHAD 36 RAx

Digital temperature / humic Operative range	lity sensor (including A/D converter) depending on sensor type	Sensor connector on the se Plug connector (Material	ensor / sensor cable s : anticorodal aluminum, anodized) IP65
Humidity Sensor Measuring range	capacitive 0 to 100 % RH	Operative range of the ele in the connecting cable (c in the grip (of hand-held	ectronics coupling) -40 to +90 °C sensors) -40 to +85 °C
Adjusted Accuracy Reproducibility Response time T ₆₃	at +23 °C and 10%, 35%, 80% RH ±1.3 % RH (at +23°C ±5 K) 0.3 % RH typical 15 seconds at typical 1 m/s	ALMEMO [®] connecting ca Coupling (length = 100 m (Materials : TPU, -40 to - Digital atm. pressure sens	able nm) with cable, length = 2 or 5 meters +90 °C) with ALMEMO [®] D6 plug or (integrated in ALMEMO [®] D6 plug)
Temperature	(without filter)	 Measuring range Accuracy 	700 to 1100 mbar ±2.5 mbar (at 23 °C ±5 K)
Sensor Measuring range Accuracy at +23 °C ±5 K	Pt100 -100 to +170 °C Please observe operative range ! (depending on sensor type) ±0.2 K	ALMEMO [®] D6 plug Refresh rate Supply voltage Current consumption	1 second for all four channels 6 to 13 VDC 12 mA
Reproducibility	0.05 °C		

DAkkS or factory calibration KH9xxx temperature, humidity for digital sensor (see chapter "Calibration certificates"). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Air humidity

Order no.

High-precision sensor for temperature, humidity, atmospheric pressure FHAD 36 RAS Automatic atmospheric pressure compensation. Digital sensor with ALMEMO® D6 plug



General description and common technical data FHAD 36 Rx (see page 08.11)

Technical data

Operative range	-50 to +90 °C		Filter cartridge	Polycarbonate	
Housing material	Polycarbonate		Filter	Polyethylene	
Accessorie		Order no			
Accessone					
Brackets for wall mount	ting (see page 08.05)	ZB9600W			

Variants Including factory test certificate and polyethylene filter

High-precision digital temperature / humidity sensor, with plug connector, including ALMEMO® connecting cable with coupling and ALMEMO® D6 plug, and integrated digital atmospheric pressure sensor Connecting cable, length 2 meters FHAD36RAS Same as above Connecting cable, length 5 meters FHAD36RASL05

Filters	
for FHAD 36-RAS	
Variants	Order no.
Filter insert made from polyethylene with a polycarbonate filter cartridge for standard applications	
good response time and good protection against fine particulates	ZB9636APE
Filter insert made from stainless-steel wire fabric with a polycarbonate filter cartridge quickest response time not suitable for environments that are bioactive or contaminated with fine particulates (risk of congestion) Filter insert made from PTEE (polytetrafluoroethylene) with a polycarbonate filter cartridge	ZB9636AWM
good protection against fine particulates, high chemical resistance, slower response time	ZB9636APTFE

100 March 1

High-precision sensor for temperature, humidity, atmospheric pressure FHAD 36 RAIC Industrial-standard design for high temperatures up to +170 °C Automatic atmospheric pressure compensation. Digital sensor with ALMEMO[®] D6 plug



General description and common technical data FHAD 36 Rx (see page 08.11)

Technical data

Operative range	-100 to +170 °C	Filter cartridge	Stainless steel 1.4301
Sensor length	144 mm incl. sensor	Filter	Stainless-steel wire fabric filter
(Other lengths 294	mm are available on request.)	Electronics	length: 111 mm
Housing material	PEEK		

Accessories		Order no.
Assembly screw fittings for 15 mm sensor Brass, nickel-plated Thread M20x1.5 Viton [®] seal, up to +200 °C ZB9636KV	Mounting flange Steel, nickel-plated Diameter 80 mm	ZB9636F

 Variants
 Including factory test certificate and stainless-steel wire fabric filter
 Order no.

 High-precision digital temperature / humidity sensor, industry-standard, with high-temperature
 sensor cable and plug connector, including ALMEMO® connecting cable with coupling and ALMEMO® D6 plug

 Integrated digital atmospheric pressure sensor
 FHAD36RAIC102

 Same as above
 Sensor cable, length = 2 meters, Connecting cable, length 2 meters
 FHAD36RAIC102

 Same as above
 Sensor cable, length = 5 meters, Connecting cable, length 2 meters
 FHAD36RAIC105

 Same as above
 Sensor cable, length = 2 meters, Connecting cable, length 5 meters
 FHAD36RAIC102L05

 Same as above
 Sensor cable, length = 5 meters, Connecting cable, length 5 meters
 FHAD36RAIC102L05

 Same as above
 Sensor cable, length = 5 meters, Connecting cable, length 5 meters
 FHAD36RAIC102L05

 Same as above
 Sensor cable, length = 5 meters, Connecting cable, length 5 meters
 FHAD36RAIC102L05

 Same as above
 Sensor cable, length = 5 meters, Connecting cable, length 5 meters
 FHAD36RAIC105L05

Filter		
for sensors with filter cartridge for FHAD 36 RAIC		
Variants		Order no.
Stainless-steel wire fabric filter quickest response time not suitable for environments that are bioactive or contaminated with fine particulates (risk of congestion) Stainless-steel sinter filter best protection in environments heavily contaminated with particulates good response time for low humidities (not to be used for high humidities) PTFE filter good protection against fine particulates, high chemical resistance, slower response time		ZB9636AIWM ZB9636AISSS ZB9636AIPTFE

Other designs are available on request

FHAD 36-RAIMx : Industry-standard humidity sensor FHAD 36 RAIM in stainless steel Diameter 15 mm, -100 to +170 °C FHAD 36-RAIEx : Screw-fit humidity sensor FHAD 36 RAIE, up to 100 bar, stainless steel Thread G 1/2-inch, -100 to +170 °C



High-precision sensor for temperature, humidity, atmospheric pressure FHAD 36 RHK Hand-held sensor for temperatures up to +170 °C Automatic atmospheric pressure compensation, Digital sensor with ALMEMO[®] D6 plug



FHAD 36-RHSx :

Humidity probe with flat blade 18 x 4 mm for taking meas. in paper or textile stacks, -40 to +85 °C

High-humidity sensor FHAD 36-E33x available on request

Digital humidity and temperature sensor for high humidity application. Humidity sensor with heatable monolithic measurement cell for measurement operations in the high-humidity range near condensation.

• Compact sensor, extremely small dimensions

- Wide operating temperature range
- Particularly suitable for measuring operations between PCBs,

Technical data

inside cases, in walls, ceilings, and insulation layers used in the construction industry, and for the protection of listed historic monuments

Operative range	-30 to +100 °C, 5 to 98 % RH	Temperature measuring circuit	
Humidity measuring circuit Measuring range 0 to 100 % RH Sensor capacitive Accuracy ±2 % RH in the range <90 % RH	SensorNTC type NAccuracy-20 to 0 ± 0.4 K, 0 to +70+70 to +100 \pm 0.6 KReproducibility0.1 K	NTC type N -20 to 0 ±0.4 K, 0 to +70 ±0.2 K +70 to +100 ±0.6 K 0.1 K	
Reproducibility Nominal temperature Response time T63	at nominal temperature <1% RH at nominal temperature +25 ±3 °C approx. 10 seconds at 1 m/s	Mechanical design Sensor tube Protective cap Cable	nickel-plated, 50 mm long, 5 mm Ø None High-temperature cable (up to +100 °C), 2 meters long, with ALMEMO [®] plug (no other lengths available)

The sensor can only be operated by plugging DIRECTLY onto an ALMEMO[®] device. (NOT with extension cables ZA9060VKx or ZA9090VKCx). Or, alternatively, the following sensor types can be used. FHAD36RAS up to +100 °C (see page 08.08) FHAD46-C2 or FHAD46-C0 Compact design (see page 08.06)

Accessories	Order no.
PTFE filter, inside diameter 5 mm suitable for protection against dust, not water-proof	ZB9646SKR

Variants

Order no.

FHA646R

Miniature sensor for temperature / humidity, with fitted high-temperature cable, length 2 meters, with ALMEMO[®] plug

DAkkS or factory calibration KH9xxx temperature, humidity for measuring chain (sensor + device) (see chapter "Calibration certificates"). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

ZB96467AP

ZB9600SK6

ZB9600SK8

Digital sensor for measuring temperature and humidity FHAD 46-C7,



- · Compact sensor made from stainless steel
- · Screw thread, for pressure pipes
- Option adapter for compressed air pipes
- Capacitive digital sensor for humidity and temperature. Additionally EEPROM data storage medium in the multisensor module.
- The sensor module is thoroughly adjusted. All sensor characteristic and adjustment data are stored on the data storage medium of the sensor module itself. In the process of readjusting the individual sensors, the adjustment values are directly saved on the data storage medium of the sensor module.
- *new:* Every sensor module has an unique serial number saved on the humidity sensor. The serial number is either displayed in the sensor menu of the measuring instrument or in the ALMEMO[®] Control software. Hence, calibrated sensor modules can clearly be assigned to the calibration certificate.
- Replacement sensor modules are inexpensive: The sensor

Pressure-sealed variant up to 16 bar, with ALMEMO[®] D6 plug

module is pluggable and can simply be exchanged on-site. Full accuracy without any adjustment, especially with calibrated sensors. The ALMEMO[®] connecting cable and the ALMEMO[®] measuring instrument have no influence on the calibration.

- The humidity variables are calculated from the two primary measuring channels (real measurable variables): temperature, relative humidity
- Three measuring channels are programmed: temperature (°C, T, t), relative humidity (%H, RH, Uw), dewpoint (°C, DT, td) One further humidity variable can also be selected: mixture(g/kg,MH,r), absolutehumidity(g/m³,AH,dv), vapor pressure (mbar, VP, e), enthalpy (kJ/kg, En, h) The configuration of the channels and the input of the system pressure for the automatic pressure compensation of the pressure dependent humidity variables is performed on the ALMEMO[®] V7 measuring instrument or directly on the PC using the USB adapter cable ZA1919AKUV (see chapter "ALMEMO[®] Network technology").

Technical data

Operative range	-20 to +80 °C, 5 to 98 % RH	ALMEMO [®] connecting	cable
Digital temperature / hu	midity sensor (including A/D converter)	PVC Length (see varia	nts) with ALMEMO® D6 plug
Humidity Measuring range Sensor Accuracy	0 to 98 % RH CMOSens [®] technology +2 0 % RH in range 10 to 90 % RH	ALMEMO [®] D6 plug Refresh time Supply voltage Current consumption	1 second for all four channels 6 to 13 VDC 3 mA
Hysteresis Nominal temperature Sensor operating pressi	± 4.0 % RH in range 5 to to 98 % RH at nominal temperature typical ± 1 % RH ± 23 °C ± 5 K are up to 16 bar	Mechanical design Sensor Filter cap Process connection	Stainless steel, diameter 12 mm Overall length approx. 77 mm PTFE sinter filter SK6 Male thread G 1/2-inch
Temperature Sensor Accuracy	CMOSens [®] technology typical ±0.2 K at 5 to 60 °C	Screw-fit cable gland	Fitted length 48 mm, Width across flats 27 Splash-protected
Reproducibility	maximum ±0.4 K at 5 to 60 °C maximum ±0.7 K at -20 to +80 °C typical ±0.1 K		Adapter for compressed air pipes
Accessories			🐨 Order no.

Accessories Adapter for compressed air pipes PTFE sinter filter (spare) (see page 08.09) Stainless-steel sinter filter (see page 08.09)

Variants	Order no.
with fitted cable and ALMEMO [®] D6 plug, manufacturer's test certificate Connecting cable, length 2 meters Connecting cable, length 5 meters Connecting cable, length 10 meters Replacement sensor element, digital, adjusted, plug-in	FHAD46C7 FHAD46C7L05 FHAD46C7L10 FH0D46C

DAkkS or factory calibration KH9xxx, temperature, humidity, for digital sensor (see chapter "Calibration certificates"). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.



Air humidity

Digital sensor for dew point, air humidity, temperature FHAD 46-DTC2, Pressure-sealed variant with screw thread, with ALMEMO® D6 plug





Technical features

- The dew point sensor is intended for continuous monitoring of Alternatively: Installing the sensor via the thread G 1/2" the dew point in industrial applications. Compressed air systems (refrigerant and adsorptions dryers), pellet dryer, medical gases, non corrosive gases, e.g. Nitrogen.
- High accuracy when measuring the dew point temperature.
- Reliably measuring the dew point in clean, dry, and oil-free gases and compressed air.
- Recommended installation of the sensor indirectly through the measuring chamber (accessory). The measuring chamber is connected to the compressed air pipe via the quick-coupling. Advantage: Simple installation and removal of the sensor (under operating pressure in the line). Fast response time of the sensor thanks to the perforated protective cap and the controlled flow. Protected installation of the sensor. For oily and dirty compressed air, a prefilter can be used in front of the measuring chamber (provided by the customer).
- directly into in the dryer respectively the compressed air pipe. Using the sintered stainless steel filter.
- The dew point sensor is also available with a process connection for high pressures (up to 350 bar) (option).
- The sensor will be supplied in a robust industrial housing.
- The digital dew point sensor works with an integrated AD converter. The measured values are calculated within the sensor and are digitally transmitted via the ALMEMO® D6 plug to the ALMEMO[®] device.
- 3 measuring channels are preprogrammed: Temperature (°C, t), Relative Humidity (%H, Uw), Dew point (°C, td).
- The overall accuracy of the digital ALMEMO® dew point sensor is independent from the ALMEMO® display device / data logger and from extension cables used.

Technical data:

Measuring range:	-80 °C to +20 °C td dew point temperature	Storage temperature:	-40 to 80 °C
Accuracy at 23 °C:	± 1 °C td from -20 to +20 °C td	Output:	digital, plug connection
± 2 °C ta from -50 to -20 °C ta ± 3 °C td from -80 to -50 °C td	Power supply:	via ALMEMO [®] D6 plug	
Nominal conditions:	23 °C ±5 K, pressure: 6 bar	with ALMEMO [®] D6 plug	
Measuring channels: Temperature: Relative humidity: Dew point:	-20.0 to +70.0 °C 0 to 9.0 % RH -80.0 to +20,0 °C td	ALMEMO [®] D6 plug: Refresh time: Supply voltage: Current consumption:	0.5 sec. for all 3 channels 6 to 13 V DC typical 20 mA
Operating temperature:	-20 to +70 °C, recommended: 0 to 50 °C	Housing:	
Process connection:	screw thread G1/2" stainless steel	Material:	zinc alloy
Protective cap:	sintered stainless steel filter (50 µm)	Protection class:	IP65
Pressure range:	-1 to 50 bar standard		

Accessories



Screw-on measuring chamber for connecting a dew point transmitter to compressed air pipes ZB9646DTCK via quick coupling, up to a maximum of 16 bar, including perforated protective cap Advantage: fast measurement without installation costs.

Option

Dew point sensor for process pressure up to 350 bar

Variants including factory calibration certificate

Digital sensor for dew point, air humidity, temperature, pressure-sealed variant with screw thread sintered stainless steel filter, plug connection, ALMEMO® connection cable 2 m with ALMEMO® D6 plug Factory calibration certificate KH93xx, dew point, for digital sensors (see chapter "Calibration certificates")

Order no.

FHAD46DTC2

OA9646DTC2P

Order no.



Digital psychrometer, FPAD 36-3 with ALMEMO[®] D6 plug with integrated atmospheric pressure sensor, for automatic pressure compensation



- *new:* Digital temperature sensors (adjusted) with high precision and synchronism up to 90 °C.
- *new:* Automatic air pressure compensation with built-in air pressure sensor.
- *new:* Flexible, thin, stable sensor cable.
- Version optimized for long-term measuring operationsAutomatic humidification of the wick after filling the water
- tank.

General features of ALMEMO® D6 sensors: see page 01.05

Technical data and functions

• *new:* The two digital Pt100 sensors for dry temperature and wet temperature are characterized by particularly high precision and synchronism up to 90 °C.

The Pt100 sensors are connected to the digital ALMEMO[®] D6 connector (as a complete measuring chain) adjusted at 0 °C and 85 °C in the calibration laboratory. The accuracy of the temperature measurement is thus independent of the ALMEMO[®] measuring instrument. The two digital Pt100 sensors are easily exchangeable in case of service.

- *new*: Flexible, thin, stable sensor cable with shielding and insulation FEP.
- *new:* The digital psychrometer can be operated with any ALMEMO[®] measuring instrument without affecting its measuring accuracy. The digital psychrometer is calibrated without ALMEMO[®] device.
- *new:* A digital atmospheric pressure sensor integrated in the ALMEMO[®] D6 plug itself provides automatic pressure compensation for all pressure-dependent humidity variables.
- *new:* Humidity calculation (Calculation is done in the ALMEMO[®] D6 connector) on the basis of formulae as per Dr. Sonntag and the enhancement factor as per W. Bögel (correction factor fw(t,p) for real mixed gas systems)

This substantially widens the measuring range and improves the accuracy of humidity variable calculations.

- *new:* Humidity variable Absolute humidity in g/m³
- Temperatures are measured using A/D converter incorporated in the ALMEMO[®] D6 plug.
- The humidity variables are calculated from the three primary measuring channels (real measurable variables): Dry temperature, wet temperature, atmospheric pressure
- Freely selectable measurable variables Four measuring channels are programmed (at our factory): dry temperature (°C, TT, t), wet temperature (°C, HT, tw), relative humidity (%H, RH, Uw), atmospheric pressure (mbar, AP, p)

Other humidity variables can also be selected: dewpoint (°C, DT, td), mixture (g/kg, MH, r), absolute humidity (g/m³, AH, dv), vapor pressure (mbar, VP, e), enthalpy (kJ/kg, En, h)

This device can be configured directly on a PC using USB adapter cable ZA 1919 AKUV. (see chapter "Networking").

Recommendations for calibration laboratories and quality assurance



ALMEMO[®] 1036-2

Reference measuring instrument ALMEMO[®] 1036-2 is ideally suited for use in calibration laboratories and quality assurance procedures. When measuring atmospheric humidity the combination of reference measuring instrument ALMEMO[®] 1036-2 and precision psychrometer FPA-836-3P3 ensures very high levels of resolution, precision, and linearity. Resolution parameters: temperature Pt100 0.001 K, relative humidity 0.01%, dewpoint 0.01K The measuring instrument incorporates a digital atmospheric pressure sensor for compensation purposes. These devices are offered in a set including the sensor and a DAkkS calibration certificate : Calibration points temperature/humidity at 25 °C / 30 % r.h. and 25 °C / 75 % r.h. and air pressure in the range 700 ... 1100 mbar.

For general description and technical data see Chapter "ALMEMO® reference measuring instruments".

Digital stationary psychrometer FPAD 36-3

Technical data

On anotin a tampa anotana	0 ± 100 %C (ma inc)
Operating temperature	0.00 ± 90 C (110.10e)
Humidity measuring range	10 to 100% RH
Measuring system	psychrometric
Accuracy	± 1 % RH under nominal conditions
Accuracy in measuring rang	e 10 100 % r. h.: typ. ±1 % r. h.
	at 25°C ±3K, 1013 mbar
Nominal conditions	+25 °C ±3 K, 1013 mbar, 50 % RH
Temperature sensors	2 x Pt100
Accuracy	ALMEMO® adjusted at 0°C and 85 °C
Ventilator power supply	12 VDC via mains unit, cable approx. 1.5 meters and extension cable 5 m (included in delivery)
Housing	Plastic PMMA
Dimensions	175 x 50 x 75 mm (LxWxH)
Weight	approx. 890 g
ALMEMO [®] connecting cable	2 Cables, FEP / Wire Shielding, 5 meters to 1 ALMEMO [®] D6 plug

Digital atmospheric pressure sensor (integrated in ALMEMO [®] D6 plug)		
Measuring range	700 to 1100 mbar	
Accuracy	±2.5 mbar (at 23 °C ±5 K)	
A/D converter incorporated	in ALMEMO [®] D6 plug	
Inputs	2 inputs, range Pt100	
Resolution	0.01 K	
Measuring current:	1 mA	
Linearization	Calculation procedure (no approximations)	
Accuracy	±0,07 K ±2 digits	
Nominal temperature	23 °C ±2 K	
Temperature drift:	0,003 %/K (30 ppm)	
Calculated humidity variables	Analytic equation (not an approximation)	
Refresh rate	0.3 seconds for all four channels	
Supply voltage	6 to 13 VDC	
Current consumption	approx. 9 mA	

Accessories

Spare wicks (2 pieces)

Variants

Digital psychrometer with Pt100 sensors Psychrometer, fitted cable, with ALMEMO[®] D6 plug, integrated digital atmospheric pressure sensor, mains unit, Extension cable for power supply unit, water bottle, two wicks, carry case

DAkkS or factory calibration KH91xx, temperature, humidity, for digital sensor (see chapter "Calibration certificates"). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Order no.

ZB98462ED

Order no.

FPAD363

Air humidity

Digital psychrometers, FNAD 46 and FNAD 46-3 with ALMEMO[®] D6 plug with integrated atmospheric pressure sensor, for automatic pressure compensation



- *new:* A digital atmospheric pressure sensor integrated in the ALMEMO[®] D6 plug itself provides automatic pressure compensation for all pressure-dependent humidity variables.
- *new:* Humidity calculation on the basis of formulae as per Dr. Sonntag and the enhancement factor as per W. Bögel (correction factor fw(t,p) for real mixed gas systems) This substantially widens the measuring range and improves the accuracy of humidity variable calculations.
- *new:* Humidity variable Absolute humidity in g/m³
- High-precision NTC sensors for dry temperature and wet temperature
- Temperatures are measured using a A/D converter incorporated in the ALMEMO[®] D6 plug.
- The humidity variables are calculated from the three

primary measuring channels (real measurable variables): Dry temperature, wet temperature, atmospheric pressure

- Freely selectable measurable variables Four measuring channels are programmed (at our factory): dry temperature (°C, TT, t), wet temperature (°C, HT, tw), relative humidity (%H, RH, Uw), atmospheric pressure (mbar, AP, p)
- Other humidity variables can also be selected: dewpoint (°C, DT, td), mixture (g/kg, MH, r), absolute humidity (g/m³, AH, dv), vapor pressure (mbar, VP, e), enthalpy (kJ/kg, En, h)
- This device can be configured directly on a PC using USB adapter cable ZA 1919 AKUV. (see chapter "Networking").

Technical data, FNAD 46 and FNAD 46-3

Digital atmospheric pressure sensor (integrated in ALMEMO [®] D6 plug)		Linearization	error-free computing method according to Galway Steinhart
Measuring range	700 to 1100 mbar		(no approximations)
Accuracy	±2.5 mbar (at 23 °C ±5 K)	Accuracy	±0.05 K
A/D converter incorporated in ALMEMO [®] D6 plug		Nominal temperature	23 °C ±2 K
Inputs	2 NTC sensors	Temperature drift:	0,004 %/K (40 ppm)
(clamped connection in plug)	(clamped connection in plug)	Calculated humidity varia	bles Analytic equation
Resolution 0.01 K	0.01 K	· · · · · · · · · · · · · · · · ·	(not an approximation)
		Refresh rate	0.4 seconds for all four channels

ALMEMO® D6

Air humidity

Hand-held digital psychrometer FNAD 46

Stationary digital psychrometer FNAD 46-3





Version optimized for long-term measuring operations Automatic humidification of the wick after filling the water tank.

General description and common technical data FNAD 46-3 (see page 08.18)

Technical data

For test measurements

FNAD 46 (see page 08.18)

General description and common technical data

Operating temperature	0 to +60 °C (no ice)
Humidity measuring range	10 to 100% RH
Measuring system Accuracy Accuracy in measuring range	psychrometric ± 1 % RH under nominal conditions $e 10 100$ % r. h.: typ. ± 1 % r. h. at 25°C ± 3 K, 1013 mbar
Nominal conditions	+25 °C ±3 K, 1013 mbar, 50 % RH
Temperature sensors Accuracy	2 x NTC type N ±0,2 K at 0 to 60 °C
Ventilator power supply	via ALMEMO® D6 plug
Housing	Plastic
Dimensions	Ø 50 mm, length 245 mm
Weight	approx. 300 g
Sensor connector	Built-in plug
ALMEMO [®] connecting cable	coupling, 1.5 meters, PVC cable with ALMEMO [®] D6 plug
Supply voltage	9 to 13 VDC
Current consumption	20 mA

Technical data

Operating temperature	0 to ± 90 °C (no ice)
Humidity measuring range	10 to 100% RH
Measuring system	psychrometric
Accuracy	± 1 % RH under nominal conditions
Accuracy in measuring rang	e 10 100 % r. h.: typ. ±1 % r. h.
	at 25°C ±3K, 1013 mbar
Nominal conditions	+25 °C ±3 K, 1013 mbar, 50 % RH
Temperature sensors	2 x NTC type N
Accuracy	±0,2 K at 0 to 70 °C,
-	±0,4 K at 70 to 90 °C
Ventilator power supply	12 VDC via mains unit, cable approx.
	1.5 meters (included in delivery)
Housing	Plastic PMMA
Dimensions	175 x 50 x 75 mm (LxWxH)
Weight	approx. 890 g
ALMEMO [®] connecting cable	Cable, FEP / silicone, 5 meters
	with ALMEMO® D6 plug
Supply voltage	6 to 13 VDC
Current consumption	4 mA

Accessories	Order no.	Accessories	Order no.
Extension pipe, 200 mm long Plastic suction hose, 300 mm long Spare wicks (2 pieces)	ZB9846VR ZB9846PS ZB9846ED	Extension cable for mains units, 3-pin bayonet coupling, length 5 meters Spare wicks (2 pieces)	ZB5090VK05 ZB98462ED

Variants	Order no.	Variants	Order n
Hand-held digital psychrometer with NTC sense	sor	Digital psychrometer with NTC se	ensor
Hand-held psychrometer, connecting cable with	n ALMEMO®	Psychrometer, fitted cable, with Al	LMEMO® D6 plug, integ-
D6 plug, integrated digital atmospheric pressur	e sensor, water	rated digital atmospheric pressure	sensor, mains unit, water
bottle, two wicks	FNAD46	bottle, two wicks, carry case	FNAD4

DAkkS or factory calibration KH91xx, temperature, humidity, for digital sensor (see chapter "Calibration certificates"). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Order no.

FNAD463

Air humidity

Digital temperature / humidity transmitter MH8D46C with double analog output V or mA





Transmitter with open housing

- Digital sensor element for humidity, temperature, air pressure All key sensor characteristics, settings, and adjustment data are saved in the sensor element itself.
- Plug-in sensor element: Spare elements are inexpensive; a replacement can be fitted on site quickly and easily by virtually anyone; it will be fully accurate straight away needing no special adjustment.
- Digital transfer of measured values from the sensor element to the transmitter
- · Factory or DAkkS calibration is erformed on the sensor element alone. Fully accurate - irrespective of connecting cable and transmitter
- Four climate variables can be measured: Double analog output Suitable for conduit mounting or wall mounting for temperature and one humidity variable relative humidity /

dewpoint / mixture ratio. The air pressure dependent humidity values are automatically compensated for air pressure (the air pressure is measured directly at the measuring point in the sensor tip).

- The transmitters can be configured via the internal display and the keypad.
- The analog output type (10 V or 20 mA) can be selected (via the keypad); the analog output range can be programmed.
- Display of measured value, channel, units, humidity range, analog start, analog end, and analog type
- The sensor tube can be connected either directly by plugging onto the transmitter itself or via a connecting cable.

Technical data

Operative range	Sensor -20 to +80 °C, 5 to 98 % RH Electronics -10 to +50 °C, IP65	Output type Resolution	0 to 10 V, 0 to 20 / 4 to 20 mA, selectable 16 bit
Humidity sensor Measuring range Sensor Fixed measuring period Accuracy	0 to 100 % RH CMOSens [®] technology / output period approx. 3 seconds ±2.0 % RH in range 10 to 90 % RH ±4.0 % RH in range 5 to < 98 % RH	Accuracy Temperature drift Time constant Connection	0.1 % of final value 10 ppm / K 100 μs Cable, via screwless clamp connector, with cable bushing Cable diameter 2 to 5 mm
Hysteresis Nominal temperature Sensor operating pressur	at nominal temperature typical ±1 % RH +23 °C ±5 K re Atmospheric pressure	Standard equipment Display, internal	2-row LCD 7 segments 4 1/2 and 5 characters 2 digits 16 segments 3 keys
Response time T ₆₃ Temperature sensor Sensor Fixed measuring period Accuracy	typical 8 seconds at +25 °C, 1 m/s (without filter) CMOSens® technology / output period approx. 3 seconds typical ±0.2 K at 5 60 °C, max ±0.4 K at 5 60 °C,	Power supply DC voltage Current consumption Connection	9 to 30 VDC 37 mA + 1.5·IOut Cable, via screwless clamp connector, with cable bushing Cable diameter 2 to 5 mm
Reproducibility Response time T ₆₃	max. ± 0.7 K at -2080 °C typical ± 0.1 K typical 20 seconds (without filter)	Mechanical design Sensor tube Protective cap	Stainless steel, diameter 12 mm SK7, metal-mesh filter
Outputs Double analog output Dig	ital-to-analog converter (DAC) electr. isol. 0 to 10 V, load >100 kilohms 0 to 20 mA, load <500 ohms	Housing Dimensions Protective class	Die-cast aluminum, closed cover 100 x 100 x 60 mm (LxWxH) IP65 (with sensor tube and connecting cable plugged in)

Air humidity

Display of measured values and programming (housing open)





Measured value display, channel M0, temperature



Selecting the analog output type,

e.g. 4 to 20 mA

Measured value display, channel M1, humidity variable, e.g. relative humidity



Programming the analog start



Selecting the humidity variable, e.g. relative humidity, % RH



Programming the analog end



Accessories	Order no.		
Angle bracket for wall mounting	ZB8D00W	Connecting cable between sensor tube and transmitter	
Rubber gasket (mat) for mounting the housing		Length $= 2$ meters	ZH9D46VK02
directly on a conduit wall (immersion depth = sensor	length + approx.	Same as above Length $= 5$ meters	ZH9D46VK05
42 mm plug length)	ZB8D00GD	Same as above Length $= 10$ meters	ZH9D46VK10
Movable brass screw with plastic sealing ring		Spare sensor, complete Sensor element inside sensor tu	ıbe
(see page 08.09)	ZB9600KV20	including protective cap SK7	
Connecting flange for screw connection,		Sensor length = 125 mm	FH9D46C1K1
pitch circle diameter 38 mm (see page 08.09)	ZB9600F20	Same as above Sensor length = 265 mm	FH9D46C1K2
Protective caps (see page 08.09)		Same as above Sensor length = 525 mm	FH9D46C1K3
Mains plug, 100 to 240 VAC, 12 VDC, 2 A	ZB1012NA10	Replacement sensor element, digital, adjusted, plug-in	FH0D46C

Variants including manufacturer's test certificate	Order no.
Digital transmitter for temperature and humidity	
with double analog output, 10 V or 20 mA (selectable via keypad), internal display, 3 keys,	
aluminum housing, IP65, with plug-in digital sensor, sensor length = 125 mm	MH8D46C1K1
Same as above Sensor length = 265 mm	MH8D46C1K2
Same as above Sensor length = 525 mm	MH8D46C1K3

DAkkS or factory calibration KH9xxx, temperature, humidity, for digital sensor (see chapter "Calibration certificates"). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

08.24

Content

The right flow sensor for each and every measuring task	09.02	
Correction factors ensure precise air speed measurement.	09.03	
Air Speed for selected Pitot tubes	09.03	
Digital precision vane anemometer FVAD 15	09.04	
Digital precision vane anemometer mini	09.05	
Digital precision vane anemometer micro	09.05	
Digital precision vane anemometer makro	09.06	
Digital vane anemometer for special applications	09.07	
Differential pressure and Pitot tube measurement		
Measuring connector	09.10	
Pitot Tubes for Differential Pressure Sensors FDA602	09.11	
Digital thermoanemometer FVAD 35 THx	09.12	
Digital thermo-anemometer omnidirectional FVAD 05-TOKx	09.13	

Air flow



The Right Flow Sensor For Any Measuring Task

For measuring the flow velocity, typically, three methods are used, which are particularly different from each other with regard

Pitot Tubes

The air velocity is determined by the dynamic pressure and the static pressure. Pitot tubes are robust and are available in special steel or nickel-plated brass. They connect to ALMEMO[®] devices by silicone hoses and a differential pressure module.

Rotating Vanes

The flow velocity is determined through a frequency measurement. Our rotating vanes are sensitive transducers with diamond bearings that are very precisely adjusted. This ensures high accuracy.

Thermoanemometers

Thermistors and hot wire anemometers are highly sensitive sensors. The measuring element is continuously heated up. A control circuit keeps the temperature of the element, which has cooled down by the air flow, on a constant value. The control current is proportional to the flow velocity. to their measuring range and the operating temperature:

Advantage:

suitable for high flow velocities and harsh operating conditions, high ambient temperatures possible, easy to clean

Advantage:

high accuracy at medium flow velocities and medium ambient temperatures, insensitive to turbulent flows

Advantage:

even very small air speeds can be measured (e.g. draught measurements), direction-independent measurements are also possible

Pitot tubes Rotating vanes

• Thermoanemometer probes

Disadvantage:

strongly directional, low flow velocities are not measurable, temperature-dependent, limited accuracy, sensitive to turbulent flows

Disadvantage:

sensitive sensor technology, sensitive to mechanical stress, directional

Disadvantage:

sensitive sensor technology, sensitive to mechanical stress and contamination, sensitive to turbulent flows, high current consumption, limited ambient temperature.

Air Temperature	940 mbar	960 mbar	980 mbar	1000 mbar	1020 mbar	1040 mbar
-30°C	0.942	0.932	0.922	0.913	0.904	0.895
-20°C	0.961	0.951	0.941	0.932	0.923	0.914
-10°C	0.980	0.970	0.960	0.950	0.941	0.931
0°C	0.998	0.988	0.978	0.968	0.958	0.949
10°C	1.016	1.005	0.995	0.985	0.975	0.966
20°C	1.035	1.024	1.013	1.003	0.993	0.983
30°C	1.051	1.040	1.029	1.019	1.009	0.999
40°C	1.069	1.057	1.047	1.036	1.026	1.016
50°C	1.085	1.074	1.063	1.052	1.042	1.031
60°C	1.102	1.09	1.079	1.068	1.057	1.047
70°C	1.118	1.106	1.095	1.084	1.073	1.063
80°C	1.135	1.123	1.111	1.100	1.089	1.078
90°C	1.151	1.139	1.127	1.116	1.105	1.094
100°C	1.167	1.154	1.142	1.131	1.120	1.109
150°C	1.242	1.229	1.216	1.204	1.192	1.180
200°C	1.314	1.300	1.287	1.274	1.261	1.249
250°C	1.381	1.367	1.353	1.339	1.326	1.313
300°C	1.446	1.431	1.416	1.402	1.388	1.375
400°C	1.567	1.55	1.534	1.519	1.504	1.489
500°C	1.68	1.663	1.646	1.629	1.613	1.597
600°C	1.784	1.766	1.748	1.73	1.713	1.696
700°C	1.884	1.865	1.846	1.827	1.809	1.791

Correction Factors for Exact Measurements of the Air Speed with Pitot Tube

temperature and the barometric air pressure. Therefore, the measured value must be corrected according to the above table

speed.

Example:

Measured air velocity 50m/s, air tempera-

The true air velocity depends on the air to obtain exact measurements of the air ture 80°C, atmospheric pressure 960mbar. The measured value must be multiplied with the correction value 1.123. The air velocity is, therefore, 56.1m/s.

Air Speed For Selected Dynamic Pressures (Prandtl Pitot Tube, T = 22°C)

Dynamic Pressure [Pa]	Dyn. Press. [mm h.o.water]	Air Speed [m/s]	
1	0.1	1.29	
2	0.2	1.83	
3	0.3	2.24	
4	0.41	2.59	
5	0.51	2.89	
10	1.02	4.09	
20	2.04	5.78	
30	3.06	7.08	
40	4.08	8.18	
50	5.1	9.14	
100	10.2	12.93	



Digital precision vane anemometer FVAD 15 -H120 / -H140 / -H220 / -H240 / -MK5 / -MK20 with ALMEMO® D6 plug



Technical data and functions

- metal.
- The flow velocity is recorded with high accuracy.
- · Every vane anemometer is adjusted individually. The multipoint adjustment is saved within the ALMEMO® D6 plug.
- Measurement operations carried out by a vane anemometer in air/gas are in practice nearly completely unaffected by environmental variables such as pressure, temperature, or humidity. The low dependence of the measured value on density can be compensated. The density of the gas can be programmed within the ALMEMO® D6 sensor menu on the ALMEMO[®] V7 device.
- The precision probe heads and the sensor shaft are made of The rugged construction is suitable for mobile as well as for stationary measurement operations.
 - The ALMEMO[®] D6 plug measures the frequency signal of the vane with high resolution.
 - One measuring channel is programmed (at our factory): flow velocity v (m/s).

Technical data:

Maximum resolution	0.01 m/s
Nominal conditions	22 °C ±2 K, 1013 mbar
Connection cable	permanently connected cable,
	2 meters, with Lemo plug
ALMEMO [®] adapter cable	Lemo coupling cable, 0.2 meters,
	with ALMEMO® D6 plug
ALMEMO [®] D6 plug	
Frequency measurement	resolution 0.01 Hz
Multi-point adjustment	sensor specific, saved within the
	ALMEMO [®] D6 plug of
	the adapter cable

Refresh rate	0.5 seconds for all channels
Averaging period	2 seconds,
	programmable from 2 to 100 s
Supply voltage	6 to 13 VDC
Current consumption	8 mA

For more information about general features of the ALMEMO® D6 sensors, refer to page 01.05

Accessories	Order no.
Lemo extension cable, length = 5m, for FVAD 15-H120/-H140/-H220/-H240 /-MK5/-MK20 to extend the sensor cable	ZB9915VKLH05
ALMEMO [®] extension cable, length = 4m (see chapter 6) ALMEMO [®] extension cable, length = 5m (see chapter 6)	ZA9060VK4 ZA9090VKC5
Extension set Ø 25mm, stainless steel, 3 tubes 350mm each, suitable for FVAD 15-H120/ -H140 Extension set Ø 16mm, stainless steel, 3 tubes 350mm each, suitable for FVAD 15-H220/ -H240	ZV9915H25VR3 ZV9915H16VR3

DAkkS or factory calibration KV90xx, air flow, for digital probe, see chapter Calibration certificates. The DAkkS calibration fulfills the requirements of DIN EN ISO/IEC 17025 for test equipment.

10/2021 • We reserve the right to make technical changes

nev

Digital precision vane anemometer mini FVAD 15 -H120 / -H140





Air flow

• The construction type as a cylindrical probe is optimized for safely introducing the probe in a flow channel. Probe head and handle have the same diameter.

Technical data:

Version:	mini, aluminum	Probe head:	aluminum, Ø 25 mm
Measured medium:	air/gas		dimensions C 60 mm
Operative range:	-20 to +125 °C (including cable)		dimensions A Ø 18.2 mm
Pressure resistance:	up to 6 bar overpressure		dimensions B 13.4 mm
Measuring range:	refer to Variants	Sensor shaft:	Aluminum, Ø 25 mm
Accuracy:	\pm (+0.5 % of final value sensor	Sensor length:	dimensions D 170 mm
	+ 1.0 % of measured value)	Cable exit:	thread M 22 x 1.5
	specific multi-point adjustment.	Cable length:	2 m

Variants (including manufacturer's test certificate)	Order no.
Digital precision vane anemometer for air/gas,	
permanently connected cable, adapter cable with ALMEMO® D6 plug	
Probe head MN20GA, measuring range of 0.3 to 20 m/s	FVAD15H120
Probe head MN40GA, measuring range of 0.4 to 40 m/s	FVAD15H140

Digital precision vane anemometer micro FVAD 15H -H220 / -H240



Technical data:

Version:	micro, aluminum,	Probe head:	aluminum,
Measured medium:	air/gas		dimensions ØK Ø 16 mm
Operative range:	-20 to +125 °C (including cable)		dimensions LK 53 mm
Pressure resistance:	up to 3 bar overpressure		dimensions B 10,65 mm
Measuring range:	refer to Variants	Sensor shaft:	Aluminum,
Accuracy:	\pm (+0.5 % of final value sensor		dimensions ØS Ø16 mm
	+ 1.0 % of measured value)	Sensor length:	dimensions C 163 mm
	specific multi-point adjustment.	Cable exit:	dimensions IG thread M 14 x 1.5
		Cable length:	2 m

Variants (including manufacturer's test certificate)	Order no.
Digital precision vane anemometer for air/gas, permanently connected cable, adapter cable with ALMEMO [®] D6-plug.	
Probe head MC20GA, measuring range of 0.6 to 20 m/s Probe head MC40GA, measuring range of 0.7 to 40 m/s	FVAD15H220 FVAD15H240



Digital precision vane anemometer makro FVAD 15 -HMK5 / -HMK20





- Anemometer with T-measuring head.
- Large cross-sectional area.
- Small measuring range available.

• Low inclined flow sensitivity.

• For measuring medium air, pure gases or gas mixtures.

Applications

The digital precision vane anemometer with measuring head makro is used in a wide variety of applications to measure air velocity.

- Measurements on ventilation, air conditioning and filtration systems.
- Control measurements on fume hoods of workbenches, workstations.Measurements in automotive engineering: during investiga-

tions in wind tunnels and in vehicle interiors.

- Measurement of laminar flow and net measurements on large inlets and outlets.
- Verification of air movements in clean rooms.

Technical data:

Version:	makro, zinc alloy	Probe head:	zinc alloy
Measured medium:	air/gas	Impeller:	aluminum
Operative range:	-20 to +125 °C (including cable)		dimensions A Ø 90 mm
Pressure resistance:	atmospheric pressure		dimensions B 80 mm
Measuring range:	refer to Variants	Sensor shaft:	stainless steel, Ø 18 mm
Accuracy:	\pm (+0.5 % of final value sensor	Sensor length:	dimensions L 225 mm
	+ 1.0 % of measured value)		(without end piece)
	specific multi-point adjustment.	Cable exit:	thread M 22 x 1.5
		Cable length:	2 m
		Weight:	approx. 1kg (incl. cable)

Accessories	Order no.
Carrying case for vane anemometer macro	ZB9605TK
Variants (including manufacturer's test certificate) Digital precision vane anemometer for air/gas, permanently connected cable, adapter cable with ALMEMO [®] D6 plug	Order no.
Probe head MK5, measuring range of 0.15 to 5 m/s Probe head MK20, measuring range of 0.25 to 20 m/s	FVAD15HMK5 FVAD15HMK20

Digital vane anemometer FVAD 15-H for special applications, with ALMEMO® D6 plug

Technical data and functions

- aluminum or stainless steel.
- The flow velocity is measured with high accuracy.
- Each vane anemometer is individually adjusted. The Multipoint adjustment is stored in the ALMEMO® D6 connector.
- In practice, measurements in air and gases are unaffected by environmental variables such as pressure, temperature, or humidity. The low dependence of the measured value on density of the gas can be compensated for. The density can be programmed in the ALMEMO® D6 sensor menu in the ALMEMO® V7 device.
- The precision measuring heads and the sensor shaft are made of Several measuring heads can be used for measurements in air and gases as well as in liquids.
 - Some variants detect the direction of flows and display the measured value with an algebraic sign.
 - The robust type of construction is suitable for mobile measuring operations as well as for stationary measuring operations.
 - The ALMEMO[®] D6 plug measures the frequency signal of the rotating vane with high resolution.
 - 1 measuring channel is preprogrammed (ex works): Flow velocity (m/s, v).

Technical data

Maximum resolution	0.01 m/s
Nominal conditions	22 °C ±2 K, 1013 mbar
Connecting cable	permanently fitted cable,
	with ALMEMO [®] D6 plug
ALMEMO [®] D6 plug	
Frequency measurement	resolution 0.01 Hz
Refresh rate	0.5 seconds for all channels

Averaging period to 100 seconds	2 seconds, programmable from 2
Supply voltage	6 to 13 VDC
Current consumption	8 mA

General features for the ALMEMO® D6 sensors: see page 01.08

Digital vane anemometer for air/gas or liquid FVAD 15-H16GFAMC40

Technical data			IG ØS B C LK
Variant:	Micro, aluminum.	Type of rotating vane:	MC40GFA, aluminum
	suitable also for liquids	Measuring head:	
Measured medium:	air and gases or liquids	dimension ØK	aluminum, Ø 16 mm
	(precondition: no cavitation)	dimension LK	53 mm
Operative range:	-20 to +100 °C (including cable)	dimension B	10.65 mm
Pressure resistance:	up to 3 bar overpressure	Sensor shaft:	Aluminum, Ø 16 mm
Measuring range:	in air: 0.6 to 40 m/s, or		(dimension ØS)
	in liquids: 0.06 to 10 m/s please specify the desired medium.	Sensor length:	163 mm (dimension C) greater lengths are optionally available with an extension bar
Accuracy:	\pm (+0.5 % of final value sensor		(only ex works)
-	+ 1.0 % of measured value)	Cable exit:	Thread M 14 x 1.5 (dimension IG
	for the specified medium	Cable length:	2 m
	specific multi-point adjustment		
Option			Order no.

Extension bar aluminum, Ø 16 mm, length 350 mm, installed on the rotating vane ex works, not removable!

OV9915HVS16A

Variants

Order no.

Digital vane anemometer for air and gases or for liquids, up to 40 m/s (air and gases), up to 100°C, integrated fixed cable, with ALMEMO® D6 plug. Please indicate the desired medium! FVAD15H16GFAMC40

DAkkS or factory calibration KV90xx, air flow, for digital sensor (see chapter ,,Calibration certificates"). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Digital vane anemometer with direction detection FVAD 15-H25RGAMN40





Digital vane anemometer FVAD 15-H25RGAMN40

Technical data

Variant:	Mini, aluminum, with integrated	Measuring head:	Aluminum, Ø 25 mm
direction detection			dimension C 66 mm
Measured medium:	air and gases		dimension A Ø 18.2 mm
Operative range:	-20 to +125 °C (including cable)		dimension B 13 mm
Pressure resistance:	up to 6 bar overpressure	Sensor shaft:	Aluminum, Ø 25 mm
Measuring range:	±0.4 to ±40 m/s	Sensor length:	166 mm (dimension D),
	with direction detection		greater lengths are optionally
Accuracy:	\pm (+0.5 % of final value sensor		available with an extension bar
	+ 1.0 % of measured value)		(only ex works)
	specific multi-point adjustment	Cable exit:	Thread M 22 x 1.5
Type of rotating vane:	MN40GA, aluminum	Cable length:	2 m

Option	Order no.
Extension bar aluminum, Ø 25 mm, length 350 mm, installed on the rotating vane ex works, not removable!	OV9915HVS25A

Variants

Order no.

Digital vane anemometer for air and gases, up to 40 m/s, with integrated direction detection, up to 125°C, integrated fixed cable, with ALMEMO® D6 plug. FVAD15H25RGAMN40

Digital vane anemometer, operating range up to 260 °C FVAD 15-H25GEMN40T2



Technical data

Variant:	Mini, stainless steel, for high-temperature up to 260 °C		dimension A Ø 18.2 mm dimension B 14 mm
Measured medium:	air and gases	Sensor shaft:	stainless steel, Ø 25 mm
Operative range:	-40 to +260 °C (including high-	Sensor length:	170 mm (dimension D),
temperature cable)			greater lengths are optionally
Pressure resistance:	up to 10 bar overpressure		available with an extension bar
Measuring range:	0.5 to 40 m/s		(only ex works)
Accuracy:	\pm (+0.5 % of final value sensor	Cable exit:	Thread M 22 x 1.5
	+ 1.0 % of measured value)	Cable length:	2 m high-temperature cable
	specific multi-point adjustment		(up to 260 °C),
Type of rotating vane:	MN40GE, stainless steel		cable repeater (-30 to 125 °C),
Measuring head:	stainless steel, Ø 25 mm		1.5 m cable (up to 125 °C)
	dimension C 81 mm		

^				
()	n	••	\mathbf{a}	n
J	U	LI	υ	
_	-		_	

Extension bar stainless steel, Ø 25 mm, length 350 mm, temperature-resistant from -20 to +240 °C (VITON O-ring), installed on the rotating vane ex works, not removable! OV9915HVS25E

Variants

Digital vane anemometer for air and gases, up to 40 m/s, up to 260 °C, integrated fixed cable, with ALMEMO[®] D6 plug.

Order no.

Order no.

FVAD15H25GEMN40T2

Differential pressure and Pitot tube measurement Measuring connector FDA 602 S1K / S6K



Measuring connector FDA602S1K / S6K

Technical data

- Pressure measuring connector in compact design for flow measurement with Pitot tubes
- Fitting for connecting hose between Pitot tube and pressure measuring connector
- Pressure measuring connector can be plugged directly onto the measuring instrument.

Overload capacity	Maximum three times final value	_ Operating range	-10 to +60 °C, 10 to 90% RH,
Max. common mode pressure	700 mbar		non-condensing
Accuracy (zero-pt adjusted)	$\pm 0.5\%$ of final value	Dimensions	74 x 20 x 8.8 mm
in	in range 0 to positive final value	Hose terminals	Ø 5 mm, 12 mm long
Nominal temperature	25 °C	Sensor material	aluminum, nylon, silicone,
Temperature drift	$<\pm1.5$ % of final value		silica gel, brass
Compensated temp. range	0 to +70 °C		

Advisory note when used in conjunction with ALMEMO[®] 2890, 5690, 5790, 8590, 8690, 500, 809: The new ALMEMO[®] pressure measuring connector is very slightly higher (8.8 mm). As a result adjacent input sockets on the ALMEMO[®] device may be partly covered. However, the 1st input socket can always be used without restriction. Or, alternatively, the ALMEMO[®] pressure measuring connector can be plugged in at any input socket using connecting cable ZA9060AK1.

On ALMEMO[®] devices to obtain precise measured results in m/s the wind tunnel temperature can be entered in the -50 to +700 °C range for compensation purposes.

FDA602S6K

Accessories	Order no.
ALMEMO [®] pressure measuring connector for barometric pressure 700 to 1100 mbar, without pressure terminal sleeve	
Technical data see chapter 10 Pressure	FDAD12SA
including programming for automatic atmospheric pressure compensation (comment *P)	OA9000PK
(variant with pressure terminal sleeve, see chapter 10 Pressure)	
Connecting cable, 0.2 meters	ZA9060AK1
Extension cable, 2 meters	ZA9060VK2
1 set of silicone hoses	
black / colorless, 2 meters	ZB2295S
Silicone hose, black, per meter	ZB2295SSL
Silicone hose, colorless, per meter	ZB2295SFL
Variants (including manufacturer's test certificate)	Order no.
(including one set of cilicone bases 2 meters)	0.001110
(including one set of sincone noses, 2 inclus)	
Measuring ranges ± 1250 Pa, Differential pressure (1 to 40 m/s), Measured variables: m/s, Pa, Measuring connector, independent of position	FDA602S1F

Measuring ranges ±6800 Pa Differential pressure (2 to 90 m/s) Measured variables m/s, Pa,

Measuring connector, independent of position

DAkkS or factory calibration KV90xx, air flow, and KD90xx, pressure, for sensor or measuring chain (sensor + device) (see chapter "Calibration certificates"). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.



- Prandtl Pitot tubes with hemispheric head.
- For measuring the dynamic pressure, the tip of the Pitot tube has an opening of 0.3d.
- For measuring the static pressure, a total of 12 holes with 0.1d Ø have been arranged at a distance of 3d.
 - Mit ALMEMO[®] devices that have an option for entering factors can also be used to perform wind velocity measurements with cylindrical probes, according to VDEH. The cylindrical Pitot tubes have a probe-related coefficient of 1.7. By entering a factor of 0.767 in the range m/s this coefficient will be considered during the measurement.

Option	Order no.
Movable screw connection for brass Pitot tubes with shaft diameter x (6; 8; 10; 20mm)	ZB9912KMx
for steel Pitot tubes with shaft diameter x (6; 8; 10; 20mm)	ZB9912KVx

1

Types and Technical Data:

Head Diameter (d)	Shaft Diameter (D)	Length	Tmax	Permiss. Dust	Material	Order no.
3 mm	6 mm	300 mm	150°C	none	Nickel-plated brass	FD991233MS
3 mm	6 mm	300 mm	300°C	none	Chrome-nickel steel	FD991233VA
5 mm	8 mm	400 mm	350°C	none	Nickel-plated brass	FD991254MS
5 mm	8 mm	400 mm	500°C	none	Chrome-nickel steel	FD991254VA
5 mm	8 mm	600 mm	350°C	none	Nickel-plated brass	FD991256MS
5 mm	8 mm	600 mm	500°C	none	Chrome-nickel steel	FD991256VA
8 mm	8 mm	400 mm	350°C	low	Nickel-plated brass	FD991284MS
8 mm	8 mm	400 mm	500°C	low	Chrome-nickel steel	FD991284VA
8 mm	8 mm	800 mm	350°C	low	Nickel-plated brass	FD991288MS
8 mm	8 mm	800 mm	600°C	low	Chrome-nickel steel	FD991288VA
10 mm	10 mm	800 mm	350°C	some	Nickel-plated brass	FD991296MS
10 mm	10 mm	800 mm	600°C	some	Chrome-nickel steel	FD991296VA*
10 mm	10 mm	1000 mm	350°C	some	Nickel-plated brass	FD991297MS
10 mm	10 mm	1000 mm	600°C	some	Chrome-nickel steel	FD991297VA*
10 mm	20 mm	1500 mm	350°C	some	Nickel-plated brass	FD991298MS
10 mm	20 mm	1500 mm	600°C	some	Chrome-nickel steel	FD991298VA*
20 mm	20 mm	2000 mm	600°C	more	Chrome-nickel steel	FD991299VA*

*) all VA Pitot tubes can be operated up to 700° C for a short period

Order no.

Order no.

FVAD35TH4

FVAD35TH5

FVAD35TH4K1

FVAD35TH4K2

FVAD35TH5K1

FVAD35TH5K2

Air flow

Digital thermoanemometer FVAD 35 THx with ALMEMO[®] D6 plug with integrated atmospheric pressure sensor, for automatic pressure compensation



Technical data

Digital thermoanemometer (Sensor including A/D converter)				
Flow				
Measuring range				
FVAD 35 TH4 / TH4Kx	0.08 to 2 m/s			
FVAD 35 TH5 / TH5Kx	0.2 to 20 m/s			
Resolution				
FVAD 35 TH4 / TH4Kx	0.001 m/s			
FVAD 35 TH5 / TH5Kx	0.01 m/s			
Response time	<1.5 seconds			
Accuracy				
FVAD 35 TH4 / TH4Kx	\pm (0.04 m/s +1% of meas. val.)			
FVAD 35 TH5 / TH5Kx	\pm (0.2 m/s +2% of meas. val.)			
Nominal conditions	22 °C ±2 K, 45 % RH ±10 % RH			
	1013 mbar			
Temperature compensation	0 to +50 °C			
Influence of temperature				
FVAD 35 TH4 / TH4Kx	± 0.5 % of measured value /°C			
	at 0.3 to 2 m/s			
FVAD 35 TH5 / TH5Kx	$\pm 0.3\%$ of measured value /°C			
	at 0.3 to 20 m/s			
Incidental flow	bidirectional			
Angle dependence	<3% of measured value			
C	with deviation <15°			
Pressure range	Ambient pressure			
Pressure compensation	automatic in range 700 to 1100mbar			
*	5			

• Automatic atmospheric pressure compensation is provided for pressure-dependent flow velocity by means of a digital atmospheric pressure sensor integrated in the ALMEMO[®] D6 plug itself.

- Digital thermoanemometer with A/D converter in the grip or integrated in the cable
- The probe tube has a small diameter, only 6 mm.
- All relevant measurable variables can be measured using just one sensor.
- Three measuring channels are programmed (at our factory): Temperature (°C, t), Flow velocity (m/s, v), Atmospheric pressure (mbar, AP, p)

General features and accessories, ALMEMO[®] D6 sensors: see page 01.08

DAkkS or factory calibration KV90xx air flow for digital sensor (see chapter "Calibration certificates"). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Temperature	
Measuring range	-20 to +70 °C
Resolution	0.1 °C
Accuracy	± 0.7 °C at 0 to 50 °C and >0.5 m/s
Response time T ₉₀	typical 10 seconds
Digital atmospheric pressu	re sensor
(integrated in ALMEMO® D	6 plug)
Measuring range	700 to 1100 mbar
Accuracy	±2.5 mbar (at 23 °C ±5 K)
ALMEMO [®] D6 plug	
Refresh rate	0.5 seconds for all 3 channels
Supply voltage	6 to 13 VDC
Current consumption	40 mA
Dimensions	
Probe diameter	6 mm
Flow aperture	approx. 10 x 3 mm
FVAD 35 TH4 / TH5	
Probe with grip,	
probe lengths 210 mm ((plus grip),
ALMEMO [®] cable 1.5 n	neters
FVAD 35 TH4Kx / TH5K	X
Probe with detached ele	ectronics unit integrated in the
cable, Probe lengths TH	IxK1, 80 mm / THxK2, 300 mm
Probe cable 5 meters to	the electronics. ALMEMO [®] cable 1.5 m

Accessories (for FVAD 35 THxK1 / K2 only)

Variants (including works certificate)

Digital thermoanemometer, fitted cable with ALMEMO® D6 plug and integrated digital atmospheric pressure sensor

Sensor 2 m/s, length = 210 mm, (with grip) Sensor 2 m/s, length = 80 mm, (detached electronics unit) Sensor 2 m/s, length = 300 mm, (detached electronics unit) Sensor 20 m/s, length = 210 mm, (with grip) Sensor 20 m/s, length = 80 mm, (detached electronics unit) Sensor 20 m/s, length = 300 mm, (detached electronics unit)

Other designs are available on request

High-temperature thermoanemometer MT8635THx Operative range -40 to +120 °C, up to 40 m/s Probe with detached electronics unit integrated in the cable





Digital thermo-anemometer omnidirectional FVAD 05-TOKx, with ALMEMO[®] D6 plug, with integrated atmospheric pressure sensor for automatic atmospheric pressure compensation



Technical data and functions

- Omnidirectional sensitive tip with exposed heat ball probe.
- Optimized version for measuring low flow velocities in air.
- Solid construction of the sensor top, suitable for mobile usage.
- Digital thermo-anemometer with integrated A/D converter in the ALMEMO[®] D6 plug.
- Automatic atmospheric pressure compensation of the flow velocities dependent on the atmospheric pressure with digital

atmospheric pressure sensor integrated in the ALMEMO[®] D6 plug. Alternatively manual input of the atmospheric pressure in the ALMEMO[®] D6 sensor menu. Two measuring channels are preprogrammed on leaving our factory: flow velocity (m/s, v), atmospheric pressure (mbar, AP, p).

For more information about general features of the ALMEMO[®] D6, refer to page 01.05.

Technical data:

Flow sensor	
Measuring range:	0.050 to 1.000 m/s or 2.500 m/s
Resolution:	0.001 m/s
Accuracy:	\pm (3 % of measured value
	+ 1 % of final value +2 digits)
Nominal conditions:	23 °C ±3 K, 50 % RH, 1013 mbar.
Temperature compensation:	effective in the range 0 to 60 °C
Temperature effect:	0.5 % of the measured value/K
Output time constant:	0.1 s (selectable in the range of
	0.05 to 10 seconds)
Incident flow:	omnidirectional
Pressure range:	environmental pressure
Atmospheric pressure compensat	ion: automatically
	in the range of 700 to 1100 mbar
Dimensions:	
Peak length:	32 mm
Probe diameter:	6.4 mm
Probe length:	300 mm including peak
Probe cable:	5 meters

Transmitter electronic	
Dimensions:	126 x 80 x 60 mm (L x W x H)
Operating temperature:	0 to 60 °C
Supply voltage:	12 VDC
Current consumption:	maximum of 350 mA
Power supply unit connection:	0.2 meter cable with connection
	3 pin connector for the power
	supply unit ZB1212NA10
ALMEMO [®] connection:	2 meter cable
with ALMEMO D6 plug	
Digital atm. pressure sensor (inclu	ided in the ALMEMO® D6 plug)
Measuring range:	700 to 1100 mbar
Accuracy:	± 2.5 mbar (at 23 °C ±5 K)
A/D converter integrated in the A	LMEMO [®] D6 plug
Refresh rate:	0.1 seconds for both channels
Supply voltage:	via the ALMEMO [®] device
	(6 to 13 VDC)

8 mA

Option Order no. Measuring range 2.5 m/s. Transmitter electronic and ALMEMO® D6 plug are pre-configured on leaving our factory OA9000TO25

Current consumption:

Variants (including manufacturer's test certificate)

Digital thermo-anemometer, omnidirectional sensitive peak.

Probe with connecting cable to the transmitter electronic. Power supply cable including a plug connection for the power supply
unit.ALMEMO® connection cable with ALMEMO® D6 plug, integrated digital atmospheric pressure sensor.Delivery including plug-in power supply unit ZB1212NA10.FVAD05TOK300

DAkkS or factory calibration KV90xx, air flow, for digital sensor (see chapter "Calibration certificates"). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Order no.

Pressure, force, displacement, speed, flow

Content

The right pressure sensor for each and every measuring task	10.02
Measurement of pressure with digital sensors	10.02
Pressure Transducer FDA602L	10.04
High-precision pressure sensor FDAD33/35M	10.05
Temperature-Compensated Pressure Sensors FD8214	10.07
Pressure transducer for measuring the temperature of refrigerants, absolute pressure FDA602LxAK	10.09
Differential pressure transmitter FDA602D	10.10
Digital atmospheric pressure sensor FDAD 12 SA, for barometric pressure	10.11
Pressure measuring connector for barometric pressure FDA 612 SA	10.11
Pressure measuring connector for differential pressure FDA 612 Sxx	10.12
Pressure Sensors for Wall Mounting FD8612DPS/APS	10.13
Differential pressure transmitter for smallest pressure with automatic zero-point correction	10.14
Technical Features of Force Transducers	10.15
ALMEMO [®] Force Measurement	10.15
ALMEMO [®] Displacement Measurement	10.16
Tension and Compression Sensor K25	10.17
Compression Sensor K22 and K1613	10.18
ALMEMO [®] input connector for measuring bridges	10.19
Displacement Sensor, Potentiometric FWA xxx T	10.20
Displacement Tracer, Potentiometric FWA xxx TR	10.21
Speed and Flow Overview	10.22
Rotational Speed Sensor FUA 9192	10.23
Axial turbine flowmeter for liquids FVA 915 VTH	10.24
Axial turbine flowmeter for liquids FVA 915 VTH25	10.25
Flow sensors for liquids FVA 645 GVx	10.26

Pressure

force, displacement, flow



The Right Pressure Sensor For Any Measuring Task

nufacturing pressure sensors that have been adapted to the correspon-

- ding application. • Thick-Film Sensors
- Thin-Film Sensors
- Piezo-Resistive Sensors

Piezo-Resistive Sensors

A silicone membrane with ,diffused in' expansion-sensitive resistors is used as the pressure-sensitive element. Due to its compatibility with many substances silicone would limit the use of the sensor. Therefore, a pressure transmission system, consisting of a filling liquid and a special steel membrane has been integrated. The pressure measuring cell is temperaturecompensated and is manufactured in demanding vacuum processes.

Advantage:

High accuracy within a wide temperature range, particularly suitable for use in high sophisticated measurement and control

Different methods are usually used for ma- Pressure transducers are principally available with 4 pressure calibrations:

- Relative pressure: Pressure related to the environmental pressure
- · Absolute pressure: Pressure related to vacuum (0bar)
- · Overpressure: Pressure related to atm.

tasks, especially for measurement of absolute pressure and low to medium relative pressure.

Disadvantage:

Generally, an expensive manufacturing process, however, cost-efficient when produced in large quantities.

Two mechanical designs are available in the ALMEMO[®] sensor range:

• Pressure sensors for hose connection: The measuring cell is housed in a compact plastic housing with two connecting fittings. The pressure sensors are available for wall mounting or as pressure modules that can be directly

plugged into measuring instruments, with measuring ranges for relative or differential pressure measurement in gases, and also for atmospheric pressure measurements.

pressure at manufacturing (approx. 1bar)

• Differential press.: Pressure related to a

second, variable pressure

• Built-In Pressure Transducers: The measuring cell is suspended in an oilfilled, all-welded special steel enclosure. All parts that come into contact with a substance are made from special steel. Therefore, these transducers are also suitable for use in chemically aggressive substances in various industrial applications.

ALMEMO[®] pressure measurement

Every ALMEMO[®] sensor can be adjusted, calibrations performed by the Ahlborn i.e. correction values of the sensor can be Company, the correction values are stored in the connector. Thus, the recorded, stored in the sensor plug and measuring accuracy can be significantly increased.

locked. The adjustment can be realized in 2 points (zero, gradient) or in over 30 During DAkkS/DKD or factory points as multi-point adjustment. Thanks

to this procedure minimal deviations are achieved on the calibrated temperature points.

The multi-point adjustment is described in detail in chapter "Input connectors" and in chapter "Calibration certificates".

Temperature Measurement with Pressure Sensors for Refrigerants

Option SB0000R

All ALMEMO® Version V5/V6 devices, including ALMEMO® data loggers and continuous temperature measurement selected or continuously indicated and (resolution 0.1K) with absolute pressure recorded. sensors (resolution 0.001 bar compulsory!).

data acquisition systems, can be used for Both, pressure and temperature can be

Measurement of pressure peaks and fast pressure changes with digital ALMEMO® D7 sensors

The new ALMEMO® V7 measuring The ALMEMO® D7 Measurement plug system makes it possible to measure pressure peaks and pressure changes with a temporal resolution of up to 2ms. The analog pressure sensor measures the pressure change with a short response time

ZED7 00-FS works with a A/D converter integrated in the plug and with a measuring rate of up to 500 measuring operations per second (2ms per measuring operation). In combination with the ALMEMO® V7 measuring instrument, e.g. ALMEMO®

710 it is therefore possible to record pressure peaks and pressure changes. The measured values are evaluated in the WinControl software as table or line diagram (see chapter "Software").



is determined only by the pressure sensor with the connected ALMEMO® D7 measuring plug, and is unaffected by the

and extension cables used.

The complete measuring chain, consisting of pressure sensor and the connected

The overall accuracy of the measurement ALMEMO[®] display device / data logger ALMEMO[®] D7 measuring plug can be calibrated. An increased accuracy can be achieved by a multi-point adjustment of the sensor during the calibration process.

High resolution measurement with digital ALMEMO[®] D7 sensor

The ALMEMO® D7 measuring plug not conversion rate. Thus, stable measured ALMEMO® plug on the ALMEMO® V7 high resolution measurements. Thereby, by using high-precision sensors. the measuring plug works with reduced The user can easily configure the

only enables fast measurements but also values with high resolution can be achieved measuring instrument.

Digital ALMEMO[®] D7sensor for pressure, consisting of Order no.

Pressure transducer series FDA 602-L



Pressure sensor FD 0602-Lx without connecting cable FD0602Lx Variants, Technical data and Accessories, see catalog page 10.04 ALMEMO® D7 connecting cable for FD 0602-Lx: cable box for sensor, with 2 meters cable, with ALMEMO® D7 measuring plug ZED7 00-FS, measuring rate 5 mops, ZDD702AKL including scaling to the measuring range of the pressure sensor. **Option:** Configuration of the connection cable: OA9007PRM500 ALMEMO® D7 measuring plug; measuring rate 500 mops For technical data of ZED7 00-FS, see chapter "Input connector".

Pressure transducer series FD 8214



Pressure sensor FD 8214-x without connecting cable FD8214x Variants, Technical data and Accessories, see catalog page 10.07 ALMEMO[®] D7 connecting cable for FD 8214-x: cable box for sensor, with 2 meters cable, with ALMEMO® D7 measuring plug ZED7 00-FS, measuring rate 5 mops including scaling to the measuring range of the pressure sensor. ZDD714AK **Option:** Configuration of the connection cable: OA9007PRM500 ALMEMO® D7 measuring plug; measuring rate 500 mops For technical data of ZED7 00-FS, see chapter "Input connector".

Pressure

Pressure Transducer FDA 602 L



- · Compact pressure sensors for industrial applications in liquid and gaseous substances.
- · Piezo-resistive, flexibly suspended silicone measuring cell in an oil-filled, all-welded special steel enclosure.
- The stable mechanical construction provides a reliable protection for the measuring cell against the test substance and immunes it against pressure peaks and vibrations.
- Available with three calibrations. Relative pressure: Pressure related to the environmental press. Absolute pressure: Pressure related to vacuum (0 bar) Overpressure: Pressure related to atm. pressure at manufacturing (approx. 1bar).

Technical Data:

Overload	Two times final value	Power supply	6.5 to 15 VDC,
Output signal	0.2 to 2.2 V	_	consumption <4 mA
Accuracy class (linearity + hysteresis + re	± 0.5 % of final value producibility)	Operating temperature	-40 to +100 °C
Total error range 0 to +50 °C	$\pm 1.0\%$ of final value	Pressure terminal	male thread G1/4" membrane not flush with
-10 to +80 °C ± 1.5 % of final value (linearity + hysteresis + reproducibility + temperature coefficients + zero-point + range tolerance)		Material in contact with med	ium Stainless steel DIN 1.4404/1.1135 External seal Viton
Response time (0 to 99 %)	<5 ms	Weight	approx. 50 g
Nominal conditions	22°C ±2 K, 10 to 90 % RH,	Protective class	IP 65
	non-condensing		G1/4"



6kt.SW19

ø16.6

3

7.5

□9.4

8

25

Quick-release coupling nominal width 5 internal thread G1/4"

nominal width 7,2 internal thread G1/4"

Other version: Pressure transducer with digital

ALMEMO[®] D7 measuring plug, see page 10.03. Digital sensor, can be calibrated without measuring device. Measurement of rapid pressure changes (pressure peaks).

Accessories

Accessories	Order no.
PTFE sealing tape, -200 to +260 °C, width 10 mm, thickness 0.1 mm, roll of 12 meters	ZB9000TB
Quick-release coupling, nominal width 5, up to 35 bar Connection internal thread G1/4", brass	ZB9602N5
Quick-release coupling, nominal width 7.2, up to 35 bar connection internal thread G1/4", brass	ZB9602N7

Types: including ALMEMO [®] cable 1.5m long		Measuring ranges overpressure:	
Measuring ranges 1 2.5 bar 5 bar 10 bar	relative pressure: FDA602L3R FDA602L4R FDA602L5R	25 bar 50 bar 100 bar 500 bar	FDA602L2U FDA602L3U FDA602L4U FDA602L6U
Measuring ranges a	absolute pressure:		
2.5 bar	FDA602L3A	Pressure transducer for measuring the temperature of refrigerants see page 10.08.	
5 bar	FDA602L4A		
10 bar	FDA602L5A	. 0	

front

DAkkS or factory calibration KD9xxx pressure for sensor or measuring chain (sensor + device) (see chapter Calibration certificates). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.
High-precision pressure sensor FDAD33/35M Very accurate over a wide temperature range, digital sensor with ALMEMO[®] D6 plug



- Technical data
- Digital pressure sensor (including A/D converter) Sampling rate, internal 200 Hz Material in contact with medium Pressure range 1 to 1000 bar Stainless steel, AISI 316L, see under variants Viton Zero-point at ambient Relative pressure Protection IP65 atmospheric pressure, current Dimensions see dimensional drawings Overpressure Zero-point at ambient Sensor connector Built-in plug atmosph. pressure, production Coupling, 2-meter PVC cable, Absolute pressure Zero-point, vacuum ALMEMO[®] connecting cable ALMEMO® D6 plug Pressure connection FDAD33 Outside thread G 1/4" ALMEMO[®] D6 plug Diaphragm, internal Refresh time 0.005 seconds for all channels FDAD35M Diaphragm, flush with front Output to the With the conversion rate of the Outside thread G 1/2" ALMEMO[®] device ALMEMO® device: max. 10 ... 100 Hz In pressure range 700/1000 bar depending on the device Outside thread G 3/4" and configuration Storage / operating temperature -40 to +120 °C Delay after sleep mode 1 second Accuracy 8 to 13 VDC Supply voltage Error margin* at +10 to +40 °C 0.05 % of final value Current consumption approx. 11 mA Error margin* at -10 to +80 °C 0.1 % of final value *Linearity, hysteresis, reproducibility, temperature coefficients, zero-point

- Stable piezo-resistive transducer with integrated A/D converter and signal processor
- Temperature-dependence and non-linearity are eliminated by means of mathematical compensation; this ensures a high level of accuracy.
- Digital output of measured value
- The current value is measured at the sensor's high sampling rate.
- To acquire transitory pressure fluctuations and pressure peaks the maximum value, minimum value, and average value are calculated from the current values in the ALMEMO[®] D6 plug and output in three function channels.
- One measuring channel is programmed (at our factory) :
- Pressure (bar, p) Uptothree function channels can also be activated (via LMEMO[®] device V6) : Maximum value, minimum value, average value. A complete configuration can be carried out either on the ALMEMO[®] V7 measuring instrument or directly on the PC with the USB adapter cable ZA 1919 AKUV (see chapter ALMEMO[®] "Network technology").

General features and accessories, ALMEMO® D6 sensors: see page 01.08

Pressure

Options	Order no.
Connecting cable Total length = 5 m	OD0D33L05
Connecting cable Total length $= 10 \text{ m}$	OD0D33L10
Greater lengths up to 100 meters on request	

Variants

Digital pressure sensor, plug connection, 2-meter connecting cable with ALMEMO® D6 plug, factory test certificate

0 1		e	1 8	~
Pressure range	Resolution	Overload	Order no.	Order no.
		Diaphragm, internal	Diaphragm, flush with front	
Relative pressure				
1 bar	0.0001 bar	2 bar	FDAD3301R	FDAD35M01R
3 bar	0.0001 bar	5 bar	FDAD3302R	FDAD35M02R
10 bar	0.001 bar	20 bar	FDAD3303R	FDAD35M03R
30 bar	0.001 bar	60 bar	FDAD3304R	FDAD35M04R
Special ranges -1 1	/ 3 / 10 bar on request			
Overpressure				
100 bar	0.01 bar	200 bar	FDAD3305U	FDAD35M05U
300 bar	0.01 bar	400 bar	FDAD3306U	FDAD35M06U
700 bar	0.1 bar	1000 bar	FDAD3307U	FDAD35M07U
1000 bar	0.1 bar	1000 bar	FDAD3308U	FDAD35M08U
Absolute pressure				
0,8 to 1,2 bar	0.0001 bar	2 bar	FDAD3300A	FDAD35M00A
1 bar	0.0001 bar	2 bar	FDAD3301A	FDAD35M01A
3 bar	0.0001 bar	5 bar	FDAD3302A	FDAD35M02A
10 bar	0.001 bar	20 bar	FDAD3303A	FDAD35M03A
30 bar	0.001 bar	60 bar	FDAD3304A	FDAD35M04A

DAkkS or factory calibration KD9xxx pressure for digital sensor (see chapter Calibration certificates).

DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.





- Compact pressure sensors for liquid and gaseous substances.
- Piezo-resistive measuring cell with temperature compensation.
- Pressure membrane and enclosure made from special steel.
- As the pressure is transmitted to the pressure membrane through a small hole in the thread part, the liquids should not be prone to crystallise and gases should not be heavily contaminated with dust. There are sensors with front-flush membranes for critical applications
- Available with three calibrations. Relative pressure: Pressure related to the environmental pressure, Absolute pressure: Pressure related to vacuum (0bar). Overpressure: Pressure related to atm. pressure at manufacturing (approx. 1bar).

Other version:

Pressure transducer with digital ALMEMO [®] **D7 measuring plug,** see page 10.03.

Digital sensor, can be calibrated without measuring device. High measured value resolution or measurement of rapid pressure changes (pressure peaks).

> Order no. internal

membrane

Option: Process connection. small flange (see under Options)

FD821407A

FD821408A

FD821409A

Measuring ranges absolute pressure:

1 bar

1.6 bar

2.5 bar

front flush

membrane

FD8214M07A

FD8214M08A

FD8214M09A

Options	Order no.		Order no.
Linearity 0.1% (for ranges 0.6 bar to 600 bar)	OR8214G1	Food compliant version	OD 001 40 41
Substance temperature -25 to $+100$ °C Substance temperature -25 to $+150$ °C	OR821411	Throttle against excess pressure	OR8214ML OR8214DS
(version with cooling fins)	OR8214T2	Output 0 to 10V	OR8214V
Process connection, small flange		Output 0 to 20mA	OR8214A
(for FD8214xxA absolute pressure)		Output 4 to 20mA	OR8214R4
KF16	OR8214KF16		

Accessories	Order no.		Order no.
Coupler socket with 2m cable	ZA8214AK	Coupler socket 6-pin Straight version	ZB9030RB
and ALMEMO [®] connector		Coupler socket 6-pin Angled version	ZB9030RBW

TypesOrder no.TypesFD 8214:

Standard version, inside membrane with G1/4" internal thread. External thread G1/2" available on request

FD 8214 M:

Membrane (welded with end of thread) flush with front, external thread G¹/₂", can be sterilised (important for food and pharmaceutical industry)

			4 bar	FD821410A	FD8214M10A
	inside	front flush membrane	6 bar	FD821411A	FD8214M11A
Measuring ranges	relative pressure:	memorane	10 bar	FD821412A	FD8214M12A
100 mbar	FD821401R	FD8214M01R	Measuring range	es overpressure:	
160 mbar	FD821402R	FD8214M01R	10 bar	FD821412U	FD8214M12U
250 mbar	FD821403R	FD8214M03R	16 bar	FD821413U	FD8214M13U
400 mbar	FD821404P	FD8214M04P	25 bar	FD821414U	FD8214M14U
600 mbar	FD821404R	FD8214M04R	40 bar	FD821415U	FD8214M15U
800 mbar	FD821406R	FD8214M06R	60 bar	FD821416U	FD8214M16U
1 bor	FD821407D	FD8214M07D	100 bar	FD821417U	FD8214M17U
1 0ai 1 6 har	FD821407K	FD8214M08R	160 bar	FD821418U	FD8214M18U
2.5 bar	FD821409R	FD8214M09R	250 bar	FD821419U	FD8214M19U
1 bor	FD821410D	FD921/M10D	400 bar	FD821420U	FD8214M20U
4 Ual 6 bar	FD821410K	FD8214M10K	600 bar	FD821421U	FD8214M21U
10 bar	FD821412R	FD8214M11R	1000 bar	FD821422U	FD8214M22U
10 000					

other measuring ranges on request

Pressure

Technical Data

OverloadRanges 600 bar, i.e. 3 times the final value (minimum 3 bar, maximum 850 bar) Ranges >600 bar, 1500 barOutput signal, power supply :Standard 0 to 2 volts, feed 6.5 to 13 volts (from ALMEMO® device), current <4 mA Option : 0 to 10 volts, feed 15 to 30 volts, load >10 kilohms, current <4 mA Option : 0 to 20 mA, feed 9 to 33 volts, (>18 volts at load 500 ohms), current <25 mA Option : 4 to 20 mA, 2 conductors, feed 9 to 33 volts, (>20 volts at load 500 ohms), current <25 mA
Output signal, power supply :Standard 0 to 2 volts, feed 6.5 to 13 volts (from ALMEMO® device), current <4 mA Option : 0 to 10 volts, feed 15 to 30 volts, load >10 kilohms, current <4 mA Option : 0 to 20 mA, feed 9 to 33 volts, (>18 volts at load 500 ohms), current <25 mA
Response time:typical 1 ms / 10 to 90 % nominal pressure
Linearity:Standard ± 0.25 % of final valueOption : ± 0.1 % of final value for ranges 0.6 bar and up to 600 bar
Media temperature: -25 to +100°C, temperature comp.: 0 to +70°C option: -25 to +100°C, temperature comp.: -25 to +85°C -25 to +150°C, temperature comp.: -25 to +85°C
Temperature drift:Zero-point $<\pm 0.08$ % of final value / °C for ranges >0.5 bar span $<\pm 0.02$ % of final value / °C for all ranges
Nominal temperature:22°C ±2 K, 10 to 90% rH non-condensingOperating temperature:Electronics: -25 to +85 °C
Material: housing, pressure connector: special steel 1.4404, membrane: special steel 1.4435, seal: Viton.
Operat. environment/Sealing: IP 67
Dimensions: see drawing
Connecting threads:Type 8214: internal thread G1/4", wrench SW 27 Option for absolute pressure: small flange KF16 Type 8214 M: external thread G1/2", wrench SW 27
Electrical connection Flush-mounting connector, binder coupling 723, 5-pin
Weight: approx 180 g







Type **FD8214M** membrane flush with front (welded with end of thread), external thread G1/2" can be easily sterilized L = 45mm

(L = 72 mm with option of medium temperature up to 150 $^{\circ}\mathrm{C}$ with cooling ribs)

Accessories	Order no.		Order no.
PTFE sealing tape, -200 to +260 °C, width 10 mm, thickness 0.1 mm, roll of 12 meters	ZB9000TB		
Quick-release coupling, nominal width 5, up to 35 bar Connection G1/4" external thread, brass	ZB8214N5	Quick-release coupling, nominal width 7.2, up to 35 Connection 1/4" external thread, brass	bar ZB8214N7

Quick-release coupling nominal width 5 external thread G1/4"



Quick-release coupling nominal width 7.2 external thread G1/4"

Pressure transducer for measuring the temperature of refrigerants FDA 602 LxAK



- Compact pressure sensors for industrial applications in liquid and gaseous substances.
- Piezo-resistive, flexibly suspended silicone measuring cell in an oil-filled, all-welded special steel enclosure.
- The stable mechanical construction provides a reliable protection for the measuring cell against the test substance and immunes it against pressure peaks and vibrations.
- Absolute pressure: pressure related to vacuum (0 bar).



Technical Data:

Overload	Two times final value	Power supply	6.5 to 15 VDC,
Output signal	0.2 to 2.2 V		consumption <4 mA
Accuracy class	$\pm 0.5\%$ of final value		via ALMEMO [®] connector
(linearity + hysteresis + re	vsteresis + reproducibility) Operating temperature -40 to		-40 to +100 °C
Total error range 0 to +50 °C	± 1.0 % of final value	Pressure terminal	male thread 7/16" membrane not flush with front
-10 to +80 °C	± 1.5 % of final value	Material in contact with me	edium Stainless steel
(linearity + hysteresis + re	producibility + temperature		DIN 1.4404/1.1135
coefficients + zero-point +	range tolerance)		External seal, Viton
Response time (0 to 99 %)	<5 ms	Weight	approx. 50 g
Nominal conditions	22°C ±2 K, 10 to 90 % RH,	Protective class	IP 65
	non-condensing		

Calculation of the refrigerant temperature with device special version SB0000R2 (LINEARIZATIONS FOR OTHER REFRIGERANTS ON REQUEST)

The ALMEMO[®] Version V6 devices, (2590-2/-3S/-4S, 2690, 2890, 8590, 8690, 5690) can be used a for continuous temperature measurement (resolution 0.1K) with absolute pressure sensors (resolution 0.001 bar compulsory !). Both, pressure and temperature can be selected or continuously indicated and recorded.

Technical data for ALMEMO® option SB0000R2:

Refigerant:	R22	R23	R134a	R404a	R404a
Pressure Range:	0 to 36 bar	0 to 49 bar	0 to 40,5 bar	0 to 32 bar	0 to 32 bar
Temperature Range:	-90°C to +79°C *	-100°C to +26°C *	-75°C to +101°C *	-60°C to +65°C *	-60°C to +65°C *
Operation point	dew-point	dew-point	dew-point	dew-point	boiling point
Refigerant:	R407C	R407C	R410A	R417A	R507
Pressure Range:	0 to 46 bar	0 to 46 bar	0 to 49 bar	0 to 27 bar	0 bis 37 bar
Temperature Range:	-50°C to +86°C *	-50°C to +86°C *	-70°C to +70°C *	-50°C to +70°C *	-70°C to +70°C *
Operating point	dew-point	boiling point	dew-point	dew-point	dew-point

*) The final temperature is obtained from the data of the refrigerant.

For pressure transducer with smaller pressure ranges, the specified final temperature changes. (Linearizations for other refrigerants on request) Special design refrigerant temperature for ALMEMO[®] devices V6

(Please order when buying new devices or send it to upgrade existing device)

· · ·	10	U	,	
Types				Order no.
including ALMEMO® connecting cable, 1.5 m, an	nd programming	g of a re	efrigerant measuring channel	
Measuring ranges Absolute pressure (resolution	0.001 bar)			
up to 10bar				FDA602L5AK
up to 30bar				FDA602L6AK
up to 50bar				FDA602L7AK

new: Measuring range up to 100 bar and up to 150 bar on request

DAkkS or factory calibration KD9xxx pressure for sensor or measuring chain (sensor + device) (see chapter Calibration certificates). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Order no. SB0000R2

Differential pressure transmitter FDA 602 D



- This measures the differential pressure in liquid and gaseous media indirectly using two absolute pressure sensors.
- This makes it less expensive but more robust with respect to asymmetrical overload.
- The differential pressure range should be at least 5% of the standard pressure range.
- Each side of the sensor incorporates two pressure connections. The transmitters can thus be used easily and conveniently in pressure pipes.
- It incorporates a high-speed, high-precision microprocessor.
- All reproducible errors affecting the pressure sensors, i.e. involving non-linearity and temperature dependency, can be completely eliminated by means of mathematical error compensation.



Technical Data:

Standard pressure range (maximum measurable pressure per pressure connection), overload, differential pressure range.		Power supply	6 to 15 VDC via ALMEMO [®] connector	
	See versions listed below.	Output	0 to 2 V	
Storage / operating temperature	e -40 to +100 °C	Electrical connection	Binder plug, including	
Compensated standard range -10 to +80 °C			ALMEMO [®] connecting cable,	
Error margin	margin $\leq 0.05\%$ typical,		2 meters	
C C	$\leq 0.1\%$ max. of final value to standard pressure range	CE conformance	EN61000-6-1 to 4 with shielded cable	
(linearity + hysteresis + repro	ducibility + temperature error)	Protective class	IP 65	
Pressure connections	G1/4" thread, female (2 per side)	Weight Low-pressure version	475 grams	
Material in contact with medium Stainless steel, 316L, DIN 1.4435		Medium-pressure version	750 grams	

Types

Differential pressure transmitter, including ALMEMO® cable, 2 meters

Standard pressure range Absolute pressure	Overload	Differential pressure range Please indicate final value	Order no.
Low-pressure version			
3 bar	10 bar	Final value 0.2 to 3 bar	FDA602D01
10 bar	20 bar	Final value 0.5 to 10 bar	FDA602D02
25 bar	30 bar	Final value 1.25 to 25 bar	FDA602D03
Medium-pressure version			
100 bar	200 bar	Final value 5 to 100 bar	FDA602D10
300 bar	450 bar	Final value 15 to 300 bar	FDA602D11

Order no. FDAD12SA

Digital atmospheric pressure sensor FDAD 12 SA, for barometric pressure Integrated in ALMEMO[®] D6 plug



General features and accessories, ALMEMO® D6 sensors

Special features

- Digital atmospheric pressure sensor with temperature compensation
- Very accurate over a wide temperature range
- The value measured for atmospheric pressure can also be used to compensate other sensors on the ALMEMO[®] device (programming comment *P).
- Compact design, without pressure connection sleeve
- Can be connected directly to the measuring instrument.
- One measuring channel is programmed (at our factory).
- Atmospheric pressure (mbar, AP, p)

see page 01.08

Digital atm. pressure se	nsor (integrated in ALMEMO [®] D6 plug)	ALMEMO [®] D6 plug		
Measuring range Accuracy	300 to 1100 mbar ±2.5 mbar in the range 700 to 1100 mbar	Refresh rate Supply voltage Current consumption	1 second for all channels 6 to 13 VDC 4 mA	
Operating range	at 23 °C ±5 K -10 to +60 °C 10 to 90 % RH non-condensing			
Dimensions	62 x 20 x 7.6 mm			

Variants (including manufacturer's test certificate)

Digital atmospheric pressure sensor for barometric pressure, integrated in ALMEMO® D6 plug

DAkkS or factory calibration KD92xx atmospheric pressure for digital sensor (see chapter Calibration certificates). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Pressure measuring connector for barometric pressure FDA 612 SA



- Compact design can be plugged directly onto measuring instrument.
- Piezo-resistive pressure sensor ensures high measuring accuracy.

Technical Data:

Measuring range	700 to 1050 mbar (total range 0 to 1050 mbar)	Sensor material	aluminum, nylon, silicone, silica gel, brass
Overload capacity	Maximum 1.5 times final value	Operating range	-10 to +60 °C, 10 to 90% RH,
Accuracy	± 0.5 % of final value		non-condensing
Nominal temperature	25 °C	Dimensions	90 x 20 x 7,6 mm
Temperature drift	$\leq \pm 1$ % final value at 0 to $+70$ °C		
Hose terminals	Ø 5 mm, 12 mm long		

Accessories	Order no.		Order no.
Connecting cable, 0.2 meters	ZA9060AK1	Extension cable, 4 meters	ZA9060VK4
Extension cable, 2 meters	ZA9060VK2		

Variants (including manufacturer's test certificate)

Pressure measuring connector for barometric pressure with pressure terminal sleeve

Order no. FDA612SA

Pressure

Pressure measuring connector for differential pressure FDA 612 SR, FDA 602 S2K



- New compact design can be plugged directly onto measuring instrument.
- Piezo-resistive pressure sensor ensures high meas. accuracy.
- Advisory note when used in conjunction with ALMEMO[®] 2890, 5690, 5790, 8590, 8690: The new ALMEMO[®] pressure measuring connector is very slightly higher (8.8 mm). As a result adjacent input sockets on the ALMEMO[®] device may be partly covered. However, the 1st input socket can always be used without restriction. Or, alternatively, the ALMEMO[®] pressure measuring connector can be plugged in at any input socket using connecting cable ZA9060AK1.

Technical Data

Overload capacity FDA612SR FDA602S2K	max. 1.5 times final value maximum 250 mbar	FDA602S2K $<\pm 2\%$ of final value	
Accuracy (zero-pt adjusted)	±0.5% of final value in range 0 to positive final value	Operating range	-10 to +60 °C, 10 to 90% RH,
Common mode pressure	FDA602S2K max. 700 mbar FDA612SR max. 3 bar	Dimensions	74 x 20 x 8.8 mm
Nominal temperature	25 °C	Hose terminals	Ø 5 mm, 12 mm long
Temperature drift FDA612SR compensated temperature	$<\pm1.5$ % of final value range 0 to +70 °C	Sensor material	aluminum, nylon, silicone, silica gel, brass

Accessories	Order no.		Order no.
Connecting cable, 0.2 meters	ZA9060AK1	Extension cable, 4 meters	ZA9060VK4
Extension cable, 2 meters	ZA9060VK2		

Variants (including manufacturer's test certificate)	Order no.
(including one set of silicone hoses, 2 meters) Pressure measuring connector for differential pressure	
Range ± 1000 mbar	FDA612SR
Range ±250 Pa (independent of position)	FDA602S2K
Range ±1250 Pa see chapter 09 Flow measurement: Pitot tube measurement	FDA602S1K
Range ± 6800 Pa see chapter 09 Flow measurement: Pitot tube measurement	FDA602S6K

Pressure Sensors for Wall Mounting FD 8612 DPS / APS



- Suitable for use in the laboratory, as well as for use in harsh industrial environments, e.g. HEVAC applications, clean room technology, medical technology, filter technology and finishing pass technology.
- The robust mechanics guarantees long term stability, linearity and good reproducibility.
- Temperature drift reduced to a minimum by specific compensation of the sensors.
- Operation is almost maintenance-free, as a result of the free-from-wear inductive measuring system.
- As standard, the integrated electronics provide a pressure proportional voltage signal from 0 to 2V as output.



Technical Data:

Linearity:	$\pm 1\%$ of final value,	Rise time:	T ₉₀ approx. 0.02s
	option: ±0.2% or ±0.5%	Temperature drift:	
Hysteresis:	$\pm 0.1\%$ of final value	Zero point	0.03% of final value / K,
Nominal temperature:	23°C	range	0.03% of final value / K
Overload capacity:	up to 400 mb: 5-fold, from 500 mb: 2-fold	Operative range:	+10 to +50°C, air humidity 10 to 90%
Max. common mode pressure: 1 bar (at differential measurement)			non-condensing
		Storage temperature:	-10 to +70°C
Power supply:	6 12 VDC, option: 230V 50/60Hz	- Housing:	material ABS 120 x 80 x 55mm (L x H x D) Safety class: 0
Power consumption:	approx. 3.5mA		
Output:	0 to 2V, option: 0 to $10V/0(4)$ to $20mA$	Protection system:	IP 54
Connection: electrical: screw terminals, screwed cable gland PG 7.		Weight:	approx. 300g
	screwed cable gland PG 7.	Sensor capacity:	approx. 3ml
pressure: 6.5mm hose connection		Volume increase:	approx. 0.2ml at nom. press.k

Optionen	Order no.		Order no.
Linearity 0.2% (DPS from final value / APS from range) with DPS only in ranges ≥ 2.5 mbar with APS only in range ≤ 100 mbar	OD8612L2	Power supply : 230 V Output 0 to 10 V (voltage supply 19 to 31 V DC)	OD8612N OD8612R2
Linearity 0.5% (DPS from final value / APS from range)	OD8612L5	Output 0 to 20 mA (voltage supply 19 to 31 V DC)	OD8612R3
with DPS only in ranges ≥ 1 mbar with APS only in range ≤ 200 mbar		Output 4 to 20 mA (voltage supply 19 to 31 V DC)	OD8612R4

Accessories	Order no.		Order no.
Connecting cable 2m long mounted with connected	or for connection		
to ALMEMO [®] devices	ZA8612AK2	Silicone hose black per m	ZB2295SSL
1 set silicone hoses 2m long black/colourless	ZB2295S	Silicone hose colourless per m	ZB2295SFL

Types	Order no.		Order no.
Measuring ranges relative and differential Pressure transducer type DPS Measuring range 2.5 to 1000 mbar Please specify measuring range Range 1 mbar (100 Pa), additional charge	pressure: FD8612DPS OD8612P10	Measuring ranges absolute pressure: Pressure transducer type APS Measuring range 900 to 1100 mbar, 800 to 1200 mbar Please specify measuring range	1000 mbar, FD8612APS
Range 0.5 mbar (50 Pa), additional charge	OD8612P05		

Force, Displacement

Technical Features of Force Transducers

The technical features of the force transducers are substantially fixed by VDI/ VDE guideline 2637. The most important terms are described below:

Measuring range:

The load range, for which the guaranteed error limits will not be exceeded.

Nominal load:

The nominal load is the upper limit of the measuring range. Depending on the sensor, the nominal load can be a tension or compression load.

Working load:

The working load is the load that can be applied to the sensor, as well as the nominal load, without affecting the specified characteristics. The working load range should only be used in exceptional cases. Load limit:

The load limit is the maximum permissible load that can be applied to the measuring cell without expecting a destruction of the measuring system. At this load the specific error limits are no longer applicable.

Breaking load:

The breaking load is the load where a permanent change or destruction occurs.

Maximum dynamic load:

Rated force related oscillation amplitude of a sinusoidally changing force in direction of the measuring axis of the sensor. At a load of 107 cycles the sensor, when being repeatedly used up to the rated force, is not subject to significant changes regarding the metrology characteristics.

Drift error:

The drift error is the maximum permissible change of the output signal of the sensor over the specified time at constant load and stable environmental conditions.

ALMEMO[®] Force Measurement

adjust the constant load (tare) to zero and calculated from this by the measuring is available for force transducers with to enter the final value as nominal value. instrument. An ALMEMO® connector that integrated reference resistor.

ALMEMO[®] force transducers allow to The correction value will be automatically switches on this resistor for the adjustment

Measurement of fast changes in force and force peaks with digital ALMEMO® D7 sensors

The new ALMEMO® V7 measuring The digital ALMEMO® D7 measuring system makes it possible to measure fast changes in force and force peaks with a temporal resolution of up to 1ms.

The (passive) measuring bridge of the force transducer measures the change in force without (electrical) delay.

plug ZKD7 00-FS works with an A/D converter integrated in the plug and with a measuring rate of up to 1000 measuring operations per second (1ms per measuring operation).

In combination with the ALMEMO® V7



The measured values are evaluated in the WinControl software as table or line diagram (see chapter "Software").





The overall accuracy of the measurement measuring plug, and is unaffected by the measuring chain, consisting of force

with the connected ALMEMO[®] D7 and extension cables used. The complete measuring plug, can be calibrated.

is determined only by the force transducer ALMEMO[®] display device / data logger transducer and connected ALMEMO[®] D7

High resolution measurement with digital ALMEMO® D7 sensors

The digital ALMEMO® D7 measuring reduced conversion rate. Thus, stable ALMEMO® plug on the ALMEMO® V7 plug not only enables fast measurements measured values with high resolution can measuring instrument. but also high resolution measurements. be achieved by using high-precision Thereby, the measuring plug works with sensors. The user can easily configure the

Force, Displacement

Force transducers with digital ALMEMO[®] D7 measuring plug

For force transducers (compression / tension), torque transducer or strain gauges. Fast measurement with 1000 measuring operations per second, resolution of 50 000 digits or high resolution of up to 200 000 digits, 10 measuring operations per second.



With digital ALMEMO® sensors, forces are measured with high measuring rates or high resolution.

Any force transducer with measuring chain becomes a digital sensor with the appropriate ALMEMO® measuring plug.

For technical data of the ALMEMO® D7 measuring plug ZKD7 00-FS, see chapter "Input connector".

Displacement transducer

Depending on the boundary and environmental conditions of the measuring task, different measuring methods can be used:

Linear inductive displacement transducer and displacement sensor:

Advantages: high accuracy, high resolution, robust, acceleration resistant, inexpensive, resistant to interference, very long-term stable, environmentally stable (dirt, humidity), spot measurement combined with basically non-contact measurement, easy assembly and handling

Conductive plastic potentiometers:

Advantages: high resolution, good linearity, inexpensive, good temperature and humidity coefficients, extensive application temperature range.

possible to record fast changes in

ALMEMO[®] Displacement Measurement

Our Potentiometric displacement sensors ALMEMO® connector before delivery. after the installation have been pre-aligned in the factory by The precise adjustment can be locally storing the correction values in the performed by the user with final measures

Measurement of fast changes in displacement with digital ALMEMO® D7 sensors

system makes it possible to measure fast changes in displacement with a temporal resolution of up to 10ms. The potentiometric displacement transducer measures changes in displacement without (electrical) delay. The digital ALMEMO® D7 measuring e.g. ALMEMO® 710, it is therefore

The new ALMEMO® V7 measuring plug ZKD7 00-FS works with an A/D converter integrated in the plug and with a measuring rate of up to 100 measuring operations per second (10ms per measuring operation). In combination with the ALMEMO® V7 measuring instrument,

displacement. The measured values are evaluated in the WinControl software as table or line diagram.



The overall accuracy of the measurement the ALMEMO® display device / data of displacement transducer and connected is determined only by the displacement transducer with the connected ALMEMO® D7 measuring plug, and is unaffected by

logger and the extension cables used.

The complete measuring chain, consisting



ALMEMO[®] D7 measuring plug, can be adjusted.

Displacement transducer with digital ALMEMO[®] D7 measuring plug

For displacement transducers and other potentiometric sensors. Fast measurement with 100 measurement operations per second, resolution of 10 000 digits



With digital ALMEMO[®] sensors, changes in displacement are measured with high measuring rate. Any potentiometric displacement transducer becomes a digital sensor with the appropriate ALMEMO® measuring plug.

For technical data of the ALMEMO® D7 measuring plug ZWD7 00-FS see chapter "Input connector".

Tension and Compression Sensor K25





Technical Data:

Max. load limit:	150% of final value
Maximum dynamic load:	70% of final value
Reference temperature:	23°C
Cable:	3m long, with axial ALMEMO [®] connector
Accuracy for tension:	<±0.1% of fin. val.
Accuracy for tension and comp	ression: $<\pm 0.2\%$ of fin. val.
Nominal measuring path:	<0.15mm
Operative range:	-10 to +70°C

- Wire strain gauges in four-conductor full-bridge circuit.
- Control resistance for final adjustment of the measuring range.
- All measuring ranges that are specified in Newton can also be supplied in kg ranges
- All ALMEMO[®] devices provide easy push-button adjustment of no-load and final value.

Other version: Force sensor with digital ALMEMO[®] D7 measuring plug, see page 10.15.

Digital sensor, can be calibrated without measuring device. High measured value resolution or measurement of rapid force changes.



Drift error at permanent load:	<0.07% per 30min
Permissible lateral forces:	$\pm 60\%$ of fin. val.
Protection system:	up to 1kN: IP 65, from 2kN: IP 67
Material:	up to 1kN: aluminium 2 to 50kN: stainless steel
Dimensions in mm	up to 10kN: A=50, B=75, C=20, D=M12 20kN, 50kN: A=65, B=85, C=40, D=M24 x2

Options for all Force Transducers	Order no.		Order no.
Indication of measured values with ALMEMO [®] devices in kg	OK9000K	Indication of measured values with ALMEMO [®] devices in N and kg	OK9000NK

Accessories	Order no.		Order no.
Knuckle eyes with external thread M 12 (2 pcs) (dimensions in mm: $D = M$ 12, $E = 16$, F = 32, $G = 12$, $L = 54$)	ZB902512	Knuckle eyes with external thread M 24 x 2 (2 pcs) (dimensions in mm: $D = M 24 x 2$, $E = 26$, F = 62, $G = 25$, $L = 94$)	ZB902524

Types (including test certificate)	Order no.
Measuring range 0.02kN 0.05kN, 0.1kN, 0.2kN, 0.5kN, 1kN, 2kN, 5kN or 10kN please specify	FKA0251
Measuring range 20kN	FKA0252
Measuring range 50kN	FKA0255
	(°C° ()

Factory calibration KK9xxx force (traction / thrust) for sensor or measuring chain (sensor + device) (see chapter Calibration certificates)

Other designs are available on request

Tension and compression sensor FKA 012 with male thread terminal $\,$ up to 1000 kN $\,$



Tension and compression sensor FKA 1563 low height, with male thread terminal up to 2 kN



Compression Sensor K 22



• Wire strain gauges in four-conductor full-bridge circuit.

Control resistance for final adjustment of the measuring range.
All measuring ranges that are specified in Newton can also be supplied in kg ranges.

All ALMEMO[®] devices provide easy push-button adjustment of no-load and final value.

Other version: Force sensor with digital ALMEMO[®] D7 measuring plug, see page 10.15. Digital sensor, can be calibrated without measuring device. High measured value resolution or measurement of rapid force changes.

Technical Data:

Max. load limit:	150% of final value		
Maximum dynamic load:	70% of final value	Nominal measuring path:	<0.2mm
Reference temperature:	23°C	Operative range:	-10 to +50°C
Cable:	radial. 3m long	Drift error at permanent load:	0.1% per 30min
	with ALMEMO [®] connector	Protection system:	IP 65
Accuracy:	$\leq \pm 0.5\%$ of final value	Material:	stainless steel

Type (including test certificate)

Measuring range 100 N, 200N, 500N, 1000N or 2000N please specify

Factory calibration KK9xxx force (tension or compression) for sensor or measuring chain (sensor + device) (see chapter Calibration certificates)

-

Compression Sensor K 1613



- Wire strain gauges in 4-conductor full-bridge circuit.
- Control resistance for final adjustment of the measuring range.
- All measuring ranges that are specified in Newton can also be supplied in kg rangesr.

All ALMEMO[®] devices provide easy push-button adjustment of no-load and final value.

Other version: Force sensor with digital ALMEMO[®] D7 measuring plug, see page 10.15.

Digital sensor, can be calibrated without measuring device. High measured value resolution or measurement of rapid force changes.

Technical Data:

Max. load limit:	150% of final value		
Maximum dynamic load:	70% of final value	Nominal measuring path:	<0.2mm
Reference temperature:	23°C	Operative range:	-10 to +50°C
Cable:	radial, 3m long	Drift error at permanent load:	0.1% per 30min
	with ALMEMO [®] connector	Protection system:	IP 65
Accuracy:	<±0.5% of final value	Material:	stainless steel

Type (including test certificate)

Measuring range 0.5kN, 1kN, 2kN, 5kN, 10kN or 20kN (50 kN on request) please specify

Order no. FKA613

Order no.

Order no. FKA022

Factory calibration KK9xxx force (tension or compression) for sensor or measuring chain (sensor + device) (see chapter Calibration certificates)

Compression Sensor

Torque sensor



ALMEMO® input connector for measuring bridges, millivolt / volt differential

Full bridges are measured in four-conductor circuits. The power supply for the bridges is provided by the ALMEMO® plug.



For technical data, see chapter "Input connectors".

Types			Order no.
Model	Meas. Range	Resolution	
55mV DC	-10.0 to +55.0	1 µV	ZA9105FS0
26mV DC	-26.0 to +26.0	1 µV	ZA9105FS1

Digital ALMEMO® D7 measuring plug for bridge differential mV

For force transducers (compression / tension), torque transducer or strain gauges. Fast measurement with 1000 measurement operations per second, resolution of 50 000 digits or high resolution of 200 000 digits, 10 measuring operations per second. Only for current ALMEMO[®] V7 measuring instruments, i.a. precision measuring instrument ALMEMO[®] 710 or ALMEMO[®] 202.

Full bridges are measured in four-conductor circuits. The power supply for the bridges is provided by the ALMEMO® D7 plug..

For technical data, see chapter "Input connectors".

Types:			Order no.
Range	Display range	Conversion rate	
DMS1*	±200 000 digits	10 mops	
or DMS2	+50 000 digits	1000 mons	7KD700FS
* Factory setting : The	e desired measuring range can be	e programmed on the ALMEMO [®] V7 device itself.	LKD / UUF S
Option: Configuration of ALMEMO [®] D7 measuring connector; measuring rate 1000 mops OA9007P			OA9007PRM1000

Displacement

Displacement Sensor, Potentiometric FWA xxx T



- · Displacement transducers are suitable for direct, accurate measurement of displacements in automatic control and metrology.
- The pickup of the displacement is performed by using a pull rod with a universal joint. This allows for an actuation that is free from backlash and transverse forces, even in case of parallel and angular displacements of transducer and measuring direction.
- Elastomer-damped, independently resilient multi-finger noble metal sliding contact for reliable contact, even at high adjustment speed, shock or vibration.
- · Long life, extraordinary linearity, pull rod running on two exact bearings, very high adjustment speed of up to 10m/s, shock and vibration resistant.

1 Pre-adjusted in the factory by storing the correction values in the ALMEMO® connector. The precise adjustment can be locally performed by the user with final measures after the installation.

Other version: Displacement transducer with digital ALMEMO[®] D7 measuring plug, see page 10.16. Digital sensor, can be calibrated without measuring device. Measurement of fast displacement changes.

Technical Data:

Independent linearity:	T25: ±0.2%; T50: ±0.15% T75: ±0.1%; T100: ±0.075% T150: ±0.075%
Housing length (meas. A+1mm)):T25: 63mm; T50: 88mm
	T75: 113mm; T100: 138mm
	1150: 188mm
Mech. stroke (meas. B ± 1.5 mm): T25: 30mm; T50: 55mm
	T75: 80mm; T100: 105mm
	T150: 155mm
Total weight (with 2m cable):	T25: 140g; T50: 160g
	T75: 170g; T100: 190g T150: 220g
Weight of the pull rod incl. cou	pling
and sliding contact block:	T25: 35g; T50: 43g
	T75: 52g; T100: 58g
	T150: 74g

Movability, ball-shaped couplir	ng ± 1 mm parallel displacement, $\pm 2.5^{\circ}$ angular displacement
Operating force (horizontal):	≤ 0.30N
Reproducibility:	0.002mm
Insulation resistance:	\geq 10MW, (500VDC, 1 bar, 2s)
Dielectric strength:	≤ 1mA, (50Hz, 2s, 1 bar, 500VAC)
Max. permissible torque:	140Ncm
Temperature range:	-30 to +100°C
Temperature coefficient:	typ. 5ppm/°C
Vibrations:	5 to 2000Hz/Amax
	= 0.75 mm/amax $= 20g$
Shock:	50g/11ms
Life span:	> 100 x 106 strokes
Protection system:	IP 40

Option

Plug connection (instead of fixed connected cable), including 3m cable with screwed round socket and ALMEMO® connector

OWA071AK

Order no.

Order no.

Types

25 mm / 0,001 mm

50 mm / 0,01 mm

Order no.

Working length/resolution, incl. ALMEMO® cable 2m long FWA025T **FWA050T FWA075T** 100 mm / 0,01 mm **FWA100T** 150 mm / 0,01 mm **FWA150T** included with delivery 2 tensioning clamps Z3-31 including 4 cap screws M4x10, 1 ball-shaped coupling





Displacement transducers FWA xxx TEX with pivot joint Protective class IP54, 10 to 300 mm



Displacement transducers FWA xxx TX2 Protective class IP67 with pivot joint, 25 to 300 mm

Displacement Tracer, Potentiometric FWA xxx TR





- Resistor and collector paths made from conducting plastic.
- · Suitable for direct measurements of displacement without a form-locking connection, position detection at stationary measuring objects, tolerance measurements and for continuous contour measurement.
- The pull rod, which is supported on both sides, allows for accepting transverse forces that, for example, occur during a continuous scan of curves or spline parts.
- Rear limit stop is used to provide a simple mechanical coupling of automatic retraction systems, such as pneumatic cylinders or electromagnets.
- · Long life, extraordinary linearity, tracer pin running on two exact bearings, DIN compliant standard measuring inserts can be used, shock and vibration resistant.
- Pre-adjusted in the factory by storing the correction values in the ALMEMO® connector. The precise adjustment can be locally performed by the user with final measures after the installation.

Other version:

Displacement transducer with digital ALMEMO® D7 measuring plug, see page 10.16.

Digital sensor, can be calibrated without measuring device. Measurement of fast displacement changes.

Independent linearity:	TR25: ±0.2%; TR50: ±0.15%	Operating force (horizontal):	$\leq 5 \text{ N}$
	TR75: ±0.1%;	Reproducibility:	0.002mm
	TR100: ±0.075%	Insulation resistance:	\geq 10MW (500VDC, 1 bar, 2s)
Housing length (meas. A+1mn	n):TR25: 63mm; TP50: 04.4mm;	Dielectric strength:	≤ 1 mA (50Hz, 2s, 1 bar, 500VAC
	TR50: 94.4mm; TR75: 134.4mm;	Max. permissible torque:	140Ncm
	TR100: 166mm	Temperature range:	-30 to +100°C
Mech. stroke (meas. B ±1.5mm): TR25: 30mm; TR50: 55mm		Temperature coefficient:	typ. 5ppm/°C
TR75: 80mm; TR100: 105mm	TR75: 80mm; TR100: 105mm	Vibrations:	5 to 2000Hz/Amax = 0.75mm/amax = 20g
Total weight (with 2m cable):	TR25: 120g; TR50: 150g	Shock:	50g/11ms
	TR75: 180g; TR100: 200g	Life span:	> 100 x 106 strokes
Weight of the pull rod incl. coupling and sliding contact block: TR25: 25g; TR50: 36g TR75: 48g; TR100: 57g	apling	Protection system:	IP 40
	TR75: 48g; TR100: 57g		
Max. operating frequency: (for upright')	r most critical application 'probe tip TR25: 18Hz: TR50: 14		

Option Plug connection (instead of fixed connected cable), including 3m cable with screwed round socket and ALMEMO® connector

TR75: 11Hz; TR100: 10Hz

Ordor no

Order no.

OWA071AK

Order no.

FWA050TR

FWA075TR

Working length/resolution, incl. ALMEMO® cable 2m long 100 mm / 0,01 mm 25 mm / 0,001 mm included with delivery FWA025TR

50 mm / 0,01 mm 75 mm / 0,01 mm

Types

Technical Data:

Order no.	
FWA100TR	

- 2 tensioning clamps Z3-31 including 4 cap screws M4x10,
- 1 probe tip with hard-metal ball

Speed, Flow

Optical Rotational Speed Meters

The optical reflection method has become the most accepted method for the measurement of revolutions of shafts, wheels, fans etc.

With single unit retroreflective photoelectric sensors the transmitters and receivers form one single unit. The light sent by the transmitter is, by an opposite located object, reflected to the receiver. The sensor performs a switch when the reflected amount of light exceeds a specific, adjustable limit value at the receiver. This quantity of light depends on the size and the reflection properties of the object. Special reflective tapes are used to increase the sensing range and to improve

the signal-to-noise ratio.

ALMEMO® rotational speed sensors can be used in two measurement setups:

photoelectric • Retroreflective sensor (DIN EN 60947: Type D) Detects only opaque objects. The range depends sensing on the reflectivity of the object, i.e. on the surface quality and colour. Sensitive with regard to contamination and against changes of the reflective properties of the object These influences (within can limits) be compensated by means of a sensitivity adjustment control

Only small mounting efforts are required as the sensor is a single unit device and a rough alignment is sufficient in most cases.

• Retroreflective light barrier (DIN EN 60947: Type R) Retroreflectors allow for long sensing ranges and an improved signal-to-noise ratio. Low susceptance to interferences, therefore, highly suitable for use under harsh conditions, e.g. outdoor applications or dirty environments

Turbine Flowmeters

The sensor contains a vane or paddle that starts rotating when a flow is present. Unlike the optical method, this method also allows for measurements in cloudy and non-transparent liquids. The rotational speed is proportional to the corresponding quantity of flow. The electrical output signal can be generated by two different methods:

• Inductive Proximity Switch: The rotor blades are provided with special steel caps, therefore, the rotor blades approaching the transducer cause a change of the inductance and the generation of a pulse type output signal. Hall Sensor: The rotor is provided with permanent magnets that affect a Hall sensor, which is located on the

transducer. The transducer electronics transforms the Hall signal into a pulse type electronical output signal.

For measuring the volume flow rate or for dosing tasks, the ALMEMO[®] sensor range includes turbine flowmeters for different measuring ranges and operating conditions:

- Radial turbine flowmeters for large flow quantities.
- Axial turbine flowmeters with rotating vane for small flow quantities



• Optical probe for measurements of rotational speed, designed as retroreflective photoelectric sensor for photoelectric detection of rotational speeds.

nev

- For evaluation of the pulses, the tachometer probe is equipped with a specific frequency meter module that calculates the number of revolutions per minute from the time period between two pulses. A stable read-out is achieved by averaging over a minimum of 500 ms.
- Easy application: A reflective adhesive tape is attached to the moving part and the probe is aligned with it. For function control purposes a yellow signal lamp at the rear side of the probe will be on when the reflective adhesive tape is recognised.
- To increase the operation reliability the sensitivity can be adjusted through a potentiometer.

Technical Data:

Measuring range:	8 bis 30000 UpM	Switching frequency:	< 1000 Hz
Resolution:	1 UpM	Ambient temperature:	-30° C to $+60^{\circ}$ C
Accuracy:		Storage temperature:	-40° C to $+70^{\circ}$ C
up to 15000 rpm:	± 0.02 % of m.v. ± 1 digit	Protection system:	IP 67
up to 30000 rpm:	\pm 0.05 % of m.v. \pm 1 digit	No-load current:	\leq 15 mA
Detection range:	20 bis 300 mm (depending on the reflector)	Supply voltage:	via ALMEMO [®] connector
Reference object:	standard white 100 mm x 100 mm	Connection:	Device connector M12x1
Sensitivity:	adjustable with potentiometers		angled, with 1.5 meters cable
Detectable object:	opaque or reflector		and ALMEMO® connector
Type of light:	red light 640 nm	Material:	
Light spot diameter:	appr. 20 mm at intervals of 300 mm	Housing:	brass, nickel plated,
A perture angle:	appr. 4°	Lens opening:	PMMA
Limit for foreign light:	EN 60947-5-2: 10000 lux	Dimensions:	M(12) 1
Display switching status:	LED yellow	length:	55mm

Accessories	Order no.
Extension cable, 1 meter long Extension cable, 2 meters long	ZA9060VK1 ZA9060VK2
Types	Order no.

Rotational Speed Sensor up to 30000rpm max., incl. 5 reflective adhesive tapes Connecting cable 1.5m long with ALMEMO[®] connector

DAkkS / DKD or factory calibration KU90xx rotational speed for digital sensor (see chapter Calibration certificates). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

FUA9193

Axial turbine flowmeter for liquids FVA 915 VTHM



- For measuring the volume flow rate or for dosing tasks with small flow rates.
- Extraordinary compact design.
- Wide, usable measuring range.
- Various options for operation: Cooling water flow, medical technology, plastics industry, solar systems, baker's equipment, machine tools, catering equipment, photographic laboratory equipment, dispensers, dosing equipment, cooling equipment, heating applications, calorimetry.

Technical Data:

swiviel nut G3/4	* 53 ±0,5
Flat gasket	
18,5 x 24 x 2 14	
SW27	
80	_

Nominal diameter	DN 15		
Measuring range	2 to 40 l / min continuous load max. 20 l/min		(from ALMEMO [®] device)
Measuring accuracy Reproducibility :	±1% of finale value ± 0,2 %	Electrical connection	4-pin connector M12x1 including PVC line (Tmax =70 °C) with ALMEMO® connector
Signal output	from 0.3 l/min	Materials	with ALMENIO connector
maximum size of particles in	n medium 0.5 mm	nine section	hross CuZn26Ph2As
maximum temperature of me	edium 85°C		NDD
Nominal pressure	PN10	Flat gasket	NBR
Process connection	G ³ / ₄ " external thread and union nuts	Turbine cage	PEI ULTEM
Pressure loss in har	$\Delta n = 0.00145 \text{ x } \Omega^2 (\Omega \text{ in } 1/\text{min})$	Rotating vane	PEI ULTEM
	approx. 0.6 bar at $201/\min$	Rotor complements	hard ferrite magnets
Protection system	approx. 2.3 bar at 40 1 / min IP 54	Axle / bearing	axle Arcap AP1D with hard metal pins
Output signal			in saphire bearings
Pulse rate / K factor	940 pulses / liter	Bearing support	Arcap AP1D
Resolution	1.1 ml / pulse	Sensor	PPO Noryl GFN3
Signal form rectan	rectangular signal, NPN,	O-ring	NBR
	open collector	Knurled swivel nut *	PA GF 30
Measuring transducer Hall sensor		* not coming into contact wi	ith the medium
Supply voltage	4,5 24 V DC	5	

Types

incl. connecting cable, 6m long with ALMEMO® connector, turbine body made of brass

DAkkS calibration KV91xx, flow rate, for digital probes, see chapter Calibration certificates. The DAkkS calibration fulfills the requirements of DIN EN ISO/IEC 17025 for test equipment.

Other designs are available on request Axial turbine flowmeters FVA915VTPx for water up to 150 °C, 300 bar, 2 to 40 l/min Figure - similar to above Magnetic-inductive flowmeters FVA 915 VMZx (new series VMZ.2) without moving parts, for small flow rates from 0.1 l/min and high flow rates up to 250 l/min



Order no.

FVA915VTHM

Axial turbine flowmeter for liquids FVA 915 VTH25M



- For measuring the volume flow rate or for dosing tasks with large flow rates.
- Compact design.
- Wide useful operating range.
- Wide variety of applications :
- Cooling water flow, medical technology, plastics industry, solar systems, baker's equipment, machine tools, catering equipment, photographic laboratory equipment, dispensers, dosing equipment, cooling equipment, heating applications, calorimetry.

Technical Data

Nominal diameter	DN 25	
Measuring range	4 to 160 l/min	
Continuous load	max. 80 l/min	
Measuring accuracy	$\pm 5\%$ of measured value up to 5l/min $\pm 7\%$ of measured value	
Reproducibility :	±0.5%	
Signal output	from < 1 l/min	
maximum size of particles in m	nedium 0.63 mm	
maximum temperature of medi	um 85°C	
Nominal pressure	PN10	
Process connection		
	G 1¼" external thread	
	including adapter for R 1"	
	(absolutely necessary)	
Pressure loss	approx. 0.1 bar at 80 1 / min approx. 0.45 bar at 160 1 / min	
Protection system	IP 54	
Output signal		
Pulse rate / K factor	65 pulses / liter	

Resolution	15 ml / pulse
Signal form	NPN, open collector
Measuring transducer	Hall sensor
Supply voltage	4,5 24 V DC
	(from ALMEMO [®] device)
Electrical connection	4-pin connector M12x1
	including PVC line (Tmax =70 °C)
	with ALMEMO® connector
Materials	
Pipe section	brass, CW602N
Turbine cage	PPO Noryl GFN 1630V
Rotation vane	PPO Noryl GFN 1520V
Rotor complements	Hard Ferrite Magnets
Axle / bearing	stainless steel 1.4539 /
	saphire, PA
Sensor socket	PPO Noryl GFN 1630V
O-ring	EPDM

Туре

incl. connecting cable, 6 m long, with ALMEMO® connector, turbine body made of brass

DAkkS calibration KV91xx, flow rate, for digital probes, see chapter Calibration certificates. The DAkkS calibration fulfills the requirements of DIN EN ISO/IEC 17025 for test equipment.

Other designs are available on request

Axial turbine flowmeters FVA 915 VTH40 6.7 to 417 l/min, DN40 Figure - similar to above

Turbine flowmeters FVA 915 VTRx Stainless steel, up to 120 °C, up to 250 bar for different flow rates from 1.8 l/min to 1133 l/min



Order no.

FVA915VTH25M

Flow

Flow sensors for liquids FVA 645-GVxQT5



Variant in stainless steel without any moving parts, with integrated temperature measuring



- Measuring section in stainless steel
- Application in systems with laminar flow, no pressure surges, no air pockets, no suspended solids
- Without any moving parts
- Integrated temperature measuring
- Low pressure loss
- Wide temperature range
- High-speed reaction time
- Using with water
- For heat output measurement in heating systems and cooling plant

Technical Data:

Flow		Suitable conditions	
Measuring principle	Pressure pulsation Kármán vortex street	Media	Water, Viscosity < 2 mm ² /s) and conductivity >2µS/cm
Measuring range	see variants	Temp. of medium	0 to +100 °C
Accuracy	using water as medium at 0 to +100°C	Ambient temperature	-25 to +60 °C
	±1.5 % of final value	Ambient humidity	up to 95 % RH, non-condensing
Resolution	see variants	Electrical connections	
Reaction time (63 %)	< 3 s	Output signal	2x 0.5 to 3.5 V (4.1 V)
Temperature		Power supply	5 VDC (±5 %), <10 mA
Measuring range	0 to +100 °C		via ALMEMO [®] connector
Accuracy	±1 K at +15 to +90 °C	Connection	Sensor with 2.9-meter
	±2 K at 0 to +100 °C		connecting cable
Resolution	0.1 K		and ALMEMO [®] connector
Reaction time (63 %)	<0,25 second under flow conditions	Fitting length	see variants
50% of final value		Materials (in contact with media)	
Process connection	2x male thread see variants	Corrosion-resistant coating EPDM, PPS, PPA 40-GF	
Pressure	10 bar	Pipe piece	Stainless steel 1.4408;
Pressure loss	0.1 bar, typical under flow conditions,50 % of final value		(inside pipe PPA 40-GF)

Variants

Sensor for flow rate and temperature over a measured section, including ALMEMO® connecting cable, 2.9 meters

Measuring range	ALMEMO [®] Resolution	Process connection	Fitting length	Order no.
1 to 18 l/min	0.01 l/min	G 3/4" male thread	ca. 110 mm	FVA645GV18QT5
2 to 40 l/min	0.01 l/min	G 3/4" male thread	ca. 110 mm	FVA645GV40QT5
5 to 100 l/min	0.1 l/min	G 1" male thread	ca. 129 mm	FVA645GV100QT5
10 to 200 l/min	0.1 l/min	G 1 1/4" male thread	ca. 137.5 mm	FVA645GV200QT5

DAkkS calibration KV91xx, flow, for probes, see chapter Calibration certificates.

The DAkkS calibration fulfills the requirements of DIN EN ISO/IEC 17025 for test equipment.

Content

11.02
11.03
11.05
11.07
11.09
11.11

ALMEMO[®] input connectors and adapter cables for all sizes see Chapter Input connectors



How Split-Core Type Transformers Work

high alternating currents without contact and without interrupting the circuit. In principle, they consist of 2 separate transformator windings $(B_1 = primary)$ winding with N_1 windings, $B_2 =$ secondary winding with N_2 windings) on one common iron core (closed magnetic circuit).

Current transformers are used to acquire If an alternating current I₁ flows through In practice, the primary winding B₁ consists the winding B_1 , a current I_2 is induced in the winding B,, which depends on the to be measured. The transformation winding ratio N_1/N_2 . In comparison with ratio of a current transformer is: stationary-installed panel transformers, split-core type transformers must be able to embrace a conductor within a magnetic circuit that is split open.

of only one winding that carries the current $I_1 \ge N_1 = I_2 \ge N_2$



IMPORTANT !

ALMEMO® measuring instruments generally allow the connection of sensors of other manufactures. We will gladly adapt your current clamp to ALMEMO®. Please contact us.

Order no.

Split-Core Type Transformer for AC Currents Chauvin Arnoux type Mini 09



- Perfectly suitable for use in maintenance and monitoring of electrical systems without interrupting their current supply.
- Application oriented design, particularly suitable for measurement in dense wiring.
- Ideal for non-contact control measurements with ALMEMO[®] hand-held devices, e.g. for fault currents or at devices with low current consumption.

Technical Data

Measuring range:	1A to 150A AC	Admissible voltage	300 V category IV or 600 V
Accuracy of meas.	40 to 150A: $\pm 4\%$		category III
at 50/60Hz:	15 to 40A: $\pm 3\% \pm 0.2A$	Operating frequency	48 to 500 Hz
	5 to $15A: \pm 6\% \pm 0.2A$	Operating conditions	-10 to +50°C, 10 to 85% RH
	1 to $5A: \pm 10\% \pm 0.2A$	Dimensions	130 x 37 x 25 mm
Encompassing capacity:	cable Ø 10mm	Weight	approx 180 grams
Transformation ratio:	100mVDC/1AAC	Storage temperature	$40 \text{ to } \pm 90^{\circ}\text{C}$
Output signal:	15VDC		
Nominal conditions	23°C ±3K, 1013 mbar, 20 to 75% RH	 Connecting cable Cable, 1.5 meters, with safety lab connectors, including safety coupling and 1.5-meter ALMEM necting cable with banana plugs 	
Electrical safety	EN 61010-2-032 (issue 2/2003)		

Types (including manufacturer's test certificate)

Single-range split-core type transformer with integrated rectifying for small AC currents incl. ALMEMO®	
connecting cable (±26VDC)	FEA6049

With test certificate of the manufacturer Chauvin Arnoux. Delivery in original packaging, adapted with ALMEMO® plug

Split-Core Type Transformer for AC Currents Chauvin Arnoux type MN 88



- Perfectly suitable for use in maintenance and monitoring of electrical systems without interrupting their current supply.
- Asymmetric shape of the jaw of tongs, particularly suitable for encompassing cables and rails.
- With polarity indicator for power measurements.
- Ideal for non-contact control measurements with ALMEMO[®] handheld devices, e.g. at low power systems.

Technical Data

Measuring range: (the higher value correspondent)	0.5A to 200A AC	Dimensions:	135 x 50 x 30mm
		Weight:	approx. 180g
Accuracy of meas. at 50Hz	$\pm 3\%$ of meas. Val. $\pm 0.5A$	Nominal conditions:	25°C ±3°C/1013mbar
Encompassing capacity:	cable Ø 20mm rail 20 x 5mm	Operating temperature:	$-10 \text{ to } +55^{\circ}\text{C}$
Transformation ratio	100mVDC/1A AC	operating temperature.	10 10 +55 C
	Relative humidity:	0% to 90% at 40°C max.	
Output signal:	20VDC	Storage temperature:	$40 \pm 70^{\circ}C$
Operating frequency:	A0Hz to 10kHz	Storage temperature.	-40.00 ± 70.0
Operating frequency.	40112 10 10K112	Connecting cable:	Connecting cable Integrated banana so-
Safety standards:	IEC 1010-1	ckets, including 1.5-meter	ALMEMO connecting cable with banana
Overvoltage protection:	category III	plugs	5

Types (including manufacturer's test certificate)

Single-range split-core type transformer with integrated rectifying for small AC currents incl. ALMEMO[®] connecting cable (±26VDC)

With test certificate of the manufacturer Chauvin Arnoux. Delivery in original packaging, adapted with ALMEMO[®] plug

Order no.

FEA604MN

Split-Core Type Transformer for AC Currents Chauvin Arnoux type Y4N



- Perfectly suitable for use in maintenance and monitoring of electrical systems without interrupting their current supply.
- Asymmetric shape of the jaw of tongs, particularly suitable for encompassing cables and rails.
- With polarity indicator for power measurements.
- Ideal for non-contact control measurements with ALMEMO[®] handheld devices, e.g. at low power systems.

Technical Data

Measuring range: (the higher value correspo	2A to 500A AC nds to 120% of the max. nominal value)		
Accuracy of meas. at 50Hz: \pm 3% of meas. val. \pm 0.5A		Weight	approx 420σ
Encompassing capacity:	cable Ø 30mm rail 30 x 63mm	Nominal conditions:	$25^{\circ}C + 3^{\circ}C/1013$ mbar
Transformation ratio:	1mVDC/1AAC	Operating temperature:	10 to ±55°C
Output signal:	0.5VDC	Delating temperature.	-10.00 + 55.0
Operating frequency:	40Hz to 1kHz	Relative numidity:	
Safety standards:	IEC 348 IEC 1010-2-032	Storage temperature:	$-40 \text{ to } + 70^{\circ}\text{C}$
Overvoltage protection:	no	 Connecting cable: Cable, 1.5 meters, with safety lab connectors including safety coupling and 1 5-meter ALMEN 	
Dimensions:	215 x 66 x 34mm	necting cable with banana	a plugs

Types (including manufacturer's test certificate)	Order no.
Single-range split-core type transformer with integrated rectifying for small and medium AC currents incl. ALMEMO [®] connecting cable (±2.6VDC)	FEA6044N

With test certificate of the manufacturer Chauvin Arnoux. Delivery in original packaging, adapted with ALMEMO® plug

Digital ALMEMO® D6 measuring module for DC voltage and DC current

Overvoltage proof measuring input. Galvanically isolated up to 6 kV. For connection to all ALMEMO[®] V6 / V7 measuring instruments.



Applications

ALMEMO® D6 measuring modules can be used for a wide variety of applications. Examples:

- Inexpensive monitoring of several DC voltage signals with a large number of measuring modules.
- Monitoring the charge and discharge processes (current, voltage) during the development of rechargeable batteries/batteries for electromobility and for other battery-operated devices.
- Monitoring the supply voltage and the current consumption of DC motors and other consumers.
- Checking switches.
- Monitoring of the electrical parameters voltage, current in addition to the physical measured variables such as temperature, pressure, air flow, flow rate, etc.

Technical data and functions

- The digital ALMEMO[®] D6 measuring module uses its own integrated AD converter. The overall accuracy of the measurement is independent from the ALMEMO[®] display unit/ data logger.
- The signals are measured at the internal sampling rate of 1 kHz and max, min and average values are calculated from them. The measured value and the calculated values are digitally

interrogated by the ALMEMO[®] measuring instrument at the conversion rate / measuring cycle of the measuring instrument.

- The ALMEMO[®] measuring instrument saves the measured values, and the measuring software WinControl will display them graphically.
- The measuring input is overvoltage proof and galvanically isolated from the ALMEMO[®] measuring device.

Technical data

Input sockets:	Safety sockets CAT III, 20 A, Ø 4 mm
Galvanic isolation:	6 kV
Sampling rate:	1 kHz internal
Refresh rate:	depending on measuring cycle / conversion rate of the ALMEMO [®] measuring device
Measuring range:	see types
Resolution:	see types
Overload:	see types
Internal resistance:	see types
Accuracy:	$\pm 0,1\%$ of fin. val. ± 2 Digit
Nominal conditions:	23 °C \pm 2 K, 10 to 90% RH (non-condensing)

Temperature drift	$max = 0.003 \frac{9}{K} (30 \text{ ppm/K})$
	111dX. 0.005 /0/K (50 ppin/K)
Suitable conditions:	$+5 \text{ to } +40 ^{\circ}\text{C}$
	(Storage temperature: -20 to +60 °C),
	10 to 90 % RH (non-condensing),
	maximum height above mean
	sea level: 2000 m
Housing:	ABS,
dimensions	127 x 83 x 42 mm (LxWxH)
Connecting cable:	2 m, permanently connected
ALMEMO® D6 plug:	for measuring channels see Types,
Configuration via the A	LMEMO [®] device
Supply voltage:	6 to 12 V via ALMEMO® device
Current consumption:	approx. 50 mA (plug and module)

ALMEMO[®] D6

Accessories			Order no.
DIN rail mounting Magnetic fastening			ZB2490HS ZB2490MH
	DIN rail mounting	Magnetic fastening	
ALMEMO [®] extension cable, lo ALMEMO [®] extension cable, lo	ength = 4 m (see chapter 6) ength = 10 m (see chapter 6)		ZA9060VK4 ZA9090VKC10

Types

Measuring module including touch-proof connecting cable, ALMEMO® connection cable permanently connected to the ALMEMO® D6 plug

DC voltage

4 ALMEMO® measuring channels: voltage, maximum value, minimum value, average value

Measuring range	Resolution	Overload	Input resistance	Order no.
±60 V DC	0.01 V	$\pm 90 \mathrm{V}$	1 MOhm	ZAD900AB3
±400 V DC	0.1 V	$\pm 400 \text{ V}$	4 MOhm	ZAD900AB5

DC current

4 ALMEMO® measuring channels: current, maximum value, minimum value, average value

Measuring range	Resolution	Overload	Input resistance	Order no.
±20 mA DC	0.01 mA	±500 mA	4.7 Ohm	ZAD901AB1
±200 mA DC	0.1 mA	$\pm 500 \text{ mA}$	1 Ohm	ZAD901AB2
±2 A DC	0.001 A	$\pm 4 \mathrm{A}$	100 mOhm	ZAD901AB3
±20 A DC*	0.01 A	±20 A	8 mOhm	ZAD901AB5

* Continuous operation up to a maximum of 10A. For currents exceeding the maximum of 10 A, the measuring period is 10 minutes. After that, the device needs to cool down to room temperature.

Other version

ALMEMO® D7 measuring module ZED7 0x-ABx see chapter 11

Power calculation via simultaneous measurement of voltage and current in one measuring module or dynamic measurements of DC signals (up to 1000 measurements/s).



DAkkS or factory calibration KE90xx electrical for digital measuring module (see chapter Calibration certificates). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.



Fast digital ALMEMO[®] D7 measuring module for DC voltage / DC current / DC power

Dynamic measurement of DC signals with 1000 mops (measuring operation per second). Overvoltage proof measuring input. Galvanically isolated up to 6 kV. For connecting current ALMEMO[®] V7 measuring instruments: ALMEMO[®] 500, 710, 809, 202, 204



٠

them graphically.

Applications

ALMEMO® D7 measuring modules can be used for a wide variety of applications. Examples:

- Inexpensive monitoring of several DC voltage signals with a large number of measuring modules.
- Monitoring the charge and discharge processes (current, voltage, power) during the development of rechargeable batteries/ batteries for electromobility and for other battery-operated devices.
- Monitoring the supply voltage and the current consumption during switch-on and switch-off processes of DC motors and other consumers.
- Checking switches and circuit breakers using fast switching cycles.

- Measuring the response time of electronic switches.
- Calculating the power by simultaneously measuring voltage and current in one measuring module.
- Monitoring the electrical parameters voltage, current and power of photovoltaic modules and photovoltaic systems while environmental parameters such as temperature, global radiation, and other meteorological parameters are recorded at the same time.
- Measuring fast changes in power during load tests with rapid load changes.

The ALMEMO® V7 measuring instrument saves the measured

values, and the measuring software WinControl will display

The maximum, minimum, and average values can be calculated

Technical data and functions

- The digital ALMEMO[®] D7 measuring module uses its own integrated AD converter. The overall accuracy of the measurement is independent from the ALMEMO[®] V7 display unit/data logger. The measurement rate is solely defined by the integrated AD converter. On the ALMEMO[®] V7 measuring instrument all D7 measuring plugs work in parallel at their own measuring rate.
- Dynamic measuring signals are measured by the ALMEMO[®] D7 measuring module at a fast conversion rate.

Technical data

by measuring functions in the measuring device or in the measuring software.
The measuring input is overvoltage proof and galvanically isolated from the ALMEMO[®] V7 measuring device.

Input sockets:	Safety sockets
1	CAT III, 20 A, Ø 4 mm
Galvanic isolation:	6 kV
Sampling rate:	1 kHz
Output cycle:	1 ms (1000 mops)
Measuring range:	see types
Resolution:	see types
Overload:	see types
Internal resistance:	see types
Accuracy:	$\pm 0,1\%$ of fin. val. ± 2 Digit
Nominal conditions:	23 °C ±2 K, 10 to 90% RH
	(non-condensing)

Temperature drift:	max. 0.003 %/K (30 ppm/K)	
Suitable conditions:	+5 to +40 °C (Storage temperature: -20 to +60 °C), 10 to 90 % RH (non-condensing),	
	maximum height above mean sea level: 2000 m	
Housing: dimensions	ABS, 127 x 83 x 42 mm (LxWxH)	
Connecting cable:	2 m, permanently connected	
ALMEMO [®] D7 plug: Configuration via the A	for measuring channels see Types, LMEMO [®] V7 device	
Supply voltage:	6 to 12 V via ALMEMO® device	
Current consumption:	approx. 50 mA (plug and module)	

ALMEMO[®] D7



Types

Measuring module including touch-proof connecting cable, ALMEMO[®] connection cable permanently connected to the ALMEMO[®] D7 plug

DC voltage

1 ALMEMO® measuring channel: voltage

Measuring range	Resolution	Overload	Input resistance	Order no.
±60 V DC	0.01 V	$\pm 90 \mathrm{V}$	1 MOhm	ZED700AB3
±400 V DC	0.1 V	$\pm 400 \text{ V}$	4 MOhm	ZED700AB5

DC current

1 ALMEMO® measuring channel: current

Measuring range	Resolution	Overload	Input resistance	Order no.
±20 mA DC	0.01 mA	±500 mA	4.7 Ohm	ZED701AB1
±200 mA DC	0.1 mA	$\pm 500 \text{ mA}$	1 Ohm	ZED701AB2
±2 A DC	0.001 A	$\pm 4 \mathrm{A}$	100 mOhm	ZED701AB3
±20 A DC*	0.01 A	±20 A	8 mOhm	ZED701AB5

* Continuous operation up to a maximum of 10A. For currents exceeding the maximum of 10 A, the measuring period is 10 minutes. After that, the device needs to cool down to room temperature.

DC power

3 ALMEMO® measuring channels: voltage, current, power

Measuring range voltage**	Measuring range current**	Measuring range power (calculated)	Resolution power	Order no.
±60 V DC	$\pm 2 \text{ A DC}$	120 W	0.1 W	ZED707AB33
±60 V DC	$\pm 20 \text{ A DC}^*$	1.2 kW	0.01 kW	ZED707AB35
±400 V DC	$\pm 2 \text{ A DC}$	800 W	0.1 W	ZED707AB53
$\pm 400 \text{ V DC}$	$\pm 20 \text{ A DC}^*$	8 kW	0.01 kW	ZED707AB55

* Continuous operation up to a maximum of 10A. For currents exceeding 10 A, the maximum measuring period is 10 minutes. After that, the device needs to cool down to room temperature.

** Resolution, Overload, Input resistance see further above.

DAkkS or factory calibration KE90xx electrical for digital measuring module (see chapter Calibration certificates). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Digital ALMEMO® D6 measuring module for AC voltage and AC current

For acquiring the true root mean square (RMS) value of a sinusoidal AC signal. Sampling rate of 1000 mops. Overvoltage proof measuring input. Galvanically isolated up to 6 kV. For connection to all ALMEMO[®] V6 / V7 measuring instruments



Applications

ALMEMO® D6 measuring modules can be used for a wide variety of applications. Examples:

- Inexpensive monitoring of several AC voltage signals with a large number of measuring modules
- Monitoring the supply voltage and the current consumption of machines, motors, and other consumers.
- Checking switches.

- Monitoring of the electrical parameters voltage, in addition to the physical measured variables such as temperature, pressure, air flow, flow rate, etc.
- Voltage and / or current measurement of 1-phase user (230 V AC) through a touch-proof Schuko-socket outlet adapter (accessory).

Technical data and function

- The digital ALMEMO[®] D6 measuring module uses its own integrated AD converter. The overall accuracy of the measurement is independent from the ALMEMO[®] display unit/ data logger.
- The AC signal with sinusoidal curve progression is digitalized at the integrated AD converter at a high sampling rate and based on that, the true RMS value will be calculated continuously. At the same time, the frequency of the AC signal will be determined.
- The measured values are digitally interrogated by the ALMEMO[®] measuring device at the conversion rate of the measuring device..
- The ALMEMO[®] measuring instrument saves the measured values and the measuring software WinControl will display them graphically.
- The measuring input is overvoltage proof and galvanically isolated from the ALMEMO[®] measuring device.

Technical data

Input sockets:	Safety sockets CAT III, 20 A, Ø 4 mm	Nominal conditions:	Alternating signal: sinusoidal 50 Hz, 23 °C \pm 2 K, 10 to 90% RH
Galvanic isolation:	6 kV		(non-condensing)
Sampling rate:	1 kHz internal	Temperature drift:	max. 0.003 %/K (30 ppm/K)
Refresh rate:	0.5s	Suitable conditions:	+5 to +40 °C
AC signals U,I:	only sinusoidal signals, no signals with phase angle control	_	(Storage temperature: -20 to +60 °C), 10 to 90 % RH (non-condensing), maximum height above mean
Response threshold U,I:	Signal U and $I > 1$ % of fin. val.	_	sea level: 2000 m
Operating range U, I, P:	DC 250 Hz	Housing:	ABS, 127 x 83 x 42 mm (LxWxH)
Measuring range U, I, P:	see Types	Connecting cable:	2 m, permanently connected
Resolution:	see Types	ALMEMO [®] D6-plug:	for measuring channels, see Types,
Overload:	see Types		configuration via ALMEMO® device
Internal resistance:	see Types	Supply voltage:	6 to 12 V via ALMEMO® device
Accuracy:	$\pm 0.1\%$ of fin. val. ± 2 Digit	Current consumption:	approx. 50 mA (plug and module)
Measuring range frequence Resolution:	y:20 to 250 Hz		

ALMEMO[®] D6

Accessories		Order no.
DIN rail mounting		ZB2490HS
Magnetic fastening		ZB2490MH
Socket adapter: max. 230 V AC / 16 A Earthed socket for the consumer. 3 safety jacks Incl. short-circuit plug for current path. Housin	: voltage, current, COM. g: W 65 x H 120 mm	ZE2000PA
	.0.	
DIN rail mounting	Magnetic fastening	Socket adapter
ALMEMO [®] extension cable, length = 4 m (see ALMEMO [®] extension cable, length = 10 m (see	e chapter 6) ee chapter 6)	ZA9060VK4 ZA9090VKC10

Types

Measuring module including touch proof connecting cable, ALMEMO[®] connection cable permanently connected to the ALMEMO[®] D6 plug

AC voltage

2 ALMEMO® measuring channels: voltage, frequency

Measuring range	Resolution	Overload	Input resistance	Order no.
25 V _{RMS} AC	0.01 V	$\pm 60 \text{ V}_{\text{RMS}}$	1 MOhm	ZAD903AB3
$400 V_{\rm RMS}^{\rm AC}$ AC	0.1 V	$\pm 400 \text{ V}_{\text{RMS}}$	4 MOhm	ZAD903AB5

AC current

2 ALMEMO® measuring channels: current, frequency

Measuring range	Resolution	Overload	Input resistance	Order no.
1,8 A _{RMS} AC	0.001 A	$\pm 4 A_{RMS}$	100 mOhm	ZAD904AB1
$20 A_{RMS} AC*$	0.01 A	$\pm 20 \ A_{_{RMS}}$	8 mOhm	ZAD904AB3

* Continuous operation up to a maximum of 10A RMS. For currents exceeding 10A RMS, the maximum measuring period is 10 minutes. After that, the device needs to cool down to room temperature.

Other version

ALMEMO® D7 measuring module ZED7 3x-ABx see chapter 11

Power calculation via simultaneous measurement of voltage and current in one measuring module or acquisition of fast signal changes during switch-on / switch-off processes.



DAkkS or factory calibration KE90xx electrical for digital measuring module (see chapter Calibration certificates). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.



Fast digital ALMEMO® D7 measuring module for AC voltage / AC current / AC power

For acquiring the true root mean square (RMS) value of a sinusoidal AC signal. Sampling rate of 1000 mops. Overvoltage proof measuring input. Galvanically isolated up to 6 kV.

For connecting current ALMEMO® V7 measuring instruments: ALMEMO® 500, 710, 809, 202, 204



Applications

ALMEMO[®] D7 measuring modules can be used for a wide variety of applications. Examples:

- · Inexpensive monitoring of several AC voltage signals with a large number of measuring modules
- Monitoring the supply voltage and the current consumption during switch-on and switch-off processes of machines, motors, and other consumers.
- · Checking switches and circuit breakers using fast switching cycles.
- Measuring the response time of electronic switches
- Power calculation (effective power, power factor) through the parallel measurement of voltage and electricity in one measuring module.
- · Monitoring of the electrical parameters voltage, electricity and power through inverter in photovoltaic systems with parallel

Technical data and function

- The digital ALMEMO® D7 measuring module uses its own integrated AD converter. The overall accuracy of the measurement is independent from the ALMEMO® V7 display unit/data logger. On the ALMEMO® V7 measuring instrument all D7 measuring plugs work in parallel using their own measuring rate.
- The AC signal with sinusoidal curve progression is digitalized at the integrated AD converter at a high sampling rate and based on that, the true RMS value will be calculated continuously. At the same time, the frequency of the AC signal will be

documentation of the environmental parameters like temperature, global radiation and other meteorological measuring variables.

- · Recording of quick power changes during loading tests with quick load changes.
- Power measurement of 1-phase user (230 V AC) through a touch-proof Schuko-socket outlet adapter (accessory).
- Recording of the power consumption of mobile machines (cleaning machines, high-pressure cleaner amongst others) and of domestic devices (refrigeratros, radiant heater, ovens amongst others) additionally to the physical measuring variables like temperature, pressure, air velocity, flow rate amongst others.

determined. The power measuring modules will measure voltage as well as current synchronically and based on these two, the effective power and the performance factor will be calculated.

- The ALMEMO® V7 measuring instrument saves the measured values and the measuring software WinControl will display them graphically.
- The measuring input is overvoltage proof and galvanically isolated from the ALMEMO® V7 measuring device.

Technical data

	Input sockets:	Safety sockets CAT III, 20 A, Ø 4 mm	Performance factor cos φ :	0.17 to 1 precondition: zero crossings!
,	Galvanic isolation:	6 kV	Resolution:	0.01
	Sampling rate:	1 kHz internal	Nominal conditions:	Alternating signal: sinusoidal 50 Hz,
	Output cycle / settling time	e: 4 periods (max. 200 ms)		23 °C ±2 K, 10 to 90% RH (non-condensing)
	AC signala U.L.	e.g. at 50 HZ. 80 his (approx. 12 hiops)	Temperature drift:	max. 0.003 %/K (30 ppm/K)
	AC signais 0,1:	no signals with phase angle control	Suitable conditions:	+5 to +40 °C
Response th Operating r	Response threshold U,I:	Signal U and $I > 1$ % of fin. val.		(Storage temperature: -20 to $+60$ °C), 10 to 90 % PH (non condensing)
	Operating range U, I, P:	DC 250 Hz		maximum height above mean sea level: 2000 m
,	Measuring range U, I, P:	see Types		
	Resolution:	see Types	Housing:	ABS, 127 x 83 x 42 mm (LxWxH)
	Overload:	see Types	Connecting cable:	2 m, permanently connected
	Internal resistance:	see Types	ALMEMO® D7-plug:	for measuring channels, see Types,
Accuracy:		$\pm 0.1\%$ of fin. val. ± 2 Digit		configuration via ALMEMO [®] V7
	Measuring range frequency	asuring range frequency: 20 to 250 Hz		
	Resolution:	0.01 Hz	Supply voltage:	6 to 12 V via ALMEMO [®] device
			Current consumption:	approx. 50 mA (plug and module)

ALMEMO[®] D7

Accessories		Order no.
DIN rail mounting Magnetic fastening Socket adapter: max. 230 V AC / 16 A Earthed socket for the consumer. 3 safety jacks: Incl. short-circuit plug for current path. Housing	voltage, current, COM. g: W 65 x H 120 mm	ZB2490HS ZB2490MH ZE2000PA
DIN rail mounting	Magnetic fastening	Socket adapter

Types

Measuring module including touch proof connecting cable, ALMEMO® connection cable permanently connected to the ALMEMO® D7 plug

AC voltage

2 ALMEMO® measuring channels: voltage, frequency

Measuring range	Resolution	Overload	Input resistance	Order no.
25 V _{RMS} AC	0.01 V	$\pm 60 \text{ V}_{\text{RMS}}$	1 MOhm	ZED730AB3
$400 \mathrm{V}_{\mathrm{RMS}}^{\mathrm{AMS}} \mathrm{AC}$	0.1 V	$\pm 400 \text{ V}_{\text{RMS}}$	4 MOhm	ZED730AB5

AC current

2 ALMEMO® measuring channels: current, frequency

Measuring range	Resolution	Overload	Input resistance	Order no.
1,8 A _{RMS} AC	0.001 A	$\pm 4 A_{RMS}$	100 mOhm	ZED731AB1
$20 A_{RMS} AC^*$	0.01 A	$\pm 20 \ A_{_{RMS}}$	8 mOhm	ZED731AB3
4 G				

* Continuous operation up to a maximum of 10A RMS. For currents exceeding 10A RMS, the maximum measuring period is 10 minutes. After that, the device needs to cool down to room temperature.

AC power

5 ALMEMO® measuring channels: voltage, current, effective power, frequency, performance factor cosp

Measuring range voltage**	Measuring range current**	Measuring range power (calculated)	Resolution power	Order no.
25 V _{RMS} AC	1.8 A _{rms} AC	45 W	0.1 W	ZED737AB31
400 V _{RMS} AC	1.8 A _{rms} AC	720 W	1 W	ZED737AB51
400 V _{RMS} AC	20 A _{RMS} AC*	8 kW	0.01 kW	ZED737AB53
* 0	C10 A F	1. 10 4		. 10

* Continuous operation up to a maximum of $10 A_{RMS}$. For currents exceeding $10 A_{RMS}$, the maximum measuring period is 10 minutes. After that, the device needs to cool down to room temperature.

** Resolution, Overload, Input resistance see further above.

DAkkS or factory calibration KE90xx electrical for digital measuring module (see chapter Calibration certificates). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Meteorology

Content

Small glossary of meteorological terms	12.02	
Compact meteorological transducer FMD760	12.03	
Mobile weather station	12.06	
Wind direction sensor FVA 614	12.09	
Wind velocity sensor FVA 615	12.10	
Global radiation probe head FLA 613 GS	12.11	
Radiation probe head FLA 613 VLM	12.11	
UVA radiation probe head FLA 613 UVA	12.12	
UVB radiation probe head FLA 613 UVB	12.12	
Digital measuring head for erythema effective UV radiation	12.13	
Star pyranometer FLA 628S	12.15	
Digital sensor for temperature, humidity,		
atmospheric pressure in protective all-weather housing	12.16	
	10.10	
Comfort index measurement in the workplace	12.18	
Digital carbon dioxide sensor for assessing the indoor air quality	12.19	
WBGT measurement for evaluating heat-exposed workplaces	12.21	

Meteorology



Compact Glossary of Meteorological Terms

Response value	The wind velocity at which the cup or the wind vane starts to move.		
Barometer	General term for the device measuring the atmospheric pressure.		
Barometric pressure	Pascal [Pa] = Newton per square meter $[N/m^2]$; 1hPa=1mbar; 1 bar=10 ⁵ Pa		
Beaufort	Classification for certain wind velocity ranges: bft m/s bft m/s bft m/s bft m/s bft m/s bft m/s 0 0 - 0.2 1 0.3 - 1.5 2 1.6 - 3.3 3 3.4 - 5.4 4 5.5 - 7.9 5 8.0 - 10.7 6 10.8 - 13.8 7 13.9 - 17.1 8 17.2 - 20.7 9 20.8 - 24.4 10 24.5 - 28.4 11 28.5 - 32.6 12 32.7 - 36.9 13 37.0 - 41.4 14 41.5 - 46.1 15 46.2 - 50.9 16 51.0 - 56.0 17 56.1 - 61.2		
Damping ratio	Measure for the damping of wind vanes. It is the ratio of successive damped deflection amplitudes (e.g. 3rd to 1st amplitude) in one direction.		
Distance constant	Is the distance that has been passed by the wind and which is reached when, after a sudden change of the wind velocity, the velocity has reached 63% of the final value.		
Gray code	One step digital code used for the wind direction.		
Altitude formula	Mathematical reduction of the barometric air pressure to a reference altitude, at minimum to sea level (QFF). Example: with each altitude increase of 8m the pressure decreases by approximately 1hPa.		
Detection limit	The lowest value of the wind velocity and wind direction where a stable measured value is established.		
Normal pressure	The barometric normal pressure (1013.25hPa) that, according to DIN ISO 2533, serves as base value for the 'high pressure' and 'low pressure' data.		
QFE	The atmospheric pressure that has been reduced to the elevation of an airport runway.		
QFF	Designation used in aviation for the barometric air pressure that has been reduced to sea level (0m). Also serves as a common base for the barometric air pressure comparison of different weather stations with different elevations of the stations and it is the base for the presentation of the isobars in weather maps.		
QNH	Designation commonly used in aviation for the barometric air pressure, which has to be entered into an altimeter as an initial value so the altimeter can indicate the altitude above sea level.		
Altitude of station	The local elevation regarding the installation of the measuring station incl. the barometer above sea level.		
Variation	The range in which the wind direction has been changing within the preceding 10 minutes (acc. to ICAO).		
Wind velocity	Usual practical units: 1m/s = 3.6km/h = 1.9455knots		
Wind direction	Specification of which direction the wind comes from. The specification is based on a clockwise setup starting from North to East (90°), South (180°) and West (270°) to North (360°).		
Wind travel	Is the distance travelled by the wind during a certain period.		
Compact meteorological transducer for professional use - FMD760 Digital sensors for measuring wind, precipitation, air temperature, atmospheric humidity, atmospheric pressure. Maintenance-free measuring procedures for wind and precipitation Forced-ventilated radiation-protected housing





Technical data and functions

Digital meteorological transducer for operating with ALMEMO[®] V7 devices

This digital meteorological transducer, with its integrated signal processor or A/D converter, can acquire all important weather variables in one device (over 20 different measurable variables). Up to 10 measuring channels can be evaluated simultaneously via the ALMEMO[®] D7 plug.

On leaving our factory the following variables are programmed : wind velocity (m/s), wind direction (°), precipitation quantity (mm), precipitation intensity (mm/h), air temperature (°C), relative atmospheric humidity (% RH), barometric atmospheric pressure (hPa).

The meteorological transducer operates with current ALMEMO[®] V7 devices, including precision measuring instrument ALMEMO[®] 710 and professional measuring instrument ALMEMO[®] 202.

For professional applications

The meteorological transducer complies in essence with all specifications laid down by the WMO (world meteorological organization) and is used in a wide variety of areas, e.g. weather services, water management, transport technology (roads, rail), agriculture, renewable energy technology, and the monitoring of air quality and atmospheric emissions.

The transducer can be fitted quickly and easily, e.g. on a mast or pole, using the supplied bracket.

The connection cable can be plugged onto the transducer. In the small connection box the signal cables are clamped and the mains unit 24V for the heating system supply are plugged. In mobile use (without mains unit 24V) heating and fan (see below) are deactivated, and the rainfall radar (see below) can be operated in Energy Saver mode. 1

Wind

Wind is measured by means of four ultrasonic sensors (the four main compass points). From the runtime differences the wind velocity is calculated in m/s and the wind direction in $^{\circ}$.

This measuring procedure is maintenance-free (no moving parts). For operation in winter the ultrasonic sensors can if so required be heated.

Precipitation, rainfall

Precipitation is acquired using tried and tested radar technology. A Doppler radar measures the velocity of individual drops of rain / snow. Precipitation quantity (in mm) and precipitation intensity (in mm/h) can be calculated on the basis of the correlation of drop size and drop velocity. The type of precipitation (rain / snow) is determined on the basis of the different velocity of descent.

This measuring procedure is maintenance-free (no moving parts). For operation in winter the precipitation sensor can if so required be heated.

Air temperature and atmospheric humidity

Air temperature is measured (in $^{\circ}$ C) by means of a high-precision NTC resistance sensor; relative atmospheric humidity is measured (in $^{\circ}$ RH) by means of a capacitive humidity sensor. These sensors are enclosed in a forced-ventilated radiation-protected housing in order to minimize external influences (e.g. solar radiation, etc.). This ensures that in spite of high solar radiation accurate measuring results can still be achieved. The forced ventilation, similarly, improves responsiveness in the event of condensation.

Atmospheric pressure

Absolute atmospheric pressure is measured (in hPa) by means of an integrated sensor.

Measured values

The sensors in the meteorological transducer measure the current measured values continuously and at their internal sampling rate. In the ALMEMO[®] D7 plug the minimum / maximum / average values and quantities are calculated (at the output cycle of the ALMEMO[®] V7 device); this is for the purpose of various measurable variables.

Technical data

Wind velocity Measuring method Measuring range Resolution Accuracy	Ultrasonic 0 to 75 m/s 0.1 m/s ±0.3 m/s or ±3 % (0 to 35 m/s)	Measuring range Resolution Accuracy sensor Sampling rate ALMEMO [®] D7 quantities	300 to 1200 hPa 0.1 hPa ±0.5 hPa (0 to +40 °C) 1 minute Current momentary value
Response threshold Sampling rate	±5 % (>35 m/s) RMS 0.3 m/s 10 seconds Average value, minimum value	Operating conditions Temperature Relative humidity	-50 to +60 °C (with heating) 0 to 100 % RH
ALMENIO D7 quantities	maximum value (at output cycle)	Dimensions (including fix Height	ture) 343 mm
Wind direction		Diameter	150 mm
Measuring method Measuring range	Ultrasonic 0 to 359.9 °	Weight	approx. 1.5 kg (including fixture, excluding connection cables)
Resolution	0.1 degrees $(2 \circ (21 \text{ m/s}))$	Housing	Plastic Protective class IP66
Response threshold Sampling rate	0.3 m/s 10 seconds	Fixture	Mast fixture, stainless steel, for \emptyset 60 to 76 mm
ALMEMO [®] D7 quantities	Average value, minimum value,	Sensor connector	Built-in plug
	maximum value, average value as text (at output cycle)	Sensor connection cable	fitted in connection box Length (see variants, accessories)
Precipitation, rainfall Measuring method Measuring range Resolution Precipitation types Reproducibility	Radar sensor Drop size 0.3 to 5.0 mm Precipitation, liquid 0.01 mm rain, snow typical >90 %	Connection box	Clamp fitting the sensor connection cable and the ALMEMO [®] connection cable Plug fitting the mains unit cable for the heating system supply Dimensions 80 x 82 x 55 mm 3 cable glands
Response threshold Sampling rate Rainfall intensity ALMEMO [®] D7 quantities	0.002 mm On reaching the response threshold, event-dependent 0 to 200 mm/h; Sampling rate 1 minute Rainfall quantity or snow quantity (at the output cycle) Rainfall intensity or snow intensity, current momentary value	Heating Supply voltage Current consumption via external mains unit 2 100 to 240 V AC / 24 V fitted in the connection	24 VDC 1.7 A (40 W) ZB1024NA2 (in delivery), DC, 4,17 A with hollow connector, box
Air temperature	NTC	ALMEMO [®] connection ca	ble fitted in connection box Length = 2 meters
Measuring methodN1CMeasuring range-50 to $+60 \ ^{\circ}C$ Resolution0.1 K (-20 to $+50 \ ^{\circ}C$), otherwise 0.2 KAccuracy sensor $\pm 0.2 \text{ K}$ (-20 to $+50 \ ^{\circ}C$), otherwise $\pm 0.5 \text{ K}$ (>-30 $\ ^{\circ}C$)Sampling rate1 minute		ALMEMO® D7 plug Refresh rate 2 seconds for all current momentary values Average value, maximum value, minimum value and quantities - at the output cycle (minimum 2 sec. up to 24 hours) of the ALMEMO® V7 device	
ALMEMO [®] D7 quantities	Current momentary value, average value, minimum value, maximum value (at output cycle)	Supply with mains unit 2 All functions available. 24 V from the mains unit	4V (default): it, max. 1,8 A.
Atmospheric humidity Measuring method Measuring range Resolution Accuracy sensor Sampling rate ALMEMO [®] D7 quantities Atmospheric pressure Measuring method	capacitive 0 to 100 % RH 0.1 % RH ±2 % RH 1 minute Current momentary value MEMS sensor, capacitive	12 V from ALMEMO® of Supply without mains un Fan and heating deactive 12 V from ALMEMO® of typ. 130 mA with rainfa Operating in Energy Saver typ. 25 mA, no rain test typ. 130 mA for 2 s / Mit typ. 130 mA continuous	device, typ. 10 mA. it 24V (mobile operation): ated. device, ll radar in continuous operation. mode 1: / no rain, in in the rain test, ly, in the rain

Accessories

Accessories	Order no.
Sensor connection cable, free ends $Length = 20$ meters	ZB9760AK20
Overvoltage arrester (for stationary operation)	ZB9760USP

Variants

12.04

Digital meteorological transducer for measuring wind, precipitation, air temperature, atmospheric humidity, atmospheric pressure. Forced-ventilated radiation-protected housing, integrated heating, bracket for mast fitting. Sensor with built-in plug, including sensor connection cable Length = 10 meters fitted in connection box, external mains unit ZB1024NA2, fitted in the connection box, ALMEMO[®] connection cable fitted in connection box Length = 2 meters with $ALMEMO^{\text{®}} D7$ plug

DAkkS / DKD or factory calibration for digital sensors, see chapter "Calibration certificates". The DAkkS / DKD calibration meets the requirements of DIN EN ISO/IEC 17025 for test equipment.

Order no.

FMD760



new Digital meteorological transmitter FMD7 70 Compact transmitter for professional use Digital sensors for global radiation and further measured variables such as wind, precipitation, air temperature, humidity, atmospheric pressure.



Technology and function

Global radiation

The global radiation is measured with the pyranometer mounted in the cap of the transmitter. For further measured quantities and general functions see FMD7 60.

Technical data

Global radiation

Measuring method	thermopile pyranometer
Spectral range	300 1100 nm
Measuring range	$0 \dots 2000 \text{ W/m}^2$
Resolution	$< 1 \text{ W/m}^2$
Measuring rate	10 seconds
ALMEMO [®] D7 range:	Actual value

For technical data on the other measured variables and general functions, see FMD7 60

Features

Order no.

Digital meteorological sensor for wind, precipitation, air temperature, humidity, atmospheric pressure and global radiation. Ventilated radiation protection, built-in heater, mounting bracket for mast mounting. Sensor with built-in plug, including sensor connection cable, length = 10 m, mounted in the connection box. Power supply unit 24 V ZB1024NA2, mounted in the connection box, ALMEMO[®] connection cable, mounted in the connection box, length = 2 mwith ALMEMO® D7 connectorr



FMD770

Digital meteorological transmitter FMD7 20 Compact transmitter for professional use Digital sensors for wind. Maintenance-free measuring method.



Technology and function

Wind

Technology for wind measurement and general functions see FMD7 60

Technical data

For technical data on wind and general functions see FMD7 60

Features

10/2021 • We reserve the right to make technical changes

Digital meteorological transmitter for wind. Built-in heater, mounting bracket for mast mounting. Sensor with built-in plug, including sensor connection cable, length = 10 m, mounted in the connection box. Power supply unit 24 V ZB1024NA2, mounted in the connection box, ALMEMO[®] connection cable, mounted in the connection box, length = 2 m with ALMEMO® D7 connector

FMD720

Order no.

Mobile weather station Digital meteorological sensor and measuring heads for radiation with ALMEMO[®] V7 data logger





FMD7 60

FMD7 70





Professional weather station for mobile use to measure all relevant meteorological parameters. Quick and easy to install, robust design, compatible with various ALMEMO[®] V7 data loggers.

Applications

- Building automation (heating, ventilation, shading)
- Photovoltaic monitoring
- Industrial emissions tracing
- Disaster control (tracing clouds of poisonous gas, etc.)
- Sporting events, Leisure facilities
- Agricultural trials
- Road weather information systems (RWIS)
- Icy roads warning systems
- Vehicle test circuits

The mobile weather station comprises :

- Digital meteorological sensor including mobile tripod
- Probe head for measuring optical radiation
- ALMEMO® V7 data logger choice of ALMEMO® 202 / 204 / 710 / 809

Digital meteorological sensors

Digital sensor incl. 10 m sensor connection cable, connection box with power supply and 2 m ALMEMO[®] connection cable with ALMEMO[®] D7 plug. Technical data see chapter Meteorology. Sensor for wind, precipitation, air temperature, Air humidity, air pressure FMD760 Transducer as FMD760, but additionally for clobal radiation

Transducer as FMD760, but additionally for global radiation	FMD770
Transmitter for wind (wind direction and wind speed)	FMD720

Mobile tripod, extendable up to approx. 4.4 meters

including set of anchoring fixtures, comprising three karabiners, three guy lines (4 meters long), three ground pegs ZB9760ST Carry-bag, space for one tripod including accessories and two probe head holders ZB9510TT

Probe head for measuring global radiation, illuminance, photosynthesis, and UVA, UVB and UVE radiation

Measuring head with 1.5 m ALMEMO® connection cable.	
Technical data see chapter meteorology	
<i>new</i> : Measurement of erythema-active UV radiation (UVE)	
up to 0.3 W/m ² , UV index, dose (MED, SED).	
Digital measuring head with ALMEMO® D7 connector.	FLD733UVE
Probe head with cable, 1.5 meters long	
Measuring of global radiation up to 1200 W/m ² ,	FLA633GS
Measuring of illuminance up to 170 kLux,	FLA633VLM
Measuring of photosynthetically active radiation	
up to 3000 µmol/m ² s,	FLA633PSM
Measuring of UVA radiation up to 3 mW/cm ² ,	FLA633UVA
Measuring of UVB radiation up to 50 μ W/cm ² ,	FLA633UVB
Option of probe head with longer cable Total length = 5 meters	OA9613K05
Probe head holder to tripod Length = approx. 0.5 meters, for one radiation probe head FLA613-GS / -VLM / -PSM / -UVA / -UVB	ZB9510MH
Advisory note	
To connect these radiation probe heads to data logger ALMEMO®	202 a digital
ALMEMO [®] D7 measuring connector is required.	-
This variant is offered on request.	



Weather-proof housing for ALMEMO* 202 / 204 / 710 / 809 devices and meteorological sensor FMD7 60 / FMD7 70 / FMD7 20

Technical data and functions

The sensor connection cable, mains unit ZB 1024 NA2 (for heating, ventilation, and sensor supply), the junction box, and the sensor's ALMEMO[®] connection cable are all permanently fitted in the weather-proof housing. (Sensor FMD7 60 / FMD7 70 / FMD7 20 should be ordered separately.)

The ALMEMO[®] measuring instrument is integrated in the DIN rail mounting. The mains unit for the device supply (mains plug assembly, NA9 design) is plugged into the integrated socket. (The measuring instrument should be ordered separately.)

The device receives its continuous 110 / 230 V supply via the mains connection cable. Length = 2 meters (Connection is on the rear of the housing.)

When using devices ALMEMO[®] 202 / 204 / 710, any short-term failures to the supply voltage are bridged; in the case of ALMEMO[®] 202 / 204, this is by means of batteries and in the case of ALMEMO[®] 710, by means of the integrated rechargeable battery.

The ALMEMO® device cannot be operated in sleep mode.

Further variants on request:

For information on protective housing ZB9015AGU for various ALMEMO[®] measuring instruments performing general applications <u>without</u> meteorological sensor FMD7 xx.

Weather-proof housing AG2 for ALMEMO $^{\circledast}$ 202 / 204 and meteorological sensor

Weather-proof housing for ALMEMO® 202 / 204, lockable transparent door, mast fixture integrated rail for fastening ALMEMO® 202 / 204 device including mains unit ZA 1312 NA9 for supplying the device permanently fitted sensor connection cable for sensor FMD7 xx integrated mains unit for supplying sensor heating and sensor ventilation Option of weather-proof housing for sensor FMD7 60 / FMD7 70 / FMD7 20 OM9760AG2

Data logger ALMEMO® 202 / 204 with accessories

ALMEMO [®] 202 professional measuring instrument	
2 measuring inputs, graphics display, keypad controls, batteries	MA202
ALMEMO [®] 204 professional measuring instrument	
4 measuring inputs, internal data logger,	
graphics display, keypad controls, batteries	MA204
DIN rail holder for the measuring instrument	ZB2490HS
Memory connector with micro SD	ZA1904SD
USB data cable	ZA1919DKU





Weather-proof housing AG7 for ALMEMO[®] 710 and meteorological sensor

Weather-proof housing for ALMEMO® 710,

lockable transparent door, mast fixture integrated rail for fastening ALMEMO[®] 710WG device including mains unit ZA 1312 NA9 for supplying the device permanently fitted sensor connection cable for sensor FMD7 xx integrated mains unit for supplying sensor heating and sensor ventilation Option of weather-proof housing for sensor FMD7 60 / FMD7 70 / FMD7 20 OM9760AG7

Data logger ALMEMO[®] 710 with accessories

AI MFMO [®] 710WC precision measuring instrument	
in well-mounted housing	
10 manufing inputs, display and operation via touch server	
To measuring inputs, display and operation via touch screen	
internal measured value memory, integrated rechargeable battery	
including mains unit NA10 (100 to 240 VAC / 12 VDC)	
and USB data cable	MA710WG
Option of external memory	
Mamony connector with micro SD	7 4 100/5D
Wiemory connector with micro SD	LA19045D

Weather-proof housing AG8 for ALMEMO[®] 809 and meteorological sensor

Weather-proof housing for ALMEMO® 809, lockable transparent door, mast fixture integrated rail for fastening ALMEMO® 809 device including mains unit ZB 1212 NA9 for supplying the device permanently fitted sensor connection cable for sensor FMD7 xx integrated mains unit for supplying sensor heating and sensor ventilation Option of weather-proof housing for sensor FMD7 60 / FMD7 70 / FMD7 20 OM9760AG8

Data logger ALMEMO[®] 809 with accessories

ALMEMO [®] 809 precision measuring instrument	
9 measuring inputs	
operation via ALMEMO® Control software	
internal measured value memory	
including mains unit NA10 (100 to 240 VAC / 12 VDC)	MA809
DIN rail holder for the measuring instrument	OA2290HS
USB data cable	ZA1919DKU
Option of external memory	
Memory connector with micro SD	ZA1904SD



Wind Direction Sensor FVA 614



- Wind direction sensor for measuring the horizontal wind direction.
- Wind vane made from robust plastic, electronics in weatherresistant aluminum housing, rotating mechanism on friction bearings.
- A special labyrinth reliably protects without friction and guards against water penetrating into the housing.
- Electronically controlled heating for operation in winter conditions to prevent bearings and external rotating parts from freezing.

 A calculation channel is required in the WinControl measuring software to calculate the mean value of the wind direction (averaging is not possible in the AL-MEMO[®] measuring device).

Technical Data

Measuring range:	0 to 360°	Connection:	Adapter cable with ALMEMO® connector
Accuracy:	$\pm 5^{\circ}$		including supply cable for heating
Resolution:	11.25° (5 bit Gray code)		(length 1.5 m, free ends)
Measuring principle:	optoelectronically (slotted disk)	_	by the user on site.
Sensor power supply:	9-30VDC through ALMEMO® device	Installation:	e.g. pole tube with holding thread
Heating:	24VAC/DC max. 20W		PG21 / drilling 29mm Ø
Operative range:	-30 to +70 °C, with heating	Weight	1100 g
Cable:	12m long, LiYCY 6 x 0.25mm ²		

Туре

Wind vane including ALMEMO® connector (0-2V) with 12m cable

Order no. FVA614



Wind Velocity Sensor FVA 615 2



- Wind velocity sensor for measuring the horizontal wind velocity.
- Cup-type made from robust plastic, electronics in weatherresistant aluminum housing, rotating mechanism on friction bearings.
- A special labyrinth reliably protects without friction and guards against water penetrating into the housing.
- Electronically controlled heating for operation in winter conditions to prevent bearings and external rotating parts from freezing.

Technical Data

Measuring range:	0.5 to 50m/s	Connection:	Adapter cable with ALMEMO [®] connector
Accuracy:	± 0.5 m/s $\pm 3\%$ of meas. value		including supply cable for heating
Resolution:	0.1m/s		(length 1.5 m, free ends)
Measuring principle:	optoelectronically (slotted disk)		by the user on site.
Sensor power supply:	9-30VDC through ALMEMO [®] device	Installation:	e.g. pole tube with holding thread
Heating:	24VAC/DC max. 20W		PG21 / drilling 29mm Ø
Operative range:	-30 to +70 °C, with heating	Weight	750 g
Cable:	12m long, LiYCY 6 x 0.25mm2		

Туре

Cup-type anemometer including ALMEMO® connector (0-2V) with 12m cable

Order no. FVA6152

Global Radiation Probe Head FLA 633 GS



- · Measuring head in anodized aluminium housing with a plastic dome that is transparent to UV light.
- Rain and splash-proof system, additionally with desiccant to prevent dome from inside condensation.
- Particularly suitable for outdoor measurements, e.g. in medical and biological research, weather information and forecast systems, climatology, agriculture and for general public information.

Technical Data

Measuring range:	0.4 to approx. 1200W/m^2	Cos correction:	error $f2 < 3\%$
Spectral sensitivity:	400nm to 1100nm	Linearity:	< 1%
Maximum spectral sense	itivity: 780nm	Absolute error:	< 10%
Signal output:	0V to 2V	Residual voltage: $(E = 0)$	< 10mV
Power supply:	+5V to +15V	Nominal temperature:	$22^{\circ}C \pm 2^{\circ}C$
Mounting:	2 screws M4, in base plate	Operating temperature:	-20°C to +60°C
Cable passage:	downwards	Dimensions:	Dome diameter: 40 mm
Housing:	anodized aluminium		Housing diameter 80 mm
Diffusor:	PTFE		Height 53 mm \pm 10 mm (conical ring) \pm 20 mm (dome)
Dome:	PMMA	Weight:	approx. 300 g
0			
Option			Order no.

Option

Longer cable Total length = 5 meters

Type (including test protocol)

Weather-proof measuring head for measuring the global radiation, incl. ALMEMO® connector with 1.5m cable FLA633GS Factory calibration KL90xx radiation for sensor (see chapter Calibration certificates)

Illuminance measuring head FLA 633 VLM



- · Measuring head in anodized aluminum housing, with UVtransparent plastic dome.
- Rain-proof, splash-protected system, with desiccant to prevent condensation forming on the inside of the dome.
- Especially suitable for measuring operations outdoors, e.g. in medical, biological, and climate research, in weather information forecast systems, in agriculture, and for the purposes of general information for the public.
- The spectral sensitivity of the receiver corresponds approximately to that of the human eye.

Technical Data

Measuring range :	0.05 to 170 klux (approx. 250 W/m ²)	Cos correction :	error f2 <3%
Spectral sensitivity :	360 to 760 nm	Linearity :	<1%
Max. spectral sensitivity :	550 nm	Absolute error :	< 10 %
Signal output	0 to 2 V	Residual voltage $(E = 0)$:	<10 mV
Power supply :	+5 to +15 V	Nominal temperature :	$22 \pm 2 \ ^{\circ}C$
Mounting :	2 screws, M4, in base plate	Operating temperature :	-20 to +60 °C
Cable passage :	downwards	Dimensions :	Dome diameter: 40 mm
Housing :	anodized aluminum		Housing diameter 80 mm
Diffusor :	PTFE		+20 mm (dome)
Dome :	РММА	Weight :	approx. 300 g

Type (including test protocol)

Weather-resistant measuring head for measuring the illuminance including cable, 1.5 m, and ALMEMO® connector Factory calibration KL90xx radiation for sensor (see chapter Calibration certificates) Order no.

OA9613K05

Order no.

FLA633VLM

UVA Radiation Probe Head FLA 633 UVA



- Measuring head in anodized aluminium housing with a plastic dome that is transparent to UV light.
- Rain and splash-proof system, additionally with desiccant to prevent dome from inside condensation.
- Particularly suitable for outdoor measurements, e.g. in medical and biological research, weather information and forecast systems, climatology, agriculture and for general public information.

Technical Data

Measuring range:	0.03 to approx. 100 W/m ²	Cos correction:	error f2 < 3%
Spectral sensitivity:	310 to 400nm	Linearity:	< 1%
Maximum spectral sensitivity: 355nm		Absolute error:	< 10%
Signal output:	0V to 2V	Residual voltage: $(E = 0)$	< 10mV
Power supply:	+5V to +15V	Nominal temperature:	$22^{\circ}C \pm 2^{\circ}C$
Mounting:	2 screws M4, in base plate	Operating temperature:	-20°C to +60°C
Cable passage:	downwards	Dimensions:	Dome diameter: 40 mm
Housing:	anodized aluminium		Housing diameter 80 mm
Diffusor:	PTFE		+20 mm (dome)
Dome:	PMMA (transparent to UV)	Weight:	approx. 300 g
Dome:	PMMA (transparent to UV)	Weight:	approx. 300 g

Type (including test protocol)

Weather-proof measuring head for measuring the UVA radiation including cable, 1.5 m, and ALMEMO $^{\circledast}$ connector

Factory calibration KL90xx radiation for sensor (see chapter Calibration certificates)

UVB RadiationProbe Head FLA 633 UVB



- Measuring head in anodized aluminium housing with a plastic dome that is transparent to UV light.
- Rain and splash-proof system, additionally with desiccant to prevent dome from inside condensation.
- Particularly suitable for outdoor measurements, e.g. in medical and biological research, weather information and forecast systems, climatology, agriculture and for general public information.

Technical Data

Measuring range:	0.02 to approx. 50mW/cm ²	Cos correction:	error $f2 < 3\%$
Spectral sensitivity:	265 to 315nm	Linearity:	<1%
Maximum spectral sensiti	vity: 297nm	Absolute error:	< 10%
Signal output:	0V to 2V	Residual voltage: $(E = 0)$	< 10mV
Power supply:	+5V to +15V	Nominal temperature:	$22^{\circ}C \pm 2^{\circ}C$
Mounting:	2 screws M4, in base plate	Operating temperature:	-20°C to +60°C
Cable passage:	downwards	Dimensions:	Dome diameter: 40 mm
Housing:	anodized aluminium		Housing diameter 80 mm
Diffusor:	PTFE		+20 mm (dome)
Dome:	PMMA (transparent to UV)	Weight:	approx. 300 g

Type (including test protocol)

Weather-proof measuring head for measuring the UVB radiation including cable, 1.5 m, and ALMEMO[®] connector Factory calibration KL90xx radiation for sensor (see chapter Calibration certificates)

Order no.

FLA633UVA

Order no.

Digital measuring head for erythema effective UV radiation (UVE) FLD7 33-UVE with ALMEMO[®] D7-connector. Weatherproof housing for outdoor use

Monitoring of UVE-radiation hazardous for human skin. Stationary measurements in meteorological applications. Supplement to the weather station FMD7 60. For connection to current measuring instruments ALMEMO® V7 : ALMEMO® 500, 710, 809, 202, 204



ALMEMO[®] UVE-measuring head in a weatherproof housing for outdoor use, FLD7 33-UVE

Erythema effective UV radiation

The natural UV radiation of the sun or the UV radiation of artificial sources has different effects to human skin dependant on the wavelength range.

- The long-wave UV radiation (more than 313 nm, UVA) tans the skin and supports the human immune system.
- The short-wave UV radiation (less than 313 nm, UVB/UVE) may cause irreversable damage.

In the recommendation of the CIE (Commission Internationale de l'Eclairage) all spectral effect functions which can have a negative effect on the human skin are summarized. This recommendation is described in the DIN 5050 resp. ISO/CIE 17166 and valuated as a directive.

UVE-measuring head FLD7 03-UVE

The measuring head records the erythema effective UV radiation. The spectral sensitivity of the measuring head complies with the standards DIN 5050 and ISO/CIE 17166 and the Ordinance on Protection against the Harmful Effects of Artificial Ultraviolet Radiation (UV-Schutz-Verordnung - UVSV, published in the Federal Law Gazette 2011 Part I No. 37). The measurement results provide direct information about medically and biologically relevant correlations in this radiation range. DIN 5050 specifies four different skin types: Skin type I to IV. The UV Protection Ordinance - UVSV extends by two further skin types: skin type V and VI. The guideline for these six skin types are taken into account in the calculation of the various parameters. The measuring head is used in areas of medical and biological research, for the measurement of

UV radiation equipment (for cosmetic purposes, medical treatments or other human applications), in weather information and forecasting systems, in climate research and for general population information.. A popular measure of "sunburn sensitivity" is



Meteorology

the UV index "UVI", which is determined by the German Weather Service.

The measuring head FLD7 33-UVE has a weatherproof, eloxated aluminium housing. The device dome consists of UV-transparent, ground quartz glass. The measurement is cos-corrected. The measuring head is suitable for continuous operation or control measurements outdoors.

Digital measuring head with ALMEMO® D7-connector

The measuring head works with its own AD converter. Extension cables and the ALMEMO[®] measuring instrument/data logger have no influence on the accuracy of the measurement. From the measured irradiance, all relevant measured variables are calculated and output to the ALMEMO[®] instrument. Different measuring channels can be selected and the measured variables can be displayed :

- UV-index: relative irradiance related to 25 mW/m^2
- UVE irradiance (erythema-effective) in mW/m².
- Dose (erythema effective irradiation) in J/m²: sum of irradiance over the irradiation period (energy).
- Relative minimum erythema-effective dose (MED): Dose related to 1 MED (= erythema-effective threshold irradiation) of the set skin type according to DIN 5050 and UVSV. Example: 1 MED for skin type 2 (light-skinned European skin type) = 250 J/m².
- Remaining time of irradiation in minutes until the dose 1 MED of the selected skin type is reached.
- Current, predicted maximum irradiation time in minutes until the dose 1 MED of the selected skin type is reached.
- Relative standard erythema effective dose (SED): Dose related to 1 SED (100 mW/m²) according to ISO 17166.

Technische Daten

Measuring range UVE:	$0,1 \dots 300 \text{ mW/m}^2$
Resolution:	0,1 mW/m ²
Sensor system:	SiC / interference filter
Spectral sensitivity:	230400 nm
Erythema effective spectra	l range: 250 298 328 nm
Max. spectral sensitivity:	295 nm
Diffuser:	PTFE
Cos-correction:	error f2 < 3 %
Linearity:	better 1 %
Absolute error:	< 7 %
Nominal temperature:	23 °C ±3 K
Operating temperature:	-30 +60°C
Switch-on time:	< 1 s
Switch-off time:	< 1 s

Dimensions:	
diameter	33 mm,
height	ca. 29 mm
Mounting:	2 screws M2
Weight (without cable)	approx. 50 g
ALMEMO [®] connecting ca	ble:
fixed attached cable, 1,5 m	n, with ALMEMO® D7-connector
ALMEMO [®] D7 connecto	r
ALMEMO® D7 connecto Refresh rate:	1 s for all channels
ALMEMO® D7 connecto Refresh rate: Settling time:	1 s for all channels 3 s (for data logger operation in
ALMEMO® D7 connecto Refresh rate: Settling time:	1 s for all channels 3 s (for data logger operation in sleep mode a sleep delay of 3 s
ALMEMO® D7 connecto Refresh rate: Settling time:	1 s for all channels 3 s (for data logger operation in sleep mode a sleep delay of 3 s has to be programmed)
ALMEMO® D7 connecto Refresh rate: Settling time: Power supply voltage:	1 s for all channels 3 s (for data logger operation in sleep mode a sleep delay of 3 s has to be programmed) from 6 V from ALMEMO* instrument



Intensity of Irradiation and UV-Index



Version for measurements in dry surroundings FLD7 03-UVE Data sheet see chapter optical radiation

Versions (incl. works test certificate)	Order no.
Digital measuring head for UVE radiation in a weatherproof housing for outdoor use. Sensor with built-in connector, incl. ALMEMO [®] connecting cable, 1,5 m, with ALMEMO [®] D7-connector.	FLD733UVE
Digital measuring head for UVE radiation, for measurements in dry surroundings. Sensor with permanently attached cable, 1,5 m, with ALMEMO [®] D7-connector Data sheet see chapter optical radiation.	FLD703UVE

Star Pyranometer FLA 628 S



- Star pyranometer, according to Dirmhirn, for measuring the global radiation, the sky radiation and the short-wave radiation.
- Independent from ambient temperature through differential temperature measurement.
- Cut precision glass cupola for shielding from external environmental effects.
- Levelling by 3 setting screws and an integrated bubble

Technical Data

Measuring range:	0 to 1500W/m ²
Resolution:	0.1W/m ²
Spectral range:	0.3 to 3µm
Output:	approx. 15mV/Wm ⁻²
Impedance:	approx. 350hms
Operative range:	-40 to +60°C
Accuracy:	cosine effect + azimuth effect + tempera- ture influence
Cosine effect:	<3% of measured value
	(0 to 80° inclination)
Inclination azimuth effect:	< 3% of meas. val.
Temperature influence:	< 1% of meas. val. (-20 to +40°C)

Nominal temperature:	$22^{\circ}C \pm 2^{\circ}C$
Linearity:	<0.5% (0.5 to 1330W/m ²)
Stability:	<1% of the meas. range per year
Settling time:	25s (t ₉₅)
Dimensions:	160mm Ø, 75mm high,
	hole circle: 134mm Ø,
	holes: 8mm Ø
Weight:	1 kg

Type (including test protocol)	Order no.
Star pyranometer including 3m cable with ALMEMO® connector and programmed calibration value	FLA628S
Factory calibration KL90xx radiation for sensor (see chapter Calibration certificates)	

Other variants are available on request





Probe for measuring global radiation FLA 613 T1B11, 3-mode sensor : It measures UVA, VIS, IRA radiation. Spectral sensitivity from 315 to 1100 nm

Probe for measuring global radiation FLA 613 GS-SDEK, This measures the global, direct, and diffused solar radiation (integrated shadow bar). Spectral sensitivity from 380 to 1100 nm

Digital sensor for temperature, humidity, atmospheric pressure FHAD 46-C4AG in protective all-weather housing with ALMEMO[®] D6 plug



On request

Temperature sensor Pt100 in protective all-weather housing

FPA930AG

- All relevant ambient parameters are measured with one sensor.
- Suitable for mounting on a wall or a mast
- Sensor cable up to 100 meters long, clamped in terminal box
- All sensors in 1 multi-sensor module: capacitive digital sensor for humidity and temperature, digital atmospheric pressure sensor. Additional EEPROM data storage medium in the sensor module
- The sensor module is thoroughly adjusted. All sensor characteristic and adjustment data are stored in the data storage medium of the sensor module itself. In the process of readjusting the individual sensors, the adjustment values are directly saved in the data storage medium of the sensor module.
- Replacement sensor modules are inexpensive: The sensor module is pluggable and can be simply exchanged on-site. Full accuracy without any adjustment, especially with calibrated sensors. The ALMEMO[®] connecting cable and the ALMEMO[®] measuring instrument have no influence on the calibration.
- *new:* The atmospheric pressure is measured directly at the measuring point in the sensor tip. Hence, the atmospheric pressure dependent humidity variables are automatically pressure compensated.
- Humidity calculation on the basis of formulae as per Dr. Sonntag and the enhancement factor as per W. Bögel (correction factor fw(t,p) for real mixed gas systems). This substantially widens the measuring range and improves the accuracy of humidity variable calculations.
- Humidity variables: Absolute humidity in g/m³.
- The humidity variables are calculated from the three primary measuring channels (real measurable variables): temperature, humidity and atmospheric pressure.
- Four measuring channels are rogrammed (ex factory): temperature (°C, T,t), relative humidity (%H, RH, Uw), dew point (°C, DT, td), atmospheric pressure (mbar, AP, p). Alternatively further humidity variables are selectable. Mixture (g/kg, MH, r), absolute humidity (g/m³, AH, dv), vapor pressure (mbar, VP, e), enthalpy (kJ/kg, En, h). The configuration is performed on the ALMEMO[®] V7 measuring instrument or directly on the PC using the USB adapter cable ZA1919AKUV (Chapter "Network technology").

Technical Data

Operative range	-30 to +60 °C, 5 to 98 % RH	Digital atm. pressure ser	nsor (integrated in the multi-sensor module)
Digital temperature / hu	midity sensor (including A/D converter)	Measuring range	700 to 1100 mbar
Humidity		Accuracy	±2.5 mbar (at 23 °C ±5 K)
Measuring range	0 to 98 % RH	ALMEMO [®] connecting	cable
Sensor	CMOSens [®] technology	PVC, for available leng	gths see variants
Accuracy	±2.0 % RH in range 10 to 90 % RH	with ALMEMO® D6 plug	
	±4.0 % RH in range 5 to to 98 % RH	ALMEMO [®] D6 plug	
	at nominal temperature	Refresh time	1 second for all four channels
Hysteresis	typical ±1 % RH	Supply voltage	6 to 13 VDC
Nominal temperature	+23 °C ±5 K	Current consumption	12 mA
Sensor operating press	ure Atmospheric pressure	Mechanical design	
Temperature		Sensor tube	Plastic, diameter 12 mm
Sensor	CMOSens [®] technology	Filter cap	PTFE-Sinterfilter, SK6
Accuracy	typical ±0.2 K at 5 to 60 °C	All-weather protection	Ø 105 mm, height approx. 110 mm
	maximum ±0.4 K at 5 to 60 °C	Terminal box	51 x 53 x 36 mm
	maximum ± 0.7 K at -20 to +80 °C	Screw-fit cable gland	Splash-protected
Reproducibility	typical ±0.1 K		

Accessories	Order no.
ALMEMO® transmitter 2490-1R02U with double analog output 10 V or 20 mA	MA24901R02U
(For other data, options, accessories, see chapter 01 Measuring instruments)	

Standard delivery	Order no.
Digital sensor for temperature, humidity, atmospheric pressure in protective all-wea with connecting cable and ALMEMO [®] D6 plug, manufacturer's test certificate, 2 fi Connecting cable	ather housing xtures for mounting on a mast
Length = 5 meters	FHAD46C4AGL05
Length $= 10$ meters	FHAD46C4AGL10
Length $= 20$ meters	FHAD46C4AGL20
Length $= 40$ meters	FHAD46C4AGL40
Length $= 100$ meters	FHAD46C4AGL100
Replacement multi-sensor module, digital, adjusted, plug-in	FH0D46C

DAkkS or factory calibration KH9xxx, temperature, humidity, and KD92xx, atmospheric pressure, for digital sensor (see chapter Calibration certificates).

DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Room air conditions

Comfort Index Measurement



Technical features

- Thermal comfort and air-conditioning calculations using WinControl software with add-on module for comfort index measurement as per DIN ISO 7730 and DIN EN 13779 (formerly DIN 1946)
- Independent measuring sequence in real-time mode
- Various display and output options Real-time mode, memory access to offline measuring operations
- Graphical presentation of measured data and calculated data in a format with data export options
- Comprehensive, clear, meaningful evaluation.

Types (sensor set for one level)

FPA805GTS Globe thermometer Digital sensors for humidity, temperature, atmospheric Pressure FHAD46C41A Thermo-anemometer, omnidirectional up to 1 m/s FVAD05TOK300 Stand for measuring operations at heights of 0.1 to 1.7 meters, including 1 set of instrument holders for 1 level (traverse including traverse holder and sensor fastening), including carry case **ZB1001PPD1** Set of instrument holders for extra levels (as above) **ZB1001MH1** optional for assessing air quality Digital carbon dioxide sensor to 10.000 ppm, with handle FYAD00CO2B10 **Device selection** ALMEMO® 2690-8A (new variant) hand-held data logger, 5 inputs, including mains unit and data cable, USB can be used for 1 measuring level (see page 01.22) **MA26908AKSU** ALMEMO® 710 data logger, 10 inputs, including mains unit, USB data cable can be used for 3 measuring levels (see page 01.32) **MA710** PC link via Ethernet, RS232, or wireless with Bluetooth see Chapter 04, ALMEMO[®] networking technology. Software: WinControl for 20 measuring points / 1 device SW5600WC1 including additional module for comfort index measurement SW5600WCZM1 Accessories: Carry case, universal, spacious, robust, for globe thermometer, humidity sensor, and data logger Exterior dimensions (WxHxD) approx. 51 x 35 x 30 cm **ZB5600TK3**

Operative range

comfort index measurement.

The software

It is possible with this measuring setup to measure all the physical parameters needed for assessing and evaluating thermal comfort simultaneously on three levels. It reliably evaluates the performance of heating and ventilating systems. The data acquired from the series of measuring operations for operative temperature (globe temperature), room temperature, and room air flow and humidity, and the necessary input parameters (e.g. clothing factor, activity level, mechanical output) is used together to calculate the PMV (predicted mean vote) and PPD (predicted percent dissatisfied) values (as per DIN ISO 7730) and the degree of turbulence (as per DIN EN 13779, formerly DIN 1946 Part 2); these values are calculated either online or offline using the AMR WinControl software in conjunction with the add-on module for

The averaging number is preset at 200 measuring points but this is variable and can be modified. The PMV and PPD values and the degree of turbulence can be displayed and documented in y/t or x/y diagrams either each one separately or together with other measurable variables. A software wizard is available to guide the user step-by-step through the various settings. If measuring is started online, the first value is indicated after completion of the first 200 measuring operations (as per DIN ISO 7730). These values continue to be calculated, updated, and displayed, and optionally - also saved and / or exported. (see Chapter 05)

DAkkS or factory calibration temperature, humidity, air flow, carbon dioxide for sensor (see chapter Calibration certificates). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Order no.

12.18



Digital carbon dioxide sensor FYAD 00-CO2Mx for assessing the indoor air quality and for checking ventilation in line with requirements. With built-in temperature sensor and air pressure sensor for automatic measured value compensation, with ALMEMO[®] D6 connector.



Technical data and functions

- Assessment of air quality for checking demand-oriented ventilation in recreation and work rooms, including classrooms, lecture halls, day care centers, meeting rooms, event rooms, production halls, health care facilities, public transportation.
- In combination with an ALMEMO[®] data logger, the measured values are continuously recorded with date, time. Based on the stored data, a differentiated analysis of the air quality during the room usage times is possible.
- Simultaneous measurement of air temperature as a criterion for assessing the quality of stay (comfort) in the rooms.
- Quantitative measurement of CO_2 concentration, measured value in ppm. Differentiated decision for concentrations near the quality levels 1000 ppm and 2000 ppm. On request: calibration of the sensor (traceable) by an accredited calibration laboratory.
- Calibrated reference system for CO₂ concentration for checking CO₂ sensors permanently installed in the building management system (BMS) / room ventilation system (AHU).

- Digital sensor with integrated signal processor. All calibration and sensor data are stored in the sensor.
- Unique auto-calibration procedure (without fresh air supply): aging effects are automatically compensated.
- Open protection cap for fast response time. Filter inside on the sensor carrier.
- Automatic compensation of carbon dioxide concentration with built-in digital temperature and barometric pressure sensor.
- Low power consumption. Long-term measurements with ALMEMO[®] data logger in sleep mode; only for current instrument types with sleep delay.
- 3 primary measurement channels (real measured variables): carbon dioxide concentration, air temperature, air pressure.

Room air conditions

Technical Data

Sensor:	2-beam infrared sensing element. Non-dispersive infrared technology (NDIR).	
Measuring range: 05 000 ppm.		
	Automatic compensation of pressure and temperature dependence of CO_2	
	measurement with the built-in sensors.	
Accuracy:	$\pm (50 \text{ ppm} + 3\% \text{ of measured value})$	
Nominal conditions:	25°C, 1013 mbar	
Switch-on time (initializati	on): 15 s	
Response time t63:	140 s	
Measuring interval:	fixed 15 s as exponential moving average over 60 s (= 4 instantaneous values 15 s).	
Range of application: FYAD 00-CO2M1B05: FYAD 00-CO2M0B05:	: -40 60 °C : -10 60 °C 095 % r.h. (non-condensing), 700 1100 mbar	
Protection cap:	Material PA12, diameter approx. 20 mm, length approx. 51 mm	
Sensor tube: FYAD 00-CO2M1B05	stainless steel, diameter 12 mm, length approx. 130 mm,	
Sensor supply:	via ALMEMO [®] D6 connector	

opm	Verlauf der Kohlendioxid-Konzentration und Umgeb 0.0 - Temperatur 0.10 - CO2 ppm	pungstemperatur im Klassenzimmer an einem Unterrichstag 90.0 - 1000 ppm Grenze 90.1 - 2000 ppm Grenze
2500		
2000		
-		
1000		
500	hand here h	
0	7:00h 8:00h 9:00h 10:00h 10:2020	11:00h 12:00h 13:00h 14:00h 15:00h



Connection: FYAD 00-CO2M1B05: permanently connected cable 2 m with ALMEMO® plug FYAD 00-CO2M0B05: sensor mounted directly on ALMEMO® connector Digital air pressure sensor (built-in) Measuring range: 700 ... 1100 mbar Accuracy: typ. ± 2 mbar (at 25 °C) Digital air temperature sensor (built-in) -40 ... +60 °C Measuring range: ± 0.5 °C (at 25 °C) Accuracy: typ. ALMEMO[®] D6 connector: Measuring channels: Carbon dioxide concentration, air temperature, air pressure Refresh rate: 15 sec. for all 3 channels Supply voltage: 6 ... 13 V DC Current consumption: typ. approx. 7 mA (average current

at measuring interval 15 s)



ALMEMO[®] measuring system (example): CO₂ sensor with data logger ALMEMO® 202/204

Versions (incl. works test certificate)

Digital carbon dioxide sensor, measuring range 5 000 ppm, digital air temperature sensor and air pressure sensor built-in. With handle, permanently connected cable with ALMEMO® D6 connector. Sensor, directly mounted on ALMEMO® D6 connector

Order no.

ÖKD calibration KY96xx, carbon dioxide concentration, for digital probe, see chapter calibration certificates The ÖKD calibration fulfills the requirements of DIN EN ISO/IEC 17025 for test equipment.

FYAD00CO2M1B05 FYAD00CO2M0B05

Order no. FPA805GTS

FNA846WB

WBGT Measurement



Application Range

The wet bulb globe temperature (WBGT) is the decisive parameter for evaluating the work stress at heat-exposed working places and the operation and cool-off times involved. Temperature, radiation and relative humidity are determined by measuring the dry temperature, the natural humid temperature of a psychrometer and the globe temperature of a globe thermometer. These are all combined as WBGT.

Note:

For WBGT measurements the use of a psychrometer with a disengageable ventilator is compulsory

Technical Data

Accuracy:	Class B	Diameter:	approx. 150mm
Sensor:	Pt100 4-conductor,	Operating temperature:	–50 to 200°C
	arranged in the center	Cable length	3 m
Globe thermometer: matt black copper globe with suspension			

Types

Globe thermometer (Pt100 4L)

Psychrometer with disengageable ventilator

DAkkS or factory calibration KT90xx temperature for sensor or measuring chain (sensor + device) (see chapter Calibration certificates). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.



On request: Sound Level Meter MA 86193 with ALMEMO[®]- cable for measured value recording

NTC-sensor FNA 305



For Indoor air measurements

Accuracy:	NTC, see page 07.04
Measuring tip	Operative range -10 to $+60$ °C
	(non-condensing)
	Protective tube in stainless steel
	Diameter = 3.0mm, $length = 50 mm$
	mounted directly on ALMEMO® connector
T _{oo}	8 s

L = 50 mm **Order no. FNA305** (No variants available)

Building physics, Moisture in materials

Content

Measuring thermal transmittance (U) and heat flow	13.02
Heat Flow PLates	13.04
Digital heat flow plate	13.05
Digital sensors for humidity, temperature, dew point	13.06
Moisture in materials	13.06
Moisture Sensor FHA 696 MF	13.07
Wood moisture probe Hand-held probe for mobile test measurements	13.07
Moisture content sensor - for wood for stationary measuring operations FHA696MFS1	13.08
Moisture content sensor - for wood for stationary measuring operations FHA636MFS1	13.09
Moisture content sensor - for wood, for stationary measuring	13.10
Sensor for measuring the moisture content in granulated materials	13.11
Water Detection Probe FHA 936 WD	13.12
Tensiometer FDA 602 TM1	
measurement of soil moisture	13.13

Building physics, Moisture in materials



Measuring thermal transmittance (U) and heat flow

structural element depend on the thermal on its structural geometry (e.g. flat or cyconductivity of the materials used, on the lindrically curved walls, etc.), and on the

The heat transfer characteristics of any thickness of its various component layers, ambient conditions at the structure's surfaces inside and outside.



Presentation of the temperature behavior

The thermal transmittance coefficient (U value) of a structural element describes the quantity of heat that passes through it from one side to the other (no matter how many layers) per second and per square meter surface at a constant difference in ambient temperature inside / outside of 1K. This thermal transmittance coefficient (U) thus also includes the surface heat transfer coefficients, i.e. the thermal energy transferred at the boundary surfaces, interior air - structure - exterior air. The thermal transmittance coefficient (U) is measured in in (W/m²K) and is internationally defined in standard ISO 6946. The measurement of the U-value on site has been described in the ISO

9869 standard since 2014. The standard contains standardized specifications for determining a reliable and generally valid U-value based on the heat flow method.

А structure's thermal transmittance coefficient (U) is the reciprocal of its total thermal resistance coefficient (R); R is the sum of the thermal transmission resistances between the structure's various contiguous layers and also the surface heat transfer resistances between the structure and the ambient media on either side (e.g. air).

Total thermal resistance (R) = thermal transmission resistances through the material + surface heat transfer resistances, inside and out

The thermal transmittance coefficient (U value) is an important rating in civil engineering and the construction industry where it is used to define a building's transmission heat loss through its various structural elements. Transmission heat loss is the term used to describe the energy-saving qualities of a building's shell (i.e. the thermal insulation of its roof, outside walls, windows, and floors). In Germany each residential structure is assigned a permissible maximum U value (depending on its external surface area and its internal volume); this is based on the most recently amended version of the Energieeinsparverordnung (EnEV) (German energy-saving legislation)

Building physics, Moisture in materials

ALMEMO[®] Measuring system for Measuring thermal transmittance (U) and heat flow

The thermal transmittance coefficient (U temperature gradient inside the heat flow value) is an important rating in civil engineering and the construction industry where it is used to define a building's transmission heat loss through its various structural elements. It is now possible, with the ALMEMO® measuring system, to measure and record all the physical parameters for the component parts of existing buildings (e.g. walls, etc.) in order to calculate their U value and other relevant thermal energy coefficients.

Measuring principle:

The measuring principle involved in quantifying heat loss at partition elements, e.g. walls, heating systems, etc., is based on the method which uses a heat flow plate (sensor) fitted on the surface of the structural element and thus incorporated directly in the heat flow. Using the known thermal characteristics of the heat flow

plate the ALMEMO® measuring system can thus measure the heat flow density q in W/m^2 .

The ALMEMO[®] measuring system can also be used to measure the surface temperatures on either side the structural element and the respective air temperatures immediately inside and outside; based on these results it is then possible to calculate all the relevant thermal coefficients.

The temperatures and heat flow density data on which these calculations are based are acquired cyclically as average values. Any influence that the structure's own thermal capacity may have on these calculations (e.g. time shifts between temperature and heat flow, affecting calculation of the U value) will, given a sufficiently long measuring period, become negligible and the calculated plate and the thermo-electrically measured average value will certainly be very close

to the structure's actual U value.

Operative range:

To ensure a stable and meaningful U value calculation it is possible to stipulate that measuring operations only be performed subject to certain specified conditions.

- The temperature difference between interior and exterior ambient air must be sufficiently large (typically 20 K, e.g. inside temperature 20°C and outside temperature 0°C).
- Any fluctuations in these temperatures (e.g. day / night) must throughout the measuring period be as small as possible.
- The measured values must be acquired and recorded on-site over a sufficiently long period (e.g. one whole day or even several days) and the parameters must be calculated on the basis of average values

Ordering information

Order no.

with straightforward calculation in the ALMEMO [®] measuring instrument:	
ALMEMO® data logger 2590-4AS, 4 inputs, including mains unit and USB data cable	MA25904ASKSU
Outside air temperature Thermo-wire sensor, with glass-fiber insulation, 5 meters long	FTA3900L05
Inside air temperature Thermo-wire sensor, with glass-fiber insulation, 1.5 meters long	FTA3900
Programming for inside sensor Differential channel and average value	OA9000PRUT
Heat flow plate, including installation materials see page 13.04 / 13.05	
e.g. type 118, approx. 120 x 120 mm, cable 2 meters	FQA018C
Programming for Heat flow plate, Average value and U-value channel	OA9000PRUQ

ALMEMO[®] measuring system - with 2 temperature sensors and 1 heat flow plate - for determining the U value -

ALMEMO[®] measuring system - with 4 temperature sensors and 1 heat flow plate - for determining the U value using WinControl software (possible both online and offline) :

ALMEMO® data logger 2690-8A, 5 inputs, including mains unit and data cable, USB	MA26908AKSU
Outside air temperature Thermo-wire sensor, with glass-fiber insulation, 5 meters long	FTA3900L05
Outside surface temperature Thermo-wire sensor, with glass-fiber insulation, 5 meters long	FTA3900L05
Inside air temperature Thermo-wire sensor, with glass-fiber insulation, 1.5 meters long	FTA3900
Inside surface temperature Thermo-wire sensor, with glass-fiber insulation, 1.5 meters long	FTA3900
Heat flow plate, including installation materials see page 13.04	
e.g. type 118, approx. 120 x 120 mm, cable 2 meters	FQA018C
WinControl software for 20 measuring points, 1 device	SW5600WC1
Additional module U-value wizard	SW5600WCZM4
Hardlock USB dongle	SW5600HL

Accessories

Carry case, large

ZB2590TK2

Heat flow

Heat Flow Plates FQAx



Technical Data:

- For determining the heat flow density up to max. 150°C.
- Application-oriented designs, consisting of a meander of opposing thermocouples that are embedded in a substrate.
- In case of thick substrates no lateral circulation of the heat flow because of sufficient meander shell zone.
- Software for U value measurement, see chapter Software
- Each heat flow plate has been assigned a calibration value, which corresponds to the heat flow density in W/m² when the plate provides an output of 1mV. The calibration value will be stored as factory-setting in the ALMEMO[®] connector so that ALMEMO[®] devices will immediately indicate the current heat flow density in W/m².

Туре	Dimensions (mm)	Meander Size (mm)	Substrate	Temperature Stability	Calibr. Val. appr. (W/m ² \approx mV)	Accuracy of Calibr. Value
117	100 x 30 x 1.5	80 x 20	epoxy resin	-40 80°C	< 50	5% at 23°C
118	120 x 120 x 1.5	90 x 90	epoxy resin	-40 80°C	< 15	5% at 23°C
119	250 x 250 x 1.5	180 x 180	epoxy resin	-40 80°C	< 8	5% at 23°C
120	33 Ø x 1.5	20 Ø	epoxy resin	-40 80°C	< 150	6% at 23°C
117SI	100 x 30 x 3	80 x 20	silikone	-40 80°C	< 50	5% at 23°C
118SI	120 x 120 x 3	90 x 90	silikone	-40 80°C	< 15	5% at 23°C
119SI	250 x 250 x 4	180 x 180	silikone	-40 80°C	< 8	5 % at 23°C
150-1	180 x 100 x 0.6	170 x 90	PTFE	150°C	< 80	5% at 25°C

Accessories	Order no.
Adhesive tape for room temperature	ZQ9017KB
Self-adhesive film 24 x 100cm for room temperature	ZQ9017KF

Types incl. connecting cable, 2 m, with ALMEMO [®] connector and manufacturer's test certificate		Order no.
Model	Application	
117	for even surfaces, e.g. casement sections	FQA017C
118	for universal applications, e.g. solar-electric systems and insulating plates	FQA018C
119	especially for constructional industry, brickwork insulating plates, old buildings	FQA019C
120	small heat flow plate, e.g. for medicine, veterinary medicine, small components etc.	FQA020C
117 SI	flexible heat flow plate, suitable for even surfaces, e.g. casement sections	FQA017CSI
118 SI	flexible heat flow plate, suitable for even surfaces, e.g. solar-electric systems and insulating plates	FQA018CSI
119 SI	flexible heat flow plate, suitable for even surfaces	FQA019CSI
150-1	flexible heat flow plate, particularly suitable for high temperatures e.g. for brickwork, insulated boilers and pipes	FQA0801H

Digital heat flow plate FQADx, with integrated temperature sensor for automatically correcting the heat flow plate's temperature coefficient, with ALMEMO[®] D6 plug



- This automatically corrects the heat flow plate's temperature coefficient using a miniature NTC sensor integrated in the heat flow plate for the purpose of measuring the plate's mean temperature.
- It measures heat flows and temperatures using a A/D converter incorporated in the ALMEMO® D6 plug.
- Two measuring channels are programmed (at our factory).
- Plate's mean temperature (°C, t) Heat flow, temperature-compensated (W/m², fq)



model 117, 118, 119

Technical Data

Heat flow sensor (see table on page 13.04)
Accuracy of calibration value at nominal
temperature 5 %
Nominal temperature 23 °C
Temperature coefficient -0.12 % / K (epoxide plate)
or -0.17 % / K (silicone plates)
Temperature sensor

Sensor element Accuracy Miniature NTC type N ±0.5 K at 0 to +80 °C

A/D converter incorporated in ALMEMO [®] D6 plug			
<u>Input 1</u>	NTC sensor		
	(clamp connector in plug)		
Resolution	0.01 K		
Linearization	computing method according		
	to Galway Steinhart (no approximations)		
Accuracy	$\pm 0.05 \text{ K}$		
Nominal temperature	23 °C ±2 K		
Temperature drift:	0.004 %/K (40 ppm)		
Input 2	Voltage mV		
	(clamp connector in plug)		
Measuring range	0 to 26 mV, 0 to 260 mV		
Precision class	AA see page 01.05		
Refresh rate	0.4 seconds for both channels		
Supply voltage	6 to 13 VDC		
Current consumption	4 mA		

Accessories

Order no.

Order no.

see page 13.03

General features and accessories, ALMEMO® D6 sensors see page 01.08

Variants including manufacturer's test certificate

te with integrated temperature sensor cable permanently fitted, PVC, length 2 meters	with ALMEMO® D6 plug.
Substrate Epoxy resin, Dimensions 100 x 30 x 1.5 mm	FQAD17T
Substrate Epoxy resin, Dimensions 120 x 120 x 1.5 mm	FQAD18T
Substrate Epoxy resin, Dimensions 250 x 250 x 1.5 mm	FQAD19T
Substrate Silicone, Dimensions 100 x 30 x 3 mm	FQAD17TSI
Substrate Silicone, Dimensions 120 x 120 x 3 mm	FQAD18TSI
Substrate Silicone, Dimensions 250 x 250 x 4 mm	FQAD19TSI
	te with integrated temperature sensor cable permanently fitted, PVC, length 2 meters Substrate Epoxy resin, Dimensions $100 \times 30 \times 1.5 \text{ mm}$ Substrate Epoxy resin, Dimensions $120 \times 120 \times 1.5 \text{ mm}$ Substrate Epoxy resin, Dimensions $250 \times 250 \times 1.5 \text{ mm}$ Substrate Silicone, Dimensions $100 \times 30 \times 3 \text{ mm}$ Substrate Silicone, Dimensions $120 \times 120 \times 3 \text{ mm}$ Substrate Silicone, Dimensions $250 \times 250 \times 4 \text{ mm}$

Digital sensors for humidity, temperature, dew point FHAD 46-Cx for measuring the equilibrium moisture content in building materials

Measuring the equilibrium moisture content

A material's equilibrium moisture content respective temperatures, establish an is that level of relative humidity prevailing in the ambient atmosphere at which the material neither gains nor loses moisture. The material humidity prevailing the emission of water vapor from the material humidity prevailing the emission of water vapor from the material humidity prevailing the emission of water vapor from the material humidity prevailing the emission of water vapor from the material humidity prevailing the emission of water vapor from the material humidity prevailing the emission of water vapor from the material humidity prevailing the emission of water vapor from the material humidity prevailing the emission of water vapor from the material humidity prevailing the emission of water vapor from the material humidity prevailing the emission of water vapor from the material humidity prevailing the emission of water vapor from the material humidity prevailing the emission of water vapor from the material humidity prevailing the emission of water vapor from the material humidity prevailing the emission of water vapor from the material humidity prevailing the emission of water vapor from the material humidity prevailing the emission of water vapor from the material humidity prevailing the emission of water vapor from the material humidity prevailing the emission of water vapor from the material humidity prevailing the emission of water vapor from the material humidity prevailing the emission of water vapor from the material humidity prevailing the emission of water vapor from the material humidity prevailing the material humidity p

All construction materials may - to a greater or lesser degree - attract water vapor from or emit water vapor to the ambient air. They are hygroscopic; i.e. they attempt to establish an equilibrium in terms of moisture content with respect to the ambient air. The construction material and the ambient air, depending on their

respective temperatures, establish an interactive balance between the adsorption of and the emission of water vapor from / to one another. Each material thus has, depending on temperature and on atmospheric humidity, a certain moisture content level (measured in water as a percentage of overall weight).

In the state of equilibrium the relationship between the water content and the equilibrium humidity of a material can be displayed graphically as a curve, the so

called moisture sorption isotherm. The sorption isotherm for the material in question indicates per atmospheric humidity value the corresponding water content value at a given constant temperature. If the composition or quality of the material changes then its sorption behavior - and thus its sorption isotherm also changes. Given the great complexity of sorption processes these isotherms cannot be determined by calculation; they have to be recorded experimentally.

Digital sensors for humidity, temperature, air pressure FHAD 46-C0, uncovered sensor element, with ALMEMO[®] D6 plug.

Uncovered sensor element: Smallest design, short response time

Description and technical data see page 08.06

Digital sensor for temperature, atmospheric humidity, and atmospheric pressure FHAD 46-C2 Version in plastic, with slotted sensor cap with ALMEMO[®] D6 plug

FHAD 46-C2 Sensor element enclosed in slotted sensor cover, compact design, short response time

FHAD 46-C0

Measurement of Moisture in Materials

Dielectric Measurement of Moisture in Materials

The measurement of the moisture in materials is performed indirectly via the determination of the dielectric constant. This is performed by using a capacity measurement via a high-frequency electrical field,

which penetrates the material without disturbances.

Advantage:

- simple and fast measuring technology
- non-destructive contact measurement
- long term use is possible
 Disadvantage:
 - limited accuracy

Measurement of the Moisture in Materials according to the Principle of Conductivity

The measurement of the moisture in materials is performed indirectly via the determination of the electrical resistance, which depends on the moisture content of the material.

- Advantage:
- simple and fast measuring technology
- Disadvantage:
- limited accuracy
- probe insertions

- only for short term control measurements
- measured values depend on various material parameters Material parameters Material parametern

DAkkS or factory calibration KH9xxx, temperature, humidity, and KD92xx, atmospheric pressure, for digital sensor (see chapter Calibration certificates).

DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

Moisture Sensor FHA 696 MF



Technical Data

- Moisture sensor for determination of the moisture content in mineral construction materials, wood and cardboard.
- Indirect measurement of the moisture through the determination of the dielectric constant.
- Capacity measurement through a high frequency electromagnetic field, which penetrates the material in a non-destructive way.

Measuring method:	capacitive	Measuring comb:	stainless spring ste	el 0.5mm, 70 x 35mm
Resolution:	0.1%	Weight:	260g	
Measuring range (moistu	re): 0 to 50% moisture,	Nominal temperature:	15 to 25°C	
	referenced to mass	Operative range:	0 to +60°C	
Measuring range (materia	al):	Storage temperature:	-20 to +80°C	
mineral construction m	aterials 0 to 20%, moisture	Signal output:	0 to 2V	
paper and cardboard	0 to 20% moisture	Power supply:	+8 to +12V	
Housing:	plastic handle with integrated electronics 40mm Ø, 130mm long	Current consumption	approx. 7 mA	
Terminal block:	aluminium/plastic 20 x 25 x 70mm			
Accessories				Order no.
Test block for min. const	ruct. materials			ZB9696PE05
Test block for wood, pap	er, cardboard			ZB9696PE30

Туре

Moisture sensor

Order no. FHA696MF

Wood moisture probe FHA 636 MF Hand-held probe for mobile test measurements



- Moisture sensor for determination of the moisture content in wood.
- Indirect moisture measurement according to the principle of conductivity.
- Determination of the moisture content in the material through the dependence of the electrical resistance on the moisture.

Technical Data

Measuring method:	principle of conductivity	Reproducibility:	± 1%
Measuring range:	7 to 30 % moisture,	Nominal temperature:	$23^{\circ}C \pm 2^{\circ}C$
	referenced to mass	Operating temperature:	0 to +60°C
Housing:	: plastic handle 40mm Ø, 130mm long	Storage temperature:	-20 to +80°C
		Signal output:	0 to 2V
Measuring tips: stainless steel, uninsulated	stainless steel, uninsulated	Power supply:	7.5 to +12V
Weight	t. 260 g	Current consumption	max. 10 mA
weight.	200g		

Accessories	Order no.
PTFE-insulated measuring tip - helps avoid measuring errors in the event of surface moisture, 1 piece (2 pieces are needed per probe)	ZB9636MFST
Туре	Order no.
Wood moisture probe	FHA636MF

Moisture content sensor - for wood, for stationary measuring operations FHA696MFS1 Capacitive sensor for applying onto the wood's surface



- Moisture content sensor for comparative measurement of moisture in wood materials
- The capacitive sensor with the measuring electronics is completely integrated in the damp-proof sensor housing. Plug-in ALMEMO[®] connecting cable
- This device is designed for stationary installation and long-term monitoring e.g. of wooden parts of buildings, roof structures (with laminated beams).
- It is also suitable for data logger operation in energy-saving sleep mode (intermittent mode).
- The sensor housing is quick and easy to install on the wooden surface in question.
- The material's moisture content is measured indirectly by determining its dielectric constant, which is moisture-dependent (but not temperature-dependent).
- Its capacity is measured via a high-frequency electrical field which penetrates the wood without destroying it.
- The ALMEMO[®] device acquires the material's moisture content based on the linearization curve stored in the ALMEMO® plug.
- This measuring operation can be performed using any current ALMEMO[®] device (version 6 and above).

Technical Data

Measuring method	capacitive	Housing	Plastic 51 x 53 x 36 mm (LxWxH)
Measuring range	0 to 50 % moisture percentage in	Signal connection	Built-in plug
	wood with respect to total mass	Protection	Housing and plug connection IP64
	(at 23 °C)	ALMEMO [®] connectir	g cable Coupling, PVC cable, 5 meters
Resolution	0.1 % moisture content	ALMEMO [®] nlug	Linearization for wood stored in the
Reproducibility	± 1 % moisture content	Alliantino piug	ALMEMO [®] plug (for ALMEMO®
Nominal temperature	23 °C ±2 K		devices version 6 and above)
Suitable conditions	0 to +80 °C	Supply voltage	via ALMEMO [®] plug (5 V)
Air humidity 0 to 90 % RH (no dew formation, no ice)		Current consumption	approx. 7 mA
Storage temperature	-20 to +80 °C		

Variants

Order no.

Moisture content sensor for wood, sensor integrated in the sensor housing, with built-in plug, connecting cable 5 meters, ALMEMO[®] plug for current ALMEMO[®] devices, version 6 and above FHA696MFS1

Moisture content sensor - for wood, for stationary measuring operations FHA 636-MFS1 Conductivity measurement with measuring tips that can be screwed into the wood Sensor with integrated temperature sensor for automatic temperature compensation

	 Moisture content s moisture in wood m Two hanger bolts connected via meas the damp-proof sens The sensor housing also fixed in position Plug-in ALMEMO[®] 	sensor for comparative measurement of naterials are screwed into the wood surface and uring lines to the measuring electronics in sor housing. y with the integrated temperature sensor is n on the wood surface.
	 The material's modetermining its eledependent. It is also tempera moisture value is a means of an integrat. The ALMEMO[®] devised on the lineariz. This measuring oper ALMEMO[®] device 	isture content is measured indirectly by ectrical conductivity, which is moisture- ture-dependent. However, the displayed utomatically temperature-compensated by ted temperature sensor. vice acquires the material's moisture content zation curve stored in the ALMEMO [®] plug. tration can be performed using any current (version 6 and above).
	This device is long-term mor roof structures Data logger op is required in o or drying out!	designed for stationary installation and nitoring e.g. of wooden parts of buildings, (with laminated beams). Deration in sleep mode (intermittent mode) order to protect the wood from salinization
Electrical conductivity 5 to 50 % moisture percentage in wood with respect to total mass	Measuring lines	2 lines, PTFE-insulated, length = 0.5 meters with circular cable lugs 4 mm
(at 23 °C)	Measuring tips	2 stainless-steel M4 hanger bolts
0.2 % moisture content		Total length = 60 mm
± 1 % moisture content		4 stainless-steel lock washers
23 °C ±2 K	— Clearance	2.5 cm at right angles to the grain
NTC, integrated in sensor housing	— Signal connection	Built-in plug
tion in range 0 to +80 °C	- Protection	Housing, including connectors IP63
0 to +80 °C	ALMEMO [®] connectin	g cable Coupling, PVC cable, 5 meters
Air humidity 0 to 90 % RH (no dew formation, no ice)	ALMEMO [®] plug	Linearization for wood, stored in the
-20 to +80 °C		devices version 6 and above)
Plastic 51 x 53 x 36 mm (LxWxH)		via ALMEMO [®] plug (5 V)
	Electrical conductivity 5 to 50 % moisture percentage in wood with respect to total mass (at 23 °C) 0.2 % moisture content ± 1 % moisture content ± 1 % moisture content ± 1 % moisture content 23 °C ± 2 K NTC, integrated in sensor housing tion in range 0 to ± 80 °C 0 to ± 80 °C Air humidity 0 to 90 % RH (no dew formation, no ice) -20 to ± 80 °C Plosting 51 x 52 x 26 mm (1 xWxH)	Electrical conductivity Measuring lines 5 to 50 % moisture content 23 °C ± 2 K NTC, integrated in sensor housing Measuring tips 23 °C ± 2 K Clearance NTC, integrated in sensor housing Signal connection 11 % moisture content 23 °C ± 2 K NTC, integrated in sensor housing Clearance Signal connection ALMEMO* connection ALMEMO* C Protection ALMEMO* C ALMEMO* connection ALMEMO* C Protection ALMEMO* C ALMEMO* plug

Variants

Order no.

Moisture content sensor for wood, with measuring tips, measuring line, sensor housing, connecting cable, 5 meters ALMEMO[®] plug, for current ALMEMO[®] devices, version 6 and above FHA636MFS1

Moisture content sensor - for wood, for stationary measuring operations FHA 636-MF10 Conductivity measurement with measuring tips that can be screwed into the wood. Interval operation for long-term measurements.



- Wood moisture probe for long-term measuring
- Switched measuring current (intermittent mode) prevents salinization or dehydration of the material.
- For long-term monitoring of wooden parts of buildings (e.g. roof structures with laminated beams)

Operation with the device in SLEEP mode is not possible.

Technical Data

Measuring methodPrinciple of conductivity Intermittent mode for long-term measuring Every 120 minutes the measuring current is activated very briefly and a new measured value is acquired; during the pauses the measuring current remains OFF.Measuring range550 % moisture content wood, meas related (at 23° C)	Measuring tips	2 stainless-steel hanger bolts M4 Total length = 60 mm including 4 stainless-steel nuts 2 stainless-steel locking washers	
	measured value is acquired; during the	Clearance	2.5 cm at right angles to the grain
	Operating temperature	0 to +60 °C	
	550 % moisture content wood, mass related (at 23° C)	Voltage supply	via ALMEMO [®] connector
Housing	Metal case 65 x 60 x 35 mm (LxWxH) with cable bushings	Connecting cable	PVC Length = 5 meters with ALMEMO [®] connector
Measuring cable	Permanently fitted, 2 sensor lines, PTFE insulated Length = 0.5 meters (= maximum possible length) with cable lugs in circular form, diameter 4 mm		

1

Variants

Order no.

FHA636MF10

Moisture content sensor for wood for long-term measurements (interval operation), with measuring tips, measuring line, connecting cable 5 m with ALMEMO[®] connector

13.10

Sensor for measuring the moisture in materials FHA 696 GF1 For determining the moisture content in granulated materials such as wood chips, wood pellets, and sawdust



- The sensor operates on the principle of an open plate capacitor. The moisture contained in a material can be measured in terms of that material's dielectric constants.
- Moisture content can be determined in a matter of seconds in wood chips or wood pellets, and sawdust, in grain and cereals, and other granulated materials.
- The characteristics of the materials to be measured can be specified on a highly customized basis; a wide variety of granulates, e.g. various cereal types, can thus be measured

Technical Data

Measuring principle	capacitive	Dimensions	
Measuring range	0 to 99.9 % water content as a weight percentage H ₂ O	Sensor head	$\emptyset = 22 \text{ mm}, \text{ length} = 200 \text{ mm}$ Rounded tip
Resolution	0.1%	Extensions	3 pieces, screw-on Q = 18 mm length = 300 mm
Measuring radius / pe	netration depth approx. 10 cm around the sensor	End piece	$\emptyset = 10$ mm, length = 30 mm Plastic $\emptyset = 22$ mm, length = 30 mm
Temp. range of material +5 to +40 °C		Cable terminal	Mountable male connector
Operating temp. range +5 to +40 °C		_	on sensor head
Storage temp. range	-20 to +70 °C	Cable	PVC, length $= 2$ meters
Signal output	ALMEMO [®] (voltage)		with ALMEMO [®] connector
Power supply	5 V from ALMEMO [®] measuring instrument		The cable is led through the extension tubes and end piecet.
Current consumption	approx 5 mA		

Option

Determining characteristics for special customer-specific materials

1. We need a sample of approx. 10 liters of your granulate (e.g. wood, cereal, plastic). This sample should be sealed in an air-tight package, e.g. shrink-wrapped in plastic film.

- 2. We use various dried samples to determine the characteristics of your particular material.
- 3. We then program these characteristics in the ALMEMO® connector for the moisture content probe..

Pro rata processing costs per material sample, net (service)

Advisory note:

If the material cannot absorb water (not hygroscopic), it will not be possible to measure its moisture content.

In this case the processing fee we charge will be reduced.

Order no. OA9696GFK

Order no.



Variants

Sensor for measuring moisture in granulated wood chips and pellets comprising :

Sensor head, 3 screw-on extensions, end piece, connecting cable 2 meters, with ALMEMO® connector programmed for wood FHA696GF1 chips (also programmable for wood pellets; if required, please indicate) including carry case Test block for FHA696GF for wood chips and wood pellets **ZB9696PE22**

Water Detection Probe FHA 936 WD



- Water detection probe for instant detection of uncombined water.
- Particularly suitable for construction applications, especially in locations that are difficult to check visually, e.g. at sealing joints, under cement floors etc.
- Indirect moisture measurement according to the principle of conductivity.
- Probe with two collets for easy electrode replacements.
- Electrodes in three different designs for matching any required application.

Technical Data

Measuring method:	detection of water	Weight:	260g
Meas. values:	<10% no water	Nominal temperature:	$23^{\circ}C \pm 2^{\circ}C$
	>10% water	_ Operating temperature:	0 to +60°C
Housing:	plastic handle	Storage temperature:	-20 to +80°C
	40mm Ø, 130mm long	 Signal output: 	ALMEMO [®] (approx. 0 to 2V)
Electrodes:	stainless steel	- Power supply:	7.5 to 15V
Electrode types:	uninsulated with rounded tip: 200 mm Q	Current consumption	max. 10 mA
	uninsulated with sharp-edged tip:		
	50mm long, 3mm Ø		
	spring steel strap:		
	200mm long, 6mm wide, 0.5mm high		

Type Water detection probe Order no. FHA936WD

Tensiometer FDA 602 TM3

- · Measurement of soil moisture through the identification of suction pressure. The suction pressure is the force with which water is being held in the soil or is available for absorption. This is the force that must be produced by the plant roots in order for water to be absorbed.
- The porous, clay tip of the tensiometer transfers water from within to the drier outer surroundings by means of capillarity, thereby, creating a sub-pressure within the sealed tensiometer tube. This sub-pressure is a measure of the moisture level and can be determined as a value or used directly to activate an electrical switch. The customary unit of measurement is hPa.
- · However, a tensiometer also functions in dry air as long as evaporation can take place over the porous, clay chamber. Therefore, moisture levels can be measured even in coarsegrained or very loose substrate.
- · Suction pressure measurements are largely independent of the salt concentration of the substrate or soil.

Typical Suction Pressure at Peat Substrates

30 - 40 hPa	very moist
50 – 120 hPa	moist
150 – 200 hPa	dried
>200 hPa	dry

Typical Suction Pressure at Open fields

(intermediate grade soil)

< 50 hPa	saturated
100 – 150 hPa	wet to moist
>200 hPa	start drying
200 – 500 hPa	Irrigation

Moisture tension meter, electronics



Insertion Tensiometer L2

Surface Tensiometer FO

ZB9602TMFO

Order no.

ZB9602TML2



Sensor completely porous for measuring in thin layers of substrate.

Dimensions: Sink deep:

Types

65 mm, Ø 70 mm approx. 30 - 60 mm

Surface Tensiometer FV

ZB9602TMFV



Technical Data

Measurement:	Measurement of soil moisture through the identification of suction pressure.
Measure range:	0 to -1000 hPa relative (negative pressure)
Output	0,3 to 3,0 V
Power supply	5 V via ALMEMO® connector
Cable	Sensor with cable, length = $5m$, with ALMEMO [®] connector

Standard model for use on capillary matting, for moist to moderately moist cultivation or for general measurement on moist surfaces.

Dimensions: 65 mm, Ø 70 mm

Type

Tensiometer electronics for screwing onto the tensiometer with cable and ALMEMO® connector Order no.

FDA602TM3

13.13

Optical radiation

Content

What is 'Optical Radiation'?	14.02
Definition of Photometric and Radiometric Meas. Variables	14.02
Comparison of Photometric and	
Radiometric Measurable Variables	14.03
Spectral Valuation Function	14.03
Determination of Photometric Characteristic Factors	14.04
Digital measuring head for illuminance FLAD 03-VL1	14.05
Radiation probe FLA 623 x	14.06
Probe for measuring illuminance FLA 623 VL	14.06
Probe for UVA radiation FLA 623 UVA	14.07
Probe for UVB radiation FLA 623 UVB	14.07
Probe for UVC radiation FLA 623 UVC	14.07
Probe for global radiation FLA 623 GS	14.08
Probe for infra-red radiation FLA 623 IR	14.08
Probe for quantum radiation FLA 623 PS	14.08
Lux probe head for illuminance FLA 613 VLK	14.09
UVA probe head spherical characteristic FLA 613U VAK	14.09
Digital measuring head for erythema effective UV radiation	14.10
Digital sensor for color temperature and illuminance	14.12
Luminance Probe Head FLA 603 LDM2	14.14
Light Flux Probe Head FLA 603 LSM4	14.14

Probe Heads for Outdoor Operation see Chapter Meteorology

Optical radiation



What is 'Optical Radiation'?

Optical radiation covers the wave length range from 100nm to 1mm of the electromagnetic radiation spectrum.

It must be considered that, with regard to the range limits, they do not preset a sharp separation, which is compulsory for all applications.

The detection of optical radiation can, for example, be measured by means of radiometric, photometric, photobiological plant-physiological measurable or variables.



Definition of Photometric and Radiometric Measurable Variables

Photometry

Limited to the range of the optical spectrum (light) that is visible to the human eye. Photometric measurable variables include: Light flux, illuminance, luminance and luminous intensity. The main characteristics of photometry is the evaluation of the brightness perception by the spectral luminosity function of the eye for photopic vision or, in rare cases, for scotopic vision (DIN 5031). Radiation detectors for photometric measuring tasks must, therefore, provide one of these spectral response characteristics. **Light Flux**

The luminous power of a light source (lamp, LED etc.). As lamps do not generally emit a completely parallel luminous beam, the light flux measurement is performed

detect the light flux independent from its geometric distribution. In most cases Ulbricht globe photometers or goniometers will be used.

Luminous Intensity

The part of a light flux, which radiates in one specific direction. The luminous intensity is an important variable for calculating the efficiency and quality of lighting equipment. The measurement is performed by detectors with a defined field of view and placed at distances that allow to consider the light source as a point light source.

Luminance

The brightness sensation provided by an illuminated or luminous surface to the eve. In many cases the luminance data will provide significantly better information by using measurement geometries, which regarding the quality of a light than the radiometry

illuminance. For measuring the luminance, measuring heads with a defined measuring field angle are used.

Illuminance

The light flux of one or several light sources striking a certain surface horizontally or vertically. In case of a non-parallel incidence (which is the typical case in practical photometry) a cosine diffusor must be used as measurement geometries. Radiometry

Metrological evaluation of optical radiation using the radiometric variables "Radiation Capacity", "Radiant Intensity", "Radiancy" and "Intensity of Irradiation". The main characteristic of radiometry is the wavelength-independent examination of the intensity of radiation. This is the significant difference between and actively weighted
measurable variables, such as variables used in photometry, photobiology, plant physiology etc.

Radiation Capacity

The overall power provided by radiation. **Radiant Intensity**

The quotient from the radiation capacity emitted by the light source into a certain direction and the solid angle being covered. The radiant intensity is used for the measurement of the geometric distribution of the radiation capacity.

Radiancy

The quotient from the radiation capacity passing through (striking) a plane in a certain direction and the product of the passed solid angle and the projection of the plane to a plane surface, which is perpendicular to the examined direction. The radiancy is used for the evaluation of aperture radiators. Steradian or telescopic adapters can be used as measurement geometries.

Intensity of Irradiation

The quotient of the radiation capacity striking a plane and the illuminated plane. For measuring the intensity of irradiation the spacial examination of the incident radiation is very important; therefore, a cosine-corrected field view function has been preset.

Comparison of Photometric and Radiometric Variables

Every photometric variable corresponds to a radiometric variable and involves the

same interrelationships between them. The variables can be distinguished by their index v (visual) and index e (energetic).

Lighting	Engineer i	ing		Rad	iation Physi	ics
Variable	Symbol	Unit		Variable	Symbol	Unit
Light Flux	$\Phi_{_{\!\scriptscriptstyle m V}}$	lm=cd∙sr	**	Radiation Capacity	${f \Phi}_{_{ m e}}$	W
Luminous Intensity	l _v	cd	Ω	Radiant Intensity	l _e	W/sr
Luminance	L _v	cd/m		Radiancy	L _e	W/sr.m
Illuminance	E _v	lx≕lm/m	X	Intensity of Irradiation	E _e	W/m
Light Quantity Lumination	Q _v H _v	lm · s lx.s		Radiation Energy Radiation	Q _e H _e	Ws Ws/m

Spectral Valuation Function

The relative spectral sensitivity of the human eye is specified with different functions for the light-adapted eye (photopic vision) or for the dark-adapted eye (scotopic vision). Due to the individual differences this data can only be considered for average values but is sufficient for most technical purposes. The detailed data of the spectral sensitivity curve are given in table format in the DIN 5031 standard. The two different spectral action functions result from the different "sensor types" of the eye.

The relative luminous efficiency for photopic vision (rods, > 10 cd/m²) is described with the function V(λ), which is

the function used in most cases. The spectral luminous efficiency for the scotopic vision (cones, < 0.001 cd/m²) is described with the function V'(λ) and can, with regard to the practical use, only be rarely found.

Determination of Photometric Characteristic Factors

properties of materials regarding their reflection, transmission and absorption, as well as the stray light of objectives, is based on internationally accepted "Radiometric

The metrological evaluation of the recommendations. These mainly include characteristics of materials", DIN 67507 the CIE 130-1998 "Practical methods for the measurements of reflectance and 5036 Part 3 transmittance", DIN photometric and

"Light transmission factor of glazing". DIN 58186 "Stray light determination of optically image-forming systems".



Why Measure Optical Radiation?

A large part of the human sense impression is of an optical nature. Light is the only visible part of the electromagnetic spectrum. The human eye perceives different wave lengths of the light as colours. The spectral response of the eye, with regard to different colours, depends on the wave length. Furthermore, the human system is also influenced by ultraviolet radiation in a short-wave range and the infrared radiation in a long-wave range of the electromagnetic spectrum.

Illumination:

People are used to daylight illumination. This can be approximately 5000 lux on a dull winter day, while on a sunny summer day approximately 100000 lux are reached. In contrast, only between 100 and 1000 lux are reached with artificial illumination. However, sufficient light is an essential factor for the well-being of people. Symptoms of tiredness, caused by insufficient light, do not generally occur at the eye but affect the whole body.

The standard DIN 5035/2, therefore, contains illumination standard values for health protection at work places.

These are legally bound in the guideline ASR 7/3 and it is imperative that this is observed.

The following nominal illuminations are valid for inside:

Offices:	office rooms	300 lux
	work places for writing and drawing	750 lux
Factories:	visual works within the production process	1000 lux
Hotels:	recreation rooms, reception, counter (cash)	200 lux
Shops:	front side of show windows	1500–2500 lux
Hospitals:	patients' rooms,	100–150 lux
-	emergencies	500 lux
Schools:	lecture rooms, gymnasiums	300 Lux

Global

Radiation: The global radiation is a measuring variable that is especially important for environmental research. It represents the entire diffuse and direct sun radiation that strikes the surface of the earth. The spectral range covers wavelengths from the shortwave range, at 300nm (UV-B), to the longwave range, at 5000nm (IR).

UVA Radiation:

The long-wave UV radiation (more than The short-wave UV range (less than 313nm) reaches the surface of the earth 313nm) can cause irreversible damages.

almost unfiltered and tans the human skin and strengthens the immune system. In solariums the biological effect of the UVA spectrum is used, combined with other spectral ranges, to trigger the direct pigmentation (melanin colouring). Damages to the connective tissue and premature skin ageing are promoted by too much radiation.

UVB Radiation:

All spectral characteristic functions that can have unfavourable effects on the human skin are summarised in the CIE recommendation. This recommendation is described in DIN 5050 and regarded as a guideline. A popular measure for the ,sunburn sensitivity' is, for example, the UV index ,UVI' provided by the German Weather Service. The measuring results provide, directly or in comparison with other spectral ranges, information that is of medical or biological relevance.

Digital measuring head for illuminance (V-Lambda) FLAD 03-VL1 with ALMEMO[®] D6 connector





V- lambda radiation

The spectral range of the visible light is referred to as V-lambda radiation and corresponds to the sensitivity of the human eye. The measured value is a measure for the perceived brightness. The wavelength range extends from the end of the UV spectrum at 400 nm to the beginning of the IR range at 720 nm with a maximum at 555 nm. The determined illuminance in "LUX" can directly be converted into the irradiance "W/m²". Measurements in this particular range have a great importance for the workplace design and lighting projects.

V- lambda radiation sensor FLAD 03 VL1

V- lambda sensors are used in the field of medical and/or biological research, for weather information and forecasting systems, for climate research, for agriculture, and for the automobile industry respectively for measuring artificial lighting. The spectral sensitivity of the receiver is extremely well adapted to the sensitivity of the human eye and complies with the device class B as per DIN 5032. The measuring head FLAD 03 VL1 has a black, anodized aluminum housing. The measurement is cos corrected. The measuring head is only suitable for indoor usage.

Digital measuring head with ALMEMO® D6 connector

The measuring head works with its own AD converter. Used extension cables and the measuring device have no influence on the accuracy of the measurement.

The entire measuring range is divided into 4 measuring ranges, so that, among other things, the smallest illuminances can be measured with a very high resolution.

Technical data	
Measuring range V-lambda	1 lx to 200 klx
ALMEMO [®] measuring range	S
up to 650.00 lx	
up to 6500.0 lx	
up to 65000 lx	
	0.021
Minimum resolution	0.02 lx
Sensor system	Si / interf. filter
Spectral sensitivity	380 nm to 720 nm
Maximum spectral sensitivity	555 nm
Diffuser	PTFE
V-Lambda adaption	<3%
Cos-correction	error f2 < 2.0%
Linearity	< 1 %
Absolute error	< 5 %
Nominal temperature	23 °C ±3 K
Operating temperature	-20°C to +60°C
Switch-on time (Duty cycle)	< 1 s
Switch-off time	< 1 s
Dimensions	diameter 33 mm,
	height approx. 29 mm
Mounting	2 screws M2
Weight	approx. 50 g
ALMEMO [®] connection cable with ALMEMO [®] D6 connected	permanently connected cable 1.5 m
ALMEMO [®] D6 connector	
Refreshrate	1.5 s for all channels
Stabilization time	3 s (For data logger operation in sleep
	mode, a sleep delay of 3 s must be

Stabilization time	3 s (For data logger operation in sleep
	mode, a sleep delay of 3 s must be
	programmed)
Supply voltage	up to 6 V from the ALMEMO [®] device
Current consumption	approx. 4 mA



Variants (incl. works test certificate)

Digital measuring head for illuminance, fixed cable, length 1.5 m, with ALMEMO $^{\tiny (8)}$ D6 connector

FLAD03VL1

Radiation probe FLA 623 x



Common technical data

Diffuser	PTFE
Cosine correction	Error f2 <3 %
Linearity	<1 %
Absolute error	<10 % (<5 % for FLA623VL)
V lambda adapter	<3 % (for FLA623VL only)
Nominal temperature	22 °C ±2 K
Operating temperature	-20 to +60 °C
Signal output	0 to +2 V
Duty cycle	<1 second
Power supply	via ALMEMO [®] connector
	(5 to 15 VDC)

Electrical connection Mountable male connector, lateral Connecting cable PVC cable, plug-in, with ALMEMO® connector Aluminum, black anodized Housing Fixture 2 screws M2 in base plate Dimensions Diameter 33 mm, height approx. 29 mm Weight approx. 50 g (without cable)

Probe for measuring illuminance FLA 623 VL



- This measures the V lambda radiation (visible light, equivalent to sensitivity of the human eye).
- For evaluating lighting conditions, e.g. in the workplace
- The sensor complies with device class B as per DIN 5032.

Technical data:

Measuring range V lambda 0.05 to approx. 170 klx		
Measuring channels	1st channel up to approx. 20,000 lx 2nd channel up to approx. 170.00 klx	
Spectral sensitivity	380 to 720 nm, max. at 555 nm	

Common technical data and image see page 14.05

Variants (including factory test certificate)

Illuminance probe with ALMEMO[®] connecting cable, length = 2 meters Options

ALMEMO[®] connecting cable, length = 5 meters

ALMEMO[®] connecting cable, length = 10 meters

- Probes for various spectral ranges:
- Illuminance (V lambda), UVA, UVB, UVC, global radiation, IR, quantum (photosynthesis)
- Sturdy aluminum housing
- ALMEMO[®] connecting cable, plug-in
- For indoor applications

Order	no.
FLA62	3VL

OA9623L05 OA9623L10

Probe for UVA radiation FLA 623 UVA



Probe for UVB radiation FLA 623 UVB



Probe for UVC radiation FLA 623 UVC



human skin). · Its spectral sensitivity is weighted towards global solar radiation.

Technical data:

Measuring range	0.03 to approx. 100 W/m^2	
Spectral sensitivity	310 to 400 nm,	
	maximum at 355 nm	
0 1 1 1 1	1: 14.05	

· This measures long-wave UV radiation (bronzing effect on

Common technical data and image see page 14.05

Variants (including factory test certificate)	Order no.
UVA probe with ALMEMO [®] connecting cable, length = 2 meters	FLA623UVA
Options: ALMEMO [®] connecting cable, length = 5 meters ALMEMO [®] connecting cable, length = 10 meters	OA9623L05 OA9623L10

- · This measures short-wave UVB radiation.
- Its spectral sensitivity is weighted towards global solar radiation likely to cause erythema (sunburn) as per CIE recommendation (Commission Internationale de l'Eclairage). The UV index can be calculated.

Technical data:

Measuring range	0.002 to approx. 5 W/m ²
Spectral sensitivity	265 to 315 nm, maximum at 297 nm

Common technical data and image see page 14.05

Variants (including factory test certificate)	Order no.
UVB probe with ALMEMO [®] connecting cable, length = 2 meters	FLA623UVB
Options ALMEMO [®] connecting cable, length = 5 meters ALMEMO [®] connecting cable, length = 10 meters	OA9623L05 OA9623L10

• This measures UVC radiation, e.g. Hg line at 256 nm.

• This probe can be used inter alia in water disinfection units.

Technical data:

Measuring range	1 to approx. 1990 mW/m^2
Spectral sensitivity	220 to 280 nm,
	maximum at 203 nm

Common technical data and image see page 14.05

Order	no.
FLA623	UVC

OA9623L05 OA9623L10

ALMEMO[®] connecting cable, length = 10 meters

Probe for global radiation FLA 623 GS



Probe for infra-red radiation FLA 623 IR



Probe for quantum radiation FLA 623 PS



• This measures the solar spectrum in the visible range and in the short-wave IR range.

· Global radiation comprises both direct and diffused solar radiation.

Technical data:

Measuring range	0.4 to approx. 1300 W/m^2
Spectral sensitivity	400 to 1100 nm,
	maximum at 780 nm

Common technical data and image see page 14.05

Variants (including factory test certificate)	Order no.
Global radiation probe with ALMEMO [®] connecting cable, length = 2 meters	FLA623GS
ALMEMO [®] connecting cable, length = 5 meters	OA9623L05
ALMEMO [®] connecting cable, length = 10 meters	OA9623L10

• This measures the solar spectrum in the short-wave IR range (excluding the visible range).

Technical data:

Measuring range	0.1 to approx. 400 W/m^2
Spectral sensitivity	800 to 1100 nm, maximum at 950 nm

Common technical data and image see page 14.05

/ariants (including factory test certificate)	Order no.
R probe with $ALMEMO^{\otimes}$ connecting cable, length = 2 meters	FLA623IR
Dptions: ALMEMO [®] connecting cable, length = 5 meters ALMEMO [®] connecting cable, length = 10 meters	OA9623L05 OA9623L10

• This measures the visible light absorbed by the chlorophyll in plants during photosynthesis.

- It determines the level of quantum radiation in the spectral range specified.
- It is used to assess the conditions in which plants develop in open field and greenhouse cultivation.

Technical data:

Measuring range	1to approx. 3000 μmol/m ² s
Spectral sensitivity	380 to 720 nm,
	maximum at 420 and 700 nm

Common technical data and image see page 14.05

Variants (including factory test certificate)

Quantum probe with ALMEMO[®] connecting cable, length = 2 meters **Options:** ALMEMO[®] connecting cable, length = 5 meters

ALMEMO[®] connecting cable, length = 10 meters

Order no. FLA623PS

> OA9623L05 OA9623L10

Illuminance measuring head FLA 613 VLK



- Measuring independent of direction thanks to the probe head's spherical characteristics
- · Weather-proof aluminum housing, with plastic globe
- Suitable for universal use, inter alia for measuring in photostability tests according to various international standards and ICH guidelines (International Conference on Harmonization)
- Spectral range of the probe head corresponds to the sensitivity of the human eye (V-lambda radiation).





Technical data:	
Measuring range	0.02 to 50 klux
Spectral sensitivity	360 to 760 nm
Maximum spectral sensitiv	vity 555 nm
Signal output	0 to 2 V
Duty cycle	<1 second
Power supply	via ALMEMO [®] connector +5 to +15 V
Fastening	2 screws, M4, in base plate
Cable passage	at side
Housing	anodized aluminum
Diffuser	Plastic
Ball	Plastic
Directional characteristic	see diagram
Linearity	<1%
Absolute error	<10%
Nominal temperature	$22 \pm 2 \ ^{\circ}C$
Operating temperature	-20 to +60 °C
Dimensions	Ball diameter : 40 mm Overall height : 76 mm
Weight	approx. 100 grams

Type (including test protocol)

Lux probe head for measuring illuminance, with spherical characteristic, including 1.5-meter cable and ALMEMO[®] connector

UVA probe head FLA 613 UVAK



- Measuring independent of direction thanks to the probe head's spherical characteristics
- Weather-proof aluminum housing, with plastic globe
- Suitable for universal use, inter alia for measuring in photostability tests according to various international standards and ICH guidelines (International Conference on Harmonization)
- Measuring head for measuring the UVA



Technical data:

Measuring range	0.02 to approx. 50 W/m^2
Spectral sensitivity	310 to 400 nm
Maximum spectral sensitiv	vity 355 nm
Signal output	0 to 2 V
Duty cycle	<1 second
Power supply	via ALMEMO [®] connector +5 to +15 V
Fastening	2 screws M4, in base plate
Cable passage	at side
Housing	anodized aluminum
Diffuser	PMMA (polymethyl methacrylate, acrylic)
Ball	PMMA (transparent to UV)
Directional characteristic	see diagram
Linearity	< 1%
Absolute error	< 10%
Nominal temperature	$22 \pm 2 \ ^{\circ}C$
Operating temperature	-20 to +60 °C
Dimensions	Ball diameter : 40 mm Overall height: 76 mm
Weight	approx. 100 grams

Type (including test protocol)

UVA probe head, with spherical characteristic, including 1.5-meter cable and ALMEMO® connector

Order no. FLA613UVAK

Order no.

FLA613VLK

Factory calibration KL90xx radiation for sensor (see chapter Calibration certificates)

Digital measuring head for erythema effective UV radiation (UVE) FLD7 03-UVE with ALMEMO[®] D7-connector

Monitoring of UVE-radiation hazardous for human skin.

Mobile measurements in meteorological, medical and biological applications.

For connection to current measuring instruments ALMEMO[®] V7 : ALMEMO[®] 500, 710, 809, 202, 204





ALMEMO[®] UVE-measuring head

Erythema effective UV radiation

The natural UV radiation of the sun or the UV radiation of artificial sources has different effects to human skin dependant on the wavelength range.

- The long-wave UV radiation (more than 313 nm, UVA) tans the skin and supports the human immune system.
- The short-wave UV radiation (less than 313 nm, UVB/UVE) may cause irreversable damage.

In the recommendation of the CIE (Commission Internationale de l'Eclairage) all spectral effect functions which can have a negative effect on the human skin are summarized. This recommendation is described in the DIN 5050 resp. ISO/CIE 17166 and valuated as a directive.

UVE-measuring head FLD7 03-UVE

The measuring head records the erythema effective UV radiation. The spectral sensitivity of the measuring head complies with the standards DIN 5050 and ISO/CIE 17166 and the Ordinance on Protection against the Harmful Effects of Artificial Ultraviolet Radiation (UV-Schutz-Verordnung - UVSV, published in the Federal Law Gazette 2011 Part I No. 37). The measurement results provide direct information about medically and biologically relevant correlations in this radiation range. DIN 5050 specifies four different skin types: Skin type I to IV. The UV Protection Ordinance - UVSV extends by two further skin types: skin type V and VI. The guideline for these six skin types are taken into account in the calculation of the various parameters. The measuring head is used in areas of medical and biological research, for the measurement of

UV radiation equipment (for cosmetic purposes, medical treatments or other human applications), in weather information and forecasting systems, in climate research and for general population information.. A popular measure of "sunburn sensitivity" is the UV index "UVI", which is determined by the German Weather Service.

The measuring head FLD7 03-UVE has a black anodized aluminum housing. The measurement is cos - corrected. The measuring head is suitable for measurements in dry environments.

Digital measuring head with ALMEMO® D7-connector

The measuring head works with its own AD converter. Extension cables and the ALMEMO[®] measuring instrument/data logger have no influence on the accuracy of the measurement..From the measured irradiance, all relevant measured variables are calculated and output to the ALMEMO[®] instrument. Different measuring channels can be selected and the measured variables can be displayed :

- UV-index: relative irradiance related to 25 mW/m^2
- UVE irradiance (erythema-effective) in mW/m².
- Dose (erythema effective irradiation) in J/m²: sum of irradiance over the irradiation period (energy).
- Relative minimum erythema-effective dose (MED): Dose related to 1 MED (= erythema-effective threshold irradiation) of the set skin type according to DIN 5050 and UVSV. Example: 1 MED for skin type 2 (light-skinned European skin type) = 250 J/m².
- Remaining time of irradiation in minutes until the dose 1 MED of the selected skin type is reached.
- Current, predicted maximum irradiation time in minutes until the dose 1 MED of the selected skin type is reached.
- Relative standard erythema effective dose (SED): Dose related to 1 SED (100 mW/m²) according to ISO 17166.

ALMEMO[®] D7

Technische Daten

Measuring range UVE:	0,1 300 mW/m ²
Resolution:	0,1 mW/m ²
Sensor system:	SiC / interference filter
Spectral sensitivity:	230400 nm
Erythema effective spectra	l range: 250 298 328 nm
Max. spectral sensitivity:	295 nm
Diffuser:	PTFE
Cos-correction:	error f2 < 3 %
Linearity:	better 1 %
Absolute error:	< 7 %
Nominal temperature:	23 °C ±3 K
Operating temperature:	-30 +60°C
Switch-on time:	< 1 s
Switch-off time:	< 1 s

Dimensions:	
diameter	33 mm,
height	ca. 29 mm
Mounting:	2 screws M2
Weight (without cable)	approx. 50 g
ALMEMO [®] connecting ca	able:
fixed attached cable, 1,5 m, with ALMEMO® D7-connector	
ALMEMO [®] D7 connector	
Refresh rate:	1 s for all channels
Settling time:	3 s (for data logger operation in
	sleep mode a sleep delay of 3 s
	has to be programmed)
Power supply voltage:	from 6 V from ALMEMO® instrument



Intensity of Irradiation and UV-Index



Version in weatherproof housing for outdoor use FLD7 33-UVE Data sheet see chapter meteorology

Versions (incl. works test certificate)	Order no.
Digital measuring head for UVE radiation, for measurements in dry surroundings. Sensor with permanently attached cable, 1,5 m, with ALMEMO [®] D7-connector	FLD703UVE
Digital measuring head for UVE radiation in a weatherproof housing for outdoor use. Sensor with built-in connector, incl. ALMEMO [®] connecting cable, 1,5 m, with ALMEMO [®] D7-connector. Data sheet see chapter meteorology.	FLD733UVE

Digital sensor for color temperature and illuminance FLAD23CCT with ALMEMO[®] D6 plug



- Color temperature and illuminance are determined as a means to plot and evaluate lighting systems.
- Compact sensor, particularly suitable for mobile applications
- Continuous measuring and updating of measured values
- Digital color temperature sensor with "TrueColorSensorchip" and integrated signal processor The TrueColorSensorchip (3 sensors on 1 chip) detects - separately - each of the three colors - red, green, blue (RGB). The respective sensitivities of these 3 color sensors are adapted to the standard spectral curves as per CIE and DIN. (see Figure) On the basis of these RGB values the computer calculates the color point within the RGB range in terms of coordinates X and Y and determines the correlated color temperature (CCT) in Kelvin.
- The display shows simultaneously both this color data and the illuminance in lux (lx) or kilolux (klx).
- Freely selectable measurable variables Two measuring channels are programmed (at our factory): Color temperature (CCT, K), Illuminance (Ev, lx) Other measurable variable can also be selected: Illuminance X-value, Y-value (Ev, klx), The configuration is performed on the ALMEMO® V7 measuring instrument or directly on the PC using the USB adapter cable ZA1919AKUV (see chapter "ALMEMO® Network technology").

Technical data:

Spectral sensitivity	380 to 720 nm	
Sensor system	TrueColor 3 sensors on 1 chin	
Maanuina nun aa	The color, 5 sensors on 1 emp	
Measuring ranges	ra (CCT) 54 to 20 000 K	
Correlated color temperatu	(0.1) 34 to 30,000 K (at 120 ly to 170 lyly)	
Accuracy	(at 120 IX to 170 KIX)	
Coordinates resolution (a	< 1070 m range 1000 to 17000 K	
Coordinates resolution (C	(x, dy) < 0.005	
mummance (v-tamoda)	$10\ 10\ 05,000\ Ix\ (lactory\ setting)$	
A	< 100/ in range 120 ly to 170 kly	
Accuracy		
Cosine correction	8 mm diffuser plate	
Cosine error	< 3%	
Measuring duration	< 3 seconds	
Nominal conditions	23 °C \pm 3 K, 0 to 90 % RH	
	(non-condensing)	
Operating temperature	-10 to +40 °C	
Dimensions	Diameter 25 mm, length 134 mm	
ALMEMO [®] connecting cable Fixed cable, 1.5 meters.		
U	with ALMEMO [®] D6 plug	
ALMEMO [®] D6 plug		
Refresh rate	1.5 seconds for all channels	
Setting time	3 seconds	
	(In order to run the data logger in	
	sleep mode a wakeup delay of	
	3 seconds must be programmed.)	
Supply voltage	6 to 13 VDC	
Current consumption	approx 4 mA	



Order no.

Digital sensor for color temperature and illuminance, fitted cable, 1.5 meters with ALMEMO[®] D6 plug

Variants



Accessories

Ulbricht integrating sphere



- 0.9 520 0.8 40 0.7 560 0.6 500 580 0.5 T_c(K) у 0.4 600 620 0.3 700 0.2 480 0.1 470 0.0↓ 0.0 4<u>60</u> 0.1 0.2 0.4 0.8 0.3 0.5 0.6 0.7
- Ulbricht integrating sphere, for measuring total radiation from any light source
- Especially suitable for measuring operations on site for light sources that have already been installed. This minimizes interference from extraneous light in the environment.

• Dimensions Measuring aperture Sphere diameter Housing diameter

13.5 mm 40 mm 44.5 mm, length 44 mm

Accessories	Order no.
An Ulbricht integrating sphere can be attached to color temperature sensor FLAD23CCT	ZB9623KU

Luminance Probe Head FLA 603 LDM2



- Luminance measuring head, equipped with achromatically corrected, low stray light optics and high quality V(l) detector according to DIN class B.
- The external sighting device allows, at a working distance of 1m, to exactly locate the measuring point, therefore, it is particularly suitable for evaluating the luminance for service and constancy tests.
- Three measuring channels with different sensitivity.
- Typical applications: Luminescent surfaces such as colour monitors, alphanumerical displays, sign plates and light panels, and reflecting surfaces, such as walls and equipment at work places, projecting screens, traffic and sign plates, guided paths and roadway lines.

Technical data:

Technical data: Measuring range:

Smallest resolution: Sensitivity:

Acceptance angle: Accuracy:

Nominal temperature: Humidity range:

Operating temperature:

Inner diameter of globe:

Test opening:

0.04 cd/m ² to appr. 6400 cd/m ²
10 mcd/m ²
1°
approx. 30 pA/(cd/m2)
approxim. to photometric valuat. function V(l) for photopic vision, class B, better than 6%
approx. 30 mm at a distance of 0.5 m approx. 40 mm at a distance of 1 m approx. 120 mm at a distance of 5 m
$24^{\circ}C \pm 2K$
e: 0 to 60°C/-10 to +80°C
10 to 90% (non-condensing)
21mm x 21mm at 1m operating distance
IEC 61223-2-5, DIN 5032-T.7
diameter 30mm, length 150 mm

Variants

Luminance probe head with 1° field of view and external sighting device, DIN quality class B, with ALMEMO[®] connecting cable 1.5m long, incl. factory calibration certificate calibration in cd/m²

FLA603LDM2

Order no.

FLA603LSM4

Order no.

Light Flux Probe Head FLA 603 LSM4



- High quality measuring head, DIN class B for light flux measurement with Ulbricht globe photometer.
- Perfect coating of the globe with BaSO4 for diffuse reflectivity and spectrally neutral reflection quality.
- Suitable for cold light sources, and lamps with high colour temperature and almost monochromatic radiation (as in LEDs).
- Examples for applications: Endoscopes, fiber optic bunches, light emitting diodes.



0.0002 lm to appr. 38 lm

DIN quality class B

10 to 90 % non-condensing

max. 100°C inside globe

0.001 lm

20nA/lm up to 90 °

 $24^{\circ}C \pm 2K$

50mm

12,7 mm

Туре

Light flux probe head with ALMEMO® connecting cable 2m long and factory calibration certificate

10/2021 • We reserve the right to make technical changes

Factory calibration KL90xx radiation for sensor (see chapter Calibration certificates)

Content

pH value, Redox potential, Conductivity	15.02
The Electrical Conductivity	15.03
Solute oxygen in liquids	15.03
pH one-bar measuring chains FY 96 PHEK, FY 96 PHER, FY 96 PHEN	15.04
pH insertion electrode FY96PHMEE1, FY96PHMEE2	15.05
Redox one-bar measuring chains FY 96 RXEN	15.05
ALMEMO [®] connecting cable for pH and redox probes	15.06
Digital connection cable for pH and redox probes	15.07
Conductivity probes FYA 641 LFP1 / LFL1	15.08
Conductivity probes FYA 641 LFP2 / LFL2, FYA 641 LFP3	15.09
Digital probes for measuring conductivity	15.10



The pH Value



The Redox Potential

The level of the Redox potential (measured in mV) indicates the strength of an oxidising or reducing reaction of a measuring solution. A negative voltage value means that the solution has reducing properties compared to a standard hydrogen electrode. A positive value indicates that the solution has an oxidising

effect.

pH7 is neutral.

As the extermination of microorganisms (disinfection) is directly related to the strength of the oxidation (e.g. of chlorine) the Redox potential is successfully being used for monitoring disinfection processes, e.g. in swimming baths. However, redox measurements are also performed for

The pH value is a logarithmic measure for

the concentration of the H ions in a hydrous

solution and indicates, by a numerical

value, whether the solution has an acid,

The pH scale ranges from pH0 to pH14,

neutral or alkaline reaction.

The further the pH value deviates from 7, the more aggressive the sample is. The acidic or alkaline effect will increase by the factor 10 per pH unit.

The illustration on the left shows some examples for pH values of typical substances

controlling the denitrification of waste waters (redox break point determination) at the detoxification in galvanic plants and for monitoring multiple chemical processes (e.g. cyanide oxidation or chromate reduction).

ALMEMO[®] pH and Redox Measurement

of pH and redox probes can be started with sockets are used, it is even possible to medium largely deviates from the reference the push of a button. As the adjustment is connect more probes with individual temperature, it is possible for all stored in the ALMEMO[®] connector, the probe can also be used with other devices.

value is based on the electrode steepness at temperature compensation.

By using reference solutions the calibration If ALMEMO[®] devices with several input 25°C. If the temperature of the measuring adjustments. The calculation of the pH ALMEMO® devices to perform a

The Electrical Conductivity

The conductivity (unit S/m = Siemens/meter) is a measure for the ion concentration in a measuring solution.

It is proportional to the salt, acid or base content in the measuring solution. Highpurity waters have a conductivity of approx. 0.05µS/cm (at 25°C), natural waters approx. 100 to 1000µS/m, some bases (e.g. potassium hydroxide solutions)

up to slightly more than 1000mS/cm.

The diagram shows further examples of hydrous solutions relevant for measurements.

In practice, the conductivity measurement is used for monitoring plants, for producing of high-purity waters or for determining the salinity of sea water.



Solute Oxygen

Oxygen is not only a component of the air but it is also contained dissolved in water and, practically, in every liquid. For example, water contains approximately 9mg/l oxygen in saturated compound at a temperature of 20°C and an atmospheric pressure of 1019mbar.

Every liquid accepts as much oxygen until the oxygen partial vapour pressure in the liquid is in a balance with the 'contacting' air or gas phase. The saturation state (airsaturated water) is reached when the

partial pressure of the physically dissolved oxygen in the liquid equals the partial pressure of the oxygen in the air.

The current oxygen concentration increases with atmospheric pressures and with decreasing temperatures. Relevant for metrology are processes, such as the oxygen consumption involved with microbiological decomposition processes or an oxygen production, e.g. due to the growth of algae.

The oxygen concentration is very important for animals and organisms living in water and for the biological treatment of municipal and industrial waste water. Additionally, corrosion processes in lines and keeping the quality of beverages depend on the solute oxygen in the liquid.

This is only possible with ALMEMO® Devices

TEMOR data la gan in du din a sousan a suin mant and a sousanies

simultaneously measure various chemical

Through the complete electrical isolation variables, and use several probes in one it is possible to connect any environmental of the measuring inputs it is possible to use sampling vessel without having any only one single ALMEMO[®] device to mutual influences of the probes! Through pre-programmed ALMEMO® connectors

sensor technology.

ALMEMO[®] system with data logger and comprehensive sensor equipment Order no.

For exploring abandoned polluted areas and their environments or for performing groundwater quality tests

A	LWIEMO [*] data logger including sensor equipment and accessories	
•	ALMEMO® 2690-8A with 5 measuring inputs, including PC data cable	MA26908AKSU
•	Temperature sensor -70 to +400 $^{\circ}$ C	FPA30L0250 + OFS0008
•	pH electrode 1 to 12 pH including connecting cable and buffer solutions pH 4/7/10	FY96PHEK + ZA9610AKY4 + ZB98PHPL4 + ZB98PHPL7 + ZB98PHPL10 + ZB98PHNL
•	Redox electrode including connecting cable and buffer solution 220 mV and KCl solution	FY96RXEK + ZA9610AKY5 + ZB98RXPL2
•	Conductivity probe 0.01 to 20.00 mS/cm including reference solution 2.77 mS/cm	FYA641LFP1
•	Probe for measuring solute oxygen 0 to 40 mg/l or 0 to 260 % saturation including filling sc	blution FYA640O2
•	Adjustment set for the oxygen probe, saturation and zero point adjustment	ZB9640AS

pH One-Bar Measuring Chain FY96PHEK



Applications:

manual measurements e.g. swimming pools, drinking water ...

Technical Data

pH range::	1 12	Reference (Electrolyt):	KCl containing gel
Operating range	0 60°C	Shaft length:	120 ± 3 mm
Operating pressure:	unpressurised	Shaft diameter:	12mm (polycarbon)
Conductivity:	$> 150 \ \mu S \ / \ cm$	Electrode head:	plug head SN6
Diaphragm type:	ceramic		

Туре

pH-one-bar measuring chain pH 1 ... 12, 0 ... 60°C for unpressurised operating

Order no. FY96PHEK

Order no.

FY96PHER

Order no.

FY96PHEN2

pH One-Bar Measuring Chain FY96PHER



Applications:

Generally for water with solid content (turbid water), water with low conductivity, e.g. from reverse osmosis. Municipal and industrial wastewater, cooling water, industrial water, water in chemistry and paper production.

Technical Data

pH range:	1 12	Reference (Electrolyt):	KCl-containing polymer)
Operating range:	0 80°C	Shaft diameter:	12mm (glass)
max. pressure:	6 bar	Screw connection	thread PG13.5
Conductivity:	$> 50 \ \mu\text{S} \ / \ \text{cm}$	Shaft length:	$120 \pm 3 mm$
Diaphragm type:	PTFE ring diaphragm	Electrode head:	plug head SN6

Туре

pH-one-bar measuring chain pH 1 ... 12; 0 ... 80°C, up to 6 bar

pH One-Bar Measuring Chain FY96PHEN2



Applications:

new

only for clear water, waste water, cooling water, chemically contaminated water.

Technical Data

pH range:	1 12	Reference (Electrolyt):	KCl solution, refillable)
Operating range	0 80°C	Installation length:	120 ±3mm
Operating pressure:	unpressurised	Shaft diameter:	12mm (material: glass)
Conductivity:	$> 150 \ \mu S \ / \ cm,$	Screw connection	thread PG13.5
Diaphragm type:	ceramic	Electrode head:	plug head SN6

Туре

pH-one-bar measuring chain pH 1 ... 12, 0 ... 80°C for unpressurised operating

.

pH Insertion Electrode FY96PHMEE1



Technical Data

Operating range:	рН 1 11 / 0 80 °С
max. pressure:	unpressurized operation
Diaphragm / Reference:	no diaphragm / polymer
Piercing tip: Ø approx. 6 mm,	Penetration depth approx. 25 mm

Type

pH Insertion Electrode, for food



Technical Data

Operating range:	pH 2 11 / 0 80 °C	
max. pressure:	unpressurized operation	
Diaphragm / Reference:	no diaphragm / polymer	
Piercing tip: Ø approx. 6 mm. Penetration depth approx. 25 mm		

Туре

pH Insertion Electrode, für for food

Redox-One-Bar Measuring Chain FY96RXEK



Technical Data

Operating temperature	0 60°C	Metal electrode :	platinum
Operating pressure:	unpressurised	Shaft length:	125 ±3mm
Conductivity:	$> 150 \ \mu S \ / \ cm$	Shaft diameter:	12 mm (material: polycarbonate)
Diaphragm / Electrolyt	ceramic / KCl containing gel	Electrode head:	plug head SN6

Type

Redox-one-bar measuring chain 0 ... 60°C for unpressurised operating

Accessories for pH-One-Bar Mea	as. Chains an	d Redox-One-Bar Meas. Chain	Order no.
Buffer solution pH 4.0 50 ml Buffer solution pH 7.0 50 ml Buffer solution pH 10.0 50 ml	Order no. ZB98PHPL4 ZB98PHPL7 ZB98PHPL10	Redox buffer solution 220 mV KCl solution, 3-molar, 50ml for refilling and storage	Order no. ZB98RXPL2 ZB98PHNL

Applications:

new

Hand measurements, for piercing solid and semi-solid samples such as meat, cheese, fruit, vegetables.

Shaft:	Ø 8 / 12 mm, length approx. 90 mm (incl. tip), material glass
Electrical connection:	plug head S7

Order no. **FY96PHMEE1**



Applications:

Stable insertion electrode, for food such as meat, sausage, cheese/butter, fruits.

Shaft::	Ø 8 / 16 mm, length approx. 100 mm (incl. tip), material glass, with plastic cover of PBT.
Electrical connection:	plug head S7

Order no. **FY96PHMEE2**

Order no.

FY96RXEK

Applications:

manual measurements e.g. swimming pools, drinking water

ALMEMO[®] connecting cable for pH and redox probes



Applications:

Transducer cables are available for all popular electrodes with a coaxial connector. To avoid the measuring signal being corrupted by the measuring instrument itself an extremely high-impedance amplifier is integrated in the ALMEMO[®] connector on the connecting cable.

Transducer cable with various electrodes

Technical Data

Transducer	High-impedance measuring amplifier (>500 Gohm), integrated	Electrode terminal	For plug-on head S7/SN6 or SMEK (see variants)
	in the ALMEMO® connector		
Туре			Order no.
ALMEMO [®] connecting cabl	e with transducer (ALMEMO [®] con	nnector, spray-coated)	
For probes with plug-on hea	d S7/SN6 (coaxial connector, screw	<u>v-fit):</u>	
Programming for pH probe			
Cable length 2 meters			ZA9610AKY4
Cable length 5 meters			ZA9610AKY4L05
Programming for redox prob	bes		
Cable length 2 meters			ZA9610AKY5
Cable length 5 meters			ZA9610AKY5L05
Programming for pH or redo	ox probe (1 probe connectable at a t	ime)	
Cable length 2 meters			ZA9610AKY6
Cable length 5 meters			ZA9610AKY6L05
-			



Туре	Order no.
ALMEMO [®] connecting cable with transducer	
For probes with SMEK plug-on head	
Cable length 2 meters	
Programming for pH probe with integrated temperature sensor NTC (30 kohm at 25 °C),	
linearization saved in ALMEMO® connector (only for current V6 ALMEMO® devices)	ZA9640AKY8
Programming for pH probe	ZA9610AKY8
Programming for redox probe	ZA9610AKY9

NTC temperature sensor for automatic temperature compensation when measuring pH



Connector programming designation *T for ALMEMO® 2490 and 2590-2/-3S/-4S and (with effect from 07/2006) for ALMEMO® 2690/ 2890/ 5690/ 8590/ 8690

Туре	Order no.
Stainless-steel sheathed sensor (see page 07.06) Diameter 3.0 mm, length 250 mm, Hexagonal cable sleeve with 1.5 meters PVC cable and ALMEMO [®] connector	FNA30L0250T
Safety hose made from PTFE (for aggressive media) Hermetically sealed on one side, inside diameter 3.1 mm, outside diameter 5.1 mm, length 500 mm	ZT9000TS7



Digital connection cable for pH and redox probes ZYD7 10-AKx and ZYD7 40-AKx, with ALMEMO[®] D7 plug



• Digital ALMEMO[®] D7 connection cable.

- Galvanically isolated from the measuring instrument.
- Temperature dependence of the probe can be compensated manually or automatically.
- Comparison of the pH probe at three points.

Technical data and functions

Digital connection cable.

The voltage of the probe is measured by an A/D converter integrated into the ALMEMO[®] D7 plug. Extension cables and the measuring device itself have no influence on the measurement accuracy.

Galvanic Isolation to the ALMEMO® V7 measuring device. It is possible to operate several pH probes simultaneously in the same sample solution on one measuring device without influencing each other.

Compensation of the temperature dependence of the probe.

To compensate the temperature dependence of the probe, the temperature of the sample solution can be entered manually. The connection cable ZYD7 40-Akx additionally features a temperature sensor. As a result, the measured temperature value will be used for automatic compensation.

Comparison of the pH probe possible at three points.

EThe comparison will be saved at pH 7 as well as at one point in the acid range and at one point in the alkaline range. The values of the reference solutions can be specified as set points.

Technical data

ALMEMO [®] D7 plug		Supply voltage:	from 6 V up, from the ALMEMO [®] measuring device
pH value	0.00 to 14.00 pH	Current consumption:	approx. 8 mA
Redox potential -1100.0 to +1100.0 mV Temperature NTC -50.00 to +125.00 °C		Temperature sensor NTC	
A/D converter	Delta Sigma	Design:	FN030L0250 with OPK03L0020
Accuracy:	$\pm 0,02$ % of measured value ± 2 digits $\pm 0,05$ K at -50 to +100 °C	Accuracy:	see chapter 07
pH/redox temperature NTC		Measuring tip: NL = 250 mm	stainless steel sheathed line, $d = 3.0$ mm,
Nominal temperature:	23 °C ±2 K	Cable sleeve:	Bross hexagonal
Temperature drift:	max. 0.004 %/K (40 ppm)	Cable sieeve.	L=65 mm, width across corners = 9 mm
Operative range: densing)	-10 to +60 °C / 10 to 90 % RH (non-con-	Cable:	2 m, FEP/FEP isolated, permanently mounted in the ALMEMO [®] D7 plug
Refresh rate:	0.8 s	Operating temperature:	-20 to 100 °C

Accessories

-
hermetically sealed on one side, inside diameter 3,0 mm, outside diameter 4,0 mm, length 700 mm ZT9000TS7
ALMEMO [®] D7 extension cable up to 100 m, see chapter 06

Digital ALMEMO® D7 connection cable for probes with plug-on head S7/SN6 (coaxial connector, screw-fit)

Programming for pH probeZYD710AK4Cable length = 2 mZYD710AK4Cable length = 5 mZYD710AK4L05Programming for redox probeZYD710AK5Cable length = 2 mZYD710AK5Cable length = 5 mZYD710AK5L05Additionally with permanently connected temperature sensor NTC,
Programming for pH probe and temperature sensorZYD740AK4Cable length = 2 mZYD740AK4

Order no.

Conductivity Probe FYA641LFP1 / LFL1



Applications:

Concentrated waste water, aggressive waters, general aqueous and partly aqueous solutions, beer, emulsions, electroplating, waters, concentrated acidic and alkaline solutions, corrosive acids and alkaline solutions, lacquers and paints, substances containing protein, soaps, detergents, suspensions, titrations in organic substances, environmental analysis.

Technical Data

Measuring range:	0.01 to 20mS/cm LFL1 up to 10mS/cm
Temperature sensor:	NTC, type N (10k at 25°C)
Temperature compensation:	0 to $+70^{\circ}$ C, automatic
Compensation coefficient:	1.9 linear
Cell constant:	approx. 1cm ⁻¹
Electrode material:	special coal
Accuracy:	\pm 3% of meas. val. \pm 0.1mS/cm
Nominal temperature:	$25^{\circ}C \pm 3^{\circ}C$
Operating temperature:	-5 to 70°C
Minimum insertion depth:	30mm

PVC - C	
LFP1: 130mm/20mm	
LFL1: 130mm/10mm	
only LFP1 145 mm / G3/4"	
LFP1: 16 bar at 25 °C	
LFL1: not suitable for use	
under pressure	
1.5m	
8 to 12V through meas. instr.	
approx ca. 3 mA	

Type (including manufacturer's test certificate)	Order no.
Active conductivity probe with automatic temperature compensation, Built-in probe, G 3/4" thread,	
suitable for use under pressure up to 20mS/cm	FYA641LFP1
Laboratory probe, not suitable for use under pressure up to 10mS/cm	FYA641LFL1
Factory calibration KY90xx conductivity for measuring chain (sensor + device) (see chapter Calibration certificates)	

On request: Sensor for dissolved oxygen FYA 640-O2



Conductivity Probe FYA641LFP2 / LFL2



Applications:

Low-salt waste water, general aqueous and partly aqueous solutions, fish tanks, emulsions, desalting/ion exchanger, beverages, waters, cold/boiler feed water, lacquers and paints, milk, samples with low ionic strength, substances containing protein, purest water, soaps, detergents, suspensions, drinking water, environmental analysis.

Technical Data

Measuring range:	10 to 200µS/cm	Shaft material:	PVC - C	
Temperature sensor:	NTC, type N (10k at 25°C)	Shaft length/Shaft diameter:	LFP2: 130mm/20mm	
Temperature compensation:	0 to $+70^{\circ}$ C, automatic		LFL2: 130mm/10mm	
Compensation coefficient:	1.9 linear	Fitting length / thread	only LFP2 145 mm / G3/4"	
Cell constant:	approx. 1cm ⁻¹	Maximum pressure	LFP2: 16 bar at 25 °C	
Electrode material:	special coal		LFL2: not suitable for use under pressure	
Accuracy:	\pm 3% of meas. val. \pm 1 $\mu S/cm$	- Cable length:	1.5m	
Nominal temperature:	$25^{\circ}C \pm 3^{\circ}C$	- Power supply:	8 to 12V through meas, instr.	
Operating temperature:	−5 to 70°C	Current consumption:	approx 3 mA	
Minimum insertion depth:	30mm	- Current consumption.	approx. 5 mA	

Type (including manufacturer's test certificate)	Order no.
Active conductivity probe 0 to 200µS/cm with automatic temperature compensation,	
Built-in probe, G 3/4" thread, suitable for use under pressure	FYA641LFP2
Laboratory probe, not suitable for use under pressure	FYA641LFL2
Factory calibration $KY90xx$ conductivity for measuring chain (sensor + device) (see chapter Calibration certificates)	

Conductivity Probe FYA641LFP3



Applications:

Concentrated waste water, aggressive waters, general aqueous and partly aqueous solutions, beer, emulsions, electroplating, waters, concentrated acid and alkaline solutions, corrosive acids and alkaline solutions, lacquers and paints, substances containing protein, soaps, detergents, suspensions, titrations in organic substances, environmental analysis.

Technical Data

Measuring range:	1 to 200 mS/cm	Shaft material:	PVC - C
Temperature sensor:	NTC, type N (10k at 25°C)	Shaft length:	145mm
Cell constant:	approx. 1cm ⁻¹	Shaft diameter:	20mm
Electrode:	4 electrodes, special coal	Fitting length / thread	130 mm / G¾"
Accuracy:	\pm 3% of meas. val. \pm 1 mS/cm	Maximum pressure	16 bar at 25 °C
Nominal temperature:	$25^{\circ}C \pm 3^{\circ}C$	Cable length:	1.5m
Operating temperature:	0 to 70°C	Power supply:	8 to 12V through meas. instr.
Minimum insertion depth:	30mm	Current consumption:	approx. 15 mA

Type (including manufacturer's test certificate)

Conductivity probe 0 to 200mS/cm without temp. compensation

Factory calibration KY90xx conductivity for measuring chain (sensor + device) (see chapter Calibration certificates)

Order no. FYA641LFP3



Just one single probe for measuring conductivity from very low (10 $\mu S/cm)$ up to very high levels (500 mS/cm)

4-contact graphite electrode with high linearity across the whole measuring range

Integrated NTC sensor for temperature compensation of measured conductivity values

Suitable for the latest ALMEMO[®] V7 devices, including professional measuring instrument ALMEMO[®] 202 and precision measuring instrument ALMEMO[®] 710.

ALMEMO® 202

Technical data and functions

The digital conductivity probe provides this high level of precision irrespective of any extension cables used and of any processing in the ALMEMO[®] V7 display device / data logger.

Overall accuracy is determined exclusively by the conductivity electrode and the ALMEMO[®] D7 plug.

All parameters for the sensor can be programmed end-to-end via the programming menu on the ALMEMO[®] V7 measuring instrument. The desired measuring range can be selected and

temperature compensation can be activated or deactivated. The temperature coefficient of the solution to be measured, if known, can also be programmed.

The probe is delivered already adjusted and ready-to-use. The electrode's measured cell constant can also be entered, if so required, and / or the probe can be adjusted using a reference solution.

Common technical data FYD 741 LFE01 and FYD 741 LFP ALMEMO[®] D7 plug with A/D converter

Measuring method	Electrical conductivity measurement with AC voltage (approx. 1 kHz)	Temperature coefficient	Natural surface water or linear in range 0.00 to 9,99
Measuring ranges Range DLF1	up to maximum 500.00 μS/cm Resolution 0.01 μS/cm up to 50.000 mS/cm Resolution 0.001 mS/cm (factory default settings) with FYD 741 LFE01 up to 500.00 mS/cm	Linearization NTC	Calculated error-free (not an approximation)
Range DLF2Resolution 0.01Range DLF2up to 50.000 mSResolution 0.001(factory default sRange DLF3with FYD 741 Lwith FYD 741 LResolution 0.01		Nominal temperature	+23 °C ±2 K
		Temperature drift	0.004 % / K (40 ppm)
		Refresh time	2.5 seconds
		Sleep mode on the device possible with wakeup delay of 5 seconds	
	with FYD 741 LFP up to 200.00 mS/cm Resolution 0.01 mS/cm	Supply voltage	6 to 13 VDC, from ALMEMO [®] device (sensor supply voltage)
Range NTC	Resolution 0.01 K	Current consumption	approx. 10 mA
Temperature compensation either automatic or non-compensated			

Digital probe for measuring conductivity FYD 741 LFP



Probe for process applications

General description and common technical data see previous page

Technical data FYD 741 LFP

Uses Conductivity	Process applications 10 µS/cm up to 200 mS/cm
Temperature Pressure	0 to +70 °C up to 16 bar under nominal conditions
Process connection	Thread G ³ / ₄ -inch Fitted length 145 mm
Electrode type	4-contact graphite electrode electrically connected to the power supply (ALMEMO [®] device ground)
Cell constant	approx. 0.5 cm ⁻¹
Temperature sensor	NTC 10 kilohms, integrated
Accuracy Conductivity	$\pm 3\%$ of meas. value $\pm 0.2\%$ of final value under nominal conditions (200 mS/cm)
Temperature	± 0.2 K under nominal conditions
Nominal conditions	+25 °C ±2 K
Minimum immersion de	pth 30 mm
Electrode shaft	Material PVC-C diameter 20 mm, length 130 mm
Connecting cable	length = 1.5 meters, permanently fitted, with ALMEMO [®] D7 plug

Digital probe for measuring conductivity FYD 741 LFE01



Probe for laboratory applications

General description and common technical data see previous page

Technical data FYD 741 LFE01

Uses	Laboratory applications
Conductivity	10 µS/cm up to 200 mS/cm,
	on demand up to 500 mS/cm
Temperature	0 to +80 °C
Pressure	Ambient pressure (unpressurized)
Electrode type	4-contact graphite electrode
	electrically connected to the power supply
	(ALMEMO [®] device ground)
Cell constant	approx. 0.5 cm ⁻¹
Temperature sensor	NTC 30 kilohms, integrated
Accuracy	
Conductivity	$\pm 2\%$ of meas. value $\pm 0.2\%$ of final value
	under nominal conditions (200 mS/cm)
Temperature	± 0.2 K under nominal conditions
Nominal conditions	+25 °C ±2 K
Minimum immersion de	epth 30 mm
Electrode shaft	Material PC (+ABS)
	diameter 12 mm, length 120 mm
Connecting cable	length = 1 meter, permanently fitted, with ALMEMO [®] D7 plug

Variants

Order no.

Variants

Order no.

Digital probe for measuring conductivity, integrated temperature sensor, with process connection G ³/₄-inch, permanently fitted cable with ALMEMO[®] D7 plug,

probe for process applications

```
FYD741LFP
```

Digital probe for measuring conductivity, integrated temperature sensor, with permanently fitted cable with ALMEMO® D7 plug,

probe for laboratory applications

FYD741LFE01

Content

The importance of measuring the quality of room air	16.02
Digital carbon dioxide sensor FYAD 00 CO2	16.04
Carbon dioxide probe FYA 600 CO2	16.05
Carbon Monoxide Probe ADOS 592 TOX	16.06
Oxygen probe FYA 600 O2	16.06
Gas probe for various gases ADOS 592 TOX	16.07



tant ones include: • Carbon dioxide (CO₂)

• Oxygen (O_2)

• Carbon monoxide (CO)

Why is the Measurement of Room Air Quality So Important?

An unsatisfactory room air quality of indoor rooms (e.g. in offices)

can easily cause tiredness, poor powers of concentration and even

diseases to people. Indicator for the room air quality is the concentration

CO₂-Concentration

An important criterion for the evaluation is experienced as stale or stagnant air. The of the room air quality is the CO₂ illustration above shows the range of CO₂ concentration. A CO, concentration, which concentrations that are relevant to a human. is too high due to insufficient ventilation,

CO-Concentration

CO is produced when carbon is only same time highly toxic - but invisible and • deficiency of air partially combusted (fuel). CO is very odorless. Reasons for the production of dangerous for humans because it is at the CO in various combustion processes:

Effects of CO in the ambient air on the human body

CO concentration Inhalation period and consequences

30 ppm	0.0003%	Maximum concentration in the workplace per 8-hour shift (German MAK value)
200 ppm	0.02%	Slight headache within 2 to 3 hours
400 ppm	0.04%	Headache within 1 to 2 hours, first in the forehead and temples, then spreading to the whole head
800 ppm	0.08%	Dizziness, nausea, and twitching limbs within 45 minutes, unconsciousness within 2 hours
1600 ppm	0.16%	Headache, dizziness, nausea within 20 minutes, death within 2 hours
3200 ppm	0.32%	Headache, dizziness, nausea within 5 to 10 minutes, death within 30 minutes
6400 ppm	0.64%	Headache and dizziness within 1 to 2 minutes, death within 10 to 15 minutes
12800 ppm	1.28%	Death within 1 to 3 minutes

of specific gases in air. The most impor-

Applications

- measurement, control, and warning system in garages,
- · monitoring of room air quality with respect to maximum permissible workplace concentration (MAK value)
- monitoring of outside air or of protected air systems in domestic and large public shelters.

CO₂ concentration ppn Human exhalation 40000 – 520000ppm Maximum permissible 500 work place concentration (threshold limit value, TLV) Unsatisfactory room air quality Limit values for 1000 indoor rooms (offices, etc.) Urban air quality 700ppm 500 Fresh air 330 – 400ppm

• too high excess of air

· too early cooling down of flame

O₂-Concentration

a ratio of 1:5. Oxygen is required for all bound with any type of noxious fires such oxidation processes; for combustion as forest and heath fires. Due to the processes, as well as for silent oxidations. permanent cycle of assimilation and Examples include the rusting of iron, photosynthesis in green plants when they oxidations, which occur in living are subject to sunshine, oxygen is processes that release energy require this consumption and oxygen production is gas, for example, heating systems or disturbed by the continuously increasing

The inhaled air consists of vital oxygen at aircraft engines. However, oxygen is also combustion of fossil combustibles. processes, or the decomposition of organic continuously re-formed from carbon material. Additionally, all combustion dioxide. The balance between oxygen automotive industry.

Therefore, many areas require control measurements of the oxygen content in the air, e.g. in air condition systems, air purifiers, oxygen rectifiers, greenhouses and oxygen incubators, as well as for exhaust emission tests, e.g. in the

Digital carbon dioxide sensor FYAD 00 CO2 with grip, integrated atmospheric pressure sensor for automatic atmospheric pressure compensation, and ALMEMO[®] D6 plug



General features and accessories. ALMEMO® D6 sensors: see page 01.08

Technical Data .

- All sensor characteristics and adjustment data are stored in the CO₂ sensor itself.
- The unique automatic calibration procedure (without fresh air intake) automatically compensates any natural ageing effects.
- The sensor is very well protected against the effects of pollution by means of replaceable PTFE filter caps. Long-term stability is outstanding.
- · Automatic atmospheric pressure compensation is provided for pressure-dependent CO₂ concentrations by means of a digital atmospheric pressure sensor integrated in the grip.
- The relevant ambient parameter, atmospheric pressure, is measured using the same sensor.
- · Long-term measuring operations can be performed with an ALMEMO[®] data logger in sleep mode; this applies only to current device types with sleep delay (180 seconds).
- 2 primary measuring channels (real measurable variables) CO₂ concentration and atmospheric pressure
- Freely selectable measurable variables Two measuring channels are programmed (at our factory). CO concentration, value average (ppm), AP. Atmospheric pressure (mbar, p). Alternatively a further variable be selected. can CO, current (ppm) concentration, value The configuration is performed on the ALMEMO® V7measuring instrument or directly on the PC using the USB adapter cable ZA1919AKUV (see chapter "ALMEMO® Network technology").

Digital carbon dioxide (CO2) sensor (including A/D converter)			
Measuring principle	non -dispersive infrared (NDIR) technology		
Sensor	2-beam infrared measuring cell		
Measuring range FYAD00CO2B10 FYAD00CO2B05	0 to 10,000 ppm 0 to 5,000 ppm		
Accuracy FYAD 00-CO2B10 FYAD 00-CO2B05	±(100 ppm +5 % of measured value) ±(50 ppm +3 % of measured value)		
Nominal conditions	+25 °C, 1013 mbar		
Temperature dependence	typical 2 ppm CO2 / K in range 0 to +50 °C		
Response time t63	105 s for averaged output value, 60 s for instantaneous value		
Operative range	-40 to +60 °C / 0 to 95 % RH (non-condensing)		
Measuring interval	Moving average 165 seconds (= 11 current values of 15 sec.)		

Filter cap	PTFE Diameter 18 mm Lenoth appr. 41 mm	
Sensor connector	Plug connection	
Grip	with socket, integrated electronics	
Dimensions:	Diameter 20 mm Total length including the sensor 245 mm	
ALMEMO [®] connecting cable fitted cable, 2 meters With ALMEMO [®] D6 plug		
Digital atmospheric pressure sensor (integrated in grip)		
Measuring range	700 to 1100 mbar	
Accuracy	±2.5 mbar (at 23 °C ±5 K)	
ALMEMO [®] D6 plug		
Refresh rate	1 second for all four channels	
Supply voltage	6 to 13 VDC	
Current consumption	25 mA	

Type (including factory test certificate)

Digital CO₂ sensor with grip, fitted cable with ALMEMO[®] D6 plug, and integrated digital atmospheric pressure sensor

Measuring range 10 000 ppm

Measuring range 5 000 ppm

FYAD00CO2B10

ÖKD calibration KY96xx carbon dioxide concentration for digital sensor (see chapter Calibration certificates)

ÖKD calibration KY96xx, carbon dioxide concentration, for digital probe, see chapter Calibration certificates. The ÖKD calibration fulfills the requirements of DIN EN ISO/IEC 17025 for test equipment.

FYAD00CO2B10 FYAD00CO2B05

Order no.

Carbon Dioxide Probe FYA600CO2



- Since the gas is supplied by means of free convection, this is especially suitable for climatology measurements.
- Various measuring ranges up to 25%.

Technical Data

Gas:	CO ₂	Power supply:	6.5 to 12VDC
Measuring principle:	IR optics		from the ALMEMO [®] device
Measuring ranges:	nominal (% CO_2): 0 2 5% 0 10% 0 25%		Operation with mains supply unit recommended !
1 0011#001/1	+2% of final value	Current consumpt.	eff. 50mA/ max. 70mA
Accuracy.		Settling time t90:	< 60s
Reproducibility:	$\pm 1\%$ of final value	Temperature coefficient:	typical -0.4% signal/K
Resolution:	(depending on measuring range) <200ppm at 2.5%	Temperature range:	5 to +40°C
Output:	0 2V on ALMEMO [®] connector	Relative humidity:	0 to 95%, noncondensing
o urp un	Linearization in ALMEMO [®] device	Dimensions:	W 96mm x H 36mm x D 64mm
Current output:	referred to GND	Weight:	241g
max. burden (load resist.): 400W		Connecting cable:	1.5m long, ALMEMO [®] connector

• Operation with the device in SLEEP mode is not possible! When operating more than one CO₂ probe on a single ALMEMO[®] device, these CO₂ probes will need their own external power supply ! On request we can offer a wide variety of power supply options to suit your particular measuring setup.

Туре

Carbon dioxide sensor including connecting cable 1.5m long for CO_2 measurements in air (Please specify measuring range !)

Order no. FYA600CO2

Factory calibration KY96xx carbon dioxide concentration for measuring chain (sensor + device) (see chapter Calibration certificates)

Carbon Monoxide Probe ADOS 592 TOX



- Applications: For measurement, control and warnings in garages, for monitoring the air quality with respect to the maximum allowable concentration at work places (MAC value, e.g. in laboratories and engine test benches)
- Operation with the device in SLEEP mode is not possible!

Technical Data

Gas:	СО
Measuring principle:	electrochemical reaction
Measuring range:	see types
Zero point error:	< 10 ppm CO -
Gauge reading balance:	< 3 ppm CO -
Error of meas. value:	±3% of full scale value –
Zero point drift:	< 2% (1 year) -
Reproducibility:	< 2% (1 year) -
Linearity:	< 2% of full scale value -
Settling time t ₉₀ :	< 60s -
Transverse sensitivity:	< 2% by integrated filter

Nominal conditions:	20 °C, 50 % r.H., 1013 mbar
Operating conditions:	-10 to +40°C, Sensor in range
	temperature compensated
	> 15 to 90 % r.H. non-condensing
Life span of the meas. cell:	approx. 2 years typical
Output:	4 20 mA on ALMEMO® connector
Supply voltage:	24V via ALMEMO® connector
Dimensions of meas. head:	Ø 80mm, height 80mm
Weight:	600g
Connecting cable:	1.5m, with ALMEMO [®] connector

Ausführung (incl. factory test certificate) Order no.

Carbon monoxide sensor including connectin	g cable 1.5m
long for CO measurements in air	
range: 0 150 ppm	FYA600COB1

range: 0 300 ppm
range: 0 5000 ppm
range: 0 5 Vol.%

FYA600COB2 FYA600COB3 FYA600COB4

Oxygen Probe FYA600O2



- Examples from the range of applications: Measurements in air conditioning systems, air purifiers, oxygen rectifiers, greenhouses and oxygen incubators.
- Approved by PTB and approved for exhaust emission measurements in the automotive industry.
- A correction value can be stored in the ALMEMO[®] connector plug to compensate for the natural ageing of the probes, so optimum output characteristics can be ensured for the whole operating life.

Technical Data

Gas:	O ₂	Operating life:	2 years, if operated in 20.9% O_2
Measuring principle:	electrochemical cell	Nominal conditions:	20°C, 50% rH, 1013mbar
Measuring range:	1 100% O ₂ , linear	Temperature range:	-20 to +50°C
Accuracy :	1% O ₂	Temperature compensation: effective in range -10 to $+40^{\circ}$ C	
Resolution :	0.01% O ₂	Pressure range:	atm. pressure ±10%
Response time:	< 40s	Relative humidity:	0 to 99% non-condensing
Signal drift:	< 2% signal/month	Connecting cable:	adapter cable 1.5m long
	(typ. < 5% over operating life)	Dimensions:	H 43 mm x Ø 29,3 mm
Offset voltage at 20°C:	$< 20 \mathrm{mV}$		

Types

Order no.

Oxygen sensor including connecting cable 1.5m longfor O_2 measurements in airFYA60002

For Reordering: Oxygen sensor ALMEMO[®] connecting cable

FY9600O2 ZA9600AKO2

Gas probe for various gases ADOS 592 TOX



- Range:
- Measurement of gas concentration in air
- multiple ranges / Modelvariants

Operation with the device in SLEEP mode is not possible!

Technical Data

Gas:	see model variants
Measuring principle:	electrochemical reaction
Measuring range:	see model variants
Error of meas. value:	$\pm 3\%$ of full scale value
Zero point drift:	< 2% (1 year)
Reproducibility:	< 2% (1 year)
Linearity:	< 2% of full scale value
Settling time t ₉₀ :	< 60s
Transverse sensitivity:	< 2% by integrated filter
Nominal conditions:	20 °C, 50 % r.H., 1013 mbar

Operating conditions:	-10 to +40°C, Sensor in range temperature compensated> 15 to 90 % r.H. non-condensing
Life span of the meas. cell:	approx. 2 years typical
Output:	4 20 mA on ALMEMO® connector
Supply voltage:	24V via ALMEMO® connector
Dimensions of meas. head:	Ø 80mm, height 80mm
Weight:	600g
Connecting cable:	1.5m, with ALMEMO [®] connector

Model variants (including factory test certificate)	Order no.
Gas probe, including connecting cable, 1.5 meters, for measuring gas in air	
Ammonia NH ₃	
Range: 0 250 ppm	FYA600ANH3
Nitrogen dioxide NO ₂	
Range: 0 30 ppm	FYA600ANO2
Nitrogen oxide NO	
Range: 0 50 ppm	FYA600ANO
Chlorine gas Cl ₂	
Range: 0 50 ppm	FYA600ACL2
Sulfur dioxide SO ₂	
Range: 0 20 ppm	FYA600ASO2B1
Range: 0 50 ppm	FYA600ASO2B2
Range: 0 250 ppm	FYA600ASO2B3
Hydrogen sulfide H ₂ S	
Range: 0 50 ppm	FYA600AH2SB2
Range: 0 250 ppm	FYA600AH2SB3
Ethylene oxide C ₂ H ₄ O	
Range: 0 20 ppm	FYA600AC2H4OB1
Range: 0 50 ppm	FYA600AC2H4OB2
Range: 0 100 ppm	FYA600AC2H4OB4

Calibration certificates

Content

What You Should Know About Calibration	17.02
Calibration certificates - temperature and pressure - sensor deviation reduced to zero	17.03
Test instrument	
Simulator Typ KA 7531	17.04
Adjustment Set for ALMEMO [®] Devices	17.06
Calibration certificates for:	
Temperature	17.07
Infrared Temperature Measurement	17.08
Meteorological transducers FMD7 60	17.08
Relative Air Humidity for Capacitive Humidity Sensors	17.08
Relative Air Humidity for Psychrometers	17.09
Relative Air Humidity at Temp 95°C	17.09
Dew Point	17.09
Pressure	17.10
Air Flow	17.11
Flow measurement for liquids	17.11
Gas Concentration	17.11
Conductivity	17.12
Measurable Variables for Optical Radiation	17.12
Optical Speed Sensors	17.12
Force	17.13
Electrical Calibration of Measuring Devices	17.13

Calibration certificates



What You Should Know About Calibration

With the introduction of quality management standards all over the world, the requirements for measuring and test

demanding. For example, the certification of the specific environment this ensures according to DIN EN ISO 9000+ requires a high reliability regarding the measuring an active quality management involving results and the traceability of the measured devices have become significantly more regular calibrations. With consideration values to the national standard.

The Result of a Calibration

- 1. The result of a calibration allows the evaluation of errors of dimension of the measuring instrument, measuring equipment or the setup of measuring instruments or the allocation of values
- to any scaled graduation marks. The result of a calibration can be fixed 2. in a document, which is often called a 'calibration report' or a 'calibration certificate'.
- 3. In many cases, the result of a calibration is specified as correction or 'calibration factor' or as 'calibration curve'.

DAkkS Calibration

• The calibration must only be performed within the range of those measurable variables, measuring ranges and measuring incertainties, which are specified in the accreditation document. The customer receives a DAkkS Calibration certificate specifying the measured values, the corresponding measuring incertainty, the designation of the calibration method, the environmental conditions and, as required, information on special measurement conditions.

The calibrated object will be identified by a label (blue). DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025 (inter alia for the monitoring of production processes and the quality assurance applied to products).

DAkkS-calibrations outside the range of accreditation services provided by the DAkkS calibration laboratory at Ahlborn Mess- und Regelungstechnik GmbH are performed by DAkkS laboratories run by our various partners.

Calibration certificates

Factory Calibration

The calibration is performed according to comparison measurements with factory standards. Factory standards are (as far as possible) PTB or DAkkS / DKD calibrated measuring instruments, sensors or measuring systems. The customer receives a factory calibration certificate specifying the measured values, the corresponding measuring incertainty, the designation of the calibration method, the environmental conditions and, as required, information on special measurement conditions. The calibrated object will be identified by a label.

Factory calibrations outside the range of accreditation services provided by the calibration laboratory at Ahlborn Mess- und Regelungstechnik GmbH are performed by laboratories run by our various partners.

How Often To Calibrate?

The time interval between calibrations • Permissible measuring tolerances highly depends on the specific application • Results of previous calibrations and is influenced by the following . Environmental conditions parameters:

- Customer-specific requirements and definitions
- Application frequency
- Application conditions

Calibration certificates - temperature and pressure - sensor deviation reduced to zero

The ALMEMO® measuring system of the AHLBORN Company has already repeatedly proven itself in a wide variety of application areas such as research and development. However, also quality audits, monitoring of measuring equipment and the system of calibration are other areas of application for the ALMEMO® measuring system. Whenever the traceability of measured values is indispensible, ALMEMO[®] is firmly established - whether as a reference

measuring instrument in calibration laboratories or as a traceable customer device.

The correction of a measuring chain is performed via a multi-point adjustment function.

During the calibration of the ALMEMO® measuring system, the sensor deviation is determined in every calibration point and then saved as correction value for that calibration point to the ALMEMO® plug.

The measured values for such multi-point adjusted sensors are then listed in the calibration certificate. This means that the identified sensor deviations are close to zero

The measured value displayed on the ALMEMO® measuring instrument is the already corrected value and can be used further. It is not necessary to correct the measured value afterwards with the correction function that was established during the calibration.

		08 -	16	
	neschlossen	an 1 Temperaturanzeigeger cted with 1 temperature mea	ät Isuring	
uiderstandsthermomete	er (Pt100), ang- rmometer (PT100), conne rmometer (PT100), conne			1
1 platinum resident device		weichung Unc	ertainty K	
t Result	Anzeige Ab	Deviation K	0,25	3
rüftemperatur	Indication °C	0,00 0,00 0,00	0,15	8
620,00	620,00 600,00 550,00	0,00 0,00 0,00	0.	0,06 0,06 0,05
600,00 550,00 500,00	450,00 450,00 400,00	0,00 0,00 0,00	F	0,05 0,04 0,04
450,00 400,00 350,00	300,00 300,00 250,00	0,00	Ŧ	0,03
300,00 250,00 200,00	150,00 100,00 50,00	0,00	1	

Test instrument

Simulator KA 7531-1



Technical features

- Universal manual simulator for simulating temperature sensors and process variables when testing measuring instruments, • Connection of peripherals via ALMEMO® clamp connectors, regulators, and other equipment
- Pt100 simulation with 5 fixed resistors in 4-conductor technology Voltage and thermocouples simulation with 15-bit D/A converter Current simulation with 15-bit D/A converter Frequency and pulse generator with quartz-crystal oscillator Continuity check with settable threshold
- All signals are available at the same time.
- Signals can be set either manually or automatically, in step or ramp form.
- All signals and all the programming can be shown on the

Technical data

- illuminated graphics display.
- cable with anti-kink protective sleeve and strain relief
- Power supply via battery or mains unit
- Modern, compact housing also suitable for DIN top-hat rail mounting
- Option of PC-controlled operation via all ALMEMO® data cables.

Signal Pt100	5 discrete resistance values in 4-conductor technology	signal frequency	14000Hz, 0.0110.00kHz, 0.140.0kHz, 1100kHz
Accuracy Temperature drift	0 / 50 / 100 / 200 / 300 °C ±0.1°C 0.01°C / K	Pulse width Accuracy Pulse range	1 to 99 % corresponds to the resolution
Signal voltage -10 to +60.000 mV -3 to 10.000 V	15-bit DAC electr. isolated load > 1 M Ω load > 100 k Ω	Period Pulse Accuracy	2µs99.999 ms, 2ms99.999 s 1µs99.998 ms, 1ms99.998 s 0.01 %
Accuracy	\pm 0.05% of measured value \pm 0.05% of final value	Continuity Threshold	current approx. 1 mA 0 to 1000 mV
Temperature drift Time constant Thermocouples	20 ppm / K 100 μ s type K, N, T, J (ITS90) resolution: 0.1K type S, R, B (ITS90) resolution: 1K \pm 0.05% of measured value \pm 0.05% final value -30100°C	Power supply: Battery: Current consumption Voltage and Current output: with illumination:	1012V DC 3 Mignon Alcaline (Battery): approx. 30 mA approx. 80mA + 4 x IOUT, approx. 40mA additional
Accuracy: CJ - temperature:		Display Illumination Keypad	graphics 128 x 64 (55 x 30 mm) 2 white LEDs 7 silicone keys (4 soft-keys)
Signal current	15-bit DAC electr. isolated $\log d \leq 500 \Omega$	— Housing	(LxWxH) 127 x 83 x 42 mm ABS (-10 to +70 °C), 290 g
Accuracy	$0.0520.0$ mA $10ad < 500 \Omega^2$ Accuracy $\pm 0.05\%$ of measured value $\pm 0.05\%$ of final valueTemperature drift 20 ppm / K Time constant $100 \mu\text{s}$	Operating range: Operating temperature: (Storage temperature)	-10 +50 °C
Temperature drift Time constant		Ambient humidity:	10 90 % rH (noncondensing)
Test instrument

Displays (examples)



Accessories	Order no.
ALMEMO [®] clamp connector (for Pt100 or universal use)	ZA1000TS
ALMEMO [®] connecting cable with 2 banana plugs and 2 test probes	ZA1000TK
Mains adapter 12 V / 1.5 A	ZA1312NA12
USB data cable, electrically isolated	ZA1919DKU
V24 data cable, electrically isolated	ZA1909DK5
Fixture for top-hat rail mounting	ZB2490HS
Rubber guard, gray	ZB2490GS2
Options	Order no.
Factory calibration certificate for Simulator KA7531:	

Electrical Calibration compared reference standards that are traceable to national standards.

Calibration in 6 ranges: Pt100 (5 points), and (3 points each) voltage 10 V, voltage 50 mV, current 20 mA, thermocouple type K, frequency Hz, Pakkage Offer addressable PC interface OA7531I

Included as standard

Simulator, 5 sockets for Pt100, thermocouples or -4 to 10 V, 0 to 20 mA, frequency, continuity tester, Graphics display and keypad, sockets DC, A1, batteries, including manufacturer's test certificate, 1 ALMEMO[®] clamp connector (for Pt100) and ALMEMO[®] and ALMEMO[®] connecting cable with 2 banana plugs and 2 test probes

Order no.

KA75311

Adjustment Set for ALMEMO[®] Devices



Туре

Order no.

Adjustment Set for ALMEMO® Devices

Input connector with 1.5 m cable and 4 banana plug (for connection to the calibrator of the customer) including ALMEMO[®] Adjustment instructions and software AMR-Control (CD)

ZA9090AKA

Calibration certificates

Temperature

Caibration certificate for temperature measuring chains consisting of a contact temperature sensor and an instrument (also individual sensors). The calibration of the sensors or sensor + measuring instrument (measuring chain) is performed in a liquid bath, in a drywell calibrator or in a climatic chamber.

DAkkS Calibration Certificate

DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025 (inter alia for the monitoring of production processes and the quality assurance applied to products).

Calibration is performed by a DAkkS authorized office which compares measured values against reference values based on national standards. .

Package offer (basic rate + 3 points 0°C, 50°C, 100°C)	KT9021D
Measuring points, freely selectable	
Basic fee	KT9001D
Measuring point fee per sensor, one measuring point, temperature range up -100 to +1200 °C	KT9011D
Measuring point fee per sensor, one measuring point -196 °C	KT9012D
Factory Calibration Certificate	
Calibration compares measured values against reference values based on national standards.	
Package offer (basic rate + 3 points 0°C, 50°C, 100°C)	KT9021W
Measuring points, freely selectable	
Basic fee	KT9001W
Measuring point fee per sensor, one measuring point, temperature range up -100 to +1200 °C	KT9011W
Measuring point fee per sensor, one measuring point -196 °C	KT9012W

Correction / adjustment of temperature sensors during calibration

To increase the accuracy, an adjustment of the probe is carried out during the initial calibration of a temperature probe. The correction values for zero point and slope are stored in the probe connector. The specified measured values in the certificate correspond to the corrected values. The correction can be performed as DAkkS and factory calibrations.

Calibration certificate - temperature - sensor deviation reduced to zero (see page 17.03)

Multi-point adjustment for ALMEMO[®] measuring chains

(preferably using Pt100 and NTC sensors)

For the measurable variable temperature, for calibration packages and for single points (at least 2 temperature points, temperature point 0 °C obligatory), additional charge per sensor for factory / DAkkS calibration (German calibration service) **KT9001DW**

Calibration and adjustment of the ALMEMO® measuring chain are performed for the whole of the sensors measuring range at the points in the calibration package.

Calibration and adjustment of the ALMEMO[®] measuring chain (preferable using Pt100 and NTC sensors) are performed on the selected temperature points (temperature point 0°C obligatory). Outside the calibrated range (below the lowest and above the highest calibration points) linear interpolation is performed up to the limits of the device's measuring range (e.g. Pt100 0.01 K from -200 to +400°C).

During the calibration of the ALMEMO® measuring system, the sensor deviation is determined in every calibration point and then saved as correction value for that calibration point to the patented ALMEMO® plug. The measured values for such multi-point adjusted sensors are then listed in the calibration certificate. This means that the identified sensor deviations are close to zero.

With thermocouples, as is generally the case, the indicated (adjusted) values in the calibration certificate are only valid if the device is in a stationary, thermally steady-state condition.

Only for device types ALMEMO® 2450 (not -L), 2490 (not -L), 2470, 2590-2/-3S/-4S/-2A/-4AS, 2690, 2890, 4390, 8590, 8690, 5690, 5790, ALMEMO® V7-Measuring instruments und ALMEMO® X6-Reference measuring instrument

These device types as of serial number H0802xxxx incorporate this function as standard; for device types of serial number H0801 and below a device firmware update is possible (noted at incoming inspection as part of the calibration service).

Advisory note :

On temperature sensors with special linearization or special measuring ranges saved to the ALMEMO® connector (e.g. ALMEMO® connector ZA9040SS3 NTC 0.001K or ALMEMO® connectors with KTY84, YSI400, or customized NTC) multi-point adjustment is not possible..

OA0006U

Order no.

Order no.

KI9201D

Calibration certificates

Infrared Temperature Measurement

Calibration certificate for temperature measuring chains consisting of an IR temperature sensor and an instrument (also individual sensors).

DAkkS-Calibration Certificate

DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025 (inter alia for the monitoring of production processes and the quality assurance applied to products).

Calibration is performed by a DAkkS authorized office which compares measured values against reference values based on national standards.

For IR transmitters MR7834, MR7838, MR7842, MR78434, ALMEMO® IR sensor FIAD43

Package offer: 3 temperature points, 25, 100, 200 °C

0	1	1					
Calibration in t	he range	–20°C t	o +550°C	in 3 individually selec	table measuring poin	nts	KI9168D
Calibration in t	he range	+550°C	to +1600°	°C in 3 individually se	electable measuring p	points	KI9178D
1 additional me	asuring p	oint, fre	ely selecta	ble, in the range -20 to	o +1600 °C		KI9168DP

Factory Calibration Certificate

Calibration compares measured values against reference values based on national standards.

For IR transmitters MR7834, MR7838, MR7842, MR7843, ALMEMO® IR sensors FIA844, FIAD43	
Package offer 3 temperature points, 25, 100, 200 °C	KI9201W
Calibration in the range -20° C to $+550^{\circ}$ C in 3 individually selectable measuring points	KI9168W
1 additional measuring point, freely selectable, in the range -20 to +1600 °C	K191/8W
(but not between 550 and 600 °C)	KI9168WP

Calibration certificates for meteorological transducers FMD7 60

DAkkS/DKD calibration certificate Order no. The DAkkS/DKD calibration meets the requirements of DIN EN ISO/IEC 17025 for test equipment (i.a. for monitoring production processes or qualification assurance of products). Calibration is performed by a DAkkS/DKD authorized office which compares measured values against reference values based on national standards. Temperature and Relative Air Humidity (description, see further below) KH9046D **KD9214D** Absolute pressure (description, see further below) Wind velocity (also for FMD7 20) Package offer (calibration in the range 4 to 16 m/s for a wind direction of approx. 0 °) KV9225D Wind direction (also for FMD7 20) Package offer (calibration in the range 5 $^{\circ}$ to 355 $^{\circ}$ for a wind velocity of approx. 10 m/s) KV9324D Factory Calibration Certificate Calibration compares measured values against reference values based on national standards. Temperature and Relative Air Humidity (description, see further below) KH9156W Absolute pressure (description, see further below) **KD9213W** Wind velocity and wind direction (also for FMD7 20) Package offer (calibration in the range 2 to 50 m/s. For wind velocities in the range of 2 to 50 m/s the deviations of the wind velocity and the wind direction are calculated from the root-mean-square of the measured values taken from different directions.) KV9425W

Relative Air Humidity for Capacitive Humidity Sensors

Calibration certificate for humidity measuring chains consisting of a capacitive humidity sensor and measuring instrument (also individual sensors).

Factory Calibration Certificate

Calibration compares measured values against reference values based on national standards. Calibration is performed in a humidity generator / climate chamber at an ambient temperature of approx. 25° C. Package offer

(Basic rate + 3 humidity points 11% / 53% / 75% r.H. + 1 temperature point at approx. 25°C) For calibration at other temperatures, see below ! Order no.

KH9046 W

Calibration certificates

Relative Air Humidity for capacitive humidity sensors / psychometer

Calibration certificate for humidity measuring chains consisting of capacitive humidity sensor / psychometer and measuring instrument.

DAkkS Calibration Certificate

The DAkkS/DKD calibration meets the requirements of DIN EN ISO/IEC 17025 for test equipment (i.a. for monitoring production processes or qualification assurance of products).

Calibration is performed by a DAkkS/DKD authorized office which compares measured values against reference values based on national standards.

Calibration is performed in a humidity generator / climate chamber at an ambient temperature of approx. 25 °C. Package offer (Basic rate + 3 humidity points 20%/53%/75% r.H. + 1 temperature point at approx. 25 °C) KH9046D

Factory Calibration Certificate

Calibration compares measured values against reference values based on national standards. Calibration is performed in a humidity generator / climate chamber at an ambient temperature of approx. 25 °C. Package offer (Basic rate + 3 humidity points 20%/53%/75% r.H. + 1 temperature point at approx. 25 °C) Package offer (Basic rate + 2 humidity points 30 % / 75 % r.H. + 1 temperature point at approx. 25 °C) KH9156W KH9146W

Relative air humidity at temperatures up to +95 °C

DAkkS calibration certificate for temperatures up to +95° C

DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025 (inter alia for the monitoring of production processes and the quality assurance applied to products).

For capacitive humidity sensors and psychrometers. Calibration is performed by a DAkkS authorized office which compares measured values against reference values based on national standards. Calibration is performed in a humidity generator / climate chamber by a DAkkS authorized office.

Measuring points, freely selectable

Basic rate	KH9166D
Points rate per sensor for 1 climate point	
Temperature in the range $+10$ to $+95$ °C and humidity in the range 10% to 95% RH	KH9166DP
Temperature in the range +10 to +95 °C and humidity in the range 10% to 98% RH	KH9166DP2
Measuring points rate per sensor for 1 temperature point:	
Temperature in the range -30 to $+150$ °C.	KH9166DT

Factory calibration certificate for temperatures up to +95 °C

For capacitive humidity sensors and psychrometers. Calibration compares measured values against reference values based on national standards. Calibration is performed in a humidity generator / climate chamber.

Measuring points, freely selectable

Basic rate	KH9166W
Points rate per sensor for 1 climate point	
Temperature in the range ± 10 to ± 95 °C and humidity in the range 10% to 95% RH	KH9166WP
Temperature in the range +10 to +95 °C and humidity in the range 10% to 98% RH	KH9166WP2
Measuring points rate per sensor for 1 temperature point:	
Temperature in the range -30 to +150°C	KH9166WT

Dew point

Test certificate - for dewpoint sensor only FHAD 46-DTC2.

Test Certificate	Order no.
Test according to the comparative method at an ambient temperature of approx. 25 °C. basic rate $+ 1$ dew point in the range -80 to $+20$ °C dew point	KH9316W
Supplement for KH9316W 1 additional dew point in the range -80 to +20 °C dew point	KH9316WP

Calibration certificates

Pressure

Calibration according to DIN 16005/16086.

This calibration can be performed in 5 or 10 measuring points with pressure transducers or transducer + measuring instrument (measuring chain): to 100bar, medium: gas to 700bar, medium: oil

DAkkS Calibration Certificate

DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025 (inter alia for the monitoring of production processes and the quality assurance applied to products).

Calibration is performed by a DAkkS authorized office which compares measured values against reference values based on national standards.

Positive overpressure in the range 0 to 700 bar, 10 points (Procedure B according to DKD-R 6-1)KD9012DPositive and negative overpressure for pressure sensors in the range -1 to 700 bar, 10 pointsKD9014DAbsolute pressure in the range from 0.03bar to 700bar, 10 points (Procedure B according to DKD-R 6-1)KD9014D

Factory Calibration Certificate

Calibration compares measured values against reference values based on national standards.

Positive overpressure in the range 0 to 700 bar, 10 points (Procedure C according to DKD-R 6-1)	KD9012W
Positive overpressure in the range 0 to 700 bar, 5 points (Procedure C according to DKD-R 6-1)	KD9013W
Positive and negative overpressure for pressure sensors in the range -1 to 700 bar, 10 points	KD9014W
Absolute pressure in the range from 0.03bar to 700bar, 10 points (Procedure C according to DKD-R 6-1)	KD9113W
Absolute pressure in the range from 0.03bar to 700bar, 5 points (Procedure C according to DKD-R 6-1)	KD9112W

Calibration certificate - pressure - sensor deviation reduced to zero (see page 17.06)

Multi-point adjustment for ALMEMO® measuring chains

For the measurable variable pressure, for calibration packages,

additional charge per sensor for factory / DAkkS calibration

For the ALMEMO[®] measuring chain, calibration and adjustment are carried out in the entire measuring range of the sensor at the points of the calibration package.

During the calibration of the ALMEMO[®] measuring system, the sensor deviation is determined in every calibration point and then saved as correction value for that calibration point to the ALMEMO[®] plug. The measured values for such multi-point adjusted sensors are then listed in the calibration certificate. This means that the identified sensor deviations are close to zero.

Only for device types ALMEMO[®] 2450 (not -L), 2490 (not -L), 2470, 2590-2/-3S/-4S/-2A/-4AS, 2690, 2890, 4390, 8590, 8690, 5690, 5790, ALMEMO[®] V7 measuring instruments and ALMEMO X6 reference measuring instrument.

These device types as of serial number H0802xxxx incorporate this function as standard; for device types of serial number. H0801 and below, a device firmware update is possible (noted at incoming inspection as part of the calibration service). **OA0006U**

Absolute pressure for digital atmospheric pressure sensor FDAD12SA

Calibration certificate for barometric pressure sensors integrated in the ALMEMO® device or in the ALMEMO® D6 plug

DAkkS Calibration Certificate

17.10

DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025 (inter alia for the monitoring of production processes and the quality assurance applied to products).

Calibration is performed by a DAkkS authorized office which compares measured values against reference values based on national standards.

Absolute pressure 5 points in the range 700 to 1100 mbar (Procedure C according to DKD-R 6-1)	KD9213D
Absolute pressure 10 points in the range 700 to 1100 mbar (Procedure B according to DKD-R 6-1)	KD9214D
Factory Calibration Certificate	
Calibration compares measured values against reference values based on national standards. Absolute pressure 5 points in the range 700 to 1100 mbar (Procedure C according to DKD-R 6-1)	KD9213W

Order no.

Order no.

Air Flow

Calibration certificate for rotating vanes, Pitot tubes and thermoanemometers.

DAkkS Calibration Certificate

DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025 (inter alia for the monitoring of production processes and the quality assurance applied to products).

Calibration is performed in a wind tunnel based on measurement comparison against a laser Doppler anemometer by a DAkkS authorized office.

Package offer (Basic rate + 5 points in the range 0,2 m/s to 65 m/s)	KV9075D
Supplement to KV9075D: 1 additional measuring point	KV9075DP

Factory Calibration Certificate

The calibration can be performed with the sensor and the meas. instrument (meas. chain). Calibration in a wind tunnel. Reference standards: Wind tunnel and reference rotating vanes (calibrated acc. to the laser-Doppler method).

Package offer (basic rate + 3 points 0.5m/s / 5m/s / 10m/s)	KV9025W
Package offer (basic rate + 3 points 5m/s / 10m/s / 19m/s)	KV9035W
Package offer (basic rate + 3 points 7m/s / 20m/s / 30m/s)	KV9045W
Package offer (basic rate + 3 points 0.5m/s / 1m/s / 1,75m/s)	KV9055W
Package offer (basic rate + 3 points 0.5m/s / 0.8m/s / 1m/s)	KV9065W
Measuring points, freely selectable	
Basic rate	KV9005W
Per measuring point and sensor Meas. range 0.2m/s to 65m/s.	KV9015W

Flow measurement in liquids

Calibration certificate for turbine flow meters or flow sensors

DAkkS Calibration Certificate

DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025 (inter alia for the monitoring of production processes and the quality assurance applied to products).

Calibration is performed by a DAkkS authorized office which compares measured values against reference values based on national standards.

Calibration of the volume flow rate in l/min (up to maximum 200 l/min) in the flow test bench.

Measuring medium: Water

Calibration at 5 measuring points, logarithmically distributed within the measuring range of the sensor.

For recalibration:

calibration of the current state. Package offer

linked to the new delivery of the flowmeter for liquids:

determination of the K factor, programming of the ALMEMO plug, calibration of the original state. Package offer

Gas Concentration

Calibration certificate for CO₂

ÖKD Calibration Certificate

ÖKD calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025 (inter alia for the monitoring of production processes and the quality assurance applied to products).

Calibration is performed by a ÖKD authorized office which compares measured values against reference values based on national standards.

Package offer for CO ₂ probe FYAD00CO2B10 (3 measuring points at approx. 1000 / 4000 / 7000 ppm)	KY9626D
Package offer for CO ₂ probe FYAD00CO2B05 (3 measuring points at approx. 500 / 2500 / 4500 ppm)	KY9627D

Factory Calibration Certificate

Calibration is performed based on measurement comparison against a reference gas specified by the manufacturer. Package offer for CO₂ probe FYA600CO2 (approx. 10 measuring points) KY9620W

Order no.

KV9145D

KV9145DE

Order no.

Order no.

Conductivity

Calibration certificate for conductivity measuring chains.	
Factory Calibration Certificate	Order no.
Calibration compares measured values against reference values based on national standards.	
Package offer for conductivity probe FYA641LF /LFP1 (Basic rate + 3 points 0.5mS / 2.77mS / 10mS) (Basic rate + 2 points 2.77mS / 12.8mS)	KY9041W KY9044W
Package offer for conductivity probe FYA641LF2 /LFP2 (Basic rate + 3 points 10μS / 147μS / 190μS)	KY9042W
Package offer for conductivity probe FYA641LF3 /LFP3 (Basic rate + 3 points 5mS / 50mS / 111,8mS)	KY9043W
Package offer for digital conductivity probe FYD7 41-LF (ALMEMO [®] D7) (Basic rate + 3 points 147 µS / 12,8 mS / 111,8 mS, i.e. 1 point per ALMEMO [®] D7 measuring range)	KY9045W
DAkkS Calibration Certificate	Order no.
The DAkkS calibration fulfills the requirements of DIN EN ISO/IEC 17025 for test equipment (e.g. for monitoring production processes or quality assurance of products).	
The calibration is carried out by a DAkkS office according to the comparison method against reference standa traceable to national standards.	rds that are
Package offer for digital conductivity probe FYD7 41-LF (ALMEMO [®] D7) (Basic fee + 3 selectable points in 1 selected ALMEMO [®] D7 measuring range: 500 µS/cm or 50 mS/cm or 500 mS/cm)	KY9043D

Measurable Variables for Optical Radiation

Calibration certificate for broad-band light detectors

Factory Calibration Certificate

single point calibration of absolute size
(ONLY for probes FLA603x, FLA613RD/UV/VL)KL9033WCalibration of absolute variable in 3 points (zero point and 2 points, sensor dependent)KL9034W(ONLY for probes FLA613x, FLA23x, FLA633x, FLADx, FLD7x)KL9034W

Optical Speed Sensors

Calibration certificate for contactless tachometers.

DAkkS Calibration Certificate

DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025 (inter alia for the monitoring of production processes and the quality assurance applied to products).

Calibration is performed by a DAkkS authorized office which compares measured values against reference values based on national standards.

Calibration of the optical transducer at 8 measuring points (not applicable for the tachometer probe FUA919-MF)

Factory Calibration Certificate

Calibration compares measured values against reference values based on national standards. Calibration of the optical transducer at 8 measuring points (not applicable for the tachometer probe FUA919-MF)

Order no.

KU9029D

KU9029W

Force

Calibration for tension and compression sensors

Factory calibration certificate

Calibration is performed based on the measurement comparison method for Ahlborn force transducers;

4 series of measuring operations upwards and 2 series downwards

3 steps (0%, 20%, 60%, 100% of final value) Tension or compression (indicate direction), up to 1 kN 3 steps (0%, 20%, 60%, 100% of final value) Tension or compression (indicate direction), up to 10 kN 3 steps (0%, 20%, 60%, 100% of final value) Tension or compression (indicate direction), up to 100 kN 3 steps (0%, 20%, 60%, 100% of final value) Tension or compression (indicate direction), up to 1000 kN

Electrical Calibration for all ALMEMO® measuring instruments with interface

DAkkS calibration certificate

DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025 (inter alia for the monitoring of production processes and the quality assurance applied to products).

Calibration is performed by a DAkkS authorized office which compares measured values against reference values based on national standards.

Full calibration of ALMEMO device in 9 measuring ranges

2.6 V (volt), 55 mV (mV), 26 mV (mV1), 260 mV (mV2), NiCr-Ni (NiCr), Pt100 0.1 K (P104), Pt100 0.01 K (P204), NTC type N (NTC), relative humidity, capacitive (% RH)

Package offer

Factory calibration certificate

Calibration compares measured values against reference values based on national standards.

Full calibration of ALMEMO® device in 9 measuring ranges

2.6 V (volt), 55 mV (mV), 26 mV (mV1), 260 mV (mV2), NiCr-Ni (NiCr), Pt100 0.1 K (P104), Pt100 0.01 K (P204), NTC type N (NTC), relative humidity, capacitive (% RH) Package offer

Electrical Calibration of Measuring and Indicating Devices

Calibration certificate for all ALMEMO® devices

DAkkS Calibration Certificate

DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025 (inter alia for the monitoring of production processes and the quality assurance applied to products). Calibration is performed by a DAkkS authorized office which compares measured values against reference values based on national standards. The calibration is performed at approx. 10 measuring points. **KE9010D** Calibration for one measuring range **KE9020D** Each further measuring range Calibration for 1 digital ALMEMO® measuring module ZA990xABx, ZAD90xABx, ZED7xxABx: AC/DC voltage up to 400 V (50 Hz) or AC/DC current up to 20 A (50 Hz) (NOT power in W) or for 1 ALMEMO® adapter cable ZA9603AKx AC voltage or measuring chain or for 1 FEA 60x AC/DC current clamp up to 10 A (50 Hz) Package offer, approx. 10 points **KE9030D** Factory Calibration Certificate

Calibration compares measured values against reference values based on national standards. The calibration is performed at approx. 10 measuring points. Calibration for one measuring range Each further measuring range Calibration for 1 digital ALMEMO® measuring module ZA990xABx, ZAD90xABx, ZED7xxABx: AC/DC voltage up to 400 V (50 Hz) or AC/DC current up to 20 A (50 Hz) (NOT power in W) or for 1 ALMEMO® adapter cable ZA9603AKx AC voltage or measuring chain or for 1 FEA 60x AC/DC current clamp up to 10 A (50 Hz) Package offer, approx. 10 points

Order no.

Order no.

KK9021W

KK9031W

KK9041W

KK9051W

KE9005W

KE9005D

Order no.

KE9010W KE9020W

KE9030W

Notes

Ahlborn Mess- und Regelungstechnik GmbH

Catalog published by :

AHLBORN Mess- und Regelungstechnik GmbH

Headquarters :

Ahlborn Mess- und Regelungstechnik GmbH Eichenfeldstraße 1 83607 Holzkirchen Germany tel: +49-8024-3007-0 fax +49-8024-300710 internet: http://www.ahlborn.com email: amr@ahlborn.com



Production and development :

Ahlborn Mess- und Regelungstechnik GmbH Bahndamm 17 98693 Ilmenau Germany





Ahlborn – always close at hand. In more than 40 countries!







Ahlborn Mess- und Regelungstechnik GmbH • Eichenfeldstraße 1 • 83607 Holzkirchen • Deutschland Tel.: +49 8024 3007-0 • Fax: +49 80243007-10 • E-Mail: amr@ahlborn.com • Internet: www.ahlborn.com